

# **Linux From Scratch**

**Version 12.2-systemd**

**Published September 1st, 2024**

**Created by Gerard Beekmans  
Managing Editor: Bruce Dubbs  
Editor: Douglas R. Reno  
Editor: DJ Lucas**

# **Linux From Scratch: Version 12.2-systemd: Published September 1st, 2024**

by Created by Gerard Beekmans, Managing Editor: Bruce Dubbs, Editor: Douglas R. Reno, and Editor: DJ Lucas

Copyright © 1999-2024 Gerard Beekmans

Copyright © 1999-2024, Gerard Beekmans

All rights reserved.

This book is licensed under a Creative Commons License.

Computer instructions may be extracted from the book under the MIT License.

Linux® is a registered trademark of Linus Torvalds.

# Table of Contents

Preface .....	viii
i. Foreword .....	viii
ii. Audience .....	viii
iii. LFS Target Architectures .....	ix
iv. Prerequisites .....	x
v. LFS and Standards .....	x
vi. Rationale for Packages in the Book .....	xi
vii. Typography .....	xvii
viii. Structure .....	xviii
ix. Errata and Security Advisories .....	xix
I. Introduction .....	1
1. Introduction .....	2
1.1. How to Build an LFS System .....	2
1.2. What's new since the last release .....	2
1.3. Changelog .....	4
1.4. Resources .....	8
1.5. Help .....	9
II. Preparing for the Build .....	11
2. Preparing the Host System .....	12
2.1. Introduction .....	12
2.2. Host System Requirements .....	12
2.3. Building LFS in Stages .....	15
2.4. Creating a New Partition .....	15
2.5. Creating a File System on the Partition .....	17
2.6. Setting The \$LFS Variable .....	18
2.7. Mounting the New Partition .....	19
3. Packages and Patches .....	21
3.1. Introduction .....	21
3.2. All Packages .....	22
3.3. Needed Patches .....	31
4. Final Preparations .....	32
4.1. Introduction .....	32
4.2. Creating a Limited Directory Layout in the LFS Filesystem .....	32
4.3. Adding the LFS User .....	32
4.4. Setting Up the Environment .....	33
4.5. About SBUs .....	36
4.6. About the Test Suites .....	36
III. Building the LFS Cross Toolchain and Temporary Tools .....	38
Important Preliminary Material .....	39
i. Introduction .....	39
ii. Toolchain Technical Notes .....	39
iii. General Compilation Instructions .....	44
5. Compiling a Cross-Toolchain .....	46
5.1. Introduction .....	46
5.2. Binutils-2.43.1 - Pass 1 .....	47

5.3. GCC-14.2.0 - Pass 1 .....	49
5.4. Linux-6.10.5 API Headers .....	52
5.5. Glibc-2.40 .....	53
5.6. Libstdc++ from GCC-14.2.0 .....	56
6. Cross Compiling Temporary Tools .....	58
6.1. Introduction .....	58
6.2. M4-1.4.19 .....	59
6.3. Ncurses-6.5 .....	60
6.4. Bash-5.2.32 .....	62
6.5. Coreutils-9.5 .....	63
6.6. Diffutils-3.10 .....	64
6.7. File-5.45 .....	65
6.8. Findutils-4.10.0 .....	66
6.9. Gawk-5.3.0 .....	67
6.10. Grep-3.11 .....	68
6.11. Gzip-1.13 .....	69
6.12. Make-4.4.1 .....	70
6.13. Patch-2.7.6 .....	71
6.14. Sed-4.9 .....	72
6.15. Tar-1.35 .....	73
6.16. Xz-5.6.2 .....	74
6.17. Binutils-2.43.1 - Pass 2 .....	75
6.18. GCC-14.2.0 - Pass 2 .....	76
7. Entering Chroot and Building Additional Temporary Tools .....	78
7.1. Introduction .....	78
7.2. Changing Ownership .....	78
7.3. Preparing Virtual Kernel File Systems .....	78
7.4. Entering the Chroot Environment .....	79
7.5. Creating Directories .....	80
7.6. Creating Essential Files and Symlinks .....	81
7.7. Gettext-0.22.5 .....	84
7.8. Bison-3.8.2 .....	85
7.9. Perl-5.40.0 .....	86
7.10. Python-3.12.5 .....	87
7.11. Texinfo-7.1 .....	88
7.12. Util-linux-2.40.2 .....	89
7.13. Cleaning up and Saving the Temporary System .....	90
IV. Building the LFS System .....	92
8. Installing Basic System Software .....	93
8.1. Introduction .....	93
8.2. Package Management .....	94
8.3. Man-pages-6.9.1 .....	98
8.4. Iana-Etc-20240806 .....	99
8.5. Glibc-2.40 .....	100
8.6. Zlib-1.3.1 .....	108
8.7. Bzip2-1.0.8 .....	109
8.8. Xz-5.6.2 .....	111

8.9. Lz4-1.10.0 .....	113
8.10. Zstd-1.5.6 .....	114
8.11. File-5.45 .....	115
8.12. Readline-8.2.13 .....	116
8.13. M4-1.4.19 .....	118
8.14. Bc-6.7.6 .....	119
8.15. Flex-2.6.4 .....	120
8.16. Tcl-8.6.14 .....	121
8.17. Expect-5.45.4 .....	123
8.18. DejaGNU-1.6.3 .....	125
8.19. Pkgconf-2.3.0 .....	126
8.20. Binutils-2.43.1 .....	127
8.21. GMP-6.3.0 .....	130
8.22. MPFR-4.2.1 .....	132
8.23. MPC-1.3.1 .....	133
8.24. Attr-2.5.2 .....	134
8.25. Acl-2.3.2 .....	135
8.26. Libcap-2.70 .....	136
8.27. Libxcrypt-4.4.36 .....	137
8.28. Shadow-4.16.0 .....	139
8.29. GCC-14.2.0 .....	143
8.30. Ncurses-6.5 .....	148
8.31. Sed-4.9 .....	151
8.32. Psmisc-23.7 .....	152
8.33. Gettext-0.22.5 .....	153
8.34. Bison-3.8.2 .....	155
8.35. Grep-3.11 .....	156
8.36. Bash-5.2.32 .....	157
8.37. Libtool-2.4.7 .....	159
8.38. GDBM-1.24 .....	160
8.39. Gperf-3.1 .....	161
8.40. Expat-2.6.2 .....	162
8.41. Inetutils-2.5 .....	163
8.42. Less-661 .....	165
8.43. Perl-5.40.0 .....	166
8.44. XML::Parser-2.47 .....	169
8.45. Intltool-0.51.0 .....	170
8.46. Autoconf-2.72 .....	171
8.47. Automake-1.17 .....	172
8.48. OpenSSL-3.3.1 .....	173
8.49. Kmod-33 .....	175
8.50. Libelf from Elfutils-0.191 .....	177
8.51. Libffi-3.4.6 .....	178
8.52. Python-3.12.5 .....	179
8.53. Flit-Core-3.9.0 .....	181
8.54. Wheel-0.44.0 .....	182
8.55. Setuptools-72.2.0 .....	183

8.56. Ninja-1.12.1 .....	184
8.57. Meson-1.5.1 .....	185
8.58. Coreutils-9.5 .....	186
8.59. Check-0.15.2 .....	191
8.60. Diffutils-3.10 .....	192
8.61. Gawk-5.3.0 .....	193
8.62. Findutils-4.10.0 .....	194
8.63. Groff-1.23.0 .....	195
8.64. GRUB-2.12 .....	198
8.65. Gzip-1.13 .....	200
8.66. IPRoute2-6.10.0 .....	201
8.67. Kbd-2.6.4 .....	203
8.68. Libpipeline-1.5.7 .....	205
8.69. Make-4.4.1 .....	206
8.70. Patch-2.7.6 .....	207
8.71. Tar-1.35 .....	208
8.72. Texinfo-7.1 .....	209
8.73. Vim-9.1.0660 .....	211
8.74. MarkupSafe-2.1.5 .....	214
8.75. Jinja2-3.1.4 .....	215
8.76. Systemd-256.4 .....	216
8.77. D-Bus-1.14.10 .....	221
8.78. Man-DB-2.12.1 .....	223
8.79. Procps-ng-4.0.4 .....	226
8.80. Util-linux-2.40.2 .....	228
8.81. E2fsprogs-1.47.1 .....	233
8.82. About Debugging Symbols .....	236
8.83. Stripping .....	236
8.84. Cleaning Up .....	238
9. System Configuration .....	239
9.1. Introduction .....	239
9.2. General Network Configuration .....	239
9.3. Overview of Device and Module Handling .....	243
9.4. Managing Devices .....	246
9.5. Configuring the System Clock .....	246
9.6. Configuring the Linux Console .....	247
9.7. Configuring the System Locale .....	249
9.8. Creating the /etc/inputrc File .....	251
9.9. Creating the /etc/shells File .....	252
9.10. Systemd Usage and Configuration .....	253
10. Making the LFS System Bootable .....	256
10.1. Introduction .....	256
10.2. Creating the /etc/fstab File .....	256
10.3. Linux-6.10.5 .....	258
10.4. Using GRUB to Set Up the Boot Process .....	264
11. The End .....	267
11.1. The End .....	267

11.2. Get Counted .....	267
11.3. Rebooting the System .....	267
11.4. Additional Resources .....	268
11.5. Getting Started After LFS .....	269
V. Appendices .....	272
A. Acronyms and Terms .....	273
B. Acknowledgments .....	276
C. Dependencies .....	279
D. LFS Licenses .....	293
D.1. Creative Commons License .....	293
D.2. The MIT License .....	297
Index .....	298

# Preface

## Foreword

My journey to learn and better understand Linux began back in 1998. I had just installed my first Linux distribution and had quickly become intrigued with the whole concept and philosophy behind Linux.

There are always many ways to accomplish a single task. The same can be said about Linux distributions. A great many have existed over the years. Some still exist, some have morphed into something else, yet others have been relegated to our memories. They all do things differently to suit the needs of their target audience. Because so many different ways to accomplish the same end goal exist, I began to realize I no longer had to be limited by any one implementation. Prior to discovering Linux, we simply put up with issues in other Operating Systems as you had no choice. It was what it was, whether you liked it or not. With Linux, the concept of choice began to emerge. If you didn't like something, you were free, even encouraged, to change it.

I tried a number of distributions and could not decide on any one. They were great systems in their own right. It wasn't a matter of right and wrong anymore. It had become a matter of personal taste. With all that choice available, it became apparent that there would not be a single system that would be perfect for me. So I set out to create my own Linux system that would fully conform to my personal preferences.

To truly make it my own system, I resolved to compile everything from source code instead of using pre-compiled binary packages. This “perfect” Linux system would have the strengths of various systems without their perceived weaknesses. At first, the idea was rather daunting. I remained committed to the idea that such a system could be built.

After sorting through issues such as circular dependencies and compile-time errors, I finally built a custom-built Linux system. It was fully operational and perfectly usable like any of the other Linux systems out there at the time. But it was my own creation. It was very satisfying to have put together such a system myself. The only thing better would have been to create each piece of software myself. This was the next best thing.

As I shared my goals and experiences with other members of the Linux community, it became apparent that there was a sustained interest in these ideas. It quickly became plain that such custom-built Linux systems serve not only to meet user specific requirements, but also serve as an ideal learning opportunity for programmers and system administrators to enhance their (existing) Linux skills. Out of this broadened interest, the *Linux From Scratch Project* was born.

This Linux From Scratch book is the central core around that project. It provides the background and instructions necessary for you to design and build your own system. While this book provides a template that will result in a correctly working system, you are free to alter the instructions to suit yourself, which is, in part, an important part of this project. You remain in control; we just lend a helping hand to get you started on your own journey.

I sincerely hope you will have a great time working on your own Linux From Scratch system and enjoy the numerous benefits of having a system that is truly your own.

--  
Gerard Beekmans  
gerard@linuxfromscratch.org

## Audience

There are many reasons why you would want to read this book. One of the questions many people raise is, “why go through all the hassle of manually building a Linux system from scratch when you can just download and install an existing one?”



One important reason for this project's existence is to help you learn how a Linux system works from the inside out. Building an LFS system helps demonstrate what makes Linux tick, and how things work together and depend on each other. One of the best things this learning experience can provide is the ability to customize a Linux system to suit your own unique needs.

Another key benefit of LFS is that it gives you control of the system without relying on someone else's Linux implementation. With LFS, you are in the driver's seat. *You* dictate every aspect of your system.

LFS allows you to create very compact Linux systems. With other distributions you are often forced to install a great many programs you neither use nor understand. These programs waste resources. You may argue that with today's hard drives and CPUs, wasted resources are no longer a consideration. Sometimes, however, you are still constrained by the system's size, if nothing else. Think about bootable CDs, USB sticks, and embedded systems. Those are areas where LFS can be beneficial.

Another advantage of a custom built Linux system is security. By compiling the entire system from source code, you are empowered to audit everything and apply all the security patches you want. You don't have to wait for somebody else to compile binary packages that fix a security hole. Unless you examine the patch and implement it yourself, you have no guarantee that the new binary package was built correctly and adequately fixes the problem.

The goal of Linux From Scratch is to build a complete and usable foundation-level system. If you do not wish to build your own Linux system from scratch, you may nevertheless benefit from the information in this book.

There are too many good reasons to build your own LFS system to list them all here. In the end, education is by far the most important reason. As you continue your LFS experience, you will discover the power that information and knowledge can bring.

## LFS Target Architectures

The primary target architectures of LFS are the AMD/Intel x86 (32-bit) and x86\_64 (64-bit) CPUs. On the other hand, the instructions in this book are also known to work, with some modifications, with the Power PC and ARM CPUs. To build a system that utilizes one of these alternative CPUs, the main prerequisite, in addition to those on the next page, is an existing Linux system such as an earlier LFS installation, Ubuntu, Red Hat/Fedora, SuSE, or some other distribution that targets that architecture. (Note that a 32-bit distribution can be installed and used as a host system on a 64-bit AMD/Intel computer.)

The gain from building on a 64-bit system, as compared to a 32-bit system, is minimal. For example, in a test build of LFS-9.1 on a Core i7-4790 CPU based system, using 4 cores, the following statistics were measured:

Architecture	Build Time	Build Size
32-bit	239.9 minutes	3.6 GB
64-bit	233.2 minutes	4.4 GB

As you can see, on the same hardware, the 64-bit build is only 3% faster (and 22% larger) than the 32-bit build. If you plan to use LFS as a LAMP server, or a firewall, a 32-bit CPU may be good enough. On the other hand, several packages in BLFS now need more than 4 GB of RAM to be built and/or to run; if you plan to use LFS as a desktop, the LFS authors recommend building a 64-bit system.

The default 64-bit build that results from LFS is a “pure” 64-bit system. That is, it supports 64-bit executables only. Building a “multi-lib” system requires compiling many applications twice, once for a 32-bit system and once for a 64-bit system. This is not directly supported in LFS because it would interfere with the educational objective of providing the minimal instructions needed for a basic Linux system. Some of the LFS/BLFS editors maintain a multilib fork of LFS, accessible at <https://www.linuxfromscratch.org/~thomas/multilib/index.html>. But that's an advanced topic.

## Prerequisites

Building an LFS system is not a simple task. It requires a certain level of existing knowledge of Unix system administration in order to resolve problems and correctly execute the commands listed. In particular, as an absolute minimum, you should already know how to use the command line (shell) to copy or move files and directories, list directory and file contents, and change the current directory. It is also expected that you know how to use and install Linux software.

Because the LFS book assumes *at least* this basic level of skill, the various LFS support forums are unlikely to provide you with much assistance in these areas. You will find that your questions regarding such basic knowledge will likely go unanswered (or you will simply be referred to the LFS essential pre-reading list).

Before building an LFS system, we urge you to read these articles:

- Software-Building-HOWTO <https://tldp.org/HOWTO/Software-Building-HOWTO.html>

This is a comprehensive guide to building and installing “generic” Unix software packages under Linux. Although it was written some time ago, it still provides a good summary of the basic techniques used to build and install software.

- Beginner's Guide to Installing from Source <https://moi.vonos.net/linux/beginners-installing-from-source/>

This guide provides a good summary of the basic skills and techniques needed to build software from source code.

## LFS and Standards

The structure of LFS follows Linux standards as closely as possible. The primary standards are:

- *POSIX.1-2008*.
- *Filesystem Hierarchy Standard (FHS) Version 3.0*
- *Linux Standard Base (LSB) Version 5.0 (2015)*

The LSB has four separate specifications: Core, Desktop, Runtime Languages, and Imaging. Some parts of Core and Desktop specifications are architecture specific. There are also two optional specifications: Gtk3 and Graphics. LFS attempts to conform to the LSB specifications for the IA32 (32-bit x86) or AMD64 (x86\_64) architectures discussed in the previous section.



### Note

Many people do not agree with these requirements. The main purpose of the LSB is to ensure that proprietary software can be installed and run on a compliant system. Since LFS is source based, the user has complete control over what packages are desired; you may choose not to install some packages that are specified by the LSB.

While it is possible to create a complete system that will pass the LSB certification tests “from scratch,” this can’t be done without many additional packages that are beyond the scope of the LFS book. Installation instructions for these additional packages can be found in BLFS.

## Packages supplied by LFS needed to satisfy the LSB Requirements

*LSB Core:*

Bash, Bc, Binutils, Coreutils, Diffutils, File, Findutils, Gawk, Grep, Gzip, M4, Man-DB, Ncurses, Procps, Psmisc, Sed, Shadow, Tar, Util-linux, Zlib

<i>LSB Desktop:</i>	None
<i>LSB Runtime Languages:</i>	Perl, Python
<i>LSB Imaging:</i>	None
<i>LSB Gtk3 and LSB Graphics (Trial Use):</i>	None

## Packages supplied by BLFS needed to satisfy the LSB Requirements

<i>LSB Core:</i>	At, Batch (a part of At), Cpio, Ed, Fcfrontab, LSB-Tools, NSPR, NSS, PAM, Pax, Sendmail (or Postfix or Exim), time
<i>LSB Desktop:</i>	Alsa, ATK, Cairo, Desktop-file-utils, Freetype, Fontconfig, Gdk-pixbuf, Glib2, GTK+2, Icon-naming-utils, Libjpeg-turbo, Libpng, Libtiff, Libxml2, MesaLib, Pango, Xdg-utils, Xorg
<i>LSB Runtime Languages:</i>	Libxml2, Libxslt
<i>LSB Imaging:</i>	CUPS, Cups-filters, Ghostscript, SANE
<i>LSB Gtk3 and LSB Graphics (Trial Use):</i>	GTK+3

## Packages not supplied by LFS or BLFS needed to satisfy the LSB Requirements

<i>LSB Core:</i>	None
<i>LSB Desktop:</i>	Qt4 (but Qt5 is provided)
<i>LSB Runtime Languages:</i>	None
<i>LSB Imaging:</i>	None
<i>LSB Gtk3 and LSB Graphics (Trial Use):</i>	None

## Rationale for Packages in the Book

The goal of LFS is to build a complete and usable foundation-level system—including all the packages needed to replicate itself—and providing a relatively minimal base from which to customize a more complete system based on the user's choices. This does not mean that LFS is the smallest system possible. Several important packages are included that are not, strictly speaking, required. The list below documents the reasons each package in the book has been included.

- **Acl**  
This package contains utilities to administer Access Control Lists, which are used to define fine-grained discretionary access rights for files and directories.
- **Attr**  
This package contains programs for managing extended attributes on file system objects.
- **Autoconf**  
This package supplies programs for producing shell scripts that can automatically configure source code from a developer's template. It is often needed to rebuild a package after the build procedure has been updated.
- **Automake**  
This package contains programs for generating Make files from a template. It is often needed to rebuild a package after the build procedure has been updated.
- **Bash**

This package satisfies an LSB core requirement to provide a Bourne Shell interface to the system. It was chosen over other shell packages because of its common usage and extensive capabilities.

- Bc

This package provides an arbitrary precision numeric processing language. It satisfies a requirement for building the Linux kernel.

- Binutils

This package supplies a linker, an assembler, and other tools for handling object files. The programs in this package are needed to compile most of the packages in an LFS system.

- Bison

This package contains the GNU version of yacc (Yet Another Compiler Compiler) needed to build several of the LFS programs.

- Bzip2

This package contains programs for compressing and decompressing files. It is required to decompress many LFS packages.

- Check

This package provides a test harness for other programs.

- Coreutils

This package contains a number of essential programs for viewing and manipulating files and directories. These programs are needed for command line file management, and are necessary for the installation procedures of every package in LFS.

- D-Bus

This package contains programs to implement a message bus system, a simple way for applications to talk to one another.

- DejaGNU

This package supplies a framework for testing other programs.

- Diffutils

This package contains programs that show the differences between files or directories. These programs can be used to create patches, and are also used in many packages' build procedures.

- E2fsprogs

This package supplies utilities for handling the ext2, ext3 and ext4 file systems. These are the most common and thoroughly tested file systems that Linux supports.

- Expat

This package yields a relatively small XML parsing library. It is required by the XML::Parser Perl module.

- Expect

This package contains a program for carrying out scripted dialogues with other interactive programs. It is commonly used for testing other packages.

- File

This package contains a utility for determining the type of a given file or files. A few packages need it in their build scripts.

- Findutils

This package provides programs to find files in a file system. It is used in many packages' build scripts.

- Flex

This package contains a utility for generating programs that recognize patterns in text. It is the GNU version of the lex (lexical analyzer) program. It is required to build several LFS packages.

- Gawk

This package supplies programs for manipulating text files. It is the GNU version of awk (Aho-Weinberg-Kernighan). It is used in many other packages' build scripts.

- GCC

This is the Gnu Compiler Collection. It contains the C and C++ compilers as well as several others not built by LFS.

- GDBM

This package contains the GNU Database Manager library. It is used by one other LFS package, Man-DB.

- Gettext

This package provides utilities and libraries for the internationalization and localization of many packages.

- Glibc

This package contains the main C library. Linux programs will not run without it.

- GMP

This package supplies math libraries that provide useful functions for arbitrary precision arithmetic. It is needed to build GCC.

- Gperf

This package produces a program that generates a perfect hash function from a set of keys. It is required by Systemd.

- Grep

This package contains programs for searching through files. These programs are used by most packages' build scripts.

- Groff

This package contributes programs for processing and formatting text. One important function of these programs is to format man pages.

- GRUB

This is the Grand Unified Boot Loader. It is the most flexible of several boot loaders available.

- Gzip

This package contains programs for compressing and decompressing files. It is needed to decompress many packages in LFS.

- Iana-etc

This package provides data for network services and protocols. It is needed to enable proper networking capabilities.

- Inetutils

This package supplies programs for basic network administration.

- Intltool

This package contributes tools for extracting translatable strings from source files.

- IProute2

This package contains programs for basic and advanced IPv4 and IPv6 networking. It was chosen over the other common network tools package (net-tools) for its IPv6 capabilities.

- Jinja2

This package is a Python module for text templating. It's required to build Systemd.

- Kbd

This package produces key-table files, keyboard utilities for non-US keyboards, and a number of console fonts.

- Kmod

This package supplies programs needed to administer Linux kernel modules.

- Less

This package contains a very nice text file viewer that allows scrolling up or down when viewing a file. Many packages use it for paging the output.

- Libcap

This package implements the userspace interfaces to the POSIX 1003.1e capabilities available in Linux kernels.

- Libelf

The elfutils project provides libraries and tools for ELF files and DWARF data. Most utilities in this package are available in other packages, but the library is needed to build the Linux kernel using the default (and most efficient) configuration.

- Libffi

This package implements a portable, high level programming interface to various calling conventions. Some programs may not know at the time of compilation what arguments are to be passed to a function. For instance, an interpreter may be told at run-time about the number and types of arguments used to call a given function. Libffi can be used in such programs to provide a bridge from the interpreter program to compiled code.

- Libpipeline

The Libpipeline package supplies a library for manipulating pipelines of subprocesses in a flexible and convenient way. It is required by the Man-DB package.

- Libtool

This package contains the GNU generic library support script. It wraps the complexity of using shared libraries into a consistent, portable interface. It is needed by the test suites in other LFS packages.

- Libxcrypt

This package provides the `libcrypt` library needed by various packages (notably, Shadow) for hashing passwords. It replaces the obsolete `libcrypt` implementation in Glibc.

- Linux Kernel

This package is the Operating System. It is the Linux in the GNU/Linux environment.

- M4

This package provides a general text macro processor useful as a build tool for other programs.

- Make

This package contains a program for directing the building of packages. It is required by almost every package in LFS.

- MarkupSafe

This package is a Python module for processing strings in HTML/XHTML/XML safely. Jinja2 requires this package.

- Man-DB

This package contains programs for finding and viewing man pages. It was chosen instead of the `man` package because of its superior internationalization capabilities. It supplies the `man` program.

- Man-pages

This package provides the actual contents of the basic Linux man pages.

- Meson

This package provides a software tool for automating the building of software. The main goal of Meson is to minimize the amount of time that software developers need to spend configuring a build system. It's required to build Systemd, as well as many BLFS packages.

- MPC

This package supplies arithmetic functions for complex numbers. It is required by GCC.

- MPFR

This package contains functions for multiple precision arithmetic. It is required by GCC.

- Ninja

This package furnishes a small build system with a focus on speed. It is designed to have its input files generated by a higher-level build system, and to run builds as fast as possible. This package is required by Meson.

- Ncurses

This package contains libraries for terminal-independent handling of character screens. It is often used to provide cursor control for a menuing system. It is needed by a number of the packages in LFS.

- Openssl

This package provides management tools and libraries relating to cryptography. These supply cryptographic functions to other packages, including the Linux kernel.

- Patch

This package contains a program for modifying or creating files by applying a *patch* file typically created by the diff program. It is needed by the build procedure for several LFS packages.

- Perl

This package is an interpreter for the runtime language PERL. It is needed for the installation and test suites of several LFS packages.

- Pkgconf

This package contains a program which helps to configure compiler and linker flags for development libraries. The program can be used as a drop-in replacement of **pkg-config**, which is needed by the building system of many packages. It's maintained more actively and slightly faster than the original Pkg-config package.

- Procps-NG

This package contains programs for monitoring processes. These programs are useful for system administration, and are also used by the LFS Bootscripts.

- Psmisc

This package produces programs for displaying information about running processes. These programs are useful for system administration.

- Python 3

This package provides an interpreted language that has a design philosophy emphasizing code readability.

- Readline

This package is a set of libraries that offer command-line editing and history capabilities. It is used by Bash.

- Sed

This package allows editing of text without opening it in a text editor. It is also needed by many LFS packages' configure scripts.

- Shadow

This package contains programs for handling passwords securely.

- Systemd

This package provides an init program and several additional boot and system control capabilities as an alternative to SysVinit. It is used by many Linux distributions.

- Tar

This package provides archiving and extraction capabilities of virtually all the packages used in LFS.

- Tcl

This package contains the Tool Command Language used in many test suites.

- Texinfo

This package supplies programs for reading, writing, and converting info pages. It is used in the installation procedures of many LFS packages.

- Util-linux

This package contains miscellaneous utility programs. Among them are utilities for handling file systems, consoles, partitions, and messages.



- Vim
 

This package provides an editor. It was chosen because of its compatibility with the classic vi editor and its huge number of powerful capabilities. An editor is a very personal choice for many users. Any other editor can be substituted, if you wish.
- Wheel
 

This package supplies a Python module that is the reference implementation of the Python wheel packaging standard.
- XML::Parser
 

This package is a Perl module that interfaces with Expat.
- XZ Utils
 

This package contains programs for compressing and decompressing files. It provides the highest compression generally available and is useful for decompressing packages in XZ or LZMA format.
- Zlib
 

This package contains compression and decompression routines used by some programs.
- Zstd
 

This package supplies compression and decompression routines used by some programs. It provides high compression ratios and a very wide range of compression / speed trade-offs.

## Typography

To make things easier to follow, there are a few typographical conventions used throughout this book. This section contains some examples of the typographical format found throughout Linux From Scratch.

```
./configure --prefix=/usr
```

This form of text is designed to be typed exactly as seen unless otherwise noted in the surrounding text. It is also used in the explanation sections to identify which of the commands is being referenced.

In some cases, a logical line is extended to two or more physical lines with a backslash at the end of the line.

```
CC="gcc -B/usr/bin/" ../binutils-2.18/configure \
--prefix=/tools --disable-nls --disable-werror
```

Note that the backslash must be followed by an immediate return. Other whitespace characters like spaces or tab characters will create incorrect results.

```
install-info: unknown option '--dir-file=/mnt/lfs/usr/info/dir'
```

This form of text (fixed-width text) shows screen output, usually as the result of commands issued. This format is also used to show filenames, such as `/etc/ld.so.conf`.



### Note

Please configure your browser to display fixed-width text with a good monospace" font-size="9ptd font, with which you can distinguish the glyphs of `111` or `00` clearly.

*Emphasis*

This form of text is used for several purposes in the book. Its main purpose is to emphasize important points or items.

*<https://www.linuxfromscratch.org/>*

This format is used for hyperlinks both within the LFS community and to external pages. It includes HOWTOs, download locations, and websites.

```
cat > $LFS/etc/group << "EOF"
root:x:0:
bin:x:1:
.....
EOF
```

This format is used when creating configuration files. The first command tells the system to create the file `$LFS/etc/group` from whatever is typed on the following lines until the sequence End Of File (EOF) is encountered. Therefore, this entire section is generally typed as seen.

*<REPLACED TEXT>*

This format is used to encapsulate text that is not to be typed as seen or for copy-and-paste operations.

*[OPTIONAL TEXT]*

This format is used to encapsulate text that is optional.

*passwd(5)*

This format is used to refer to a specific manual (man) page. The number inside parentheses indicates a specific section inside the manuals. For example, **passwd** has two man pages. Per LFS installation instructions, those two man pages will be located at `/usr/share/man/man1/passwd.1` and `/usr/share/man/man5/passwd.5`. When the book uses *passwd(5)* it is specifically referring to `/usr/share/man/man5/passwd.5`. **man passwd** will print the first man page it finds that matches “passwd,” which will be `/usr/share/man/man1/passwd.1`. For this example, you will need to run **man 5 passwd** in order to read the page being specified. Note that most man pages do not have duplicate page names in different sections. Therefore, **man <program name>** is generally sufficient. In the LFS book these references to man pages are also hyperlinks, so clicking on such a reference will open the man page rendered in HTML from *Arch Linux manual pages*.

## Structure

This book is divided into the following parts.

### Part I - Introduction

Part I explains a few important notes on how to proceed with the LFS installation. This section also provides meta-information about the book.

### Part II - Preparing for the Build

Part II describes how to prepare for the building process—making a partition, downloading the packages, and compiling temporary tools.

### Part III - Building the LFS Cross Toolchain and Temporary Tools

Part III provides instructions for building the tools needed for constructing the final LFS system.

## Part IV - Building the LFS System

Part IV guides the reader through the building of the LFS system—compiling and installing all the packages one by one, setting up the boot scripts, and installing the kernel. The resulting Linux system is the foundation on which other software can be built to expand the system as desired. At the end of this book, there is an easy to use reference listing all of the programs, libraries, and important files that have been installed.

## Part V - Appendices

Part V provides information about the book itself including acronyms and terms, acknowledgments, package dependencies, a listing of LFS boot scripts, licenses for the distribution of the book, and a comprehensive index of packages, programs, libraries, and scripts.

## Errata and Security Advisories

The software used to create an LFS system is constantly being updated and enhanced. Security warnings and bug fixes may become available after the LFS book has been released. To check whether the package versions or instructions in this release of LFS need any modifications—to repair security vulnerabilities or to fix other bugs—please visit <https://www.linuxfromscratch.org/lfs/errata/12.2-systemd/> before proceeding with your build. You should note any changes shown and apply them to the relevant sections of the book as you build the LFS system.

In addition, the Linux From Scratch editors maintain a list of security vulnerabilities discovered *after* a book has been released. To read the list, please visit <https://www.linuxfromscratch.org/lfs/advisories/> before proceeding with your build. You should apply the changes suggested by the advisories to the relevant sections of the book as you build the LFS system. And, if you will use the LFS system as a real desktop or server system, you should continue to consult the advisories and fix any security vulnerabilities, even when the LFS system has been completely constructed.

# Part I. Introduction

# Chapter 1. Introduction

## 1.1. How to Build an LFS System

The LFS system will be built by using an already installed Linux distribution (such as Debian, OpenMandriva, Fedora, or openSUSE). This existing Linux system (the host) will be used as a starting point to provide necessary programs, including a compiler, linker, and shell, to build the new system. Select the “development” option during the distribution installation to include these tools.



### Note

There are many ways to install a Linux distribution and the defaults are usually not optimal for building an LFS system. For suggestions on setting up a commercial distribution see: <https://www.linuxfromscratch.org/hints/downloads/files/partitioning-for-lfs.txt>.

As an alternative to installing a separate distribution on your machine, you may wish to use a LiveCD from a commercial distribution.

Chapter 2 of this book describes how to create a new Linux native partition and file system, where the new LFS system will be compiled and installed. Chapter 3 explains which packages and patches must be downloaded to build an LFS system, and how to store them on the new file system. Chapter 4 discusses the setup of an appropriate working environment. Please read Chapter 4 carefully as it explains several important issues you should be aware of before you begin to work your way through Chapter 5 and beyond.

Chapter 5 explains the installation of the initial tool chain, (binutils, gcc, and glibc) using cross-compilation techniques to isolate the new tools from the host system.

Chapter 6 shows you how to cross-compile basic utilities using the just built cross-toolchain.

Chapter 7 then enters a "chroot" environment, where we use the new tools to build all the rest of the tools needed to create the LFS system.

This effort to isolate the new system from the host distribution may seem excessive. A full technical explanation as to why this is done is provided in Toolchain Technical Notes.

In Chapter 8 the full-blown LFS system is built. Another advantage provided by the chroot environment is that it allows you to continue using the host system while LFS is being built. While waiting for package compilations to complete, you can continue using your computer as usual.

To finish the installation, the basic system configuration is set up in Chapter 9, and the kernel and boot loader are created in Chapter 10. Chapter 11 contains information on continuing the LFS experience beyond this book. After the steps in this chapter have been implemented, the computer is ready to boot into the new LFS system.

This is the process in a nutshell. Detailed information on each step is presented in the following chapters. Items that seem complicated now will be clarified, and everything will fall into place as you commence your LFS adventure.

## 1.2. What's new since the last release

Here is a list of the packages updated since the previous release of LFS.

**Upgraded to:**

-

- Automake-1.17
- Bash-5.2.32
- Bc-6.7.6
- Binutils-2.43.1
- Coreutils-9.5
- E2fsprogs-1.47.1
- Expat-2.6.2
- Findutils-4.10.0
- GCC-14.2.0
- GDBM-1.24
- Gettext-0.22.5
- Glibc-2.40
- Iana-Etc-20240806
- IPRoute2-6.10.0
- Jinja2-3.1.4
- Kmod-33
- Less-661
- Libcap-2.70
- Libelf from Elfutils-0.191
- Libffi-3.4.6
- Linux-6.10.5
- Lz4-1.10.0
- Man-DB-2.12.1
- Man-pages-6.9.1
- Meson-1.5.1
- Ncurses-6.5
- Ninja-1.12.1
- OpenSSL-3.3.1
- Perl-5.40.0
- Pkgconf-2.3.0
- Psmisc-23.7
- Python-3.12.5
- Readline-8.2.13

- Setuptools-72.2.0
- Shadow-4.16.0
- Systemd-256.4
- Tcl-8.6.14
- Util-linux-2.40.2
- Vim-9.1.0660
- Wheel-0.44.0
- Xz-5.6.2
- Zstd-1.5.6

**Added:**

- Lz4-1.10.0

**Removed:**

- bash-5.2.21-upstream\_fixes-1.patch
- readline-8.2-upstream\_fixes-3.patch

## 1.3. Changelog

This is version 12.2-systemd of the Linux From Scratch book, dated September 1st, 2024. If this book is more than six months old, a newer and better version is probably already available. To find out, please check one of the mirrors via <https://www.linuxfromscratch.org/mirrors.html>.

Below is a list of changes made since the previous release of the book.

**Changelog Entries:**

- 2024-09-01
  - [bdubbs] - LFS-12.2 released.
- 2024-08-17
  - [bdubbs] - Update to setuptools-72.2.0. Fixes #5542.
  - [bdubbs] - Update to kmod-33. Fixes #5540.
  - [bdubbs] - Update to binutils-2.43.1. Fixes #5543.
  - [bdubbs] - Update to linux-6.10.5. Fixes #5541.
- 2024-08-15
  - [bdubbs] - Update to iana-etc-20240806. Addresses #5006.
  - [bdubbs] - Update to pkgconf-2.3.0. Fixes #5537.
  - [bdubbs] - Update to python3-3.12.5. Fixes #5538.
  - [bdubbs] - Update to linux-6.10.4. Fixes #5539.
- 2024-08-05

- [bdubbs] - Update to bash-5.2.32. Fixes #5532.
- [bdubbs] - Update to iana-etc-20240801. Addresses #5006.
- [bdubbs] - Update to vim-9.1.0660. Addresses #4500.
- [bdubbs] - Update to binutils-2.43. Fixes #5535.
- [bdubbs] - Update to linux-6.10.3. Fixes #5534.
- [bdubbs] - Update to readline-8.2.13. Fixes #5533.
- [bdubbs] - Update to wheel-0.44.0. Fixes #5536.
- 2024-08-01
  - [bdubbs] - Update to gcc-14.2.0. Fixes #5530.
  - [bdubbs] - Update to iana-etc-20240723. Addresses #5006.
  - [bdubbs] - Update to glibc-2.40. Fixes #5529.
  - [bdubbs] - Update to iproute2-6.10.0. Fixes #5523.
  - [bdubbs] - Update to linux-6.10.2. Fixes #5521.
  - [bdubbs] - Update to lz4-1.10.0. Fixes #5526.
  - [bdubbs] - Update to meson-1.5.1. Fixes #5527.
  - [bdubbs] - Update to setuptools-72.1.0. Fixes #5531.
  - [bdubbs] - Update to systemd-256.4. Fixes #5518.
- 2024-07-15
  - [bdubbs] - Update to iana-etc-20240701. Addresses #5006.
  - [bdubbs] - Update to vim-9.1.0580. Addresses #4500.
  - [bdubbs] - Update to automake-1.17. Fixes #5520.
  - [bdubbs] - Update to gdbm-1.24. Fixes #5515.
  - [bdubbs] - Update to linux-6.9.9. Fixes #5517.
  - [bdubbs] - Update to less-661. Fixes #5513.
  - [bdubbs] - Update to meson-1.5.0. Fixes #5519.
  - [bdubbs] - Update to setuptools-70.3.0. Fixes #5514.
  - [bdubbs] - Update to util-linux-2.40.2. Fixes #5516.
- 2024-07-01
  - [bdubbs] - Update to iana-etc-20240612. Addresses #5006.
  - [bdubbs] - Update to bc-6.7.6. Fixes #5506.
  - [bdubbs] - Update to man-pages-6.9.1. Fixes #5507.
  - [bdubbs] - Update to linux-6.9.7. Fixes #5508.
  - [bdubbs] - Update to shadow-4.16.0. Fixes #5510.
  - [bdubbs] - Update to systemd-256.1. Fixes #5511.
  - [bdubbs] - Update to setuptools-70.1.1. Fixes #5512.
- 2024-06-15



- [bdubbs] - Update to vim-9.1.0478. Addresses #4500.
- [bdubbs] - Update to iana-etc-20240607. Addresses #5006.
- [bdubbs] - Update to systemd-256. Fixes #5504.
- [bdubbs] - Update to python3-3.12.4. Fixes #5502.
- [bdubbs] - Update to perl-5.40.0. Fixes #5503.
- [bdubbs] - Update to openssl-3.3.1 (Security fix). Fixes #5500.
- [bdubbs] - Update to linux-6.9.4. Fixes #5505.
- [bdubbs] - Update to findutils-4.10.0. Fixes #5499.
- 2024-05-31
  - [bdubbs] - Update to meson-1.4.1. Fixes #5498.
  - [bdubbs] - Update to xz-5.6.2. Fixes #5471.
  - [bdubbs] - Add linux-6.9.x compatibility instructions to systemd . Fixes #5496.
  - [bdubbs] - Update to setuputils-70.0.0 (python module). Fixes #5491.
  - [bdubbs] - Update to ninja-1.12.1. Fixes #5489.
  - [bdubbs] - Update to man-pages-6.8. Fixes #5494.
  - [bdubbs] - Update to linux-6.9.3. Fixes #5491.
  - [bdubbs] - Update to libcap-2.70. Fixes #5493.
  - [bdubbs] - Update to iproute2-6.9.0. Fixes #5492.
  - [bdubbs] - Update to e2fsprogs-1.47.1. Fixes #5495.
- 2024-05-13
  - [xry111] - Synchronize coreutils i18n patch from Fedora to fix a build failure on 32-bit x86 and an alarming compiler warning on both 32-bit x86 and x86\_64 with GCC 14.1 or later.
- 2024-05-11
  - [bdubbs] - Update to vim-9.1.0405. Addresses #4500.
  - [bdubbs] - Update to util-linux-2.40.1. Fixes #5482.
  - [bdubbs] - Update to linux-6.8.9. Fixes #5484.
  - [bdubbs] - Update to jinja2-3.1.4 (Python module). Fixes #5485.
  - [bdubbs] - Update to iana-etc-20240502. Addresses #5006.
  - [bdubbs] - Update to gcc-14.1.0. Fixes #5486.
- 2024-05-01
  - [bdubbs] - Add security fix to glibc. Fixes #5481.
  - [bdubbs] - Update to linux-6.8.8. Fixes #5480.
  - [bdubbs] - Update to ncurses-6.5. Fixes #5483.
- 2024-04-16
  - [bdubbs] - Make minor change to ifup script output text.
- 2024-04-15

- [bdubbs] - Update to setuptools-69.5.1. Fixes #5478.
- [bdubbs] - Update to python3-3.12.3. Fixes #5476.
- [bdubbs] - Update to openssl-3.3.0. Fixes #5475.
- [bdubbs] - Update to ninja-1.12.0. Fixes #5477.
- [bdubbs] - Update to man-db-2.12.1. Fixes #5474.
- [bdubbs] - Update to linux-6.8.6. Fixes #5472.
- [bdubbs] - Update to iana-etc-20240412. Addresses #5006.
- [bdubbs] - Update to vim-9.1.0330. Addresses #4500.
- 2024-03-31
  - [bdubbs] - Update to iana-etc-20240318. Addresses #5006.
  - [bdubbs] - Update to zstd-1.5.6. Fixes #5468.
  - [bdubbs] - Update to util-linux-2.40. Fixes #5430.
  - [bdubbs] - Update to shadow-4.15.1. Fixes #5465.
  - [bdubbs] - Update to pkgconf-2.2.0. Fixes #5469.
  - [bdubbs] - Update to linux-6.8.2. Fixes #5467.
  - [bdubbs] - Update to coreutils-9.5. Fixes #5470.
- 2024-03-29
  - [bdubbs] - Revert to xz-5.4.6 due to upstream compromise.
- 2024-03-19
  - [renodr] - Update to iproute2-6.8.0. Fixes #5458.
  - [renodr] - Update to man-pages-6.7. Fixes #5464.
  - [renodr] - Update to Linux-6.8.1. Fixes #5453.
  - [renodr] - Added LZ4 to the book. Fixes #5463.
- 2024-03-15
  - [bdubbs] - Update to wheel-0.43.0. Fixes #5459.
  - [bdubbs] - Update to setuptools-69.2.0 (Python module). Fixes #5462.
  - [bdubbs] - Update to meson-1.4.0. Fixes #5460.
  - [bdubbs] - Update to expat-2.6.2 (Security fix). Fixes #5461.
  - [bdubbs] - Update to iana-etc-20240305. Addresses #5006.
  - [bdubbs] - Update to vim-9.1.0161. Addresses #4500.
  - [bdubbs] - Update to xz-5.6.1. Fixes #5457.
  - [bdubbs] - Update to shadow-4.15.0. Fixes #5456.
  - [bdubbs] - Update to psmisc-23.7. Fixes #5454.
  - [bdubbs] - Update to kmod-32. Fixes #5455.
  - [bdubbs] - Update to elfutils-0.191. Fixes #5451.
- 2024-03-02

- [bdubbs] - Update to iana-etc-20240222. Addresses #5006.
- [bdubbs] - Update to vim-9.1.0145. Addresses #4500.
- [bdubbs] - Update to xz-5.6.0. Fixes #5447.
- [bdubbs] - Update to tcl-8.6.14. Fixes #5448.
- [bdubbs] - Update to shadow-4.14.6. Fixes #5450.
- [bdubbs] - Update to setuptools-69.1.1. Fixes #5446.
- [bdubbs] - Update to linux-6.7.7. Fixes #5444.
- [bdubbs] - Update to libffi-3.4.6. Fixes #5443.
- [bdubbs] - Update to gettext-0.22.5. Fixes #5445.
- [bdubbs] - Update to expat-2.6.1. Fixes #5449.
- 2024-03-01
  - [bdubbs] - LFS-12.1 released.

## 1.4. Resources

### 1.4.1. FAQ

If during the building of the LFS system you encounter any errors, have any questions, or think there is a typo in the book, please start by consulting the list of Frequently Asked Questions (FAQ), located at <https://www.linuxfromscratch.org/faq/>.

### 1.4.2. Mailing Lists

The [linuxfromscratch.org](https://www.linuxfromscratch.org) server hosts a number of mailing lists used for the development of the LFS project. These lists include the main development and support lists, among others. If you cannot find an answer to your problem on the FAQ page, the next step would be to search the mailing lists at <https://www.linuxfromscratch.org/search.html>.

For information on the different lists, how to subscribe, archive locations, and additional information, visit <https://www.linuxfromscratch.org/mail.html>.

### 1.4.3. IRC

Several members of the LFS community offer assistance via Internet Relay Chat (IRC). Before using this support, please make sure your question is not already answered in the LFS FAQ or the mailing list archives. You can find the IRC network at [irc.libera.chat](https://irc.libera.chat). The support channel is named #lfs-support.

### 1.4.4. Mirror Sites

The LFS project has a number of world-wide mirrors to make accessing the website and downloading the required packages more convenient. Please visit the LFS website at <https://www.linuxfromscratch.org/mirrors.html> for a list of current mirrors.

### 1.4.5. Contact Information

Please direct all your questions and comments to one of the LFS mailing lists (see above).

## 1.5. Help



### Note

In case you've hit an issue building one package with the LFS instruction, we strongly discourage posting the issue directly onto the upstream support channel before discussing via a LFS support channel listed in Section 1.4, “Resources.” Doing so is often quite inefficient because the upstream maintainers are rarely familiar with LFS building procedure. Even if you've really hit an upstream issue, the LFS community can still help to isolate the information wanted by the upstream maintainers and make a proper report.

If you must ask a question directly via an upstream support channel, you shall at least note that many upstream projects have the support channels separated from the bug tracker. The “bug” reports for asking questions are considered invalid and may annoy upstream developers for these projects.

If an issue or a question is encountered while working through this book, please check the FAQ page at <https://www.linuxfromscratch.org/faq/#generalfaq>. Questions are often already answered there. If your question is not answered on that page, try to find the source of the problem. The following hint will give you some guidance for troubleshooting: <https://www.linuxfromscratch.org/hints/downloads/files/errors.txt>.

If you cannot find your problem listed in the FAQ, search the mailing lists at <https://www.linuxfromscratch.org/search.html>.

We also have a wonderful LFS community that is willing to offer assistance through the mailing lists and IRC (see the Section 1.4, “Resources” section of this book). However, we get several support questions every day, and many of them could have been easily answered by going to the FAQ or by searching the mailing lists first. So, for us to offer the best assistance possible, you should first do some research on your own. That allows us to focus on the more unusual support needs. If your searches do not produce a solution, please include all the relevant information (mentioned below) in your request for help.

### 1.5.1. Things to Mention

Apart from a brief explanation of the problem being experienced, any request for help should include these essential things:

- The version of the book being used (in this case 12.2-systemd)
- The host distribution and version being used to create LFS
- The output from the Host System Requirements script
- The package or section the problem was encountered in
- The exact error message, or a clear description of the problem
- Note whether you have deviated from the book at all



### Note

Deviating from this book does *not* mean that we will not help you. After all, LFS is about personal preference. Being up-front about any changes to the established procedure helps us evaluate and determine possible causes of your problem.

### 1.5.2. Configure Script Problems

If something goes wrong while running the **configure** script, review the `config.log` file. This file may contain errors encountered during **configure** which were not printed to the screen. Include the *relevant* lines if you need to ask for help.

### 1.5.3. Compilation Problems

Both the screen output and the contents of various files are useful in determining the cause of compilation problems. The screen output from the **configure** script and the **make** run can be helpful. It is not necessary to include the entire output, but do include all of the relevant information. Here is an example of the type of information to include from the **make** screen output.

```
gcc -D ALIASEPATH="/mnt/lfs/usr/share/locale:."
-D LOCALEDIR="/mnt/lfs/usr/share/locale"
-D LIBDIR="/mnt/lfs/usr/lib"
-D INCLUDEDIR="/mnt/lfs/usr/include" -D HAVE_CONFIG_H -I. -I.
-g -O2 -c getopt1.c
gcc -g -O2 -static -o make ar.o arscan.o commands.o dir.o
expand.o file.o function.o getopt.o implicit.o job.o main.o
misc.o read.o remake.o rule.o signame.o variable.o vpath.o
default.o remote-stub.o version.o opt1.o
-lutil job.o: In function `load_too_high':
/lfs/tmp/make-3.79.1/job.c:1565: undefined reference
to `getloadavg'
collect2: ld returned 1 exit status
make[2]: *** [make] Error 1
make[2]: Leaving directory `/lfs/tmp/make-3.79.1'
make[1]: *** [all-recursive] Error 1
make[1]: Leaving directory `/lfs/tmp/make-3.79.1'
make: *** [all-recursive-am] Error 2
```

In this case, many people would just include the bottom section:

```
make [2]: *** [make] Error 1
```

This is not enough information to diagnose the problem, because it only notes that something went wrong, not *what* went wrong. The entire section, as in the example above, is what should be saved because it includes the command that was executed and all the associated error messages.

An excellent article about asking for help on the Internet is available online at <http://catb.org/~esr/faqs/smart-questions.html>. Read this document, and follow the hints. Doing so will increase the likelihood of getting the help you need.

## **Part II. Preparing for the Build**

# Chapter 2. Preparing the Host System

## 2.1. Introduction

In this chapter, the host tools needed for building LFS are checked and, if necessary, installed. Then a partition which will host the LFS system is prepared. We will create the partition itself, create a file system on it, and mount it.

## 2.2. Host System Requirements

### 2.2.1. Hardware

The LFS editors recommend that the system CPU have at least four cores and that the system have at least 8 GB of memory. Older systems that do not meet these requirements will still work, but the time to build packages will be significantly longer than documented.

### 2.2.2. Software

Your host system should have the following software with the minimum versions indicated. This should not be an issue for most modern Linux distributions. Also note that many distributions will place software headers into separate packages, often in the form of `<package-name>-devel` or `<package-name>-dev`. Be sure to install those if your distribution provides them.

Earlier versions of the listed software packages may work, but have not been tested.

- **Bash-3.2** (/bin/sh should be a symbolic or hard link to bash)
- **Binutils-2.13.1** (Versions greater than 2.43.1 are not recommended as they have not been tested)
- **Bison-2.7** (/usr/bin/yacc should be a link to bison or a small script that executes bison)
- **Coreutils-8.1**
- **Diffutils-2.8.1**
- **Findutils-4.2.31**
- **Gawk-4.0.1** (/usr/bin/awk should be a link to gawk)
- **GCC-5.2** including the C++ compiler, `g++` (Versions greater than 14.2.0 are not recommended as they have not been tested). C and C++ standard libraries (with headers) must also be present so the C++ compiler can build hosted programs
- **Grep-2.5.1a**
- **Gzip-1.3.12**
- **Linux Kernel-4.19**

The reason for the kernel version requirement is that we specify that version when building `glibc` in Chapter 5 and Chapter 8, so the workarounds for older kernels are not enabled and the compiled `glibc` is slightly faster and smaller. As at Feb 2024, 4.19 is the oldest kernel release still supported by the kernel developers. Some kernel releases older than 4.19 may be still supported by third-party teams, but they are not considered official upstream kernel releases; read <https://kernel.org/category/releases.html> for the details.

If the host kernel is earlier than 4.19 you will need to replace the kernel with a more up-to-date version. There are two ways you can go about this. First, see if your Linux vendor provides a 4.19 or later kernel package. If so, you may wish to install it. If your vendor doesn't offer an acceptable kernel package, or you would prefer not to install it, you can compile a kernel yourself. Instructions for compiling the kernel and configuring the boot loader (assuming the host uses GRUB) are located in Chapter 10.

We require the host kernel to support UNIX 98 pseudo terminal (PTY). It should be enabled on all desktop or server distros shipping Linux 4.19 or a newer kernel. If you are building a custom host kernel, ensure `CONFIG_UNIX98_PTYS` is set to `y` in the kernel configuration.

- **M4-1.4.10**
- **Make-4.0**
- **Patch-2.5.4**
- **Perl-5.8.8**
- **Python-3.4**
- **Sed-4.1.5**
- **Tar-1.22**
- **Texinfo-5.0**
- **Xz-5.0.0**



### Important

Note that the symlinks mentioned above are required to build an LFS system using the instructions contained within this book. Symlinks that point to other software (such as dash, mawk, etc.) may work, but are not tested or supported by the LFS development team, and may require either deviation from the instructions or additional patches to some packages.

To see whether your host system has all the appropriate versions, and the ability to compile programs, run the following commands:

```
cat > version-check.sh << "EOF"
#!/bin/bash
# A script to list version numbers of critical development tools

# If you have tools installed in other directories, adjust PATH here AND
# in ~lfs/.bashrc (section 4.4) as well.

LC_ALL=C
PATH=/usr/bin:/bin

bail() { echo "FATAL: $1"; exit 1; }
grep --version > /dev/null 2> /dev/null || bail "grep does not work"
sed '' /dev/null || bail "sed does not work"
sort /dev/null || bail "sort does not work"

ver_check()
{
    if ! type -p $2 &>/dev/null
    then
        echo "ERROR: Cannot find $2 ($1)"; return 1;
    fi
    v=$(($2 --version 2>&1 | grep -E -o '[0-9]+\.[0-9\.]+[a-z]*' | head -n1)
    if printf '%s\n' $3 $v | sort --version-sort --check &>/dev/null
    then
        printf "OK:    %-9s %-6s >= $3\n" "$1" "$v"; return 0;
    else
        printf "ERROR: %-9s is TOO OLD ($3 or later required)\n" "$1";
        return 1;
    fi
}

ver_kernel()
{
```



```

kver=$(uname -r | grep -E -o '[0-9\.]+')
if printf '%s\n' $1 $kver | sort --version-sort --check &>/dev/null
then
    printf "OK:    Linux Kernel $kver >= $1\n"; return 0;
else
    printf "ERROR: Linux Kernel ($kver) is TOO OLD ($1 or later required)\n" "$kver";
    return 1;
fi
}

# Coreutils first because --version-sort needs Coreutils >= 7.0
ver_check Coreutils      sort      8.1 || bail "Coreutils too old, stop"
ver_check Bash           bash      3.2
ver_check Binutils       ld        2.13.1
ver_check Bison          bison    2.7
ver_check Diffutils      diff     2.8.1
ver_check Findutils      find     4.2.31
ver_check Gawk           gawk     4.0.1
ver_check GCC            gcc      5.2
ver_check "GCC (C++)"    g++     5.2
ver_check Grep           grep     2.5.1a
ver_check Gzip           gzip     1.3.12
ver_check M4             m4      1.4.10
ver_check Make           make     4.0
ver_check Patch          patch    2.5.4
ver_check Perl           perl     5.8.8
ver_check Python         python3  3.4
ver_check Sed            sed     4.1.5
ver_check Tar            tar     1.22
ver_check Texinfo        texi2any 5.0
ver_check Xz            xz      5.0.0
ver_kernel 4.19

if mount | grep -q 'devpts on /dev/pts' && [ -e /dev/ptmx ]
then echo "OK:    Linux Kernel supports UNIX 98 PTY";
else echo "ERROR: Linux Kernel does NOT support UNIX 98 PTY"; fi

alias_check() {
    if $1 --version 2>&1 | grep -qi $2
    then printf "OK:    %-4s is $2\n" "$1";
    else printf "ERROR: %-4s is NOT $2\n" "$1"; fi
}
echo "Aliases:"
alias_check awk GNU
alias_check yacc Bison
alias_check sh Bash

echo "Compiler check:"
if printf "int main(){}" | g++ -x c++ -
then echo "OK:    g++ works";
else echo "ERROR: g++ does NOT work"; fi
rm -f a.out

if [ "$(nproc)" = "" ]; then
    echo "ERROR: nproc is not available or it produces empty output"
else
    echo "OK: nproc reports $(nproc) logical cores are available"
fi
EOF

bash version-check.sh

```

## 2.3. Building LFS in Stages

LFS is designed to be built in one session. That is, the instructions assume that the system will not be shut down during the process. This does not mean that the system has to be built in one sitting. The issue is that certain procedures must be repeated after a reboot when resuming LFS at different points.

### 2.3.1. Chapters 1–4

These chapters run commands on the host system. When restarting, be certain of one thing:

- Procedures performed as the `root` user after Section 2.4 must have the LFS environment variable set *FOR THE ROOT USER*.

### 2.3.2. Chapters 5–6

- The `/mnt/lfs` partition must be mounted.
- These two chapters *must* be done as user `lfs`. A `su - lfs` command must be issued before performing any task in these chapters. If you don't do that, you are at risk of installing packages to the host, and potentially rendering it unusable.
- The procedures in General Compilation Instructions are critical. If there is any doubt a package has been installed correctly, ensure the previously expanded tarball has been removed, then re-extract the package, and complete all the instructions in that section.

### 2.3.3. Chapters 7–10

- The `/mnt/lfs` partition must be mounted.
- A few operations, from “Changing Ownership” to “Entering the Chroot Environment,” must be done as the `root` user, with the LFS environment variable set for the `root` user.
- When entering chroot, the LFS environment variable must be set for `root`. The LFS variable is not used after the chroot environment has been entered.
- The virtual file systems must be mounted. This can be done before or after entering chroot by changing to a host virtual terminal and, as `root`, running the commands in Section 7.3.1, “Mounting and Populating `/dev`” and Section 7.3.2, “Mounting Virtual Kernel File Systems.”

## 2.4. Creating a New Partition

Like most other operating systems, LFS is usually installed on a dedicated partition. The recommended approach to building an LFS system is to use an available empty partition or, if you have enough unpartitioned space, to create one.

A minimal system requires a partition of around 10 gigabytes (GB). This is enough to store all the source tarballs and compile the packages. However, if the LFS system is intended to be the primary Linux system, additional software will probably be installed which will require additional space. A 30 GB partition is a reasonable size to provide for growth. The LFS system itself will not take up this much room. A large portion of this requirement is to provide sufficient free temporary storage as well as for adding additional capabilities after LFS is complete. Additionally, compiling packages can require a lot of disk space which will be reclaimed after the package is installed.

Because there is not always enough Random Access Memory (RAM) available for compilation processes, it is a good idea to use a small disk partition as `swap` space. This is used by the kernel to store seldom-used data and leave more memory available for active processes. The `swap` partition for an LFS system can be the same as the one used by the host system, in which case it is not necessary to create another one.

Start a disk partitioning program such as **cdisk** or **fdisk** with a command line option naming the hard disk on which the new partition will be created—for example `/dev/sda` for the primary disk drive. Create a Linux native partition and a `swap` partition, if needed. Please refer to *cdisk(8)* or *fdisk(8)* if you do not yet know how to use the programs.



### Note

For experienced users, other partitioning schemes are possible. The new LFS system can be on a software *RAID* array or an *LVM* logical volume. However, some of these options require an *initramfs*, which is an advanced topic. These partitioning methodologies are not recommended for first time LFS users.

Remember the designation of the new partition (e.g., `sda5`). This book will refer to this as the LFS partition. Also remember the designation of the `swap` partition. These names will be needed later for the `/etc/fstab` file.

## 2.4.1. Other Partition Issues

Requests for advice on system partitioning are often posted on the LFS mailing lists. This is a highly subjective topic. The default for most distributions is to use the entire drive with the exception of one small swap partition. This is not optimal for LFS for several reasons. It reduces flexibility, makes sharing of data across multiple distributions or LFS builds more difficult, makes backups more time consuming, and can waste disk space through inefficient allocation of file system structures.

### 2.4.1.1. The Root Partition

A root LFS partition (not to be confused with the `/root` directory) of twenty gigabytes is a good compromise for most systems. It provides enough space to build LFS and most of BLFS, but is small enough so that multiple partitions can be easily created for experimentation.

### 2.4.1.2. The Swap Partition

Most distributions automatically create a swap partition. Generally the recommended size of the swap partition is about twice the amount of physical RAM, however this is rarely needed. If disk space is limited, hold the swap partition to two gigabytes and monitor the amount of disk swapping.

If you want to use the hibernation feature (suspend-to-disk) of Linux, it writes out the contents of RAM to the swap partition before turning off the machine. In this case the size of the swap partition should be at least as large as the system's installed RAM.

Swapping is never good. For mechanical hard drives you can generally tell if a system is swapping by just listening to disk activity and observing how the system reacts to commands. With an SSD you will not be able to hear swapping, but you can tell how much swap space is being used by running the **top** or **free** programs. Use of an SSD for a swap partition should be avoided if possible. The first reaction to swapping should be to check for an unreasonable command such as trying to edit a five gigabyte file. If swapping becomes a normal occurrence, the best solution is to purchase more RAM for your system.

### 2.4.1.3. The Grub Bios Partition

If the *boot disk* has been partitioned with a GUID Partition Table (GPT), then a small, typically 1 MB, partition must be created if it does not already exist. This partition is not formatted, but must be available for GRUB to use during installation of the boot loader. This partition will normally be labeled 'BIOS Boot' if using **fdisk** or have a code of *EF02* if using the **gdisk** command.



## Note

The Grub Bios partition must be on the drive that the BIOS uses to boot the system. This is not necessarily the drive that holds the LFS root partition. The disks on a system may use different partition table types. The necessity of the Grub Bios partition depends only on the partition table type of the boot disk.

### 2.4.1.4. Convenience Partitions

There are several other partitions that are not required, but should be considered when designing a disk layout. The following list is not comprehensive, but is meant as a guide.

- `/boot` – Highly recommended. Use this partition to store kernels and other booting information. To minimize potential boot problems with larger disks, make this the first physical partition on your first disk drive. A partition size of 200 megabytes is adequate.
- `/boot/efi` – The EFI System Partition, which is needed for booting the system with UEFI. Read *the BLFS page* for details.
- `/home` – Highly recommended. Share your home directory and user customization across multiple distributions or LFS builds. The size is generally fairly large and depends on available disk space.
- `/usr` – In LFS, `/bin`, `/lib`, and `/sbin` are symlinks to their counterparts in `/usr`. So `/usr` contains all the binaries needed for the system to run. For LFS a separate partition for `/usr` is normally not needed. If you create it anyway, you should make a partition large enough to fit all the programs and libraries in the system. The root partition can be very small (maybe just one gigabyte) in this configuration, so it's suitable for a thin client or diskless workstation (where `/usr` is mounted from a remote server). However, you should be aware that an `initramfs` (not covered by LFS) will be needed to boot a system with a separate `/usr` partition.
- `/opt` – This directory is most useful for BLFS, where multiple large packages like KDE or Texlive can be installed without embedding the files in the `/usr` hierarchy. If used, 5 to 10 gigabytes is generally adequate.
- `/tmp` – By default, `systemd` mounts a `tmpfs` here. If you want to override that behavior, follow Section 9.10.3, “Disabling `tmpfs` for `/tmp`” when configuring the LFS system.
- `/usr/src` – This partition is very useful for providing a location to store BLFS source files and share them across LFS builds. It can also be used as a location for building BLFS packages. A reasonably large partition of 30-50 gigabytes provides plenty of room.

Any separate partition that you want automatically mounted when the system starts must be specified in the `/etc/fstab` file. Details about how to specify partitions will be discussed in Section 10.2, “Creating the `/etc/fstab` File”.

## 2.5. Creating a File System on the Partition

A partition is just a range of sectors on a disk drive, delimited by boundaries set in a partition table. Before the operating system can use a partition to store any files, the partition must be formatted to contain a file system, typically consisting of a label, directory blocks, data blocks, and an indexing scheme to locate a particular file on demand. The file system also helps the OS keep track of free space on the partition, reserve the needed sectors when a new file is created or an existing file is extended, and recycle the free data segments created when files are deleted. It may also provide support for data redundancy, and for error recovery.

LFS can use any file system recognized by the Linux kernel, but the most common types are `ext3` and `ext4`. The choice of the right file system can be complex; it depends on the characteristics of the files and the size of the partition. For example:

ext2

is suitable for small partitions that are updated infrequently such as /boot.

ext3

is an upgrade to ext2 that includes a journal to help recover the partition's status in the case of an unclean shutdown. It is commonly used as a general purpose file system.

ext4

is the latest version of the ext family of file systems. It provides several new capabilities including nano-second timestamps, creation and use of very large files (up to 16 TB), and speed improvements.

Other file systems, including FAT32, NTFS, JFS, and XFS are useful for specialized purposes. More information about these file systems, and many others, can be found at [https://en.wikipedia.org/wiki/Comparison\\_of\\_file\\_systems](https://en.wikipedia.org/wiki/Comparison_of_file_systems).

LFS assumes that the root file system (/) is of type ext4. To create an ext4 file system on the LFS partition, issue the following command:

```
mkfs -v -t ext4 /dev/<xxx>
```

Replace <xxx> with the name of the LFS partition.

If you are using an existing swap partition, there is no need to format it. If a new swap partition was created, it will need to be initialized with this command:

```
mkswap /dev/<yyy>
```

Replace <yyy> with the name of the swap partition.

## 2.6. Setting The \$LFS Variable

Throughout this book, the environment variable LFS will be used several times. You should ensure that this variable is always defined throughout the LFS build process. It should be set to the name of the directory where you will be building your LFS system - we will use /mnt/lfs as an example, but you may choose any directory name you want. If you are building LFS on a separate partition, this directory will be the mount point for the partition. Choose a directory location and set the variable with the following command:

```
export LFS=/mnt/lfs
```

Having this variable set is beneficial in that commands such as **mkdir -v \$LFS/tools** can be typed literally. The shell will automatically replace “\$LFS” with “/mnt/lfs” (or whatever value the variable was set to) when it processes the command line.



### Caution

Do not forget to check that LFS is set whenever you leave and reenter the current working environment (such as when doing a **su** to root or another user). Check that the LFS variable is set up properly with:

```
echo $LFS
```

Make sure the output shows the path to your LFS system's build location, which is /mnt/lfs if the provided example was followed. If the output is incorrect, use the command given earlier on this page to set \$LFS to the correct directory name.



## Note

One way to ensure that the `LFS` variable is always set is to edit the `.bash_profile` file in both your personal home directory and in `/root/.bash_profile` and enter the export command above. In addition, the shell specified in the `/etc/passwd` file for all users that need the `LFS` variable must be `bash` to ensure that the `/root/.bash_profile` file is incorporated as a part of the login process.

Another consideration is the method that is used to log into the host system. If logging in through a graphical display manager, the user's `.bash_profile` is not normally used when a virtual terminal is started. In this case, add the export command to the `.bashrc` file for the user and `root`. In addition, some distributions use an "if" test, and do not run the remaining `.bashrc` instructions for a non-interactive bash invocation. Be sure to place the export command ahead of the test for non-interactive use.

## 2.7. Mounting the New Partition

Now that a file system has been created, the partition must be mounted so the host system can access it. This book assumes that the file system is mounted at the directory specified by the `LFS` environment variable described in the previous section.

Strictly speaking, one cannot "mount a partition." One mounts the *file system* embedded in that partition. But since a single partition can't contain more than one file system, people often speak of the partition and the associated file system as if they were one and the same.

Create the mount point and mount the LFS file system with these commands:

```
mkdir -pv $LFS
mount -v -t ext4 /dev/<xxx> $LFS
```

Replace `<xxx>` with the name of the LFS partition.

If you are using multiple partitions for LFS (e.g., one for `/` and another for `/home`), mount them like this:

```
mkdir -pv $LFS
mount -v -t ext4 /dev/<xxx> $LFS
mkdir -v $LFS/home
mount -v -t ext4 /dev/<yyy> $LFS/home
```

Replace `<xxx>` and `<yyy>` with the appropriate partition names.

Ensure that this new partition is not mounted with permissions that are too restrictive (such as the `nosuid` or `nodev` options). Run the `mount` command without any parameters to see what options are set for the mounted LFS partition. If `nosuid` and/or `nodev` are set, the partition must be remounted.



## Warning

The above instructions assume that you will not restart your computer throughout the LFS process. If you shut down your system, you will either need to remount the LFS partition each time you restart the build process, or modify the host system's `/etc/fstab` file to automatically remount it when you reboot. For example, you might add this line to your `/etc/fstab` file:

```
/dev/<xxx> /mnt/lfs ext4 defaults 1 1
```

If you use additional optional partitions, be sure to add them also.

If you are using a `swap` partition, ensure that it is enabled using the **swapon** command:

```
/sbin/swapon -v /dev/<zzz>
```

Replace `<zzz>` with the name of the `swap` partition.

Now that the new LFS partition is open for business, it's time to download the packages.

# Chapter 3. Packages and Patches

## 3.1. Introduction

This chapter includes a list of packages that need to be downloaded in order to build a basic Linux system. The listed version numbers correspond to versions of the software that are known to work, and this book is based on their use. We highly recommend against using different versions, because the build commands for one version may not work with a different version, unless the different version is specified by an LFS erratum or security advisory. The newest package versions may also have problems that require work-arounds. These work-arounds will be developed and stabilized in the development version of the book.

For some packages, the release tarball and the (Git or SVN) repository snapshot tarball for that release may be published with similar file names. A release tarball contains generated files (for example, a **configure** script generated by **autoconf**), in addition to the contents of the corresponding repository snapshot. The book uses release tarballs whenever possible. Using a repository snapshot instead of a release tarball specified by the book will cause problems.

Download locations may not always be accessible. If a download location has changed since this book was published, Google (<https://www.google.com/>) provides a useful search engine for most packages. If this search is unsuccessful, try one of the alternative means of downloading at <https://www.linuxfromscratch.org/lfs/mirrors.html#files>.

Downloaded packages and patches will need to be stored somewhere that is conveniently available throughout the entire build. A working directory is also required to unpack the sources and build them. `$LFS/sources` can be used both as the place to store the tarballs and patches and as a working directory. By using this directory, the required elements will be located on the LFS partition and will be available during all stages of the building process.

To create this directory, execute the following command, as user `root`, before starting the download session:

```
mkdir -v $LFS/sources
```

Make this directory writable and sticky. “Sticky” means that even if multiple users have write permission on a directory, only the owner of a file can delete the file within a sticky directory. The following command will enable the write and sticky modes:

```
chmod -v a+wt $LFS/sources
```

There are several ways to obtain all the necessary packages and patches to build LFS:

- The files can be downloaded individually as described in the next two sections.
- For stable versions of the book, a tarball of all the needed files can be downloaded from one of the mirror sites listed at <https://www.linuxfromscratch.org/mirrors.html#files>.
- The files can be downloaded using **wget** and a `wget-list` as described below.

To download all of the packages and patches by using `wget-list-systemd` as an input to the **wget** command, use:

```
wget --input-file=wget-list-systemd --continue --directory-prefix=$LFS/sources
```

Additionally, starting with LFS-7.0, there is a separate file, `md5sums`, which can be used to verify that all the correct packages are available before proceeding. Place that file in `$LFS/sources` and run:

```
pushd $LFS/sources
md5sum -c md5sums
popd
```



This check can be used after retrieving the needed files with any of the methods listed above.

If the packages and patches are downloaded as a non-`root` user, these files will be owned by the user. The file system records the owner by its UID, and the UID of a normal user in the host distro is not assigned in LFS. So the files will be left owned by an unnamed UID in the final LFS system. If you won't assign the same UID for your user in the LFS system, change the owners of these files to `root` now to avoid this issue:

```
chown root:root $LFS/sources/*
```

## 3.2. All Packages



### Note

Read the *security advisories* before downloading packages to figure out if a newer version of any package should be used to avoid security vulnerabilities.

The upstream sources may remove old releases, especially when those releases contain a security vulnerability. If one URL below is not reachable, you should read the security advisories first to figure out if a newer version (with the vulnerability fixed) should be used. If not, try to download the removed package from a mirror. Although it's possible to download an old release from a mirror even if this release has been removed because of a vulnerability, it's not a good idea to use a release known to be vulnerable when building your system.

Download or otherwise obtain the following packages:

- **Acl (2.3.2) - 363 KB:**

Home page: <https://savannah.nongnu.org/projects/acl>

Download: <https://download.savannah.gnu.org/releases/acl/acl-2.3.2.tar.xz>

MD5 sum: 590765dee95907dbc3c856f7255bd669

- **Attr (2.5.2) - 484 KB:**

Home page: <https://savannah.nongnu.org/projects/attr>

Download: <https://download.savannah.gnu.org/releases/attr/attr-2.5.2.tar.gz>

MD5 sum: 227043ec2f6ca03c0948df5517f9c927

- **Autoconf (2.72) - 1,360 KB:**

Home page: <https://www.gnu.org/software/autoconf/>

Download: <https://ftp.gnu.org/gnu/autoconf/autoconf-2.72.tar.xz>

MD5 sum: 1be79f7106ab6767f18391c5e22be701

- **Automake (1.17) - 1,614 KB:**

Home page: <https://www.gnu.org/software/automake/>

Download: <https://ftp.gnu.org/gnu/automake/automake-1.17.tar.xz>

MD5 sum: 7ab3a02318fee6f5bd42adfc369abf10

- **Bash (5.2.32) - 10,697 KB:**

Home page: <https://www.gnu.org/software/bash/>

Download: <https://ftp.gnu.org/gnu/bash/bash-5.2.32.tar.gz>

MD5 sum: f204835b2e06c06e37b5ad776ff907f4

• **Bc (6.7.6) - 463 KB:**

Home page: <https://git.gavinhoward.com/gavin/bc>

Download: <https://github.com/gavinhoward/bc/releases/download/6.7.6/bc-6.7.6.tar.xz>

MD5 sum: a47aa5e4e7395fbc159a9228613b97b

• **Binutils (2.43.1) - 27,514 KB:**

Home page: <https://www.gnu.org/software/binutils/>

Download: <https://sourceware.org/pub/binutils/releases/binutils-2.43.1.tar.xz>

MD5 sum: 9202d02925c30969d1917e4bad5a2320

• **Bison (3.8.2) - 2,752 KB:**

Home page: <https://www.gnu.org/software/bison/>

Download: <https://ftp.gnu.org/gnu/bison/bison-3.8.2.tar.xz>

MD5 sum: c28f119f405a2304ff0a7ccdcc629713

• **Bzip2 (1.0.8) - 792 KB:**

Download: <https://www.sourceware.org/pub/bzip2/bzip2-1.0.8.tar.gz>

MD5 sum: 67e051268d0c475ea773822f7500d0e5

• **Check (0.15.2) - 760 KB:**

Home page: <https://libcheck.github.io/check>

Download: <https://github.com/libcheck/check/releases/download/0.15.2/check-0.15.2.tar.gz>

MD5 sum: 50fcdfcecd5a380415b12e9c574e0b2

• **Coreutils (9.5) - 5,867 KB:**

Home page: <https://www.gnu.org/software/coreutils/>

Download: <https://ftp.gnu.org/gnu/coreutils/coreutils-9.5.tar.xz>

MD5 sum: e99adfa059a63db3503cc71f3d151e31

• **D-Bus (1.14.10) - 1,344 KB:**

Home page: <https://www.freedesktop.org/wiki/Software/dbus>

Download: <https://dbus.freedesktop.org/releases/dbus/dbus-1.14.10.tar.xz>

MD5 sum: 46070a3487817ff690981f8cd2ba9376

• **DejaGNU (1.6.3) - 608 KB:**

Home page: <https://www.gnu.org/software/dejagnu/>

Download: <https://ftp.gnu.org/gnu/dejagnu/dejagnu-1.6.3.tar.gz>

MD5 sum: 68c5208c58236eba447d7d6d1326b821

• **Diffutils (3.10) - 1,587 KB:**

Home page: <https://www.gnu.org/software/diffutils/>

Download: <https://ftp.gnu.org/gnu/diffutils/diffutils-3.10.tar.xz>

MD5 sum: 2745c50f6f4e395e7b7d52f902d075bf

• **E2fsprogs (1.47.1) - 9,720 KB:**

Home page: <https://e2fsprogs.sourceforge.net/>

Download: <https://downloads.sourceforge.net/project/e2fsprogs/e2fsprogs/v1.47.1/e2fsprogs-1.47.1.tar.gz>

MD5 sum: 75e6d1353cbe6d5728a98fb0267206cb

• **Elfutils (0.191) - 9,092 KB:**

Home page: <https://sourceware.org/elfutils/>

Download: <https://sourceware.org/ftp/elfutils/0.191/elfutils-0.191.tar.bz2>

MD5 sum: 636547248fb3fae58ec48030298d3ef7

- **Expat (2.6.2) - 474 KB:**

Home page: <https://libexpat.github.io/>

Download: <https://prdownloads.sourceforge.net/expat/expat-2.6.2.tar.xz>

MD5 sum: 0cb75c8feb842c0794ba89666b762a2d

- **Expect (5.45.4) - 618 KB:**

Home page: <https://core.tcl.tk/expect/>

Download: <https://prdownloads.sourceforge.net/expect/expect5.45.4.tar.gz>

MD5 sum: 00fce8de158422f5ccd2666512329bd2

- **File (5.45) - 1,218 KB:**

Home page: <https://www.darwinsys.com/file/>

Download: <https://astron.com/pub/file/file-5.45.tar.gz>

MD5 sum: 26b2a96d4e3a8938827a1e572afd527a

- **Findutils (4.10.0) - 2,189 KB:**

Home page: <https://www.gnu.org/software/findutils/>

Download: <https://ftp.gnu.org/gnu/findutils/findutils-4.10.0.tar.xz>

MD5 sum: 870cfd71c07d37ebe56f9f4aaf4ad872

- **Flex (2.6.4) - 1,386 KB:**

Home page: <https://github.com/westes/flex>

Download: <https://github.com/westes/flex/releases/download/v2.6.4/flex-2.6.4.tar.gz>

MD5 sum: 2882e3179748cc9f9c23ec593d6adc8d

- **Flit-core (3.9.0) - 41 KB:**

Home page: <https://pypi.org/project/flit-core/>

Download: [https://pypi.org/packages/source/f/flit-core/flit\\_core-3.9.0.tar.gz](https://pypi.org/packages/source/f/flit-core/flit_core-3.9.0.tar.gz)

MD5 sum: 3bc52f1952b9a78361114147da63c35b

- **Gawk (5.3.0) - 3,356 KB:**

Home page: <https://www.gnu.org/software/gawk/>

Download: <https://ftp.gnu.org/gnu/gawk/gawk-5.3.0.tar.xz>

MD5 sum: 97c5a7d83f91a7e1b2035ebbe6ac7abd

- **GCC (14.2.0) - 90,144 KB:**

Home page: <https://gcc.gnu.org/>

Download: <https://ftp.gnu.org/gnu/gcc/gcc-14.2.0/gcc-14.2.0.tar.xz>

MD5 sum: 2268420ba02dc01821960e274711bde0

- **GDBM (1.24) - 1,168 KB:**

Home page: <https://www.gnu.org/software/gdbm/>

Download: <https://ftp.gnu.org/gnu/gdbm/gdbm-1.24.tar.gz>

MD5 sum: c780815649e52317be48331c1773e987

- **Gettext (0.22.5) - 10,031 KB:**

Home page: <https://www.gnu.org/software/gettext/>

Download: <https://ftp.gnu.org/gnu/gettext/gettext-0.22.5.tar.xz>

MD5 sum: 3ae5580599d84be93e6213930facb2db

**• Glibc (2.40) - 18,313 KB:**Home page: <https://www.gnu.org/software/libc/>Download: <https://ftp.gnu.org/gnu/glibc/glibc-2.40.tar.xz>

MD5 sum: b390feef233022114950317f10c4fa97

**Note**

The Glibc developers maintain a *Git branch* containing patches considered worthy for Glibc-2.40 but unfortunately developed after Glibc-2.40 release. The LFS editors will issue a security advisory if any security fix is added into the branch, but no actions will be taken for other newly added patches. You may review the patches yourself and incorporate some patches if you consider them important.

**• GMP (6.3.0) - 2,046 KB:**Home page: <https://www.gnu.org/software/gmp/>Download: <https://ftp.gnu.org/gnu/gmp/gmp-6.3.0.tar.xz>

MD5 sum: 956dc04e864001a9c22429f761f2c283

**• Gperf (3.1) - 1,188 KB:**Home page: <https://www.gnu.org/software/gperf/>Download: <https://ftp.gnu.org/gnu/gperf/gperf-3.1.tar.gz>

MD5 sum: 9e251c0a618ad0824b51117d5d9db87e

**• Grep (3.11) - 1,664 KB:**Home page: <https://www.gnu.org/software/grep/>Download: <https://ftp.gnu.org/gnu/grep/grep-3.11.tar.xz>

MD5 sum: 7c9bbd74492131245f7cdb291fa142c0

**• Groff (1.23.0) - 7,259 KB:**Home page: <https://www.gnu.org/software/groff/>Download: <https://ftp.gnu.org/gnu/groff/groff-1.23.0.tar.gz>

MD5 sum: 5e4f40315a22bb8a158748e7d5094c7d

**• GRUB (2.12) - 6,524 KB:**Home page: <https://www.gnu.org/software/grub/>Download: <https://ftp.gnu.org/gnu/grub/grub-2.12.tar.xz>

MD5 sum: 60c564b1bdc39d8e43b3aab4bc0fb140

**• Gzip (1.13) - 819 KB:**Home page: <https://www.gnu.org/software/gzip/>Download: <https://ftp.gnu.org/gnu/gzip/gzip-1.13.tar.xz>

MD5 sum: d5c9fc9441288817a4a0be2da0249e29

**• Iana-Etc (20240806) - 590 KB:**Home page: <https://www.iana.org/protocols>Download: <https://github.com/Mic92/iana-etc/releases/download/20240806/iana-etc-20240806.tar.gz>

MD5 sum: ea3c37c00d22f1159fc3b7d988de8476

**• Inetutils (2.5) - 1,632 KB:**Home page: <https://www.gnu.org/software/inetutils/>Download: <https://ftp.gnu.org/gnu/inetutils/inetutils-2.5.tar.xz>

MD5 sum: 9e5a6dfd2d794dc056a770e8ad4a9263

• **Intltool (0.51.0) - 159 KB:**

Home page: <https://freedesktop.org/wiki/Software/intltool>

Download: <https://launchpad.net/intltool/trunk/0.51.0/+download/intltool-0.51.0.tar.gz>

MD5 sum: 12e517cac2b57a0121cda351570f1e63

• **IPRoute2 (6.10.0) - 900 KB:**

Home page: <https://www.kernel.org/pub/linux/utils/net/iproute2/>

Download: <https://www.kernel.org/pub/linux/utils/net/iproute2/iproute2-6.10.0.tar.xz>

MD5 sum: 6282e47de9c5b230e83537fba7181c9c

• **Jinja2 (3.1.4) - 235 KB:**

Home page: <https://jinja.palletsprojects.com/en/3.1.x/>

Download: <https://pypi.org/packages/source/J/Jinja2/jinja2-3.1.4.tar.gz>

MD5 sum: 02ca9a6364c92e83d14b037bef4732bc

• **Kbd (2.6.4) - 1,470 KB:**

Home page: <https://kbd-project.org/>

Download: <https://www.kernel.org/pub/linux/utils/kbd/kbd-2.6.4.tar.xz>

MD5 sum: e2fd7adccf6b1e98eb1ae8d5a1ce5762

• **Kmod (33) - 503 KB:**

Home page: <https://github.com/kmod-project/kmod>

Download: <https://www.kernel.org/pub/linux/utils/kernel/kmod/kmod-33.tar.xz>

MD5 sum: c451c4aa61521adbe8af147f498046f8

• **Less (661) - 634 KB:**

Home page: <https://www.greenwoodsoftware.com/less/>

Download: <https://www.greenwoodsoftware.com/less/less-661.tar.gz>

MD5 sum: 44f54b6313c5d71fa1ac224d8d84766a

• **Libcap (2.70) - 187 KB:**

Home page: <https://sites.google.com/site/fullycapable/>

Download: <https://www.kernel.org/pub/linux/libs/security/linux-privs/libcap2/libcap-2.70.tar.xz>

MD5 sum: df0e20c6eeca849347b87d5d6a8870c0

• **Libffi (3.4.6) - 1,360 KB:**

Home page: <https://sourceware.org/libffi/>

Download: <https://github.com/libffi/libffi/releases/download/v3.4.6/libffi-3.4.6.tar.gz>

MD5 sum: b9cac6c5997dca2b3787a59ede34e0eb

• **Libpipeline (1.5.7) - 956 KB:**

Home page: <https://libpipeline.nongnu.org/>

Download: <https://download.savannah.gnu.org/releases/libpipeline/libpipeline-1.5.7.tar.gz>

MD5 sum: 1a48b5771b9f6c790fb4efdb1ac71342

• **Libtool (2.4.7) - 996 KB:**

Home page: <https://www.gnu.org/software/libtool/>

Download: <https://ftp.gnu.org/gnu/libtool/libtool-2.4.7.tar.xz>

MD5 sum: 2fc0b6ddcd66a89ed6e45db28fa44232

- **Libxcrypt (4.4.36) - 610 KB:**

Home page: <https://github.com/besser82/libxcrypt/>

Download: <https://github.com/besser82/libxcrypt/releases/download/v4.4.36/libxcrypt-4.4.36.tar.xz>

MD5 sum: b84cd4104e08c975063ec6c4d0372446

- **Linux (6.10.5) - 141,739 KB:**

Home page: <https://www.kernel.org/>

Download: <https://www.kernel.org/pub/linux/kernel/v6.x/linux-6.10.5.tar.xz>

MD5 sum: 276ef1f11ed3713ec5d6f506ff55ac12



### Note

The Linux kernel is updated quite frequently, many times due to discoveries of security vulnerabilities. The latest available stable kernel version may be used, unless the errata page says otherwise.

For users with limited speed or expensive bandwidth who wish to update the Linux kernel, a baseline version of the package and patches can be downloaded separately. This may save some time or cost for a subsequent patch level upgrade within a minor release.

- **Lz4 (1.10.0) - 379 KB:**

Home page: <https://lz4.org/>

Download: <https://github.com/lz4/lz4/releases/download/v1.10.0/lz4-1.10.0.tar.gz>

MD5 sum: dead9f5f1966d9ae56e1e32761e4e675

- **M4 (1.4.19) - 1,617 KB:**

Home page: <https://www.gnu.org/software/m4/>

Download: <https://ftp.gnu.org/gnu/m4/m4-1.4.19.tar.xz>

MD5 sum: 0d90823e1426f1da2fd872df0311298d

- **Make (4.4.1) - 2,300 KB:**

Home page: <https://www.gnu.org/software/make/>

Download: <https://ftp.gnu.org/gnu/make/make-4.4.1.tar.gz>

MD5 sum: c8469a3713cbb04d955d4ae4be23eeb

- **Man-DB (2.12.1) - 1,994 KB:**

Home page: <https://www.nongnu.org/man-db/>

Download: <https://download.savannah.gnu.org/releases/man-db/man-db-2.12.1.tar.xz>

MD5 sum: 7b044e5020aab89db41ac7ee59d6d84a

- **Man-pages (6.9.1) - 1,821 KB:**

Home page: <https://www.kernel.org/doc/man-pages/>

Download: <https://www.kernel.org/pub/linux/docs/man-pages/man-pages-6.9.1.tar.xz>

MD5 sum: 4d56775b6cce4edf1e496249e7c01c1a

- **MarkupSafe (2.1.5) - 19 KB:**

Home page: <https://palletsprojects.com/p/markupsafe/>

Download: <https://pypi.org/packages/source/M/MarkupSafe/MarkupSafe-2.1.5.tar.gz>

MD5 sum: 8fe7227653f2fb9b1ffe7f9f2058998a

- **Meson (1.5.1) - 2,205 KB:**

Home page: <https://mesonbuild.com>

Download: <https://github.com/mesonbuild/meson/releases/download/1.5.1/meson-1.5.1.tar.gz>

MD5 sum: c4f2b3e5ea632685f61ba1b833c4905c

• **MPC (1.3.1) - 756 KB:**

Home page: <https://www.multiprecision.org/>

Download: <https://ftp.gnu.org/gnu/mpc/mpc-1.3.1.tar.gz>

MD5 sum: 5c9bc658c9fd0f940e8e3e0f09530c62

• **MPFR (4.2.1) - 1,459 KB:**

Home page: <https://www.mpfr.org/>

Download: <https://ftp.gnu.org/gnu/mpfr/mpfr-4.2.1.tar.xz>

MD5 sum: 523c50c6318dde6f9dc523bc0244690a

• **Ncurses (6.5) - 2,156 KB:**

Home page: <https://www.gnu.org/software/ncurses/>

Download: <https://invisible-mirror.net/archives/ncurses/ncurses-6.5.tar.gz>

MD5 sum: ac2d2629296f04c8537ca706b6977687

• **Ninja (1.12.1) - 235 KB:**

Home page: <https://ninja-build.org/>

Download: <https://github.com/ninja-build/ninja/archive/v1.12.1/ninja-1.12.1.tar.gz>

MD5 sum: 6288992b05e593a391599692e2f7e490

• **OpenSSL (3.3.1) - 17,633 KB:**

Home page: <https://www.openssl.org/>

Download: <https://www.openssl.org/source/openssl-3.3.1.tar.gz>

MD5 sum: 8a4342b399c18f870ca6186299195984

• **Patch (2.7.6) - 766 KB:**

Home page: <https://savannah.gnu.org/projects/patch/>

Download: <https://ftp.gnu.org/gnu/patch/patch-2.7.6.tar.xz>

MD5 sum: 78ad9937e4caadcba1526ef1853730d5

• **Perl (5.40.0) - 13,481 KB:**

Home page: <https://www.perl.org/>

Download: <https://www.cpan.org/src/5.0/perl-5.40.0.tar.xz>

MD5 sum: cfe14ef0709b9687f9c514042e8e1e82

• **Pkgconf (2.3.0) - 309 KB:**

Home page: <https://github.com/pkgconf/pkgconf>

Download: <https://distfiles.ariadne.space/pkgconf/pkgconf-2.3.0.tar.xz>

MD5 sum: 833363e77b5bed0131c7bc4cc6f7747b

• **Procps (4.0.4) - 1,369 KB:**

Home page: <https://gitlab.com/procps-ng/procps/>

Download: <https://sourceforge.net/projects/procps-ng/files/Production/procps-ng-4.0.4.tar.xz>

MD5 sum: 2f747fc7df8ccf402d03e375c565cf96

• **Psmisc (23.7) - 423 KB:**

Home page: <https://gitlab.com/psmisc/psmisc>

Download: <https://sourceforge.net/projects/psmisc/files/psmisc/psmisc-23.7.tar.xz>

MD5 sum: 53eae841735189a896d614cba440eb10

**• Python (3.12.5) - 19,944 KB:**Home page: <https://www.python.org/>Download: <https://www.python.org/ftp/python/3.12.5/Python-3.12.5.tar.xz>

MD5 sum: 02c7d269e077f4034963bba6befdc715

**• Python Documentation (3.12.5) - 8,188 KB:**Download: <https://www.python.org/ftp/python/doc/3.12.5/python-3.12.5-docs-html.tar.bz2>

MD5 sum: 52274d813236ca4a972fb6988480dc56

**• Readline (8.2.13) - 2,974 KB:**Home page: <https://tiswww.case.edu/php/chet/readline/rltop.html>Download: <https://ftp.gnu.org/gnu/readline/readline-8.2.13.tar.gz>

MD5 sum: 05080bf3801e6874bb115cd6700b708f

**• Sed (4.9) - 1,365 KB:**Home page: <https://www.gnu.org/software/sed/>Download: <https://ftp.gnu.org/gnu/sed/sed-4.9.tar.xz>

MD5 sum: 6aac9b2dbafcd5b7a67a8a9bcb8036c3

**• Setuptools (72.2.0) - 2,363 KB:**Home page: <https://pypi.org/project/setuptools/>Download: <https://pypi.org/packages/source/s/setuptools/setuptools-72.2.0.tar.gz>

MD5 sum: 2e0ffd0f6fc632a11442b79d9b1c68bd

**• Shadow (4.16.0) - 2,154 KB:**Home page: <https://github.com/shadow-maint/shadow/>Download: <https://github.com/shadow-maint/shadow/releases/download/4.16.0/shadow-4.16.0.tar.xz>

MD5 sum: eb70bad3316d08f0d3bb3d4bbeccb3b4

**• Systemd (256.4) - 15,291 KB:**Home page: <https://www.freedesktop.org/wiki/Software/systemd/>Download: <https://github.com/systemd/systemd/archive/v256.4/systemd-256.4.tar.gz>

MD5 sum: 03bd1ff158ec0bc55428c77a8f8495bd

**• Systemd Man Pages (256.4) - 676 KB:**Home page: <https://www.freedesktop.org/wiki/Software/systemd/>Download: <https://anduin.linuxfromscratch.org/LFS/systemd-man-pages-256.4.tar.xz>

MD5 sum: 8dbcf0ff0d8e5e9d3565f9d2fc153310

**Note**

The Linux From Scratch team generates its own tarball of the man pages using the systemd source. This is done in order to avoid unnecessary dependencies.

**• Tar (1.35) - 2,263 KB:**Home page: <https://www.gnu.org/software/tar/>Download: <https://ftp.gnu.org/gnu/tar/tar-1.35.tar.xz>

MD5 sum: a2d8042658cfd8ea939e6d911eaf4152

**• Tcl (8.6.14) - 11,355 KB:**Home page: <https://tcl.sourceforge.net/>Download: <https://downloads.sourceforge.net/tcl/tcl8.6.14-src.tar.gz>

MD5 sum: c30b57c6051be28fa928d09aca82841e



- **Tcl Documentation (8.6.14) - 1,167 KB:**

Download: <https://downloads.sourceforge.net/tcl/tcl8.6.14-html.tar.gz>

MD5 sum: 5467198f8d57c54835bf80b98ffb0170

- **Texinfo (7.1) - 5,416 KB:**

Home page: <https://www.gnu.org/software/texinfo/>

Download: <https://ftp.gnu.org/gnu/texinfo/texinfo-7.1.tar.xz>

MD5 sum: edd9928b4a3f82674bcc3551616eef3b

- **Time Zone Data (2024a) - 444 KB:**

Home page: <https://www.iana.org/time-zones>

Download: <https://www.iana.org/time-zones/repository/releases/tzdata2024a.tar.gz>

MD5 sum: 2349edd8335245525cc082f2755d5bf4

- **Util-linux (2.40.2) - 8,648 KB:**

Home page: <https://git.kernel.org/pub/scm/utils/util-linux/util-linux.git/>

Download: <https://www.kernel.org/pub/linux/utils/util-linux/v2.40/util-linux-2.40.2.tar.xz>

MD5 sum: 88faefc8fefced097e58142077a3d14e

- **Vim (9.1.0660) - 17,629 KB:**

Home page: <https://www.vim.org>

Download: <https://github.com/vim/vim/archive/v9.1.0660/vim-9.1.0660.tar.gz>

MD5 sum: c512a99b3704f193be1a181cc644b2b2



### Note

The version of vim changes daily. To get the latest version, go to <https://github.com/vim/vim/tags>.

- **Wheel (0.44.0) - 99 KB:**

Home page: <https://pypi.org/project/wheel/>

Download: <https://pypi.org/packages/source/w/wheel/wheel-0.44.0.tar.gz>

MD5 sum: 440ff4fe51579b7ed16f02af8f8d9494

- **XML::Parser (2.47) - 276 KB:**

Home page: <https://github.com/chorny/XML-Parser>

Download: <https://cpan.metacpan.org/authors/id/T/TO/TODDR/XML-Parser-2.47.tar.gz>

MD5 sum: 89a8e82cfd2ad948b349c0a69c494463

- **Xz Utils (5.6.2) - 1,277 KB:**

Home page: <https://tukaani.org/xz>

Download: <https://github.com/tukaani-project/xz/releases/download/v5.6.2/xz-5.6.2.tar.xz>

MD5 sum: bbf73fb28425cebb854328599f85c4cf

- **Zlib (1.3.1) - 1,478 KB:**

Home page: <https://zlib.net/>

Download: <https://zlib.net/fossils/zlib-1.3.1.tar.gz>

MD5 sum: 9855b6d802d7fe5b7bd5b196a2271655

- **Zstd (1.5.6) - 2,351 KB:**

Home page: <https://facebook.github.io/zstd/>

Download: <https://github.com/facebook/zstd/releases/download/v1.5.6/zstd-1.5.6.tar.gz>

MD5 sum: 5a473726b3445d0e5d6296afd1ab6854

Total size of these packages: about 517 MB

### 3.3. Needed Patches

In addition to the packages, several patches are also required. These patches correct any mistakes in the packages that should be fixed by the maintainer. The patches also make small modifications to make the packages easier to work with. The following patches will be needed to build an LFS system:

- **Bzip2 Documentation Patch - 1.6 KB:**

Download: [https://www.linuxfromscratch.org/patches/lfs/12.2/bzip2-1.0.8-install\\_docs-1.patch](https://www.linuxfromscratch.org/patches/lfs/12.2/bzip2-1.0.8-install_docs-1.patch)

MD5 sum: 6a5ac7e89b791aae556de0f745916f7f

- **Coreutils Internationalization Fixes Patch - 164 KB:**

Download: <https://www.linuxfromscratch.org/patches/lfs/12.2/coreutils-9.5-i18n-2.patch>

MD5 sum: 58961caf5bbdb02462591fa506c73b6d

- **Expect GCC14 Patch - 7.8 KB:**

Download: <https://www.linuxfromscratch.org/patches/lfs/12.2/expect-5.45.4-gcc14-1.patch>

MD5 sum: 0b8b5ac411d011263ad40b0664c669f0

- **Glibc FHS Patch - 2.8 KB:**

Download: <https://www.linuxfromscratch.org/patches/lfs/12.2/glibc-2.40-fhs-1.patch>

MD5 sum: 9a5997c3452909b1769918c759eff8a2

- **Kbd Backspace/Delete Fix Patch - 12 KB:**

Download: <https://www.linuxfromscratch.org/patches/lfs/12.2/kbd-2.6.4-backspace-1.patch>

MD5 sum: f75cca16a38da6caa7d52151f7136895

Total size of these patches: about 188.2 KB

In addition to the above required patches, there exist a number of optional patches created by the LFS community. These optional patches solve minor problems or enable functionality that is not enabled by default. Feel free to peruse the patches database located at <https://www.linuxfromscratch.org/patches/downloads/> and acquire any additional patches to suit your system needs.

# Chapter 4. Final Preparations

## 4.1. Introduction

In this chapter, we will perform a few additional tasks to prepare for building the temporary system. We will create a set of directories in `$LFS` (in which we will install the temporary tools), add an unprivileged user, and create an appropriate build environment for that user. We will also explain the units of time (“SBUs”) we use to measure how long it takes to build LFS packages, and provide some information about package test suites.

## 4.2. Creating a Limited Directory Layout in the LFS Filesystem

In this section, we begin populating the LFS filesystem with the pieces that will constitute the final Linux system. The first step is to create a limited directory hierarchy, so that the programs compiled in Chapter 6 (as well as `glibc` and `libstdc++` in Chapter 5) can be installed in their final location. We do this so those temporary programs will be overwritten when the final versions are built in Chapter 8.

Create the required directory layout by issuing the following commands as `root`:

```
mkdir -pv $LFS/{etc,var} $LFS/usr/{bin,lib,sbin}

for i in bin lib sbin; do
  ln -sv usr/$i $LFS/$i
done

case $(uname -m) in
  x86_64) mkdir -pv $LFS/lib64 ;;
esac
```

Programs in Chapter 6 will be compiled with a cross-compiler (more details can be found in section Toolchain Technical Notes). This cross-compiler will be installed in a special directory, to separate it from the other programs. Still acting as `root`, create that directory with this command:

```
mkdir -pv $LFS/tools
```



### Note

The LFS editors have deliberately decided not to use a `/usr/lib64` directory. Several steps are taken to be sure the toolchain will not use it. If for any reason this directory appears (either because you made an error in following the instructions, or because you installed a binary package that created it after finishing LFS), it may break your system. You should always be sure this directory does not exist.

## 4.3. Adding the LFS User

When logged in as user `root`, making a single mistake can damage or destroy a system. Therefore, the packages in the next two chapters are built as an unprivileged user. You could use your own user name, but to make it easier to set up a clean working environment, we will create a new user called `lfs` as a member of a new group (also named `lfs`) and run commands as `lfs` during the installation process. As `root`, issue the following commands to add the new user:

```
groupadd lfs
useradd -s /bin/bash -g lfs -m -k /dev/null lfs
```

This is what the command line options mean:

```
-s /bin/bash
```

This makes **bash** the default shell for user `lfs`.

`-g lfs`

This option adds user `lfs` to group `lfs`.

`-m`

This creates a home directory for `lfs`.

`-k /dev/null`

This parameter prevents possible copying of files from a skeleton directory (the default is `/etc/skel`) by changing the input location to the special null device.

`lfs`

This is the name of the new user.

If you want to log in as `lfs` or switch to `lfs` from a non-`root` user (as opposed to switching to user `lfs` when logged in as `root`, which does not require the `lfs` user to have a password), you need to set a password for `lfs`. Issue the following command as the `root` user to set the password:

```
passwd lfs
```

Grant `lfs` full access to all the directories under `$LFS` by making `lfs` the owner:

```
chown -v lfs $LFS/{usr{,/*},lib,var,etc,bin,sbin,tools}
case $(uname -m) in
  x86_64) chown -v lfs $LFS/lib64 ;;
esac
```



### Note

In some host systems, the following `su` command does not complete properly and suspends the login for the `lfs` user to the background. If the prompt "`lfs:~$`" does not appear immediately, entering the `fg` command will fix the issue.

Next, start a shell running as user `lfs`. This can be done by logging in as `lfs` on a virtual console, or with the following substitute/switch user command:

```
su - lfs
```

The “-” instructs `su` to start a login shell as opposed to a non-login shell. The difference between these two types of shells is described in detail in *bash(1)* and **info bash**.

## 4.4. Setting Up the Environment

Set up a good working environment by creating two new startup files for the **bash** shell. While logged in as user `lfs`, issue the following command to create a new `.bash_profile`:

```
cat > ~/.bash_profile << "EOF"
exec env -i HOME=$HOME TERM=$TERM PS1='\u:\w\$ ' /bin/bash
EOF
```

When logged on as user `lfs`, or when switched to the `lfs` user using an `su` command with the “-” option, the initial shell is a *login* shell which reads the `/etc/profile` of the host (probably containing some settings and environment variables) and then `.bash_profile`. The `exec env -i.../bin/bash` command in the `.bash_profile` file replaces the running shell with a new one with a completely empty environment, except for the `HOME`, `TERM`, and `PS1` variables. This ensures that no unwanted and potentially hazardous environment variables from the host system leak into the build environment.

The new instance of the shell is a *non-login* shell, which does not read, and execute, the contents of the `/etc/profile` or `.bash_profile` files, but rather reads, and executes, the `.bashrc` file instead. Create the `.bashrc` file now:

```
cat > ~/.bashrc << "EOF"
set +h
umask 022
LFS=/mnt/lfs
LC_ALL=POSIX
LFS_TGT=$(uname -m)-lfs-linux-gnu
PATH=/usr/bin
if [ ! -L /bin ]; then PATH=/bin:$PATH; fi
PATH=$LFS/tools/bin:$PATH
CONFIG_SITE=$LFS/usr/share/config.site
export LFS LC_ALL LFS_TGT PATH CONFIG_SITE
EOF
```

### The meaning of the settings in `.bashrc`

```
set +h
```

The `set +h` command turns off `bash`'s hash function. Hashing is ordinarily a useful feature—`bash` uses a hash table to remember the full path to executable files to avoid searching the `PATH` time and again to find the same executable. However, the new tools should be used as soon as they are installed. Switching off the hash function forces the shell to search the `PATH` whenever a program is to be run. As such, the shell will find the newly compiled tools in `$LFS/tools/bin` as soon as they are available without remembering a previous version of the same program provided by the host distro, in `/usr/bin` or `/bin`.

```
umask 022
```

Setting the user file-creation mask (`umask`) to `022` ensures that newly created files and directories are only writable by their owner, but are readable and executable by anyone (assuming default modes are used by the `open(2)` system call, new files will end up with permission mode `644` and directories with mode `755`).

```
LFS=/mnt/lfs
```

The `LFS` variable should be set to the chosen mount point.

```
LC_ALL=POSIX
```

The `LC_ALL` variable controls the localization of certain programs, making their messages follow the conventions of a specified country. Setting `LC_ALL` to “`POSIX`” or “`C`” (the two are equivalent) ensures that everything will work as expected in the cross-compilation environment.

```
LFS_TGT=$(uname -m)-lfs-linux-gnu
```

The `LFS_TGT` variable sets a non-default, but compatible machine description for use when building our cross-compiler and linker and when cross-compiling our temporary toolchain. More information is provided by Toolchain Technical Notes.

```
PATH=/usr/bin
```

Many modern Linux distributions have merged `/bin` and `/usr/bin`. When this is the case, the standard `PATH` variable should be set to `/usr/bin/` for the Chapter 6 environment. When this is not the case, the following line adds `/bin` to the path.

```
if [ ! -L /bin ]; then PATH=/bin:$PATH; fi
```

If `/bin` is not a symbolic link, it must be added to the `PATH` variable.

```
PATH=$LFS/tools/bin:$PATH
```

By putting `$LFS/tools/bin` ahead of the standard `PATH`, the cross-compiler installed at the beginning of Chapter 5 is picked up by the shell immediately after its installation. This, combined with turning off hashing, limits the risk that the compiler from the host is used instead of the cross-compiler.

```
CONFIG_SITE=$LFS/usr/share/config.site
```

In Chapter 5 and Chapter 6, if this variable is not set, **configure** scripts may attempt to load configuration items specific to some distributions from `/usr/share/config.site` on the host system. Override it to prevent potential contamination from the host.

```
export ...
```

While the preceding commands have set some variables, in order to make them visible within any sub-shells, we export them.



### Important

Several commercial distributions add an undocumented instantiation of `/etc/bash.bashrc` to the initialization of **bash**. This file has the potential to modify the `lfs` user's environment in ways that can affect the building of critical LFS packages. To make sure the `lfs` user's environment is clean, check for the presence of `/etc/bash.bashrc` and, if present, move it out of the way. As the `root` user, run:

```
[ ! -e /etc/bash.bashrc ] || mv -v /etc/bash.bashrc /etc/bash.bashrc.NOUSE
```

When the `lfs` user is no longer needed (at the beginning of Chapter 7), you may safely restore `/etc/bash.bashrc` (if desired).

Note that the LFS Bash package we will build in Section 8.36, “Bash-5.2.32” is not configured to load or execute `/etc/bash.bashrc`, so this file is useless on a completed LFS system.

For many modern systems with multiple processors (or cores) the compilation time for a package can be reduced by performing a "parallel make" by telling the `make` program how many processors are available via a command line option or an environment variable. For instance, an Intel Core i9-13900K processor has 8 P (performance) cores and 16 E (efficiency) cores, and a P core can simultaneously run two threads so each P core are modeled as two logical cores by the Linux kernel. As the result there are 32 logical cores in total. One obvious way to use all these logical cores is allowing **make** to spawn up to 32 build jobs. This can be done by passing the `-j32` option to **make**:

```
make -j32
```

Or set the `MAKEFLAGS` environment variable and its content will be automatically used by **make** as command line options:

```
export MAKEFLAGS=-j32
```



### Important

Never pass a `-j` option without a number to **make** or set such an option in `MAKEFLAGS`. Doing so will allow **make** to spawn infinite build jobs and cause system stability problems.

To use all logical cores available for building packages in Chapter 5 and Chapter 6, set `MAKEFLAGS` now in `.bashrc`:

```
cat >> ~/.bashrc << "EOF"
export MAKEFLAGS=-j$(nproc)
EOF
```

Replace `$(nproc)` with the number of logical cores you want to use if you don't want to use all the logical cores.

Finally, to ensure the environment is fully prepared for building the temporary tools, force the **bash** shell to read the new user profile:

```
source ~/.bash_profile
```

## 4.5. About SBUs

Many people would like to know beforehand approximately how long it takes to compile and install each package. Because Linux From Scratch can be built on many different systems, it is impossible to provide absolute time estimates. The biggest package (`gcc`) will take approximately 5 minutes on the fastest systems, but could take days on slower systems! Instead of providing actual times, the Standard Build Unit (SBU) measure will be used instead.

The SBU measure works as follows. The first package to be compiled is `binutils` in Chapter 5. The time it takes to compile using one core is what we will refer to as the Standard Build Unit or SBU. All other compile times will be expressed in terms of this unit of time.

For example, consider a package whose compilation time is 4.5 SBUs. This means that if your system took 4 minutes to compile and install the first pass of `binutils`, it will take *approximately* 18 minutes to build the example package. Fortunately, most build times are shorter than one SBU.

SBUs are not entirely accurate because they depend on many factors, including the host system's version of GCC. They are provided here to give an estimate of how long it might take to install a package, but the numbers can vary by as much as dozens of minutes in some cases.

On some newer systems, the motherboard is capable of controlling the system clock speed. This can be controlled with a command such as `powerprofilesctl`. This is not available in LFS, but may be available on the host distro. After LFS is complete, it can be added to a system with the procedures at the *BLFS power-profiles-daemon* page. Before measuring the build time of any package it is advisable to use a system power profile set for maximum performance (and maximum power consumption). Otherwise the measured SBU value may be inaccurate because the system may react differently when building `binutils-pass1` or other packages. Be aware that a significant inaccuracy can still show up even if the same profile is used for both packages because the system may respond slower if the system is idle when starting the build procedure. Setting the power profile to “performance” will minimize this problem. And obviously doing so will also make the system build LFS faster.

If `powerprofilesctl` is available, issue the `powerprofilesctl set performance` command to select the `performance` profile. Some distros provides the `tuned-adm` command for managing the profiles instead of `powerprofilesctl`, on these distros issue the `tuned-adm profile throughput-performance` command to select the `throughput-performance` profile.



### Note

When multiple processors are used in this way, the SBU units in the book will vary even more than they normally would. In some cases, the `make` step will simply fail. Analyzing the output of the build process will also be more difficult because the lines from different processes will be interleaved. If you run into a problem with a build step, revert to a single processor build to properly analyze the error messages.

The times presented here for all packages (except `binutils-pass1` which is based on one core) are based upon using four cores (`-j4`). The times in Chapter 8 also include the time to run the regression tests for the package unless specified otherwise.

## 4.6. About the Test Suites

Most packages provide a test suite. Running the test suite for a newly built package is a good idea because it can provide a “sanity check” indicating that everything compiled correctly. A test suite that passes its set of checks usually proves that the package is functioning as the developer intended. It does not, however, guarantee that the package is totally bug free.

Some test suites are more important than others. For example, the test suites for the core toolchain packages—GCC, binutils, and glibc—are of the utmost importance due to their central role in a properly functioning system. The test suites for GCC and glibc can take a very long time to complete, especially on slower hardware, but are strongly recommended.



### Note

Running the test suites in Chapter 5 and Chapter 6 is pointless; since the test programs are compiled with a cross-compiler, they probably can't run on the build host.

A common issue with running the test suites for binutils and GCC is running out of pseudo terminals (PTYs). This can result in a large number of failing tests. This may happen for several reasons, but the most likely cause is that the host system does not have the `devpts` file system set up correctly. This issue is discussed in greater detail at <https://www.linuxfromscratch.org/lfs/faq.html#no-ptys>.

Sometimes package test suites will fail for reasons which the developers are aware of and have deemed non-critical. Consult the logs located at <https://www.linuxfromscratch.org/lfs/build-logs/12.2/> to verify whether or not these failures are expected. This site is valid for all test suites throughout this book.



## **Part III. Building the LFS Cross Toolchain and Temporary Tools**

# Important Preliminary Material

## Introduction

This part is divided into three stages: first, building a cross compiler and its associated libraries; second, using this cross toolchain to build several utilities in a way that isolates them from the host distribution; and third, entering the chroot environment (which further improves host isolation) and constructing the remaining tools needed to build the final system.



### Important

This is where the real work of building a new system begins. Be very careful to follow the instructions exactly as the book shows them. You should try to understand what each command does, and no matter how eager you are to finish your build, you should refrain from blindly typing the commands as shown. Read the documentation when there is something you do not understand. Also, keep track of your typing and of the output of commands, by using the `tee` utility to send the terminal output to a file. This makes debugging easier if something goes wrong.

The next section is a technical introduction to the build process, while the following one presents **very important** general instructions.

## Toolchain Technical Notes

This section explains some of the rationale and technical details behind the overall build method. Don't try to immediately understand everything in this section. Most of this information will be clearer after performing an actual build. Come back and re-read this chapter at any time during the build process.

The overall goal of Chapter 5 and Chapter 6 is to produce a temporary area containing a set of tools that are known to be good, and that are isolated from the host system. By using the `chroot` command, the compilations in the remaining chapters will be isolated within that environment, ensuring a clean, trouble-free build of the target LFS system. The build process has been designed to minimize the risks for new readers, and to provide the most educational value at the same time.

This build process is based on *cross-compilation*. Cross-compilation is normally used to build a compiler and its associated toolchain for a machine different from the one that is used for the build. This is not strictly necessary for LFS, since the machine where the new system will run is the same as the one used for the build. But cross-compilation has one great advantage: anything that is cross-compiled cannot depend on the host environment.

## About Cross-Compilation



### Note

The LFS book is not (and does not contain) a general tutorial to build a cross- (or native) toolchain. Don't use the commands in the book for a cross-toolchain for some purpose other than building LFS, unless you really understand what you are doing.

Cross-compilation involves some concepts that deserve a section of their own. Although this section may be omitted on a first reading, coming back to it later will help you gain a fuller understanding of the process.

Let us first define some terms used in this context.

**The build**

is the machine where we build programs. Note that this machine is also referred to as the “host.”

**The host**

is the machine/system where the built programs will run. Note that this use of “host” is not the same as in other sections.

**The target**

is only used for compilers. It is the machine the compiler produces code for. It may be different from both the build and the host.

As an example, let us imagine the following scenario (sometimes referred to as “Canadian Cross”). We have a compiler on a slow machine only, let's call it machine A, and the compiler ccA. We also have a fast machine (B), but no compiler for (B), and we want to produce code for a third, slow machine (C). We will build a compiler for machine C in three stages.

Stage	Build	Host	Target	Action
1	A	A	B	Build cross-compiler cc1 using ccA on machine A.
2	A	B	C	Build cross-compiler cc2 using cc1 on machine A.
3	B	C	C	Build compiler ccC using cc2 on machine B.

Then, all the programs needed by machine C can be compiled using cc2 on the fast machine B. Note that unless B can run programs produced for C, there is no way to test the newly built programs until machine C itself is running. For example, to run a test suite on ccC, we may want to add a fourth stage:

Stage	Build	Host	Target	Action
4	C	C	C	Rebuild and test ccC using ccC on machine C.

In the example above, only `cc1` and `cc2` are cross-compilers, that is, they produce code for a machine different from the one they are run on. The other compilers `ccA` and `ccC` produce code for the machine they are run on. Such compilers are called *native* compilers.

## Implementation of Cross-Compilation for LFS



### Note

All the cross-compiled packages in this book use an autoconf-based building system. The autoconf-based building system accepts system types in the form `cpu-vendor-kernel-os`, referred to as the system triplet. Since the vendor field is often irrelevant, autoconf lets you omit it.

An astute reader may wonder why a “triplet” refers to a four component name. The kernel field and the os field began as a single “system” field. Such a three-field form is still valid today for some systems, for example, `x86_64-unknown-freebsd`. But two systems can share the same kernel and still be too different to use the same triplet to describe them. For example, Android running on a mobile phone is completely different from Ubuntu running on an ARM64 server, even though they are both running on the same type of CPU (ARM64) and using the same kernel (Linux).

Without an emulation layer, you cannot run an executable for a server on a mobile phone or vice versa. So the “system” field has been divided into kernel and os fields, to designate these systems unambiguously. In our example, the Android system is designated `aarch64-unknown-linux-android`, and the Ubuntu system is designated `aarch64-unknown-linux-gnu`.

The word “triplet” remains embedded in the lexicon. A simple way to determine your system triplet is to run the `config.guess` script that comes with the source for many packages. Unpack the binutils sources, run the script `./config.guess`, and note the output. For example, for a 32-bit Intel processor the output will be `i686-pc-linux-gnu`. On a 64-bit system it will be `x86_64-pc-linux-gnu`. On most Linux systems the even simpler `gcc -dumpmachine` command will give you similar information.

You should also be aware of the name of the platform's dynamic linker, often referred to as the dynamic loader (not to be confused with the standard linker `ld` that is part of binutils). The dynamic linker provided by package `glibc` finds and loads the shared libraries needed by a program, prepares the program to run, and then runs it. The name of the dynamic linker for a 32-bit Intel machine is `ld-linux.so.2`; it's `ld-linux-x86-64.so.2` on 64-bit systems. A sure-fire way to determine the name of the dynamic linker is to inspect a random binary from the host system by running: `readelf -l <name of binary> | grep interpreter` and noting the output. The authoritative reference covering all platforms is in *a Glibc wiki page*.

In order to fake a cross-compilation in LFS, the name of the host triplet is slightly adjusted by changing the “vendor” field in the `LFS_TGT` variable so it says “lfs”. We also use the `--with-sysroot` option when building the cross-linker and cross-compiler, to tell them where to find the needed host files. This ensures that none of the other programs built in Chapter 6 can link to libraries on the build machine. Only two stages are mandatory, plus one more for tests.

Stage	Build	Host	Target	Action
1	pc	pc	lfs	Build cross-compiler <code>cc1</code> using <code>cc-pc</code> on <code>pc</code> .

Stage	Build	Host	Target	Action
2	pc	lfs	lfs	Build compiler cc-lfs using cc1 on pc.
3	lfs	lfs	lfs	Rebuild and test cc-lfs using cc-lfs on lfs.

In the preceding table, “on pc” means the commands are run on a machine using the already installed distribution. “On lfs” means the commands are run in a chrooted environment.

This is not yet the end of the story. The C language is not merely a compiler; it also defines a standard library. In this book, the GNU C library, named glibc, is used (there is an alternative, "musl"). This library must be compiled for the LFS machine; that is, using the cross-compiler cc1. But the compiler itself uses an internal library providing complex subroutines for functions not available in the assembler instruction set. This internal library is named libgcc, and it must be linked to the glibc library to be fully functional. Furthermore, the standard library for C++ (libstdc++) must also be linked with glibc. The solution to this chicken and egg problem is first to build a degraded cc1-based libgcc, lacking some functionalities such as threads and exception handling, and then to build glibc using this degraded compiler (glibc itself is not degraded), and also to build libstdc++. This last library will lack some of the functionality of libgcc.

The upshot of the preceding paragraph is that cc1 is unable to build a fully functional libstdc++ with the degraded libgcc, but cc1 is the only compiler available for building the C/C++ libraries during stage 2. There are two reasons we don't immediately use the compiler built in stage 2, cc-lfs, to build those libraries.

- Generally speaking, cc-lfs cannot run on pc (the host system). Even though the triplets for pc and lfs are compatible with each other, an executable for lfs must depend on glibc-2.40; the host distro may utilize either a different implementation of libc (for example, musl), or a previous release of glibc (for example, glibc-2.13).
- Even if cc-lfs can run on pc, using it on pc would create a risk of linking to the pc libraries, since cc-lfs is a native compiler.

So when we build gcc stage 2, we instruct the building system to rebuild libgcc and libstdc++ with cc1, but we link libstdc++ to the newly rebuilt libgcc instead of the old, degraded build. This makes the rebuilt libstdc++ fully functional.

In Chapter 8 (or “stage 3”), all the packages needed for the LFS system are built. Even if a package has already been installed into the LFS system in a previous chapter, we still rebuild the package. The main reason for rebuilding these packages is to make them stable: if we reinstall an LFS package on a completed LFS system, the reinstalled content of the package should be the same as the content of the same package when first installed in Chapter 8. The temporary packages installed in Chapter 6 or Chapter 7 cannot satisfy this requirement, because some of them are built without optional dependencies, and autoconf cannot perform some feature checks in Chapter 6 because of cross-compilation, causing the temporary packages to lack optional features, or use suboptimal code routines. Additionally, a minor reason for rebuilding the packages is to run the test suites.

## Other Procedural Details

The cross-compiler will be installed in a separate `$LFS/tools` directory, since it will not be part of the final system.

Binutils is installed first because the **configure** runs of both `gcc` and `glibc` perform various feature tests on the assembler and linker to determine which software features to enable or disable. This is more important than one might realize at first. An incorrectly configured `gcc` or `glibc` can result in a subtly broken toolchain, where the impact of such breakage might not show up until near the end of the build of an entire distribution. A test suite failure will usually highlight this error before too much additional work is performed.

Binutils installs its assembler and linker in two locations, `$LFS/tools/bin` and `$LFS/tools/$LFS_TGT/bin`. The tools in one location are hard linked to the other. An important facet of the linker is its library search order. Detailed information can be obtained from `ld` by passing it the `--verbose` flag. For example, `$LFS_TGT-ld --verbose | grep SEARCH` will illustrate the current search paths and their order. (Note that this example can be run as shown only while logged in as user `lfs`. If you come back to this page later, replace `$LFS_TGT-ld` with `ld`).

The next package installed is `gcc`. An example of what can be seen during its run of **configure** is:

```
checking what assembler to use... /mnt/lfs/tools/i686-lfs-linux-gnu/bin/as
checking what linker to use... /mnt/lfs/tools/i686-lfs-linux-gnu/bin/ld
```

This is important for the reasons mentioned above. It also demonstrates that `gcc`'s `configure` script does not search the `PATH` directories to find which tools to use. However, during the actual operation of `gcc` itself, the same search paths are not necessarily used. To find out which standard linker `gcc` will use, run: `$LFS_TGT-gcc -print-prog-name=ld`. (Again, remove the `$LFS_TGT-` prefix if coming back to this later.)

Detailed information can be obtained from `gcc` by passing it the `-v` command line option while compiling a program. For example, `$LFS_TGT-gcc -v example.c` (or without `$LFS_TGT-` if coming back later) will show detailed information about the preprocessor, compilation, and assembly stages, including `gcc`'s search paths for included headers and their order.

Next up: sanitized Linux API headers. These allow the standard C library (`glibc`) to interface with features that the Linux kernel will provide.

Next comes `glibc`. The most important considerations for building `glibc` are the compiler, binary tools, and kernel headers. The compiler and binary tools are generally not an issue since `glibc` will always those relating to the `--host` parameter passed to its `configure` script; e.g., in our case, the compiler will be `$LFS_TGT-gcc` and the `readelf` tool will be `$LFS_TGT-readelf`. The kernel headers can be a bit more complicated. Therefore, we take no risks and use the available `configure` switch to enforce the correct selection. After the run of **configure**, check the contents of the `config.make` file in the `build` directory for all important details. These items highlight an important aspect of the `glibc` package—it is very self-sufficient in terms of its build machinery, and generally does not rely on toolchain defaults.

As mentioned above, the standard C++ library is compiled next, followed in Chapter 6 by other programs that must be cross-compiled to break circular dependencies at build time. The install step of all those packages uses the `DESTDIR` variable to force installation in the LFS filesystem.

At the end of Chapter 6 the native LFS compiler is installed. First `binutils-pass2` is built, in the same `DESTDIR` directory as the other programs, then the second pass of `gcc` is constructed, omitting some non-critical libraries. Due to some weird logic in `gcc`'s `configure` script, `CC_FOR_TARGET` ends up as `cc` when the host is the same as the target, but different from the build system. This is why `CC_FOR_TARGET=$LFS_TGT-gcc` is declared explicitly as one of the configuration options.

Upon entering the `chroot` environment in Chapter 7, the temporary installations of programs needed for the proper operation of the toolchain are performed. From this point onwards, the core toolchain is self-contained and self-hosted. In Chapter 8, final versions of all the packages needed for a fully functional system are built, tested, and installed.

## General Compilation Instructions



### Caution

During a development cycle of LFS, the instructions in the book are often modified to adapt for a package update or take the advantage of new features from updated packages. Mixing up the instructions of different versions of the LFS book can cause subtle breakages. This kind of issue is generally a result from reusing some script created for a prior LFS release. Such a reuse is strongly discouraged. If you are reusing scripts for a prior LFS release for any reason, you'll need to be very careful to update the scripts to match current version of the LFS book.

Here are some things you should know about building each package:

- Several packages are patched before compilation, but only when the patch is needed to circumvent a problem. A patch is often needed in both the current and the following chapters, but sometimes, when the same package is built more than once, the patch is not needed right away. Therefore, do not be concerned if instructions for a downloaded patch seem to be missing. Warning messages about *offset* or *fuzz* may also be encountered when applying a patch. Do not worry about these warnings; the patch was still successfully applied.
- During the compilation of most packages, some warnings will scroll by on the screen. These are normal and can safely be ignored. These warnings are usually about deprecated, but not invalid, use of the C or C++ syntax. C standards change fairly often, and some packages have not yet been updated. This is not a serious problem, but it does cause the warnings to appear.
- Check one last time that the `LFS` environment variable is set up properly:

```
echo $LFS
```

Make sure the output shows the path to the LFS partition's mount point, which is `/mnt/lfs`, using our example.

- Finally, two important items must be emphasized:



### Important

The build instructions assume that the Host System Requirements, including symbolic links, have been set properly:

- **bash** is the shell in use.
- **sh** is a symbolic link to **bash**.
- `/usr/bin/awk` is a symbolic link to **gawk**.
- `/usr/bin/yacc` is a symbolic link to **bison**, or to a small script that executes bison.



## Important

Here is a synopsis of the build process.

1. Place all the sources and patches in a directory that will be accessible from the chroot environment, such as `/mnt/lfs/sources/`.
2. Change to the `/mnt/lfs/sources/` directory.
3. For each package:
  - a. Using the **tar** program, extract the package to be built. In Chapter 5 and Chapter 6, ensure you are the *lfs* user when extracting the package.

Do not use any method except the **tar** command to extract the source code. Notably, using the **cp -R** command to copy the source code tree somewhere else can destroy timestamps in the source tree, and cause the build to fail.

- b. Change to the directory created when the package was extracted.
- c. Follow the instructions for building the package.
- d. Change back to the sources directory when the build is complete.
- e. Delete the extracted source directory unless instructed otherwise.



# Chapter 5. Compiling a Cross-Toolchain

## 5.1. Introduction

This chapter shows how to build a cross-compiler and its associated tools. Although here cross-compilation is faked, the principles are the same as for a real cross-toolchain.

The programs compiled in this chapter will be installed under the `$LFS/tools` directory to keep them separate from the files installed in the following chapters. The libraries, on the other hand, are installed into their final place, since they pertain to the system we want to build.

## 5.2. Binutils-2.43.1 - Pass 1

The Binutils package contains a linker, an assembler, and other tools for handling object files.

**Approximate build time:** 1 SBU

**Required disk space:** 677 MB

### 5.2.1. Installation of Cross Binutils



#### Note

Go back and re-read the notes in the section titled General Compilation Instructions. Understanding the notes labeled important can save you a lot of problems later.

It is important that Binutils be the first package compiled because both Glibc and GCC perform various tests on the available linker and assembler to determine which of their own features to enable.

The Binutils documentation recommends building Binutils in a dedicated build directory:

```
mkdir -v build
cd      build
```



#### Note

In order for the SBU values listed in the rest of the book to be of any use, measure the time it takes to build this package from the configuration, up to and including the first install. To achieve this easily, wrap the commands in a **time** command like this: `time { ../configure ... && make && make install; }`.

Now prepare Binutils for compilation:

```
../configure --prefix=$LFS/tools \
             --with-sysroot=$LFS \
             --target=$LFS_TGT \
             --disable-nls \
             --enable-gprofng=no \
             --disable-werror \
             --enable-new-dtags \
             --enable-default-hash-style=gnu
```

**The meaning of the configure options:**

`--prefix=$LFS/tools`

This tells the configure script to prepare to install the Binutils programs in the `$LFS/tools` directory.

`--with-sysroot=$LFS`

For cross compilation, this tells the build system to look in `$LFS` for the target system libraries as needed.

`--target=$LFS_TGT`

Because the machine description in the `LFS_TGT` variable is slightly different than the value returned by the **config.guess** script, this switch will tell the **configure** script to adjust binutil's build system for building a cross linker.

`--disable-nls`

This disables internationalization as `i18n` is not needed for the temporary tools.

`--enable-gprofng=no`

This disables building `gprofng` which is not needed for the temporary tools.

`--disable-werror`

This prevents the build from stopping in the event that there are warnings from the host's compiler.

`--enable-new-dtags`

This makes the linker use the “runpath” tag for embedding library search paths into executables and shared libraries, instead of the traditional “rpath” tag. It makes debugging dynamically linked executables easier and works around potential issues in the test suite of some packages.

`--enable-default-hash-style=gnu`

By default, the linker would generate both the GNU-style hash table and the classic ELF hash table for shared libraries and dynamically linked executables. The hash tables are only intended for a dynamic linker to perform symbol lookup. On LFS the dynamic linker (provided by the Glibc package) will always use the GNU-style hash table which is faster to query. So the classic ELF hash table is completely useless. This makes the linker only generate the GNU-style hash table by default, so we can avoid wasting time to generate the classic ELF hash table when we build the packages, or wasting disk space to store it.

Continue with compiling the package:

```
make
```

Install the package:

```
make install
```

Details on this package are located in Section 8.20.2, “Contents of Binutils.”

## 5.3. GCC-14.2.0 - Pass 1

The GCC package contains the GNU compiler collection, which includes the C and C++ compilers.

**Approximate build time:** 3.2 SBU

**Required disk space:** 4.9 GB

### 5.3.1. Installation of Cross GCC

GCC requires the GMP, MPFR and MPC packages. As these packages may not be included in your host distribution, they will be built with GCC. Unpack each package into the GCC source directory and rename the resulting directories so the GCC build procedures will automatically use them:



#### Note

There are frequent misunderstandings about this chapter. The procedures are the same as every other chapter, as explained earlier (Package build instructions). First, extract the gcc-14.2.0 tarball from the sources directory, and then change to the directory created. Only then should you proceed with the instructions below.

```
tar -xf ../mpfr-4.2.1.tar.xz
mv -v mpfr-4.2.1 mpfr
tar -xf ../gmp-6.3.0.tar.xz
mv -v gmp-6.3.0 gmp
tar -xf ../mpc-1.3.1.tar.gz
mv -v mpc-1.3.1 mpc
```

On x86\_64 hosts, set the default directory name for 64-bit libraries to “lib”:

```
case $(uname -m) in
  x86_64)
    sed -e '/m64=/s/lib64/lib/' \
        -i.orig gcc/config/i386/t-linux64
  ;;
esac
```

The GCC documentation recommends building GCC in a dedicated build directory:

```
mkdir -v build
cd      build
```

Prepare GCC for compilation:

```

./configure \
  --target=$LFS_TGT \
  --prefix=$LFS/tools \
  --with-glibc-version=2.40 \
  --with-sysroot=$LFS \
  --with-newlib \
  --without-headers \
  --enable-default-pie \
  --enable-default-ssp \
  --disable-nls \
  --disable-shared \
  --disable-multilib \
  --disable-threads \
  --disable-libatomic \
  --disable-libgomp \
  --disable-libquadmath \
  --disable-libssp \
  --disable-libvtv \
  --disable-libstdcxx \
  --enable-languages=c,c++

```

### The meaning of the configure options:

*--with-glibc-version=2.40*

This option specifies the version of Glibc which will be used on the target. It is not relevant to the libc of the host distro because everything compiled by pass1 GCC will run in the chroot environment, which is isolated from libc of the host distro.

*--with-newlib*

Since a working C library is not yet available, this ensures that the `inhibit_libc` constant is defined when building `libgcc`. This prevents the compiling of any code that requires libc support.

*--without-headers*

When creating a complete cross-compiler, GCC requires standard headers compatible with the target system. For our purposes these headers will not be needed. This switch prevents GCC from looking for them.

*--enable-default-pie and --enable-default-ssp*

Those switches allow GCC to compile programs with some hardening security features (more information on those in the note on PIE and SSP in chapter 8) by default. They are not strictly needed at this stage, since the compiler will only produce temporary executables. But it is cleaner to have the temporary packages be as close as possible to the final ones.

*--disable-shared*

This switch forces GCC to link its internal libraries statically. We need this because the shared libraries require Glibc, which is not yet installed on the target system.

*--disable-multilib*

On `x86_64`, LFS does not support a multilib configuration. This switch is harmless for `x86`.

*--disable-threads, --disable-libatomic, --disable-libgomp, --disable-libquadmath, --disable-libssp, --disable-libvtv, --disable-libstdcxx*

These switches disable support for threading, `libatomic`, `libgomp`, `libquadmath`, `libssp`, `libvtv`, and the C++ standard library respectively. These features may fail to compile when building a cross-compiler and are not necessary for the task of cross-compiling the temporary libc.

*--enable-languages=c,c++*

This option ensures that only the C and C++ compilers are built. These are the only languages needed now.

Compile GCC by running:

```
make
```

Install the package:

```
make install
```

This build of GCC has installed a couple of internal system headers. Normally one of them, `limits.h`, would in turn include the corresponding system `limits.h` header, in this case, `$LFS/usr/include/limits.h`. However, at the time of this build of GCC `$LFS/usr/include/limits.h` does not exist, so the internal header that has just been installed is a partial, self-contained file and does not include the extended features of the system header. This is adequate for building Glibc, but the full internal header will be needed later. Create a full version of the internal header using a command that is identical to what the GCC build system does in normal circumstances:



### Note

The command below shows an example of nested command substitution using two methods: backquotes and a `$()` construct. It could be rewritten using the same method for both substitutions, but is shown this way to demonstrate how they can be mixed. Generally the `$()` method is preferred.

```
cd ..
cat gcc/limitx.h gcc/glimits.h gcc/limity.h > \
  `dirname $($LFS_TGT-gcc -print-libgcc-file-name)~/include/limits.h
```

Details on this package are located in Section 8.29.2, “Contents of GCC.”

## 5.4. Linux-6.10.5 API Headers

The Linux API Headers (in linux-6.10.5.tar.xz) expose the kernel's API for use by Glibc.

**Approximate build time:** less than 0.1 SBU

**Required disk space:** 1.6 GB

### 5.4.1. Installation of Linux API Headers

The Linux kernel needs to expose an Application Programming Interface (API) for the system's C library (Glibc in LFS) to use. This is done by way of sanitizing various C header files that are shipped in the Linux kernel source tarball.

Make sure there are no stale files embedded in the package:

```
make mrproper
```

Now extract the user-visible kernel headers from the source. The recommended make target “headers\_install” cannot be used, because it requires rsync, which may not be available. The headers are first placed in `./usr`, then copied to the needed location.

```
make headers
find usr/include -type f ! -name '*.h' -delete
cp -rv usr/include $LFS/usr
```

### 5.4.2. Contents of Linux API Headers

**Installed headers:** `/usr/include/asm/*.h`, `/usr/include/asm-generic/*.h`, `/usr/include/drm/*.h`, `/usr/include/linux/*.h`, `/usr/include/misc/*.h`, `/usr/include/mtd/*.h`, `/usr/include/rdma/*.h`, `/usr/include/scsi/*.h`, `/usr/include/sound/*.h`, `/usr/include/video/*.h`, and `/usr/include/xen/*.h`

**Installed directories:** `/usr/include/asm`, `/usr/include/asm-generic`, `/usr/include/drm`, `/usr/include/linux`, `/usr/include/misc`, `/usr/include/mtd`, `/usr/include/rdma`, `/usr/include/scsi`, `/usr/include/sound`, `/usr/include/video`, and `/usr/include/xen`

### Short Descriptions

<code>/usr/include/asm/*.h</code>	The Linux API ASM Headers
<code>/usr/include/asm-generic/*.h</code>	The Linux API ASM Generic Headers
<code>/usr/include/drm/*.h</code>	The Linux API DRM Headers
<code>/usr/include/linux/*.h</code>	The Linux API Linux Headers
<code>/usr/include/misc/*.h</code>	The Linux API Miscellaneous Headers
<code>/usr/include/mtd/*.h</code>	The Linux API MTD Headers
<code>/usr/include/rdma/*.h</code>	The Linux API RDMA Headers
<code>/usr/include/scsi/*.h</code>	The Linux API SCSI Headers
<code>/usr/include/sound/*.h</code>	The Linux API Sound Headers
<code>/usr/include/video/*.h</code>	The Linux API Video Headers
<code>/usr/include/xen/*.h</code>	The Linux API Xen Headers

## 5.5. Glibc-2.40

The Glibc package contains the main C library. This library provides the basic routines for allocating memory, searching directories, opening and closing files, reading and writing files, string handling, pattern matching, arithmetic, and so on.

**Approximate build time:** 1.3 SBU

**Required disk space:** 828 MB

### 5.5.1. Installation of Glibc

First, create a symbolic link for LSB compliance. Additionally, for `x86_64`, create a compatibility symbolic link required for proper operation of the dynamic library loader:

```
case $(uname -m) in
  i?86)  ln -sfv ld-linux.so.2 $LFS/lib/ld-lsb.so.3
        ;;
  x86_64) ln -sfv ../lib/ld-linux-x86-64.so.2 $LFS/lib64
          ln -sfv ../lib/ld-linux-x86-64.so.2 $LFS/lib64/ld-lsb-x86-64.so.3
        ;;
esac
```



#### Note

The above command is correct. The **ln** command has several syntactic versions, so be sure to check **info coreutils ln** and *ln(1)* before reporting what may appear to be an error.

Some of the Glibc programs use the non-FHS-compliant `/var/db` directory to store their runtime data. Apply the following patch to make such programs store their runtime data in the FHS-compliant locations:

```
patch -Np1 -i ../glibc-2.40-fhs-1.patch
```

The Glibc documentation recommends building Glibc in a dedicated build directory:

```
mkdir -v build
cd      build
```

Ensure that the **ldconfig** and **sln** utilities are installed into `/usr/sbin`:

```
echo "rootsbindir=/usr/sbin" > configparms
```

Next, prepare Glibc for compilation:

```
../configure \
  --prefix=/usr \
  --host=$LFS_TGT \
  --build=$(../scripts/config.guess) \
  --enable-kernel=4.19 \
  --with-headers=$LFS/usr/include \
  --disable-nscd \
  libc_cv_slibdir=/usr/lib
```

**The meaning of the configure options:**

```
--host=$LFS_TGT, --build=$(../scripts/config.guess)
```

The combined effect of these switches is that Glibc's build system configures itself to be cross-compiled, using the cross-linker and cross-compiler in `$LFS/tools`.



```
--enable-kernel=4.19
```

This tells Glibc to compile the library with support for 4.19 and later Linux kernels. Workarounds for older kernels are not enabled.

```
--with-headers=$LFS/usr/include
```

This tells Glibc to compile itself against the headers recently installed to the `$LFS/usr/include` directory, so that it knows exactly what features the kernel has and can optimize itself accordingly.

```
libc_cv_slibdir=/usr/lib
```

This ensures that the library is installed in `/usr/lib` instead of the default `/lib64` on 64-bit machines.

```
--disable-nscd
```

Do not build the name service cache daemon which is no longer used.

During this stage the following warning might appear:

```
configure: WARNING:
*** These auxiliary programs are missing or
*** incompatible versions: msgfmt
*** some features will be disabled.
*** Check the INSTALL file for required versions.
```

The missing or incompatible **msgfmt** program is generally harmless. This **msgfmt** program is part of the Gettext package, which the host distribution should provide.



### Note

There have been reports that this package may fail when building as a “parallel make.” If that occurs, rerun the make command with the `-j1` option.

Compile the package:

```
make
```

Install the package:



### Warning

If `LFS` is not properly set, and despite the recommendations, you are building as `root`, the next command will install the newly built Glibc to your host system, which will almost certainly render it unusable. So double-check that the environment is correctly set, and that you are not `root`, before running the following command.

```
make DESTDIR=$LFS install
```

**The meaning of the make install option:**

```
DESTDIR=$LFS
```

The `DESTDIR` make variable is used by almost all packages to define the location where the package should be installed. If it is not set, it defaults to the root (`/`) directory. Here we specify that the package is installed in `$LFS`, which will become the root directory in Section 7.4, “Entering the Chroot Environment”.

Fix a hard coded path to the executable loader in the **ldd** script:

```
sed 's@/usr/bin/ldd@/s@usr@g' -i $LFS/usr/bin/ldd
```



## Caution

At this point, it is imperative to stop and ensure that the basic functions (compiling and linking) of the new toolchain are working as expected. To perform a sanity check, run the following commands:

```
echo 'int main(){}' | $LFS_TGT-gcc -xc -
readelf -l a.out | grep ld-linux
```

If everything is working correctly, there should be no errors, and the output of the last command will be of the form:

```
[Requesting program interpreter: /lib64/ld-linux-x86-64.so.2]
```

Note that for 32-bit machines, the interpreter name will be `/lib/ld-linux.so.2`.

If the output is not as shown above, or there is no output at all, then something is wrong. Investigate and retrace the steps to find out where the problem is and correct it. This issue must be resolved before continuing.

Once all is well, clean up the test file:

```
rm -v a.out
```



## Note

Building the packages in the next chapter will serve as an additional check that the toolchain has been built properly. If some package, especially `Binutils-pass2` or `GCC-pass2`, fails to build, it is an indication that something has gone wrong with the preceding `Binutils`, `GCC`, or `Glibc` installations.

Details on this package are located in Section 8.5.3, “Contents of `Glibc`.”

## 5.6. Libstdc++ from GCC-14.2.0

Libstdc++ is the standard C++ library. It is needed to compile C++ code (part of GCC is written in C++), but we had to defer its installation when we built `gcc-pass1` because Libstdc++ depends on Glibc, which was not yet available in the target directory.

**Approximate build time:** 0.2 SBU

**Required disk space:** 1.2 GB

### 5.6.1. Installation of Target Libstdc++



#### Note

Libstdc++ is part of the GCC sources. You should first unpack the GCC tarball and change to the `gcc-14.2.0` directory.

Create a separate build directory for Libstdc++ and enter it:

```
mkdir -v build
cd build
```

Prepare Libstdc++ for compilation:

```
../libstdc++-v3/configure \
--host=$LFS_TGT \
--build=$(./config.guess) \
--prefix=/usr \
--disable-multilib \
--disable-nls \
--disable-libstdcxx-pch \
--with-gxx-include-dir=/tools/$LFS_TGT/include/c++/14.2.0
```

**The meaning of the configure options:**

`--host=...`

Specifies that the cross-compiler we have just built should be used instead of the one in `/usr/bin`.

`--disable-libstdcxx-pch`

This switch prevents the installation of precompiled include files, which are not needed at this stage.

`--with-gxx-include-dir=/tools/$LFS_TGT/include/c++/14.2.0`

This specifies the installation directory for include files. Because Libstdc++ is the standard C++ library for LFS, this directory should match the location where the C++ compiler (`$LFS_TGT-g++`) would search for the standard C++ include files. In a normal build, this information is automatically passed to the Libstdc++ **configure** options from the top level directory. In our case, this information must be explicitly given. The C++ compiler will prepend the `sysroot` path `$LFS` (specified when building `GCC-pass1`) to the include file search path, so it will actually search in `$LFS/tools/$LFS_TGT/include/c++/14.2.0`. The combination of the `DESTDIR` variable (in the **make install** command below) and this switch causes the headers to be installed there.

Compile Libstdc++ by running:

```
make
```

Install the library:

```
make DESTDIR=$LFS install
```

Remove the libtool archive files because they are harmful for cross-compilation:

```
rm -v $LFS/usr/lib/lib{stdc++{,exp,fs},supc++}.la
```

Details on this package are located in Section 8.29.2, “Contents of GCC.”

# Chapter 6. Cross Compiling Temporary Tools

## 6.1. Introduction

This chapter shows how to cross-compile basic utilities using the just built cross-toolchain. Those utilities are installed into their final location, but cannot be used yet. Basic tasks still rely on the host's tools. Nevertheless, the installed libraries are used when linking.

Using the utilities will be possible in the next chapter after entering the “chroot” environment. But all the packages built in the present chapter need to be built before we do that. Therefore we cannot be independent of the host system yet.

Once again, let us recall that improper setting of `LFS` together with building as `root`, may render your computer unusable. This whole chapter must be done as user `lfs`, with the environment as described in Section 4.4, “Setting Up the Environment.”

## 6.2. M4-1.4.19

The M4 package contains a macro processor.

**Approximate build time:** 0.1 SBU

**Required disk space:** 31 MB

### 6.2.1. Installation of M4

Prepare M4 for compilation:

```
./configure --prefix=/usr \
            --host=$LFS_TGT \
            --build=$(build-aux/config.guess)
```

Compile the package:

```
make
```

Install the package:

```
make DESTDIR=$LFS install
```

Details on this package are located in Section 8.13.2, “Contents of M4.”

## 6.3. Ncurses-6.5

The Ncurses package contains libraries for terminal-independent handling of character screens.

**Approximate build time:** 0.4 SBU

**Required disk space:** 53 MB

### 6.3.1. Installation of Ncurses

First, ensure that **gawk** is found first during configuration:

```
sed -i s/mawk// configure
```

Then, run the following commands to build the “tic” program on the build host:

```
mkdir build
pushd build
  ./configure
  make -C include
  make -C progs tic
popd
```

Prepare Ncurses for compilation:

```
./configure --prefix=/usr \
            --host=$LFS_TGT \
            --build=$(./config.guess) \
            --mandir=/usr/share/man \
            --with-manpage-format=normal \
            --with-shared \
            --without-normal \
            --with-cxx-shared \
            --without-debug \
            --without-ada \
            --disable-stripping
```

**The meaning of the new configure options:**

*--with-manpage-format=normal*

This prevents Ncurses from installing compressed manual pages, which may happen if the host distribution itself has compressed manual pages.

*--with-shared*

This makes Ncurses build and install shared C libraries.

*--without-normal*

This prevents Ncurses from building and installing static C libraries.

*--without-debug*

This prevents Ncurses from building and installing debug libraries.

*--with-cxx-shared*

This makes Ncurses build and install shared C++ bindings. It also prevents it building and installing static C++ bindings.

*--without-ada*

This ensures that Ncurses does not build support for the Ada compiler, which may be present on the host but will not be available once we enter the **chroot** environment.

`--disable-stripping`

This switch prevents the building system from using the **strip** program from the host. Using host tools on cross-compiled programs can cause failure.

Compile the package:

```
make
```

Install the package:

```
make DESTDIR=$LFS TIC_PATH=$(pwd)/build/progs/tic install
ln -sv libncursesw.so $LFS/usr/lib/libncurses.so
sed -e 's/^#if.*XOPEN.*$/#if 1/' \
-i $LFS/usr/include/curses.h
```

**The meaning of the install options:**

`TIC_PATH=$(pwd)/build/progs/tic`

We need to pass the path of the newly built **tic** program that runs on the building machine, so the terminal database can be created without errors.

**ln -sv libncursesw.so \$LFS/usr/lib/libncurses.so**

The `libncurses.so` library is needed by a few packages we will build soon. We create this symlink to use `libncursesw.so` as a replacement.

**sed -e 's/^#if.\*XOPEN.\*\$/#if 1/' ...**

The header file `curses.h` contains the definition of various Ncurses data structures. With different preprocessor macro definitions two different sets of the data structure definition may be used: the 8-bit definition is compatible with `libncurses.so` and the wide-character definition is compatible with `libncursesw.so`. Since we are using `libncursesw.so` as a replacement of `libncurses.so`, edit the header file so it will always use the wide-character data structure definition compatible with `libncursesw.so`.

Details on this package are located in Section 8.30.2, “Contents of Ncurses.”



## 6.4. Bash-5.2.32

The Bash package contains the Bourne-Again Shell.

**Approximate build time:** 0.2 SBU

**Required disk space:** 67 MB

### 6.4.1. Installation of Bash

Prepare Bash for compilation:

```
./configure --prefix=/usr \
            --build=$(sh support/config.guess) \
            --host=$LFS_TGT \
            --without-bash-malloc \
            bash_cv_strtold_broken=no
```

**The meaning of the configure options:**

*--without-bash-malloc*

This option turns off the use of Bash's memory allocation (`malloc`) function which is known to cause segmentation faults. By turning this option off, Bash will use the `malloc` functions from Glibc which are more stable.

Compile the package:

```
make
```

Install the package:

```
make DESTDIR=$LFS install
```

Make a link for the programs that use `sh` for a shell:

```
ln -sv bash $LFS/bin/sh
```

Details on this package are located in Section 8.36.2, “Contents of Bash.”

## 6.5. Coreutils-9.5

The Coreutils package contains the basic utility programs needed by every operating system.

**Approximate build time:** 0.3 SBU

**Required disk space:** 175 MB

### 6.5.1. Installation of Coreutils

Prepare Coreutils for compilation:

```
./configure --prefix=/usr \
            --host=$LFS_TGT \
            --build=$(build-aux/config.guess) \
            --enable-install-program=hostname \
            --enable-no-install-program=kill,uptime
```

The meaning of the configure options:

```
--enable-install-program=hostname
```

This enables the **hostname** binary to be built and installed – it is disabled by default but is required by the Perl test suite.

Compile the package:

```
make
```

Install the package:

```
make DESTDIR=$LFS install
```

Move programs to their final expected locations. Although this is not necessary in this temporary environment, we must do so because some programs hardcode executable locations:

```
mv -v $LFS/usr/bin/chroot $LFS/usr/sbin
mkdir -pv $LFS/usr/share/man/man8
mv -v $LFS/usr/share/man/man1/chroot.1 $LFS/usr/share/man/man8/chroot.8
sed -i 's/"1"/"8"/'
```

Details on this package are located in Section 8.58.2, “Contents of Coreutils.”

## 6.6. Diffutils-3.10

The Diffutils package contains programs that show the differences between files or directories.

**Approximate build time:** 0.1 SBU

**Required disk space:** 29 MB

### 6.6.1. Installation of Diffutils

Prepare Diffutils for compilation:

```
./configure --prefix=/usr \
            --host=$LFS_TGT \
            --build=$(./build-aux/config.guess)
```

Compile the package:

```
make
```

Install the package:

```
make DESTDIR=$LFS install
```

Details on this package are located in Section 8.60.2, “Contents of Diffutils.”

## 6.7. File-5.45

The File package contains a utility for determining the type of a given file or files.

**Approximate build time:** 0.1 SBU

**Required disk space:** 37 MB

### 6.7.1. Installation of File

The **file** command on the build host needs to be the same version as the one we are building in order to create the signature file. Run the following commands to make a temporary copy of the **file** command:

```
mkdir build
pushd build
  ./configure --disable-bzlib      \
              --disable-libseccomp \
              --disable-xzlib     \
              --disable-zlib
  make
popd
```

**The meaning of the new configure option:**

*--disable-\**

The configuration script attempts to use some packages from the host distribution if the corresponding library files exist. It may cause compilation failure if a library file exists, but the corresponding header files do not. These options prevent using these unneeded capabilities from the host.

Prepare File for compilation:

```
./configure --prefix=/usr --host=$LFS_TGT --build=$(./config.guess)
```

Compile the package:

```
make FILE_COMPILE=$(pwd)/build/src/file
```

Install the package:

```
make DESTDIR=$LFS install
```

Remove the libtool archive file because it is harmful for cross compilation:

```
rm -v $LFS/usr/lib/libmagic.la
```

Details on this package are located in Section 8.11.2, “Contents of File.”

## 6.8. Findutils-4.10.0

The Findutils package contains programs to find files. Programs are provided to search through all the files in a directory tree and to create, maintain, and search a database (often faster than the recursive find, but unreliable unless the database has been updated recently). Findutils also supplies the **xargs** program, which can be used to run a specified command on each file selected by a search.

**Approximate build time:** 0.2 SBU

**Required disk space:** 48 MB

### 6.8.1. Installation of Findutils

Prepare Findutils for compilation:

```
./configure --prefix=/usr          \
            --localstatedir=/var/lib/locate \
            --host=$LFS_TGT        \
            --build=$(build-aux/config.guess)
```

Compile the package:

```
make
```

Install the package:

```
make DESTDIR=$LFS install
```

Details on this package are located in Section 8.62.2, “Contents of Findutils.”

## 6.9. Gawk-5.3.0

The Gawk package contains programs for manipulating text files.

**Approximate build time:** 0.1 SBU

**Required disk space:** 47 MB

### 6.9.1. Installation of Gawk

First, ensure some unneeded files are not installed:

```
sed -i 's/extras//' Makefile.in
```

Prepare Gawk for compilation:

```
./configure --prefix=/usr \
            --host=$LFS_TGT \
            --build=$(build-aux/config.guess)
```

Compile the package:

```
make
```

Install the package:

```
make DESTDIR=$LFS install
```

Details on this package are located in Section 8.61.2, “Contents of Gawk.”

## 6.10. Grep-3.11

The Grep package contains programs for searching through the contents of files.

**Approximate build time:** 0.1 SBU

**Required disk space:** 27 MB

### 6.10.1. Installation of Grep

Prepare Grep for compilation:

```
./configure --prefix=/usr \
            --host=$LFS_TGT \
            --build=$(./build-aux/config.guess)
```

Compile the package:

```
make
```

Install the package:

```
make DESTDIR=$LFS install
```

Details on this package are located in Section 8.35.2, “Contents of Grep.”

## 6.11. Gzip-1.13

The Gzip package contains programs for compressing and decompressing files.

**Approximate build time:** 0.1 SBU

**Required disk space:** 11 MB

### 6.11.1. Installation of Gzip

Prepare Gzip for compilation:

```
./configure --prefix=/usr --host=$LFS_TGT
```

Compile the package:

```
make
```

Install the package:

```
make DESTDIR=$LFS install
```

Details on this package are located in Section 8.65.2, “Contents of Gzip.”



## 6.12. Make-4.4.1

The Make package contains a program for controlling the generation of executables and other non-source files of a package from source files.

**Approximate build time:** less than 0.1 SBU

**Required disk space:** 15 MB

### 6.12.1. Installation of Make

Prepare Make for compilation:

```
./configure --prefix=/usr \
            --without-guile \
            --host=$LFS_TGT \
            --build=$(build-aux/config.guess)
```

**The meaning of the new configure option:**

*--without-guile*

Although we are cross-compiling, configure tries to use guile from the build host if it finds it. This makes compilation fail, so this switch prevents using it.

Compile the package:

```
make
```

Install the package:

```
make DESTDIR=$LFS install
```

Details on this package are located in Section 8.69.2, “Contents of Make.”

## 6.13. Patch-2.7.6

The Patch package contains a program for modifying or creating files by applying a “patch” file typically created by the **diff** program.

**Approximate build time:** 0.1 SBU

**Required disk space:** 12 MB

### 6.13.1. Installation of Patch

Prepare Patch for compilation:

```
./configure --prefix=/usr \
            --host=$LFS_TGT \
            --build=$(build-aux/config.guess)
```

Compile the package:

```
make
```

Install the package:

```
make DESTDIR=$LFS install
```

Details on this package are located in Section 8.70.2, “Contents of Patch.”

## 6.14. Sed-4.9

The Sed package contains a stream editor.

**Approximate build time:** 0.1 SBU

**Required disk space:** 21 MB

### 6.14.1. Installation of Sed

Prepare Sed for compilation:

```
./configure --prefix=/usr \
            --host=$LFS_TGT \
            --build=$(./build-aux/config.guess)
```

Compile the package:

```
make
```

Install the package:

```
make DESTDIR=$LFS install
```

Details on this package are located in Section 8.31.2, “Contents of Sed.”

## 6.15. Tar-1.35

The Tar package provides the ability to create tar archives as well as perform various other kinds of archive manipulation. Tar can be used on previously created archives to extract files, to store additional files, or to update or list files which were already stored.

**Approximate build time:** 0.1 SBU

**Required disk space:** 42 MB

### 6.15.1. Installation of Tar

Prepare Tar for compilation:

```
./configure --prefix=/usr          \  
            --host=$LFS_TGT       \  
            --build=$(build-aux/config.guess)
```

Compile the package:

```
make
```

Install the package:

```
make DESTDIR=$LFS install
```

Details on this package are located in Section 8.71.2, “Contents of Tar.”

## 6.16. Xz-5.6.2

The Xz package contains programs for compressing and decompressing files. It provides capabilities for the lzma and the newer xz compression formats. Compressing text files with **xz** yields a better compression percentage than with the traditional **gzip** or **bzip2** commands.

**Approximate build time:** 0.1 SBU

**Required disk space:** 20 MB

### 6.16.1. Installation of Xz

Prepare Xz for compilation:

```
./configure --prefix=/usr          \  
            --host=$LFS_TGT        \  
            --build=$(build-aux/config.guess) \  
            --disable-static       \  
            --docdir=/usr/share/doc/xz-5.6.2
```

Compile the package:

```
make
```

Install the package:

```
make DESTDIR=$LFS install
```

Remove the libtool archive file because it is harmful for cross compilation:

```
rm -v $LFS/usr/lib/liblzma.la
```

Details on this package are located in Section 8.8.2, “Contents of Xz.”

## 6.17. Binutils-2.43.1 - Pass 2

The Binutils package contains a linker, an assembler, and other tools for handling object files.

**Approximate build time:** 0.4 SBU

**Required disk space:** 549 MB

### 6.17.1. Installation of Binutils

Binutils building system relies on an shipped libtool copy to link against internal static libraries, but the libiberty and zlib copies shipped in the package do not use libtool. This inconsistency may cause produced binaries mistakenly linked against libraries from the host distro. Work around this issue:

```
sed '6009s/$add_dir//' -i ltmain.sh
```

Create a separate build directory again:

```
mkdir -v build
cd      build
```

Prepare Binutils for compilation:

```
../configure          \
--prefix=/usr         \
--build=$(../config.guess) \
--host=$LFS_TGT       \
--disable-nls         \
--enable-shared       \
--enable-gprofng=no   \
--disable-werror      \
--enable-64-bit-bfd   \
--enable-new-dtags    \
--enable-default-hash-style=gnu
```

**The meaning of the new configure options:**

*--enable-shared*

Builds `libbfd` as a shared library.

*--enable-64-bit-bfd*

Enables 64-bit support (on hosts with smaller word sizes). This may not be needed on 64-bit systems, but it does no harm.

Compile the package:

```
make
```

Install the package:

```
make DESTDIR=$LFS install
```

Remove the libtool archive files because they are harmful for cross compilation, and remove unnecessary static libraries:

```
rm -v $LFS/usr/lib/lib{bfd,ctf,ctf-nobfd,opcodes,sframe}.{a,la}
```

Details on this package are located in Section 8.20.2, “Contents of Binutils.”

## 6.18. GCC-14.2.0 - Pass 2

The GCC package contains the GNU compiler collection, which includes the C and C++ compilers.

**Approximate build time:** 4.2 SBU

**Required disk space:** 5.5 GB

### 6.18.1. Installation of GCC

As in the first build of GCC, the GMP, MPFR, and MPC packages are required. Unpack the tarballs and move them into the required directories:

```
tar -xf ../mpfr-4.2.1.tar.xz
mv -v mpfr-4.2.1 mpfr
tar -xf ../gmp-6.3.0.tar.xz
mv -v gmp-6.3.0 gmp
tar -xf ../mpc-1.3.1.tar.gz
mv -v mpc-1.3.1 mpc
```

If building on x86\_64, change the default directory name for 64-bit libraries to “lib”:

```
case $(uname -m) in
  x86_64)
    sed -e '/m64=/s/lib64/lib/' \
        -i.orig gcc/config/i386/t-linux64
    ;;
esac
```

Override the building rule of libgcc and libstdc++ headers, to allow building these libraries with POSIX threads support:

```
sed '/thread_header =/s/@.*@/gthr-posix.h/' \
    -i libgcc/Makefile.in libstdc++-v3/include/Makefile.in
```

Create a separate build directory again:

```
mkdir -v build
cd      build
```

Before starting to build GCC, remember to unset any environment variables that override the default optimization flags.

Now prepare GCC for compilation:

```
../configure \
--build=$(../config.guess) \
--host=$LFS_TGT \
--target=$LFS_TGT \
LDFLAGS_FOR_TARGET=-L$PWD/$LFS_TGT/libgcc \
--prefix=/usr \
--with-build-sysroot=$LFS \
--enable-default-pie \
--enable-default-ssp \
--disable-nls \
--disable-multilib \
--disable-libatomic \
--disable-libgomp \
--disable-libquadmath \
--disable-lsanitizer \
--disable-libssp \
--disable-libvtv \
--enable-languages=c,c++
```

**The meaning of the new configure options:**

```
--with-build-sysroot=$LFS
```

Normally, using `--host` ensures that a cross-compiler is used for building GCC, and that compiler knows that it has to look for headers and libraries in `$LFS`. But the build system for GCC uses other tools, which are not aware of this location. This switch is needed so those tools will find the needed files in `$LFS`, and not on the host.

```
--target=$LFS_TGT
```

We are cross-compiling GCC, so it's impossible to build target libraries (`libgcc` and `libstdc++`) with the GCC binaries compiled in this pass—those binaries won't run on the host. The GCC build system will attempt to use the host's C and C++ compilers as a workaround by default. Building the GCC target libraries with a different version of GCC is not supported, so using the host's compilers may cause the build to fail. This parameter ensures the libraries are built by GCC pass 1.

```
LDFLAGS_FOR_TARGET=...
```

Allow `libstdc++` to use the `libgcc` being built in this pass, instead of the previous version built in `gcc-pass1`. The previous version cannot properly support C++ exception handling because it was built without `libc` support.

```
--disable-libsanitizer
```

Disable GCC sanitizer runtime libraries. They are not needed for the temporary installation. In `gcc-pass1` it was implied by `--disable-libstdcxx`, and now we can explicitly pass it.

**Compile the package:**

```
make
```

**Install the package:**

```
make DESTDIR=$LFS install
```

As a finishing touch, create a utility symlink. Many programs and scripts run `cc` instead of `gcc`, which is used to keep programs generic and therefore usable on all kinds of UNIX systems where the GNU C compiler is not always installed. Running `cc` leaves the system administrator free to decide which C compiler to install:

```
ln -sv gcc $LFS/usr/bin/cc
```

Details on this package are located in Section 8.29.2, “Contents of GCC.”



# Chapter 7. Entering Chroot and Building Additional Temporary Tools

## 7.1. Introduction

This chapter shows how to build the last missing bits of the temporary system: the tools needed to build the various packages. Now that all circular dependencies have been resolved, a “chroot” environment, completely isolated from the host operating system (except for the running kernel), can be used for the build.

For proper operation of the isolated environment, some communication with the running kernel must be established. This is done via the so-called *Virtual Kernel File Systems*, which will be mounted before entering the chroot environment. You may want to verify that they are mounted by issuing the **findmnt** command.

Until Section 7.4, “Entering the Chroot Environment”, the commands must be run as `root`, with the `LFS` variable set. After entering chroot, all commands are run as `root`, fortunately without access to the OS of the computer you built LFS on. Be careful anyway, as it is easy to destroy the whole LFS system with bad commands.

## 7.2. Changing Ownership



### Note

The commands in the remainder of this book must be performed while logged in as user `root` and no longer as user `lfs`. Also, double check that `$LFS` is set in `root`'s environment.

Currently, the whole directory hierarchy in `$LFS` is owned by the user `lfs`, a user that exists only on the host system. If the directories and files under `$LFS` are kept as they are, they will be owned by a user ID without a corresponding account. This is dangerous because a user account created later could get this same user ID and would own all the files under `$LFS`, thus exposing these files to possible malicious manipulation.

To address this issue, change the ownership of the `$LFS/*` directories to user `root` by running the following command:

```
chown --from lfs -R root:root $LFS/{usr,lib,var,etc,bin,sbin,tools}
case $(uname -m) in
  x86_64) chown --from lfs -R root:root $LFS/lib64 ;;
esac
```

## 7.3. Preparing Virtual Kernel File Systems

Applications running in userspace utilize various file systems created by the kernel to communicate with the kernel itself. These file systems are virtual: no disk space is used for them. The content of these file systems resides in memory. These file systems must be mounted in the `$LFS` directory tree so the applications can find them in the chroot environment.

Begin by creating the directories on which these virtual file systems will be mounted:

```
mkdir -pv $LFS/{dev,proc,sys,run}
```

### 7.3.1. Mounting and Populating /dev

During a normal boot of an LFS system, the kernel automatically mounts the `devtmpfs` file system on the `/dev` directory; the kernel creates device nodes on that virtual file system during the boot process, or when a device is first detected or accessed. The `udev` daemon may change the ownership or permissions of the device nodes created by the kernel,

and create new device nodes or symlinks, to ease the work of distro maintainers and system administrators. (See Section 9.3.2.2, “Device Node Creation” for details.) If the host kernel supports `devtmpfs`, we can simply mount a `devtmpfs` at `$LFS/dev` and rely on the kernel to populate it.

But some host kernels lack `devtmpfs` support; these host distros use different methods to create the content of `/dev`. So the only host-agnostic way to populate the `$LFS/dev` directory is by bind mounting the host system's `/dev` directory. A bind mount is a special type of mount that makes a directory subtree or a file visible at some other location. Use the following command to do this.

```
mount -v --bind /dev $LFS/dev
```

## 7.3.2. Mounting Virtual Kernel File Systems

Now mount the remaining virtual kernel file systems:

```
mount -vt devpts devpts -o gid=5,mode=0620 $LFS/dev/pts
mount -vt proc proc $LFS/proc
mount -vt sysfs sysfs $LFS/sys
mount -vt tmpfs tmpfs $LFS/run
```

**The meaning of the mount options for `devpts`:**

*gid=5*

This ensures that all `devpts`-created device nodes are owned by group ID 5. This is the ID we will use later on for the `tty` group. We use the group ID instead of a name, since the host system might use a different ID for its `tty` group.

*mode=0620*

This ensures that all `devpts`-created device nodes have mode 0620 (user readable and writable, group writable). Together with the option above, this ensures that `devpts` will create device nodes that meet the requirements of `grantpt()`, meaning the Glibc `pt_chown` helper binary (which is not installed by default) is not necessary.

In some host systems, `/dev/shm` is a symbolic link to a directory, typically `/run/shm`. The `/run tmpfs` was mounted above so in this case only a directory needs to be created with the correct permissions.

In other host systems `/dev/shm` is a mount point for a `tmpfs`. In that case the mount of `/dev` above will only create `/dev/shm` as a directory in the chroot environment. In this situation we must explicitly mount a `tmpfs`:

```
if [ -h $LFS/dev/shm ]; then
    install -v -d -m 1777 $LFS$(realpath /dev/shm)
else
    mount -vt tmpfs -o nosuid,nodev tmpfs $LFS/dev/shm
fi
```

## 7.4. Entering the Chroot Environment

Now that all the packages which are required to build the rest of the needed tools are on the system, it is time to enter the chroot environment and finish installing the temporary tools. This environment will also be used to install the final system. As user `root`, run the following command to enter the environment that is, at the moment, populated with nothing but temporary tools:

```
chroot "$LFS" /usr/bin/env -i \
    HOME=/root \
    TERM="$TERM" \
    PS1='(lfs chroot) \u:\w\$ ' \
    PATH=/usr/bin:/usr/sbin \
    MAKEFLAGS="-j$(nproc)" \
    TESTSUITEFLAGS="-j$(nproc)" \
    /bin/bash --login
```

If you don't want to use all available logical cores, replace `$(nproc)` with the number of logical cores you want to use for building packages in this chapter and the following chapters. The test suites of some packages (notably Autoconf, Libtool, and Tar) in Chapter 8 are not affected by `MAKEFLAGS`, they use a `TESTSUITEFLAGS` environment variable instead. We set that here as well for running these test suites with multiple cores.

The `-i` option given to the `env` command will clear all the variables in the chroot environment. After that, only the `HOME`, `TERM`, `PS1`, and `PATH` variables are set again. The `TERM=$TERM` construct sets the `TERM` variable inside chroot to the same value as outside chroot. This variable is needed so programs like `vim` and `less` can operate properly. If other variables are desired, such as `CFLAGS` or `CXXFLAGS`, this is a good place to set them.

From this point on, there is no need to use the `LFS` variable any more because all work will be restricted to the LFS file system; the `chroot` command runs the Bash shell with the root (`/`) directory set to `$LFS`.

Notice that `/tools/bin` is not in the `PATH`. This means that the cross toolchain will no longer be used.

Also note that the `bash` prompt will say `I have no name!` This is normal because the `/etc/passwd` file has not been created yet.



### Note

It is important that all the commands throughout the remainder of this chapter and the following chapters are run from within the chroot environment. If you leave this environment for any reason (rebooting for example), ensure that the virtual kernel filesystems are mounted as explained in Section 7.3.1, “Mounting and Populating `/dev`” and Section 7.3.2, “Mounting Virtual Kernel File Systems” and enter chroot again before continuing with the installation.

## 7.5. Creating Directories

It is time to create the full directory structure in the LFS file system.



### Note

Some of the directories mentioned in this section may have already been created earlier with explicit instructions, or when installing some packages. They are repeated below for completeness.

Create some root-level directories that are not in the limited set required in the previous chapters by issuing the following command:

```
mkdir -pv /{boot,home,mnt,opt,svr}
```

Create the required set of subdirectories below the root-level by issuing the following commands:

```
mkdir -pv /etc/{opt,sysconfig}
mkdir -pv /lib/firmware
mkdir -pv /media/{floppy,cdrom}
mkdir -pv /usr/{,local/}{include,src}
mkdir -pv /usr/lib/locale
mkdir -pv /usr/local/{bin,lib,sbin}
mkdir -pv /usr/{,local/}share/{color,dict,doc,info,locale,man}
mkdir -pv /usr/{,local/}share/{misc,terminfo,zoneinfo}
mkdir -pv /usr/{,local/}share/man/man{1..8}
mkdir -pv /var/{cache,local,log,mail,opt,spool}
mkdir -pv /var/lib/{color,misc,locate}

ln -sfv /run /var/run
ln -sfv /run/lock /var/lock

install -dv -m 0750 /root
install -dv -m 1777 /tmp /var/tmp
```

Directories are, by default, created with permission mode 755, but this is not desirable everywhere. In the commands above, two changes are made—one to the home directory of user `root`, and another to the directories for temporary files.

The first mode change ensures that not just anybody can enter the `/root` directory—just like a normal user would do with his or her own home directory. The second mode change makes sure that any user can write to the `/tmp` and `/var/tmp` directories, but cannot remove another user's files from them. The latter is prohibited by the so-called “sticky bit,” the highest bit (1) in the 1777 bit mask.

### 7.5.1. FHS Compliance Note

This directory tree is based on the Filesystem Hierarchy Standard (FHS) (available at <https://refspecs.linuxfoundation.org/fhs.shtml>). The FHS also specifies the optional existence of additional directories such as `/usr/local/games` and `/usr/share/games`. In LFS, we create only the directories that are really necessary. However, feel free to create more directories, if you wish.



#### Warning

The FHS does not mandate the existence of the directory `/usr/lib64`, and the LFS editors have decided not to use it. For the instructions in LFS and BLFS to work correctly, it is imperative that this directory be non-existent. From time to time you should verify that it does not exist, because it is easy to create it inadvertently, and this will probably break your system.

## 7.6. Creating Essential Files and Symlinks

Historically, Linux maintained a list of the mounted file systems in the file `/etc/mtab`. Modern kernels maintain this list internally and expose it to the user via the `/proc` filesystem. To satisfy utilities that expect to find `/etc/mtab`, create the following symbolic link:

```
ln -sv /proc/self/mounts /etc/mtab
```

Create a basic `/etc/hosts` file to be referenced in some test suites, and in one of Perl's configuration files as well:

```
cat > /etc/hosts << EOF
127.0.0.1 localhost $(hostname)
::1 localhost
EOF
```

In order for user `root` to be able to login and for the name “`root`” to be recognized, there must be relevant entries in the `/etc/passwd` and `/etc/group` files.

Create the `/etc/passwd` file by running the following command:

```
cat > /etc/passwd << "EOF"
root:x:0:0:root:/root:/bin/bash
bin:x:1:1:bin:/dev/null:/usr/bin/false
daemon:x:6:6:Daemon User:/dev/null:/usr/bin/false
messagebus:x:18:18:D-Bus Message Daemon User:/run/dbus:/usr/bin/false
systemd-journal-gateway:x:73:73:systemd Journal Gateway:/:/usr/bin/false
systemd-journal-remote:x:74:74:systemd Journal Remote:/:/usr/bin/false
systemd-journal-upload:x:75:75:systemd Journal Upload:/:/usr/bin/false
systemd-network:x:76:76:systemd Network Management:/:/usr/bin/false
systemd-resolve:x:77:77:systemd Resolver:/:/usr/bin/false
systemd-timesync:x:78:78:systemd Time Synchronization:/:/usr/bin/false
systemd-coredump:x:79:79:systemd Core Dumper:/:/usr/bin/false
uidd:x:80:80:UUID Generation Daemon User:/dev/null:/usr/bin/false
systemd-oom:x:81:81:systemd Out Of Memory Daemon:/:/usr/bin/false
nobody:x:65534:65534:Unprivileged User:/dev/null:/usr/bin/false
EOF
```

The actual password for `root` will be set later.

Create the `/etc/group` file by running the following command:

```
cat > /etc/group << "EOF"
root:x:0:
bin:x:1:daemon
sys:x:2:
kmem:x:3:
tape:x:4:
tty:x:5:
daemon:x:6:
floppy:x:7:
disk:x:8:
lp:x:9:
dialout:x:10:
audio:x:11:
video:x:12:
utmp:x:13:
cdrom:x:15:
adm:x:16:
messagebus:x:18:
systemd-journal:x:23:
input:x:24:
mail:x:34:
kvm:x:61:
systemd-journal-gateway:x:73:
systemd-journal-remote:x:74:
systemd-journal-upload:x:75:
systemd-network:x:76:
systemd-resolve:x:77:
systemd-timesync:x:78:
systemd-coredump:x:79:
uidd:x:80:
systemd-oom:x:81:
wheel:x:97:
users:x:999:
nogroup:x:65534:
EOF
```

The created groups are not part of any standard—they are groups decided on in part by the requirements of the Udev configuration in Chapter 9, and in part by common conventions employed by a number of existing Linux distributions. In addition, some test suites rely on specific users or groups. The Linux Standard Base (LSB, available at <https://refspecs.linuxfoundation.org/lsb.shtml>) only recommends that, besides the group `root` with a Group ID (GID) of 0, a group `bin` with a GID of 1 be present. The GID of 5 is widely used for the `tty` group, and the number 5 is also used in systemd for the `devpts` filesystem. All other group names and GIDs can be chosen freely by the system administrator since well-written programs do not depend on GID numbers, but rather use the group's name.

The ID 65534 is used by the kernel for NFS and separate user namespaces for unmapped users and groups (those exist on the NFS server or the parent user namespace, but “do not exist” on the local machine or in the separate namespace). We assign `nobody` and `nogroup` to avoid an unnamed ID. But other distros may treat this ID differently, so any portable program should not depend on this assignment.

Some packages need a locale.

```
localedef -i C -f UTF-8 C.UTF-8
```

Some tests in Chapter 8 need a regular user. We add this user here and delete this account at the end of that chapter.

```
echo "tester:x:101:101::/home/tester:/bin/bash" >> /etc/passwd
echo "tester:x:101:" >> /etc/group
install -o tester -d /home/tester
```

To remove the “I have no name!” prompt, start a new shell. Since the `/etc/passwd` and `/etc/group` files have been created, user name and group name resolution will now work:

```
exec /usr/bin/bash --login
```

The `login`, `agetty`, and `init` programs (and others) use a number of log files to record information such as who was logged into the system and when. However, these programs will not write to the log files if they do not already exist. Initialize the log files and give them proper permissions:

```
touch /var/log/{btmp,lastlog,faillog,wtmp}
chgrp -v utmp /var/log/lastlog
chmod -v 664 /var/log/lastlog
chmod -v 600 /var/log/btmp
```

The `/var/log/wtmp` file records all logins and logouts. The `/var/log/lastlog` file records when each user last logged in. The `/var/log/faillog` file records failed login attempts. The `/var/log/btmp` file records the bad login attempts.



## Note

The `wtmp`, `btmp`, and `lastlog` files use 32-bit integers for timestamps and they'll be fundamentally broken after year 2038. Many packages have stopped using them and other packages are going to stop using them. It is probably best to consider them deprecated.

## 7.7. Gettext-0.22.5

The Gettext package contains utilities for internationalization and localization. These allow programs to be compiled with NLS (Native Language Support), enabling them to output messages in the user's native language.

**Approximate build time:** 1.1 SBU

**Required disk space:** 321 MB

### 7.7.1. Installation of Gettext

For our temporary set of tools, we only need to install three programs from Gettext.

Prepare Gettext for compilation:

```
./configure --disable-shared
```

**The meaning of the configure option:**

*--disable-shared*

We do not need to install any of the shared Gettext libraries at this time, therefore there is no need to build them.

Compile the package:

```
make
```

Install the **msgfmt**, **msgmerge**, and **xgettext** programs:

```
cp -v gettext-tools/src/{msgfmt,msgmerge,xgettext} /usr/bin
```

Details on this package are located in Section 8.33.2, “Contents of Gettext.”

## 7.8. Bison-3.8.2

The Bison package contains a parser generator.

**Approximate build time:** 0.2 SBU

**Required disk space:** 57 MB

### 7.8.1. Installation of Bison

Prepare Bison for compilation:

```
./configure --prefix=/usr \  
            --docdir=/usr/share/doc/bison-3.8.2
```

**The meaning of the new configure option:**

```
--docdir=/usr/share/doc/bison-3.8.2
```

This tells the build system to install bison documentation into a versioned directory.

Compile the package:

```
make
```

Install the package:

```
make install
```

Details on this package are located in Section 8.34.2, “Contents of Bison.”



## 7.9. Perl-5.40.0

The Perl package contains the Practical Extraction and Report Language.

**Approximate build time:** 0.6 SBU

**Required disk space:** 285 MB

### 7.9.1. Installation of Perl

Prepare Perl for compilation:

```
sh Configure -des \
-D prefix=/usr \
-D vendorprefix=/usr \
-D useshrplib \
-D privlib=/usr/lib/perl5/5.40/core_perl \
-D archlib=/usr/lib/perl5/5.40/core_perl \
-D sitelib=/usr/lib/perl5/5.40/site_perl \
-D sitearch=/usr/lib/perl5/5.40/site_perl \
-D vendorlib=/usr/lib/perl5/5.40/vendor_perl \
-D vendorarch=/usr/lib/perl5/5.40/vendor_perl
```

**The meaning of the Configure options:**

*-des*  
This is a combination of three options: *-d* uses defaults for all items; *-e* ensures completion of all tasks; *-s* silences non-essential output.

*-D vendorprefix=/usr*  
This ensures **perl** knows how to tell packages where they should install their Perl modules.

*-D useshrplib*  
Build `libperl` needed by some Perl modules as a shared library, instead of a static library.

*-D privlib, -D archlib, -D sitelib, ...*  
These settings define where Perl looks for installed modules. The LFS editors chose to put them in a directory structure based on the MAJOR.MINOR version of Perl (5.40) which allows upgrading Perl to newer patch levels (the patch level is the last dot separated part in the full version string like 5.40.0) without reinstalling all of the modules.

Compile the package:

```
make
```

Install the package:

```
make install
```

Details on this package are located in Section 8.43.2, “Contents of Perl.”

## 7.10. Python-3.12.5

The Python 3 package contains the Python development environment. It is useful for object-oriented programming, writing scripts, prototyping large programs, and developing entire applications. Python is an interpreted computer language.

**Approximate build time:** 0.4 SBU

**Required disk space:** 603 MB

### 7.10.1. Installation of Python



#### Note

There are two package files whose name starts with the “python” prefix. The one to extract from is `Python-3.12.5.tar.xz` (notice the uppercase first letter).

Prepare Python for compilation:

```
./configure --prefix=/usr \
            --enable-shared \
            --without-ensurepip
```

**The meaning of the configure option:**

*--enable-shared*

This switch prevents installation of static libraries.

*--without-ensurepip*

This switch disables the Python package installer, which is not needed at this stage.

Compile the package:

```
make
```



#### Note

Some Python 3 modules can't be built now because the dependencies are not installed yet. For the `ssl` module, a message `Python requires a OpenSSL 1.1.1 or newer` is outputted. The message should be ignored. Just make sure the toplevel **make** command has not failed. The optional modules are not needed now and they will be built in Chapter 8.

Install the package:

```
make install
```

Details on this package are located in Section 8.52.2, “Contents of Python 3.”

## 7.11. Texinfo-7.1

The Texinfo package contains programs for reading, writing, and converting info pages.

**Approximate build time:** 0.2 SBU

**Required disk space:** 130 MB

### 7.11.1. Installation of Texinfo

Prepare Texinfo for compilation:

```
./configure --prefix=/usr
```

Compile the package:

```
make
```

Install the package:

```
make install
```

Details on this package are located in Section 8.72.2, “Contents of Texinfo.”

## 7.12. Util-linux-2.40.2

The Util-linux package contains miscellaneous utility programs.

**Approximate build time:** 0.2 SBU

**Required disk space:** 180 MB

### 7.12.1. Installation of Util-linux

The FHS recommends using the `/var/lib/hwclock` directory instead of the usual `/etc` directory as the location for the `adjtime` file. Create this directory with:

```
mkdir -pv /var/lib/hwclock
```

Prepare Util-linux for compilation:

```
./configure --libdir=/usr/lib \
            --runstatedir=/run \
            --disable-chfn-chsh \
            --disable-login \
            --disable-nologin \
            --disable-su \
            --disable-setpriv \
            --disable-runuser \
            --disable-pylibmount \
            --disable-static \
            --disable-libblastlog2 \
            --without-python \
            ADJTIME_PATH=/var/lib/hwclock/adjtime \
            --docdir=/usr/share/doc/util-linux-2.40.2
```

**The meaning of the configure options:**

```
ADJTIME_PATH=/var/lib/hwclock/adjtime
```

This sets the location of the file recording information about the hardware clock in accordance to the FHS. This is not strictly needed for this temporary tool, but it prevents creating a file at another location, which would not be overwritten or removed when building the final util-linux package.

```
--libdir=/usr/lib
```

This switch ensures the `.so` symlinks targeting the shared library file in the same directory (`/usr/lib`) directly.

```
--disable-*
```

These switches prevent warnings about building components that require packages not in LFS or not installed yet.

```
--without-python
```

This switch disables using Python. It avoids trying to build unneeded bindings.

```
runstatedir=/run
```

This switch sets the location of the socket used by **uuid** and `libuuid` correctly.

Compile the package:

```
make
```

Install the package:

```
make install
```

Details on this package are located in Section 8.80.2, “Contents of Util-linux.”

## 7.13. Cleaning up and Saving the Temporary System

### 7.13.1. Cleaning

First, remove the currently installed documentation files to prevent them from ending up in the final system, and to save about 35 MB:

```
rm -rf /usr/share/{info,man,doc}/*
```

Second, on a modern Linux system, the libtool .la files are only useful for libltdl. No libraries in LFS are loaded by libltdl, and it's known that some .la files can cause BLFS package failures. Remove those files now:

```
find /usr/{lib,libexec} -name \*.la -delete
```

The current system size is now about 3 GB, however the /tools directory is no longer needed. It uses about 1 GB of disk space. Delete it now:

```
rm -rf /tools
```

### 7.13.2. Backup

At this point the essential programs and libraries have been created and your current LFS system is in a good state. Your system can now be backed up for later reuse. In case of fatal failures in the subsequent chapters, it often turns out that removing everything and starting over (more carefully) is the best way to recover. Unfortunately, all the temporary files will be removed, too. To avoid spending extra time to redo something which has been done successfully, creating a backup of the current LFS system may prove useful.



#### Note

All the remaining steps in this section are optional. Nevertheless, as soon as you begin installing packages in Chapter 8, the temporary files will be overwritten. So it may be a good idea to do a backup of the current system as described below.

The following steps are performed from outside the chroot environment. That means you have to leave the chroot environment first before continuing. The reason for that is to get access to file system locations outside of the chroot environment to store/read the backup archive, which ought not be placed within the \$LFS hierarchy.

If you have decided to make a backup, leave the chroot environment:

```
exit
```



#### Important

All of the following instructions are executed by `root` on your host system. Take extra care about the commands you're going to run as mistakes made here can modify your host system. Be aware that the environment variable `LFS` is set for user `lfs` by default but may *not* be set for `root`.

Whenever commands are to be executed by `root`, make sure you have set `LFS`.

This has been discussed in Section 2.6, “Setting The \$LFS Variable.”

Before making a backup, unmount the virtual file systems:

```
mountpoint -q $LFS/dev/shm && umount $LFS/dev/shm
umount $LFS/dev/pts
umount $LFS/{sys,proc,run,dev}
```

Make sure you have at least 1 GB free disk space (the source tarballs will be included in the backup archive) on the file system containing the directory where you create the backup archive.

Note that the instructions below specify the home directory of the host system's `root` user, which is typically found on the root file system. Replace `$HOME` by a directory of your choice if you do not want to have the backup stored in `root`'s home directory.

Create the backup archive by running the following command:



### Note

Because the backup archive is compressed, it takes a relatively long time (over 10 minutes) even on a reasonably fast system.

```
cd $LFS
tar -cJpf $HOME/lfs-temp-tools-12.2-systemd.tar.xz .
```



### Note

If continuing to chapter 8, don't forget to reenter the chroot environment as explained in the “Important” box below.

## 7.13.3. Restore

In case some mistakes have been made and you need to start over, you can use this backup to restore the system and save some recovery time. Since the sources are located under `$LFS`, they are included in the backup archive as well, so they do not need to be downloaded again. After checking that `$LFS` is set properly, you can restore the backup by executing the following commands:



### Warning

The following commands are extremely dangerous. If you run `rm -rf /*` as the `root` user and you do not change to the `$LFS` directory or the `LFS` environment variable is not set for the `root` user, it will destroy your entire host system. **YOU ARE WARNED.**

```
cd $LFS
rm -rf /*
tar -xpf $HOME/lfs-temp-tools-12.2-systemd.tar.xz
```

Again, double check that the environment has been set up properly and continue building the rest of the system.



### Important

If you left the chroot environment to create a backup or restart building using a restore, remember to check that the virtual file systems are still mounted (`findmnt | grep $LFS`). If they are not mounted, remount them now as described in Section 7.3, “Preparing Virtual Kernel File Systems” and re-enter the chroot environment (see Section 7.4, “Entering the Chroot Environment”) before continuing.

## **Part IV. Building the LFS System**

# Chapter 8. Installing Basic System Software

## 8.1. Introduction

In this chapter, we start constructing the LFS system in earnest.

The installation of this software is straightforward. Although in many cases the installation instructions could be made shorter and more generic, we have opted to provide the full instructions for every package to minimize the possibilities for mistakes. The key to learning what makes a Linux system work is to know what each package is used for and why you (or the system) may need it.

We do not recommend using customized optimizations. They can make a program run slightly faster, but they may also cause compilation difficulties, and problems when running the program. If a package refuses to compile with a customized optimization, try to compile it without optimization and see if that fixes the problem. Even if the package does compile when using a customized optimization, there is the risk it may have been compiled incorrectly because of the complex interactions between the code and the build tools. Also note that the `-march` and `-mtune` options using values not specified in the book have not been tested. This may cause problems with the toolchain packages (Binutils, GCC and Glibc). The small potential gains achieved by customizing compiler optimizations are often outweighed by the risks. First-time builders of LFS are encouraged to build without custom optimizations.

On the other hand, we keep the optimizations enabled by the default configuration of the packages. In addition, we sometimes explicitly enable an optimized configuration provided by a package but not enabled by default. The package maintainers have already tested these configurations and consider them safe, so it's not likely they would break the build. Generally the default configuration already enables `-O2` or `-O3`, so the resulting system will still run very fast without any customized optimization, and be stable at the same time.

Before the installation instructions, each installation page provides information about the package, including a concise description of what it contains, approximately how long it will take to build, and how much disk space is required during this building process. Following the installation instructions, there is a list of programs and libraries (along with brief descriptions) that the package installs.



### Note

The SBU values and required disk space include test suite data for all applicable packages in Chapter 8. SBU values have been calculated using four CPU cores (`-j4`) for all operations unless specified otherwise.

### 8.1.1. About Libraries

In general, the LFS editors discourage building and installing static libraries. Most static libraries have been made obsolete in a modern Linux system. In addition, linking a static library into a program can be detrimental. If an update to the library is needed to remove a security problem, every program that uses the static library will need to be relinked with the new library. Since the use of static libraries is not always obvious, the relevant programs (and the procedures needed to do the linking) may not even be known.

The procedures in this chapter remove or disable installation of most static libraries. Usually this is done by passing a `--disable-static` option to **configure**. In other cases, alternate means are needed. In a few cases, especially Glibc and GCC, the use of static libraries remains an essential feature of the package building process.

For a more complete discussion of libraries, see *Libraries: Static or shared?* in the BLFS book.



## 8.2. Package Management

Package Management is an often requested addition to the LFS Book. A Package Manager tracks the installation of files, making it easier to remove and upgrade packages. A good package manager will also handle the configuration files specially to keep the user configuration when the package is reinstalled or upgraded. Before you begin to wonder, NO—this section will not talk about nor recommend any particular package manager. What it does provide is a roundup of the more popular techniques and how they work. The perfect package manager for you may be among these techniques, or it may be a combination of two or more of these techniques. This section briefly mentions issues that may arise when upgrading packages.

Some reasons why no package manager is mentioned in LFS or BLFS include:

- Dealing with package management takes the focus away from the goals of these books—teaching how a Linux system is built.
- There are multiple solutions for package management, each having its strengths and drawbacks. Finding one solution that satisfies all audiences is difficult.

There are some hints written on the topic of package management. Visit the *Hints Project* and see if one of them fits your needs.

### 8.2.1. Upgrade Issues

A Package Manager makes it easy to upgrade to newer versions when they are released. Generally the instructions in the LFS and BLFS books can be used to upgrade to the newer versions. Here are some points that you should be aware of when upgrading packages, especially on a running system.

- If the Linux kernel needs to be upgraded (for example, from 5.10.17 to 5.10.18 or 5.11.1), nothing else needs to be rebuilt. The system will keep working fine thanks to the well-defined interface between the kernel and userspace. Specifically, Linux API headers need not be upgraded along with the kernel. You will merely need to reboot your system to use the upgraded kernel.
- If Glibc needs to be upgraded to a newer version, (e.g., from Glibc-2.36 to Glibc-2.40), some extra steps are needed to avoid breaking the system. Read Section 8.5, “Glibc-2.40” for details.
- If a package containing a shared library is updated, and if the name of the library changes, then any packages dynamically linked to the library must be recompiled, to link against the newer library. (Note that there is no correlation between the package version and the name of the library.) For example, consider a package `foo-1.2.3` that installs a shared library with the name `libfoo.so.1`. Suppose you upgrade the package to a newer version `foo-1.2.4` that installs a shared library with the name `libfoo.so.2`. In this case, any packages that are dynamically linked to `libfoo.so.1` need to be recompiled to link against `libfoo.so.2` in order to use the new library version. You should not remove the old libraries until all the dependent packages have been recompiled.
- If a package is (directly or indirectly) linked to both the old and new names of a shared library (for example, the package links to both `libfoo.so.2` and `libbar.so.1`, while the latter links to `libfoo.so.3`), the package may malfunction because the different revisions of the shared library present incompatible definitions for some symbol names. This can be caused by recompiling some, but not all, of the packages linked to the old shared library after the package providing the shared library is upgraded. To avoid the issue, users will need to rebuild every package linked to a shared library with an updated revision (e.g. `libfoo.so.2` to `libfoo.so.3`) as soon as possible.
- If a package containing a shared library is updated, and the name of the library doesn't change, but the version number of the library **file** decreases (for example, the library is still named `libfoo.so.1`, but the name of the library file is changed from `libfoo.so.1.25` to `libfoo.so.1.24`), you should remove the library file from the previously

installed version (`libfoo.so.1.25` in this case). Otherwise, a **ldconfig** command (invoked by yourself from the command line, or by the installation of some package) will reset the symlink `libfoo.so.1` to point to the old library file because it seems to be a “newer” version; its version number is larger. This situation may arise if you have to downgrade a package, or if the authors change the versioning scheme for library files.

- If a package containing a shared library is updated, and the name of the library doesn't change, but a severe issue (especially, a security vulnerability) is fixed, all running programs linked to the shared library should be restarted. The following command, run as `root` after the update is complete, will list which processes are using the old versions of those libraries (replace `libfoo` with the name of the library):

```
grep -l 'libfoo.*deleted' /proc/*/maps | tr -cd 0-9\\n | xargs -r ps u
```

If OpenSSH is being used to access the system and it is linked to the updated library, you must restart the **sshd** service, then logout, login again, and run the preceding command again to confirm that nothing is still using the deleted libraries.

If the **systemd** daemon (running as PID 1) is linked to the updated library, you can restart it without rebooting by running **systemctl daemon-reexec** as the `root` user.

- If an executable program or a shared library is overwritten, the processes using the code or data in that program or library may crash. The correct way to update a program or a shared library without causing the process to crash is to remove it first, then install the new version. The **install** command provided by `coreutils` has already implemented this, and most packages use that command to install binary files and libraries. This means that you won't be troubled by this issue most of the time. However, the install process of some packages (notably SpiderMonkey in BLFS) just overwrites the file if it exists; this causes a crash. So it's safer to save your work and close unneeded running processes before updating a package.

## 8.2.2. Package Management Techniques

The following are some common package management techniques. Before making a decision on a package manager, do some research on the various techniques, particularly the drawbacks of each particular scheme.

### 8.2.2.1. It is All in My Head!

Yes, this is a package management technique. Some folks do not need a package manager because they know the packages intimately and know which files are installed by each package. Some users also do not need any package management because they plan on rebuilding the entire system whenever a package is changed.

### 8.2.2.2. Install in Separate Directories

This is a simplistic package management technique that does not need a special program to manage the packages. Each package is installed in a separate directory. For example, package `foo-1.1` is installed in `/opt/foo-1.1` and a symlink is made from `/opt/foo` to `/opt/foo-1.1`. When a new version `foo-1.2` comes along, it is installed in `/opt/foo-1.2` and the previous symlink is replaced by a symlink to the new version.

Environment variables such as `PATH`, `MANPATH`, `INFOPATH`, `PKG_CONFIG_PATH`, `CPPFLAGS`, `LDFLAGS`, and the configuration file `/etc/ld.so.conf` may need to be expanded to include the corresponding subdirectories in `/opt/foo-x.y`.

This scheme is used by the BLFS book to install some very large packages to make it easier to upgrade them. If you install more than a few packages, this scheme becomes unmanageable. And some packages (for example Linux API headers and Glibc) may not work well with this scheme. **Never use this scheme system-wide.**

### 8.2.2.3. Symlink Style Package Management

This is a variation of the previous package management technique. Each package is installed as in the previous scheme. But instead of making the symlink via a generic package name, each file is symlinked into the `/usr` hierarchy. This removes the need to expand the environment variables. Though the symlinks can be created by the user, many package managers use this approach, and automate the creation of the symlinks. A few of the popular ones include Stow, Epkg, Graft, and Depot.

The installation script needs to be fooled, so the package thinks it is installed in `/usr` though in reality it is installed in the `/usr/pkg` hierarchy. Installing in this manner is not usually a trivial task. For example, suppose you are installing a package `libfoo-1.1`. The following instructions may not install the package properly:

```
./configure --prefix=/usr/pkg/libfoo/1.1
make
make install
```

The installation will work, but the dependent packages may not link to `libfoo` as you would expect. If you compile a package that links against `libfoo`, you may notice that it is linked to `/usr/pkg/libfoo/1.1/lib/libfoo.so.1` instead of `/usr/lib/libfoo.so.1` as you would expect. The correct approach is to use the `DESTDIR` variable to direct the installation. This approach works as follows:

```
./configure --prefix=/usr
make
make DESTDIR=/usr/pkg/libfoo/1.1 install
```

Most packages support this approach, but there are some which do not. For the non-compliant packages, you may either need to install the package manually, or you may find that it is easier to install some problematic packages into `/opt`.

### 8.2.2.4. Timestamp Based

In this technique, a file is timestamped before the installation of the package. After the installation, a simple use of the `find` command with the appropriate options can generate a log of all the files installed after the timestamp file was created. A package manager that uses this approach is `install-log`.

Though this scheme has the advantage of being simple, it has two drawbacks. If, during installation, the files are installed with any timestamp other than the current time, those files will not be tracked by the package manager. Also, this scheme can only be used when packages are installed one at a time. The logs are not reliable if two packages are installed simultaneously from two different consoles.

### 8.2.2.5. Tracing Installation Scripts

In this approach, the commands that the installation scripts perform are recorded. There are two techniques that one can use:

The `LD_PRELOAD` environment variable can be set to point to a library to be preloaded before installation. During installation, this library tracks the packages that are being installed by attaching itself to various executables such as `cp`, `install`, `mv` and tracking the system calls that modify the filesystem. For this approach to work, all the executables need to be dynamically linked without the `suid` or `sgid` bit. Preloading the library may cause some unwanted side-effects during installation. Therefore, it's a good idea to perform some tests to ensure that the package manager does not break anything, and that it logs all the appropriate files.

Another technique is to use `strace`, which logs all the system calls made during the execution of the installation scripts.

### 8.2.2.6. Creating Package Archives

In this scheme, the package installation is faked into a separate tree as previously described in the symlink style package management section. After the installation, a package archive is created using the installed files. This archive is then used to install the package on the local machine or even on other machines.

This approach is used by most of the package managers found in the commercial distributions. Examples of package managers that follow this approach are RPM (which, incidentally, is required by the *Linux Standard Base Specification*), pkg-utils, Debian's apt, and Gentoo's Portage system. A hint describing how to adopt this style of package management for LFS systems is located at <https://www.linuxfromscratch.org/hints/downloads/files/fakeroot.txt>.

The creation of package files that include dependency information is complex, and beyond the scope of LFS.

Slackware uses a **tar**-based system for package archives. This system purposely does not handle package dependencies as more complex package managers do. For details of Slackware package management, see <https://www.slackbook.org/html/package-management.html>.

### 8.2.2.7. User Based Management

This scheme, unique to LFS, was devised by Matthias Benkmann, and is available from the *Hints Project*. In this scheme, each package is installed as a separate user into the standard locations. Files belonging to a package are easily identified by checking the user ID. The features and shortcomings of this approach are too complex to describe in this section. For the details please see the hint at [https://www.linuxfromscratch.org/hints/downloads/files/more\\_control\\_and\\_pkg\\_man.txt](https://www.linuxfromscratch.org/hints/downloads/files/more_control_and_pkg_man.txt).

## 8.2.3. Deploying LFS on Multiple Systems

One of the advantages of an LFS system is that there are no files that depend on the position of files on a disk system. Cloning an LFS build to another computer with the same architecture as the base system is as simple as using **tar** on the LFS partition that contains the root directory (about 900MB uncompressed for a basic LFS build), copying that file via network transfer or CD-ROM / USB stick to the new system, and expanding it. After that, a few configuration files will have to be changed. Configuration files that may need to be updated include: `/etc/hosts`, `/etc/fstab`, `/etc/passwd`, `/etc/group`, `/etc/shadow`, and `/etc/ld.so.conf`.

A custom kernel may be needed for the new system, depending on differences in system hardware and the original kernel configuration.



#### Note

There have been some reports of issues when copying between similar but not identical architectures. For instance, the instruction set for an Intel system is not identical with the AMD processor's instructions, and later versions of some processors may provide instructions that are unavailable with earlier versions.

Finally, the new system has to be made bootable via Section 10.4, “Using GRUB to Set Up the Boot Process”.

## 8.3. Man-pages-6.9.1

The Man-pages package contains over 2,400 man pages.

**Approximate build time:** 0.1 SBU

**Required disk space:** 52 MB

### 8.3.1. Installation of Man-pages

Remove two man pages for password hashing functions. Libxcrypt will provide a better version of these man pages:

```
rm -v man3/crypt*
```

Install Man-pages by running:

```
make prefix=/usr install
```

### 8.3.2. Contents of Man-pages

**Installed files:** various man pages

#### Short Descriptions

`man pages` Describe C programming language functions, important device files, and significant configuration files

## 8.4. Iana-Etc-20240806

The Iana-Etc package provides data for network services and protocols.

**Approximate build time:** less than 0.1 SBU

**Required disk space:** 4.8 MB

### 8.4.1. Installation of Iana-Etc

For this package, we only need to copy the files into place:

```
cp services protocols /etc
```

### 8.4.2. Contents of Iana-Etc

**Installed files:** /etc/protocols and /etc/services

#### Short Descriptions

<code>/etc/protocols</code>	Describes the various DARPA Internet protocols that are available from the TCP/IP subsystem
<code>/etc/services</code>	Provides a mapping between friendly textual names for internet services, and their underlying assigned port numbers and protocol types

## 8.5. Glibc-2.40

The Glibc package contains the main C library. This library provides the basic routines for allocating memory, searching directories, opening and closing files, reading and writing files, string handling, pattern matching, arithmetic, and so on.

**Approximate build time:** 12 SBU

**Required disk space:** 3.1 GB

### 8.5.1. Installation of Glibc

Some of the Glibc programs use the non-FHS compliant `/var/db` directory to store their runtime data. Apply the following patch to make such programs store their runtime data in the FHS-compliant locations:

```
patch -Np1 -i ../glibc-2.40-fhs-1.patch
```

The Glibc documentation recommends building Glibc in a dedicated build directory:

```
mkdir -v build
cd      build
```

Ensure that the `ldconfig` and `sln` utilities will be installed into `/usr/sbin`:

```
echo "rootsbindir=/usr/sbin" > configparms
```

Prepare Glibc for compilation:

```
../configure --prefix=/usr          \
              --disable-werror      \
              --enable-kernel=4.19  \
              --enable-stack-protector=strong \
              --disable-nscd        \
              libc_cv_slibdir=/usr/lib
```

#### The meaning of the configure options:

`--disable-werror`

This option disables the `-Werror` option passed to GCC. This is necessary for running the test suite.

`--enable-kernel=4.19`

This option tells the build system that this Glibc may be used with kernels as old as 4.19. This means generating workarounds in case a system call introduced in a later version cannot be used.

`--enable-stack-protector=strong`

This option increases system security by adding extra code to check for buffer overflows, such as stack smashing attacks. Note that Glibc always explicitly overrides the default of GCC, so this option is still needed even though we've already specified `--enable-default-ssp` for GCC.

`--disable-nscd`

Do not build the name service cache daemon which is no longer used.

`libc_cv_slibdir=/usr/lib`

This variable sets the correct library for all systems. We do not want `lib64` to be used.

Compile the package:

```
make
```



## Important

In this section, the test suite for Glibc is considered critical. Do not skip it under any circumstance.

Generally a few tests do not pass. The test failures listed below are usually safe to ignore.

```
make check
```

You may see some test failures. The Glibc test suite is somewhat dependent on the host system. A few failures out of over 5000 tests can generally be ignored. This is a list of the most common issues seen for recent versions of LFS:

- *io/tst-lchmod* is known to fail in the LFS chroot environment.
- Some tests, for example *nss/tst-nss-files-hosts-multi* and *nptl/tst-thread-affinity\** are known to fail due to a timeout (especially when the system is relatively slow and/or running the test suite with multiple parallel make jobs). These tests can be identified with:

```
grep "Timed out" $(find -name \*.out)
```

It's possible to re-run a single test with enlarged timeout with **TIMEOUTFACTOR=<factor> make test t=<test name>**. For example, **TIMEOUTFACTOR=10 make test t=nss/tst-nss-files-hosts-multi** will re-run *nss/tst-nss-files-hosts-multi* with ten times the original timeout.

- Additionally, some tests may fail with a relatively old CPU model (for example *elf/tst-cpu-features-cpuinfo*) or host kernel version (for example *stdlib/tst-arc4random-thread*).

Though it is a harmless message, the install stage of Glibc will complain about the absence of `/etc/ld.so.conf`. Prevent this warning with:

```
touch /etc/ld.so.conf
```

Fix the Makefile to skip an outdated sanity check that fails with a modern Glibc configuration:

```
sed '/test-installation/s@$(PERL)@echo not running@' -i ../Makefile
```





## Important

If upgrading Glibc to a new minor version (for example, from Glibc-2.36 to Glibc-2.40) on a running LFS system, you need to take some extra precautions to avoid breaking the system:

- Upgrading Glibc on a LFS system prior to 11.0 (exclusive) is not supported. Rebuild LFS if you are running such an old LFS system but you need a newer Glibc.
- If upgrading on a LFS system prior to 12.0 (exclusive), install Libxcrypt following Section 8.27, “Libxcrypt-4.4.36.” In addition to a normal Libxcrypt installation, **you MUST follow the note in Libxcrypt section to install libxcrypt.so.1\* (replacing libxcrypt.so.1 from the prior Glibc installation).**
- If upgrading on a LFS system prior to 12.1 (exclusive), remove the **nscd** program:

```
rm -f /usr/sbin/nscd
```

If this system (prior to LFS 12.1, exclusive) is based on Systemd, it's also needed to disable and stop the **nscd** service now:

```
systemctl disable --now nscd
```

- Upgrade the kernel and reboot if it's older than 4.19 (check the current version with **uname -r**) or if you want to upgrade it anyway, following Section 10.3, “Linux-6.10.5.”
- Upgrade the kernel API headers if it's older than 4.19 (check the current version with **cat /usr/include/linux/version.h**) or if you want to upgrade it anyway, following Section 5.4, “Linux-6.10.5 API Headers” (but removing `$LFS` from the **cp** command).
- Perform a `DESTDIR` installation and upgrade the Glibc shared libraries on the system using one single **install** command:

```
make DESTDIR=$PWD/dest install
install -vm755 dest/usr/lib/*.so.* /usr/lib
```

It's imperative to strictly follow these steps above unless you completely understand what you are doing. **Any unexpected deviation may render the system completely unusable. YOU ARE WARNED.**

Then continue to run the **make install** command, the **sed** command against `/usr/bin/ldd`, and the commands to install the locales. Once they are finished, reboot the system immediately.

Install the package:

```
make install
```

Fix a hardcoded path to the executable loader in the **ldd** script:

```
sed '/RTLDLIST=/s@/usr@g' -i /usr/bin/ldd
```

Next, install the locales that can make the system respond in a different language. None of these locales are required, but if some of them are missing, the test suites of some packages will skip important test cases.

Individual locales can be installed using the **localedef** program. E.g., the second **localedef** command below combines the `/usr/share/i18n/locales/cs_CZ` charset-independent locale definition with the `/usr/share/i18n/charmaps/UTF-8.gz` charmap definition and appends the result to the `/usr/lib/locale/locale-archive` file. The following instructions will install the minimum set of locales necessary for the optimal coverage of tests:

```
localedef -i C -f UTF-8 C.UTF-8
localedef -i cs_CZ -f UTF-8 cs_CZ.UTF-8
localedef -i de_DE -f ISO-8859-1 de_DE
localedef -i de_DE@euro -f ISO-8859-15 de_DE@euro
localedef -i de_DE -f UTF-8 de_DE.UTF-8
localedef -i el_GR -f ISO-8859-7 el_GR
localedef -i en_GB -f ISO-8859-1 en_GB
localedef -i en_GB -f UTF-8 en_GB.UTF-8
localedef -i en_HK -f ISO-8859-1 en_HK
localedef -i en_PH -f ISO-8859-1 en_PH
localedef -i en_US -f ISO-8859-1 en_US
localedef -i en_US -f UTF-8 en_US.UTF-8
localedef -i es_ES -f ISO-8859-15 es_ES@euro
localedef -i es_MX -f ISO-8859-1 es_MX
localedef -i fa_IR -f UTF-8 fa_IR
localedef -i fr_FR -f ISO-8859-1 fr_FR
localedef -i fr_FR@euro -f ISO-8859-15 fr_FR@euro
localedef -i fr_FR -f UTF-8 fr_FR.UTF-8
localedef -i is_IS -f ISO-8859-1 is_IS
localedef -i is_IS -f UTF-8 is_IS.UTF-8
localedef -i it_IT -f ISO-8859-1 it_IT
localedef -i it_IT -f ISO-8859-15 it_IT@euro
localedef -i it_IT -f UTF-8 it_IT.UTF-8
localedef -i ja_JP -f EUC-JP ja_JP
localedef -i ja_JP -f SHIFT_JIS ja_JP.SJIS 2> /dev/null || true
localedef -i ja_JP -f UTF-8 ja_JP.UTF-8
localedef -i nl_NL@euro -f ISO-8859-15 nl_NL@euro
localedef -i ru_RU -f KOI8-R ru_RU.KOI8-R
localedef -i ru_RU -f UTF-8 ru_RU.UTF-8
localedef -i se_NO -f UTF-8 se_NO.UTF-8
localedef -i ta_IN -f UTF-8 ta_IN.UTF-8
localedef -i tr_TR -f UTF-8 tr_TR.UTF-8
localedef -i zh_CN -f GB18030 zh_CN.GB18030
localedef -i zh_HK -f BIG5-HKSCS zh_HK.BIG5-HKSCS
localedef -i zh_TW -f UTF-8 zh_TW.UTF-8
```

In addition, install the locale for your own country, language and character set.

Alternatively, install all the locales listed in the `glibc-2.40/localedata/SUPPORTED` file (it includes every locale listed above and many more) at once with the following time-consuming command:

```
make localedata/install-locales
```

Then use the **localedef** command to create and install locales not listed in the `glibc-2.40/localedata/SUPPORTED` file when you need them. For instance, the following two locales are needed for some tests later in this chapter:

```
localedef -i C -f UTF-8 C.UTF-8
localedef -i ja_JP -f SHIFT_JIS ja_JP.SJIS 2> /dev/null || true
```



## Note

Glibc now uses `libidn2` when resolving internationalized domain names. This is a run time dependency. If this capability is needed, the instructions for installing `libidn2` are in the *BLFS libidn2 page*.

## 8.5.2. Configuring Glibc

### 8.5.2.1. Adding nsswitch.conf

The `/etc/nsswitch.conf` file needs to be created because the Glibc defaults do not work well in a networked environment.

Create a new file `/etc/nsswitch.conf` by running the following:

```
cat > /etc/nsswitch.conf << "EOF"
# Begin /etc/nsswitch.conf

passwd: files systemd
group: files systemd
shadow: files systemd

hosts: mymachines resolve [!UNAVAIL=return] files myhostname dns
networks: files

protocols: files
services: files
ethers: files
rpc: files

# End /etc/nsswitch.conf
EOF
```

### 8.5.2.2. Adding Time Zone Data

Install and set up the time zone data with the following:

```
tar -xf ../../tzdata2024a.tar.gz

ZONEINFO=/usr/share/zoneinfo
mkdir -pv $ZONEINFO/{posix,right}

for tz in etcetera southamerica northamerica europe africa antarctica \
        asia australasia backward; do
    zic -L /dev/null -d $ZONEINFO      ${tz}
    zic -L /dev/null -d $ZONEINFO/posix ${tz}
    zic -L leapseconds -d $ZONEINFO/right ${tz}
done

cp -v zone.tab zone1970.tab iso3166.tab $ZONEINFO
zic -d $ZONEINFO -p America/New_York
unset ZONEINFO
```

**The meaning of the zic commands:**

```
zic -L /dev/null ...
```

This creates posix time zones without any leap seconds. It is conventional to put these in both `zoneinfo` and `zoneinfo/posix`. It is necessary to put the POSIX time zones in `zoneinfo`, otherwise various test suites will report errors. On an embedded system, where space is tight and you do not intend to ever update the time zones, you could save 1.9 MB by not using the `posix` directory, but some applications or test suites might produce some failures.

```
zic -L leapseconds ...
```

This creates right time zones, including leap seconds. On an embedded system, where space is tight and you do not intend to ever update the time zones, or care about the correct time, you could save 1.9MB by omitting the `right` directory.

```
zic ... -p ...
```

This creates the `posixrules` file. We use New York because POSIX requires the daylight saving time rules to be in accordance with US rules.

One way to determine the local time zone is to run the following script:

```
tzselect
```

After answering a few questions about the location, the script will output the name of the time zone (e.g., *America/Edmonton*). There are also some other possible time zones listed in `/usr/share/zoneinfo` such as *Canada/Eastern* or *EST5EDT* that are not identified by the script but can be used.

Then create the `/etc/localtime` file by running:

```
ln -sfv /usr/share/zoneinfo/<xxx> /etc/localtime
```

Replace `<xxx>` with the name of the time zone selected (e.g., *Canada/Eastern*).

### 8.5.2.3. Configuring the Dynamic Loader

By default, the dynamic loader (`/lib/ld-linux.so.2`) searches through `/usr/lib` for dynamic libraries that are needed by programs as they are run. However, if there are libraries in directories other than `/usr/lib`, these need to be added to the `/etc/ld.so.conf` file in order for the dynamic loader to find them. Two directories that are commonly known to contain additional libraries are `/usr/local/lib` and `/opt/lib`, so add those directories to the dynamic loader's search path.

Create a new file `/etc/ld.so.conf` by running the following:

```
cat > /etc/ld.so.conf << "EOF"
# Begin /etc/ld.so.conf
/usr/local/lib
/opt/lib
EOF
```

If desired, the dynamic loader can also search a directory and include the contents of files found there. Generally the files in this include directory are one line specifying the desired library path. To add this capability run the following commands:

```
cat >> /etc/ld.so.conf << "EOF"
# Add an include directory
include /etc/ld.so.conf.d/*.conf
EOF
mkdir -pv /etc/ld.so.conf.d
```

### 8.5.3. Contents of Glibc

<b>Installed programs:</b>	gencat, getconf, getent, iconv, iconvconfig, ldconfig, ldd, lddlibc4, ld.so (symlink to ld-linux-x86-64.so.2 or ld-linux.so.2), locale, localedef, makedb, mtrace, pcprofiledump, pldd, sln, sotruss, sprof, tzselect, xtrace, zdump, and zic
<b>Installed libraries:</b>	ld-linux-x86-64.so.2, ld-linux.so.2, libBrokenLocale.{a,so}, libanl.{a,so}, libc.{a,so}, libc_nonshared.a, libc_malloc_debug.so, libdl.{a,so.2}, libg.a, libm.{a,so}, libmcheck.a, libmemusage.so, libmvec.{a,so}, libnsl.so.1, libnss_compat.so, libnss_dns.so, libnss_files.so, libnss_hesiod.so, libpcprofile.so, libpthread.{a,so.0}, libresolv.{a,so}, librt.{a,so.1}, libthread_db.so, and libutil.{a,so.1}
<b>Installed directories:</b>	/usr/include/arpa, /usr/include/bits, /usr/include/gnu, /usr/include/net, /usr/include/netash, /usr/include/netatalk, /usr/include/netax25, /usr/include/neteconet, /usr/include/netinet, /usr/include/netipx, /usr/include/netiucv, /usr/include/netpacket, /usr/include/netrom, /usr/include/netrose, /usr/include/nfs, /usr/include/protocols, /usr/include/rpc, /usr/include/sys, /usr/lib/audit, /usr/lib/gconv, /usr/lib/locale, /usr/libexec/getconf, /usr/share/i18n, /usr/share/zoneinfo, and /var/lib/nss_db

### Short Descriptions

<b>gencat</b>	Generates message catalogues
<b>getconf</b>	Displays the system configuration values for file system specific variables
<b>getent</b>	Gets entries from an administrative database
<b>iconv</b>	Performs character set conversion
<b>iconvconfig</b>	Creates fastloading <b>iconv</b> module configuration files
<b>ldconfig</b>	Configures the dynamic linker runtime bindings
<b>ldd</b>	Reports which shared libraries are required by each given program or shared library
<b>lddlibc4</b>	Assists <b>ldd</b> with object files. It does not exist on newer architectures like x86_64
<b>locale</b>	Prints various information about the current locale
<b>localedef</b>	Compiles locale specifications
<b>makedb</b>	Creates a simple database from textual input
<b>mtrace</b>	Reads and interprets a memory trace file and displays a summary in human-readable format
<b>pcprofiledump</b>	Dump information generated by PC profiling
<b>pldd</b>	Lists dynamic shared objects used by running processes
<b>sln</b>	A statically linked <b>ln</b> program
<b>sotruss</b>	Traces shared library procedure calls of a specified command
<b>sprof</b>	Reads and displays shared object profiling data
<b>tzselect</b>	Asks the user about the location of the system and reports the corresponding time zone description
<b>xtrace</b>	Traces the execution of a program by printing the currently executed function
<b>zdump</b>	The time zone dumper
<b>zic</b>	The time zone compiler
<b>ld-* .so</b>	The helper program for shared library executables

<code>libBrokenLocale</code>	Used internally by Glibc as a gross hack to get broken programs (e.g., some Motif applications) running. See comments in <code>glibc-2.40/locale/broken_cur_max.c</code> for more information
<code>libanl</code>	Dummy library containing no functions. Previously was the asynchronous name lookup library, whose functions are now in <code>libc</code>
<code>libc</code>	The main C library
<code>libc_malloc_debug</code>	Turns on memory allocation checking when preloaded
<code>libdl</code>	Dummy library containing no functions. Previously was the dynamic linking interface library, whose functions are now in <code>libc</code>
<code>libg</code>	Dummy library containing no functions. Previously was a runtime library for <code>g++</code>
<code>libm</code>	The mathematical library
<code>libmvec</code>	The vector math library, linked in as needed when <code>libm</code> is used
<code>libmcheck</code>	Turns on memory allocation checking when linked to
<code>libmemusage</code>	Used by <b>memusage</b> to help collect information about the memory usage of a program
<code>libnsl</code>	The network services library, now deprecated
<code>libnss_*</code>	The Name Service Switch modules, containing functions for resolving host names, user names, group names, aliases, services, protocols, etc. Loaded by <code>libc</code> according to the configuration in <code>/etc/nsswitch.conf</code>
<code>libpcprofile</code>	Can be preloaded to PC profile an executable
<code>libpthread</code>	Dummy library containing no functions. Previously contained functions providing most of the interfaces specified by the POSIX.1c Threads Extensions and the semaphore interfaces specified by the POSIX.1b Real-time Extensions, now the functions are in <code>libc</code>
<code>libresolv</code>	Contains functions for creating, sending, and interpreting packets to the Internet domain name servers
<code>librt</code>	Contains functions providing most of the interfaces specified by the POSIX.1b Real-time Extensions
<code>libthread_db</code>	Contains functions useful for building debuggers for multi-threaded programs
<code>libutil</code>	Dummy library containing no functions. Previously contained code for “standard” functions used in many different Unix utilities. These functions are now in <code>libc</code>

## 8.6. Zlib-1.3.1

The Zlib package contains compression and decompression routines used by some programs.

**Approximate build time:** less than 0.1 SBU

**Required disk space:** 6.4 MB

### 8.6.1. Installation of Zlib

Prepare Zlib for compilation:

```
./configure --prefix=/usr
```

Compile the package:

```
make
```

To test the results, issue:

```
make check
```

Install the package:

```
make install
```

Remove a useless static library:

```
rm -fv /usr/lib/libz.a
```

### 8.6.2. Contents of Zlib

**Installed libraries:** libz.so

#### Short Descriptions

`libz` Contains compression and decompression functions used by some programs

## 8.7. Bzip2-1.0.8

The Bzip2 package contains programs for compressing and decompressing files. Compressing text files with **bzip2** yields a much better compression percentage than with the traditional **gzip**.

**Approximate build time:** less than 0.1 SBU

**Required disk space:** 7.2 MB

### 8.7.1. Installation of Bzip2

Apply a patch that will install the documentation for this package:

```
patch -Np1 -i ../bzip2-1.0.8-install_docs-1.patch
```

The following command ensures installation of symbolic links are relative:

```
sed -i 's@(\ln -s -f \)$(PREFIX)/bin/@\1@' Makefile
```

Ensure the man pages are installed into the correct location:

```
sed -i "s@(PREFIX)/man@(PREFIX)/share/man@g" Makefile
```

Prepare Bzip2 for compilation with:

```
make -f Makefile-libbz2_so
make clean
```

**The meaning of the make parameter:**

```
-f Makefile-libbz2_so
```

This will cause Bzip2 to be built using a different `Makefile` file, in this case the `Makefile-libbz2_so` file, which creates a dynamic `libbz2.so` library and links the Bzip2 utilities against it.

Compile and test the package:

```
make
```

Install the programs:

```
make PREFIX=/usr install
```

Install the shared library:

```
cp -av libbz2.so.* /usr/lib
ln -sv libbz2.so.1.0.8 /usr/lib/libbz2.so
```

Install the shared **bzip2** binary into the `/usr/bin` directory, and replace two copies of **bzip2** with symlinks:

```
cp -v bzip2-shared /usr/bin/bzip2
for i in /usr/bin/{bzcat,bunzip2}; do
  ln -sfv bzip2 $i
done
```

Remove a useless static library:

```
rm -fv /usr/lib/libbz2.a
```



## 8.7.2. Contents of Bzip2

<b>Installed programs:</b>	bunzip2 (link to bzip2), bzcata (link to bzip2), bzcmap (link to bzdiff), bzdiff, bzegrep (link to bzgrep), bzfgrep (link to bzgrep), bzgrep, bzip2, bzip2recover, bzless (link to bzmora), and bzmora
<b>Installed libraries:</b>	libbz2.so
<b>Installed directory:</b>	/usr/share/doc/bzip2-1.0.8

### Short Descriptions

<b>bunzip2</b>	Decompresses bzipped files
<b>bzcata</b>	Decompresses to standard output
<b>bzcmap</b>	Runs <b>cmp</b> on bzipped files
<b>bzdiff</b>	Runs <b>diff</b> on bzipped files
<b>bzegrep</b>	Runs <b>egrep</b> on bzipped files
<b>bzfgrep</b>	Runs <b>fgrep</b> on bzipped files
<b>bzgrep</b>	Runs <b>grep</b> on bzipped files
<b>bzip2</b>	Compresses files using the Burrows-Wheeler block sorting text compression algorithm with Huffman coding; the compression rate is better than that achieved by more conventional compressors using “Lempel-Ziv” algorithms, like <b>gzip</b>
<b>bzip2recover</b>	Tries to recover data from damaged bzipped files
<b>bzless</b>	Runs <b>less</b> on bzipped files
<b>bzmora</b>	Runs <b>more</b> on bzipped files
libbz2	The library implementing lossless, block-sorting data compression, using the Burrows-Wheeler algorithm

## 8.8. Xz-5.6.2

The Xz package contains programs for compressing and decompressing files. It provides capabilities for the lzma and the newer xz compression formats. Compressing text files with **xz** yields a better compression percentage than with the traditional **gzip** or **bzip2** commands.

**Approximate build time:** 0.1 SBU

**Required disk space:** 21 MB

### 8.8.1. Installation of Xz

Prepare Xz for compilation with:

```
./configure --prefix=/usr \
            --disable-static \
            --docdir=/usr/share/doc/xz-5.6.2
```

Compile the package:

```
make
```

To test the results, issue:

```
make check
```

Install the package:

```
make install
```

### 8.8.2. Contents of Xz

**Installed programs:** lzcat (link to xz), lzcmp (link to xzdiff), lzdiff (link to xzdiff), lzegrep (link to xzgrep), lzfgrep (link to xzgrep), lzgrep (link to xzgrep), lzless (link to xzless), lzma (link to xz), lzmadec, lzmainfo, lzmore (link to xzmore), unlzma (link to xz), unxz (link to xz), xz, xzcat (link to xz), xzcmp (link to xzdiff), xzdec, xzdiff, xzegrep (link to xzgrep), xzfgrep (link to xzgrep), xzgrep, xzless, and xzmore

**Installed libraries:** liblzma.so

**Installed directories:** /usr/include/lzma and /usr/share/doc/xz-5.6.2

### Short Descriptions

<b>lzcat</b>	Decompresses to standard output
<b>lzcmp</b>	Runs <b>cmp</b> on LZMA compressed files
<b>lzdiff</b>	Runs <b>diff</b> on LZMA compressed files
<b>lzegrep</b>	Runs <b>egrep</b> on LZMA compressed files
<b>lzfgrep</b>	Runs <b>fgrep</b> on LZMA compressed files
<b>lzgrep</b>	Runs <b>grep</b> on LZMA compressed files
<b>lzless</b>	Runs <b>less</b> on LZMA compressed files
<b>lzma</b>	Compresses or decompresses files using the LZMA format
<b>lzmadec</b>	A small and fast decoder for LZMA compressed files
<b>lzmainfo</b>	Shows information stored in the LZMA compressed file header

<b>lzmore</b>	Runs <b>more</b> on LZMA compressed files
<b>unlzma</b>	Decompresses files using the LZMA format
<b>unxz</b>	Decompresses files using the XZ format
<b>xz</b>	Compresses or decompresses files using the XZ format
<b>xzcat</b>	Decompresses to standard output
<b>xzcmp</b>	Runs <b>cmp</b> on XZ compressed files
<b>xzdec</b>	A small and fast decoder for XZ compressed files
<b>xzdiff</b>	Runs <b>diff</b> on XZ compressed files
<b>xzegrep</b>	Runs <b>egrep</b> on XZ compressed files
<b>xzfgrep</b>	Runs <b>fgrep</b> on XZ compressed files
<b>xzgrep</b>	Runs <b>grep</b> on XZ compressed files
<b>xzless</b>	Runs <b>less</b> on XZ compressed files
<b>xzmore</b>	Runs <b>more</b> on XZ compressed files
liblzma	The library implementing lossless, block-sorting data compression, using the Lempel-Ziv-Markov chain algorithm

## 8.9. Lz4-1.10.0

Lz4 is a lossless compression algorithm, providing compression speed greater than 500 MB/s per core. It features an extremely fast decoder, with speed in multiple GB/s per core. Lz4 can work with Zstandard to allow both algorithms to compress data faster.

**Approximate build time:** 0.1 SBU

**Required disk space:** 4.2 MB

### 8.9.1. Installation of Lz4

Compile the package:

```
make BUILD_STATIC=no PREFIX=/usr
```

To test the results, issue:

```
make -j1 check
```

Install the package:

```
make BUILD_STATIC=no PREFIX=/usr install
```

### 8.9.2. Contents of Lz4

**Installed programs:** lz4, lz4c (link to lz4), lz4cat (link to lz4), and unlz4 (link to lz4)

**Installed library:** liblz4.so

#### Short Descriptions

<b>lz4</b>	Compresses or decompresses files using the LZ4 format
<b>lz4c</b>	Compresses files using the LZ4 format
<b>lz4cat</b>	Lists the contents of a file compressed using the LZ4 format
<b>unlz4</b>	Decompresses files using the LZ4 format
<code>liblz4</code>	The library implementing lossless data compression, using the LZ4 algorithm

## 8.10. Zstd-1.5.6

Zstandard is a real-time compression algorithm, providing high compression ratios. It offers a very wide range of compression / speed trade-offs, while being backed by a very fast decoder.

**Approximate build time:** 0.4 SBU

**Required disk space:** 84 MB

### 8.10.1. Installation of Zstd

Compile the package:

```
make prefix=/usr
```



#### Note

In the test output there are several places that indicate 'failed'. These are expected and only 'FAIL' is an actual test failure. There should be no test failures.

To test the results, issue:

```
make check
```

Install the package:

```
make prefix=/usr install
```

Remove the static library:

```
rm -v /usr/lib/libzstd.a
```

### 8.10.2. Contents of Zstd

**Installed programs:** zstd, zstdcat (link to zstd), zstdgrep, zstdless, zstdmt (link to zstd), and unzstd (link to zstd)

**Installed library:** libzstd.so

#### Short Descriptions

<b>zstd</b>	Compresses or decompresses files using the ZSTD format
<b>zstdgrep</b>	Runs <b>grep</b> on ZSTD compressed files
<b>zstdless</b>	Runs <b>less</b> on ZSTD compressed files
<code>libzstd</code>	The library implementing lossless data compression, using the ZSTD algorithm

## 8.11. File-5.45

The File package contains a utility for determining the type of a given file or files.

**Approximate build time:** less than 0.1 SBU

**Required disk space:** 17 MB

### 8.11.1. Installation of File

Prepare File for compilation:

```
./configure --prefix=/usr
```

Compile the package:

```
make
```

To test the results, issue:

```
make check
```

Install the package:

```
make install
```

### 8.11.2. Contents of File

**Installed programs:** file

**Installed library:** libmagic.so

### Short Descriptions

**file** Tries to classify each given file; it does this by performing several tests—file system tests, magic number tests, and language tests

libmagic Contains routines for magic number recognition, used by the **file** program

## 8.12. Readline-8.2.13

The Readline package is a set of libraries that offer command-line editing and history capabilities.

**Approximate build time:** less than 0.1 SBU

**Required disk space:** 16 MB

### 8.12.1. Installation of Readline

Reinstalling Readline will cause the old libraries to be moved to <libraryname>.old. While this is normally not a problem, in some cases it can trigger a linking bug in **ldconfig**. This can be avoided by issuing the following two seds:

```
sed -i '/MV.*old/d' Makefile.in
sed -i '/{OLDSUFF}/c:' support/shlib-install
```

Prevent hard coding library search paths (rpath) into the shared libraries. This package does not need rpath for an installation into the standard location, and rpath may sometimes cause unwanted effects or even security issues:

```
sed -i 's/-Wl,-rpath,[^ ]*//' support/shobj-conf
```

Prepare Readline for compilation:

```
./configure --prefix=/usr \
            --disable-static \
            --with-curses \
            --docdir=/usr/share/doc/readline-8.2.13
```

**The meaning of the new configure option:**

*--with-curses*

This option tells Readline that it can find the termcap library functions in the curses library, not a separate termcap library. This will generate the correct `readline.pc` file.

Compile the package:

```
make SHLIB_LIBS="-lncursesw"
```

**The meaning of the make option:**

*SHLIB\_LIBS="-lncursesw"*

This option forces Readline to link against the `libncursesw` library.

This package does not come with a test suite.

Install the package:

```
make SHLIB_LIBS="-lncursesw" install
```

If desired, install the documentation:

```
install -v -m644 doc/*.{ps,pdf,html,dvi} /usr/share/doc/readline-8.2.13
```

### 8.12.2. Contents of Readline

**Installed libraries:** libhistory.so and libreadline.so

**Installed directories:** /usr/include/readline and /usr/share/doc/readline-8.2.13

### Short Descriptions

`libhistory` Provides a consistent user interface for recalling lines of history

`libreadline`

Provides a set of commands for manipulating text entered in an interactive session of a program



## 8.13. M4-1.4.19

The M4 package contains a macro processor.

**Approximate build time:** 0.3 SBU

**Required disk space:** 48 MB

### 8.13.1. Installation of M4

Prepare M4 for compilation:

```
./configure --prefix=/usr
```

Compile the package:

```
make
```

To test the results, issue:

```
make check
```

Install the package:

```
make install
```

### 8.13.2. Contents of M4

**Installed program:** m4

#### Short Descriptions

**m4** Copies the given files while expanding the macros that they contain. These macros are either built-in or user-defined and can take any number of arguments. Besides performing macro expansion, **m4** has built-in functions for including named files, running Unix commands, performing integer arithmetic, manipulating text, recursion, etc. The **m4** program can be used either as a front end to a compiler or as a macro processor in its own right

## 8.14. Bc-6.7.6

The Bc package contains an arbitrary precision numeric processing language.

**Approximate build time:** less than 0.1 SBU

**Required disk space:** 7.8 MB

### 8.14.1. Installation of Bc

Prepare Bc for compilation:

```
CC=gcc ./configure --prefix=/usr -G -O3 -r
```

**The meaning of the configure options:**

*CC=gcc*

This parameter specifies the compiler to use.

*-G*

Omit parts of the test suite that won't work until the bc program has been installed.

*-O3*

Specify the optimization to use.

*-r*

Enable the use of Readline to improve the line editing feature of bc.

Compile the package:

```
make
```

To test bc, run:

```
make test
```

Install the package:

```
make install
```

### 8.14.2. Contents of Bc

**Installed programs:** bc and dc

#### Short Descriptions

**bc** A command line calculator

**dc** A reverse-polish command line calculator

## 8.15. Flex-2.6.4

The Flex package contains a utility for generating programs that recognize patterns in text.

**Approximate build time:** 0.1 SBU

**Required disk space:** 33 MB

### 8.15.1. Installation of Flex

Prepare Flex for compilation:

```
./configure --prefix=/usr \
            --docdir=/usr/share/doc/flex-2.6.4 \
            --disable-static
```

Compile the package:

```
make
```

To test the results (about 0.5 SBU), issue:

```
make check
```

Install the package:

```
make install
```

A few programs do not know about **flex** yet and try to run its predecessor, **lex**. To support those programs, create a symbolic link named `lex` that runs `flex` in **lex** emulation mode, and also create the man page of **lex** as a symlink:

```
ln -sv flex /usr/bin/lex
ln -sv flex.1 /usr/share/man/man1/lex.1
```

### 8.15.2. Contents of Flex

**Installed programs:** flex, flex++ (link to flex), and lex (link to flex)

**Installed libraries:** libfl.so

**Installed directory:** /usr/share/doc/flex-2.6.4

### Short Descriptions

**flex** A tool for generating programs that recognize patterns in text; it allows for the versatility to specify the rules for pattern-finding, eradicating the need to develop a specialized program

**flex++** An extension of flex, is used for generating C++ code and classes. It is a symbolic link to **flex**

**lex** A symbolic link that runs **flex** in **lex** emulation mode

`libfl` The `flex` library

## 8.16. Tcl-8.6.14

The Tcl package contains the Tool Command Language, a robust general-purpose scripting language. The Expect package is written in Tcl (pronounced "tickle").

**Approximate build time:** 3.2 SBU

**Required disk space:** 91 MB

### 8.16.1. Installation of Tcl

This package and the next two (Expect and DejaGNU) are installed to support running the test suites for Binutils, GCC and other packages. Installing three packages for testing purposes may seem excessive, but it is very reassuring, if not essential, to know that the most important tools are working properly.

Prepare Tcl for compilation:

```
SRCDIR=$(pwd)
cd unix
./configure --prefix=/usr          \
            --mandir=/usr/share/man \
            --disable-rpath
```

**The meaning of the new configure parameters:**

*--disable-rpath*

This parameter prevents hard coding library search paths (rpath) into the binary executable files and shared libraries. This package does not need rpath for an installation into the standard location, and rpath may sometimes cause unwanted effects or even security issues.

Build the package:

```
make

sed -e "s|${SRCDIR}/unix|/usr/lib|" \
    -e "s|${SRCDIR}|/usr/include|" \
    -i tclConfig.sh

sed -e "s|${SRCDIR}/unix/pkgs/tdbc1.1.7|/usr/lib/tdbc1.1.7|" \
    -e "s|${SRCDIR}/pkgs/tdbc1.1.7/generic|/usr/include|" \
    -e "s|${SRCDIR}/pkgs/tdbc1.1.7/library|/usr/lib/tcl8.6|" \
    -e "s|${SRCDIR}/pkgs/tdbc1.1.7|/usr/include|" \
    -i pkgs/tdbc1.1.7/tdbcConfig.sh

sed -e "s|${SRCDIR}/unix/pkgs/itcl4.2.4|/usr/lib/itcl4.2.4|" \
    -e "s|${SRCDIR}/pkgs/itcl4.2.4/generic|/usr/include|" \
    -e "s|${SRCDIR}/pkgs/itcl4.2.4|/usr/include|" \
    -i pkgs/itcl4.2.4/itclConfig.sh

unset SRCDIR
```

The various “sed” instructions after the “make” command remove references to the build directory from the configuration files and replace them with the install directory. This is not mandatory for the remainder of LFS, but may be needed if a package built later uses Tcl.

To test the results, issue:

```
make test
```

Install the package:

```
make install
```

Make the installed library writable so debugging symbols can be removed later:

```
chmod -v u+w /usr/lib/libtcl8.6.so
```

Install Tcl's headers. The next package, Expect, requires them.

```
make install-private-headers
```

Now make a necessary symbolic link:

```
ln -sfv tclsh8.6 /usr/bin/tclsh
```

Rename a man page that conflicts with a Perl man page:

```
mv /usr/share/man/man3/{Thread,Tcl_Thread}.3
```

Optionally, install the documentation by issuing the following commands:

```
cd ..
tar -xf ../tcl8.6.14-html.tar.gz --strip-components=1
mkdir -v -p /usr/share/doc/tcl-8.6.14
cp -v -r ./html/* /usr/share/doc/tcl-8.6.14
```

## 8.16.2. Contents of Tcl

**Installed programs:** tclsh (link to tclsh8.6) and tclsh8.6  
**Installed library:** libtcl8.6.so and libtclstub8.6.a

### Short Descriptions

<b>tclsh8.6</b>	The Tcl command shell
<b>tclsh</b>	A link to tclsh8.6
libtcl8.6.so	The Tcl library
libtclstub8.6.a	The Tcl Stub library

## 8.17. Expect-5.45.4

The Expect package contains tools for automating, via scripted dialogues, interactive applications such as **telnet**, **ftp**, **passwd**, **fsck**, **rlogin**, and **tip**. Expect is also useful for testing these same applications as well as easing all sorts of tasks that are prohibitively difficult with anything else. The DejaGnu framework is written in Expect.

**Approximate build time:** 0.2 SBU

**Required disk space:** 3.9 MB

### 8.17.1. Installation of Expect

Expect needs PTYs to work. Verify that the PTYs are working properly inside the chroot environment by performing a simple test:

```
python3 -c 'from pty import spawn; spawn(["echo", "ok"])'
```

This command should output `ok`. If, instead, the output includes `OSError: out of pty devices`, then the environment is not set up for proper PTY operation. You need to exit from the chroot environment, read Section 7.3, “Preparing Virtual Kernel File Systems” again, and ensure the `devpts` file system (and other virtual kernel file systems) mounted correctly. Then reenter the chroot environment following Section 7.4, “Entering the Chroot Environment”. This issue needs to be resolved before continuing, or the test suites requiring Expect (for example the test suites of Bash, Binutils, GCC, GDBM, and of course Expect itself) will fail catastrophically, and other subtle breakages may also happen.

Now, make some changes to allow the package with `gcc-14.1` or later:

```
patch -Np1 -i ../expect-5.45.4-gcc14-1.patch
```

Prepare Expect for compilation:

```
./configure --prefix=/usr \
            --with-tcl=/usr/lib \
            --enable-shared \
            --disable-rpath \
            --mandir=/usr/share/man \
            --with-tclinclude=/usr/include
```

**The meaning of the configure options:**

`--with-tcl=/usr/lib`

This parameter is needed to tell **configure** where the `tclConfig.sh` script is located.

`--with-tclinclude=/usr/include`

This explicitly tells Expect where to find Tcl's internal headers.

Build the package:

```
make
```

To test the results, issue:

```
make test
```

Install the package:

```
make install
ln -svf expect5.45.4/libexpect5.45.4.so /usr/lib
```

## 8.17.2. Contents of Expect

**Installed program:** expect  
**Installed library:** libexpect5.45.4.so

### Short Descriptions

<b>expect</b>	Communicates with other interactive programs according to a script
<code>libexpect-5.45.4.so</code>	Contains functions that allow Expect to be used as a Tcl extension or to be used directly from C or C++ (without Tcl)

## 8.18. DejaGNU-1.6.3

The DejaGnu package contains a framework for running test suites on GNU tools. It is written in **expect**, which itself uses Tcl (Tool Command Language).

**Approximate build time:** less than 0.1 SBU  
**Required disk space:** 6.9 MB

### 8.18.1. Installation of DejaGNU

The upstream recommends building DejaGNU in a dedicated build directory:

```
mkdir -v build
cd      build
```

Prepare DejaGNU for compilation:

```
../configure --prefix=/usr
makeinfo --html --no-split -o doc/dejagnum.html ../doc/dejagnum.texi
makeinfo --plaintext      -o doc/dejagnum.txt  ../doc/dejagnum.texi
```

To test the results, issue:

```
make check
```

Install the package:

```
make install
install -v -dm755 /usr/share/doc/dejagnum-1.6.3
install -v -m644  doc/dejagnum.{html,txt} /usr/share/doc/dejagnum-1.6.3
```

### 8.18.2. Contents of DejaGNU

**Installed program:** dejagnum and runtest

#### Short Descriptions

**dejagnum** DejaGNU auxiliary command launcher

**runtest** A wrapper script that locates the proper **expect** shell and then runs DejaGNU



## 8.19. Pkgconf-2.3.0

The pkgconf package is a successor to pkg-config and contains a tool for passing the include path and/or library paths to build tools during the configure and make phases of package installations.

**Approximate build time:** less than 0.1 SBU

**Required disk space:** 4.7 MB

### 8.19.1. Installation of Pkgconf

Prepare Pkgconf for compilation:

```
./configure --prefix=/usr          \
            --disable-static       \
            --docdir=/usr/share/doc/pkgconf-2.3.0
```

Compile the package:

```
make
```

Install the package:

```
make install
```

To maintain compatibility with the original Pkg-config create two symlinks:

```
ln -sv pkgconf /usr/bin/pkg-config
ln -sv pkgconf.1 /usr/share/man/man1/pkg-config.1
```

### 8.19.2. Contents of Pkgconf

**Installed programs:** pkgconf, pkg-config (link to pkgconf), and bomtool

**Installed library:** libpkgconf.so

**Installed directory:** /usr/share/doc/pkgconf-2.3.0

#### Short Descriptions

**pkgconf** Returns meta information for the specified library or package

**bomtool** Generates a Software Bill Of Materials from pkg-config .pc files

**libpkgconf** Contains most of pkgconf's functionality, while allowing other tools like IDEs and compilers to use its frameworks

## 8.20. Binutils-2.43.1

The Binutils package contains a linker, an assembler, and other tools for handling object files.

**Approximate build time:** 2.0 SBU

**Required disk space:** 2.7 GB

### 8.20.1. Installation of Binutils

The Binutils documentation recommends building Binutils in a dedicated build directory:

```
mkdir -v build
cd      build
```

Prepare Binutils for compilation:

```
../configure --prefix=/usr      \
             --sysconfdir=/etc  \
             --enable-gold      \
             --enable-ld=default \
             --enable-plugins   \
             --enable-shared    \
             --disable-werror   \
             --enable-64-bit-bfd \
             --enable-new-dtags \
             --with-system-zlib  \
             --enable-default-hash-style=gnu
```

**The meaning of the new configure parameters:**

*--enable-gold*

Build the gold linker and install it as `ld.gold` (alongside the default linker).

*--enable-ld=default*

Build the original bfd linker and install it as both `ld` (the default linker) and `ld.bfd`.

*--enable-plugins*

Enables plugin support for the linker.

*--with-system-zlib*

Use the installed zlib library instead of building the included version.

Compile the package:

```
make tooldir=/usr
```

**The meaning of the make parameter:**

*tooldir=/usr*

Normally, the `tooldir` (the directory where the executables will ultimately be located) is set to `$(exec_prefix)/$(target_alias)`. For example, `x86_64` machines would expand that to `/usr/x86_64-pc-linux-gnu`. Because this is a custom system, this target-specific directory in `/usr` is not required. `$(exec_prefix)/$(target_alias)` would be used if the system were used to cross-compile (for example, compiling a package on an Intel machine that generates code that can be executed on PowerPC machines).



### Important

The test suite for Binutils in this section is considered critical. Do not skip it under any circumstances.

Test the results:

```
make -k check
```

For a list of failed tests, run:

```
grep '^FAIL:' $(find -name '*.log')
```

Twelve tests fail in the gold test suite when the `--enable-default-pie` and `--enable-default-ssp` options are passed to GCC.

Install the package:

```
make tooldir=/usr install
```

Remove useless static libraries:

```
rm -fv /usr/lib/lib{bfd,ctf,ctf-nobfd,gprofng,opcodes,sframe}.a
```

## 8.20.2. Contents of Binutils

<b>Installed programs:</b>	addr2line, ar, as, c++filt, dwp, elfedit, gprof, gprofng, ld, ld.bfd, ld.gold, nm, objcopy, objdump, ranlib, readelf, size, strings, and strip
<b>Installed libraries:</b>	libbfd.so, libctf.so, libctf-nobfd.so, libgprofng.so, libopcodes.so, and libsframe.so
<b>Installed directory:</b>	/usr/lib/ldscripts

### Short Descriptions

<b>addr2line</b>	Translates program addresses to file names and line numbers; given an address and the name of an executable, it uses the debugging information in the executable to determine which source file and line number are associated with the address
<b>ar</b>	Creates, modifies, and extracts from archives
<b>as</b>	An assembler that assembles the output of <b>gcc</b> into object files
<b>c++filt</b>	Used by the linker to de-mangle C++ and Java symbols and to keep overloaded functions from clashing
<b>dwp</b>	The DWARF packaging utility
<b>elfedit</b>	Updates the ELF headers of ELF files
<b>gprof</b>	Displays call graph profile data
<b>gprofng</b>	Gathers and analyzes performance data
<b>ld</b>	A linker that combines a number of object and archive files into a single file, relocating their data and tying up symbol references
<b>ld.gold</b>	A cut down version of <b>ld</b> that only supports the elf object file format
<b>ld.bfd</b>	A hard link to <b>ld</b>
<b>nm</b>	Lists the symbols occurring in a given object file
<b>objcopy</b>	Translates one type of object file into another
<b>objdump</b>	Displays information about the given object file, with options controlling the particular information to display; the information shown is useful to programmers who are working on the compilation tools

<b>ranlib</b>	Generates an index of the contents of an archive and stores it in the archive; the index lists all of the symbols defined by archive members that are relocatable object files
<b>readelf</b>	Displays information about ELF type binaries
<b>size</b>	Lists the section sizes and the total size for the given object files
<b>strings</b>	Outputs, for each given file, the sequences of printable characters that are of at least the specified length (defaulting to four); for object files, it prints, by default, only the strings from the initializing and loading sections while for other types of files, it scans the entire file
<b>strip</b>	Discards symbols from object files
libbfd	The Binary File Descriptor library
libctf	The Compat ANSI-C Type Format debugging support library
libctf-nobfd	A libctf variant which does not use libbfd functionality
libgprofng	A library containing most routines used by <b>gprofng</b>
libopcodes	A library for dealing with opcodes—the “readable text” versions of instructions for the processor; it is used for building utilities like <b>objdump</b>
libsframe	A library to support online backtracing using a simple unwinder

## 8.21. GMP-6.3.0

The GMP package contains math libraries. These have useful functions for arbitrary precision arithmetic.

**Approximate build time:** 0.3 SBU

**Required disk space:** 54 MB

### 8.21.1. Installation of GMP



#### Note

If you are building for 32-bit x86, but you have a CPU which is capable of running 64-bit code *and* you have specified `CFLAGS` in the environment, the configure script will attempt to configure for 64-bits and fail. Avoid this by invoking the configure command below with

```
ABI=32 ./configure ...
```



#### Note

The default settings of GMP produce libraries optimized for the host processor. If libraries suitable for processors less capable than the host's CPU are desired, generic libraries can be created by appending the `--host=none-linux-gnu` option to the **configure** command.

Prepare GMP for compilation:

```
./configure --prefix=/usr \
            --enable-cxx \
            --disable-static \
            --docdir=/usr/share/doc/gmp-6.3.0
```

**The meaning of the new configure options:**

`--enable-cxx`

This parameter enables C++ support

`--docdir=/usr/share/doc/gmp-6.3.0`

This variable specifies the correct place for the documentation.

Compile the package and generate the HTML documentation:

```
make
make html
```



#### Important

The test suite for GMP in this section is considered critical. Do not skip it under any circumstances.

Test the results:

```
make check 2>&1 | tee gmp-check-log
```



#### Caution

The code in gmp is highly optimized for the processor where it is built. Occasionally, the code that detects the processor misidentifies the system capabilities and there will be errors in the tests or other applications using the gmp libraries with the message `Illegal instruction`. In this case, gmp should be reconfigured with the option `--host=none-linux-gnu` and rebuilt.

Ensure that at least 199 tests in the test suite passed. Check the results by issuing the following command:

```
awk '/# PASS:/{total+=$3} ; END{print total}' gmp-check-log
```

Install the package and its documentation:

```
make install  
make install-html
```

## 8.21.2. Contents of GMP

**Installed libraries:** libgmp.so and libgmpxx.so

**Installed directory:** /usr/share/doc/gmp-6.3.0

### Short Descriptions

libgmp Contains precision math functions

libgmpxx Contains C++ precision math functions

## 8.22. MPFR-4.2.1

The MPFR package contains functions for multiple precision math.

**Approximate build time:** 0.2 SBU

**Required disk space:** 43 MB

### 8.22.1. Installation of MPFR

Prepare MPFR for compilation:

```
./configure --prefix=/usr      \
            --disable-static   \
            --enable-thread-safe \
            --docdir=/usr/share/doc/mpfr-4.2.1
```

Compile the package and generate the HTML documentation:

```
make
make html
```



#### Important

The test suite for MPFR in this section is considered critical. Do not skip it under any circumstances.

Test the results and ensure that all 198 tests passed:

```
make check
```

Install the package and its documentation:

```
make install
make install-html
```

### 8.22.2. Contents of MPFR

**Installed libraries:** libmpfr.so

**Installed directory:** /usr/share/doc/mpfr-4.2.1

#### Short Descriptions

`libmpfr` Contains multiple-precision math functions

## 8.23. MPC-1.3.1

The MPC package contains a library for the arithmetic of complex numbers with arbitrarily high precision and correct rounding of the result.

**Approximate build time:** 0.1 SBU

**Required disk space:** 22 MB

### 8.23.1. Installation of MPC

Prepare MPC for compilation:

```
./configure --prefix=/usr \
            --disable-static \
            --docdir=/usr/share/doc/mpc-1.3.1
```

Compile the package and generate the HTML documentation:

```
make
make html
```

To test the results, issue:

```
make check
```

Install the package and its documentation:

```
make install
make install-html
```

### 8.23.2. Contents of MPC

**Installed libraries:** libmpc.so

**Installed directory:** /usr/share/doc/mpc-1.3.1

#### Short Descriptions

`libmpc` Contains complex math functions



## 8.24. Attr-2.5.2

The Attr package contains utilities to administer the extended attributes of filesystem objects.

**Approximate build time:** less than 0.1 SBU

**Required disk space:** 4.1 MB

### 8.24.1. Installation of Attr

Prepare Attr for compilation:

```
./configure --prefix=/usr      \  
            --disable-static  \  
            --sysconfdir=/etc  \  
            --docdir=/usr/share/doc/attr-2.5.2
```

Compile the package:

```
make
```

The tests must be run on a filesystem that supports extended attributes such as the ext2, ext3, or ext4 filesystems. To test the results, issue:

```
make check
```

Install the package:

```
make install
```

### 8.24.2. Contents of Attr

**Installed programs:** attr, getfattr, and setfattr

**Installed library:** libattr.so

**Installed directories:** /usr/include/attr and /usr/share/doc/attr-2.5.2

### Short Descriptions

<b>attr</b>	Extends attributes on filesystem objects
<b>getfattr</b>	Gets the extended attributes of filesystem objects
<b>setfattr</b>	Sets the extended attributes of filesystem objects
<b>libattr</b>	Contains the library functions for manipulating extended attributes

## 8.25. Acl-2.3.2

The Acl package contains utilities to administer Access Control Lists, which are used to define fine-grained discretionary access rights for files and directories.

**Approximate build time:** less than 0.1 SBU

**Required disk space:** 6.3 MB

### 8.25.1. Installation of Acl

Prepare Acl for compilation:

```
./configure --prefix=/usr      \
            --disable-static   \
            --docdir=/usr/share/doc/acl-2.3.2
```

Compile the package:

```
make
```

The Acl tests must be run on a filesystem that supports access controls, but not until the Coreutils package has been built, using the Acl libraries. If desired, return to this package and run **make check** after the Coreutils package has been built.

Install the package:

```
make install
```

### 8.25.2. Contents of Acl

**Installed programs:** chacl, getfacl, and setfacl

**Installed library:** libacl.so

**Installed directories:** /usr/include/acl and /usr/share/doc/acl-2.3.2

#### Short Descriptions

<b>chacl</b>	Changes the access control list of a file or directory
<b>getfacl</b>	Gets file access control lists
<b>setfacl</b>	Sets file access control lists
libacl	Contains the library functions for manipulating Access Control Lists

## 8.26. Libcap-2.70

The Libcap package implements the userspace interface to the POSIX 1003.1e capabilities available in Linux kernels. These capabilities partition the all-powerful root privilege into a set of distinct privileges.

**Approximate build time:** less than 0.1 SBU  
**Required disk space:** 2.9 MB

### 8.26.1. Installation of Libcap

Prevent static libraries from being installed:

```
sed -i '/install -m.*STA/d' libcap/Makefile
```

Compile the package:

```
make prefix=/usr lib=lib
```

**The meaning of the make option:**

```
lib=lib
```

This parameter sets the library directory to `/usr/lib` rather than `/usr/lib64` on `x86_64`. It has no effect on `x86`.

To test the results, issue:

```
make test
```

Install the package:

```
make prefix=/usr lib=lib install
```

### 8.26.2. Contents of Libcap

**Installed programs:** capsh, getcap, getpcaps, and setcap  
**Installed library:** libcap.so and libpsx.so

#### Short Descriptions

<b>capsh</b>	A shell wrapper to explore and constrain capability support
<b>getcap</b>	Examines file capabilities
<b>getpcaps</b>	Displays the capabilities of the queried process(es)
<b>setcap</b>	Sets file capabilities
<code>libcap</code>	Contains the library functions for manipulating POSIX 1003.1e capabilities
<code>libpsx</code>	Contains functions to support POSIX semantics for syscalls associated with the pthread library

## 8.27. Libxcrypt-4.4.36

The Libxcrypt package contains a modern library for one-way hashing of passwords.

**Approximate build time:** 0.1 SBU

**Required disk space:** 12 MB

### 8.27.1. Installation of Libxcrypt

Prepare Libxcrypt for compilation:

```
./configure --prefix=/usr \
            --enable-hashes=strong,glibc \
            --enable-obsolete-api=no \
            --disable-static \
            --disable-failure-tokens
```

**The meaning of the new configure options:**

*--enable-hashes=strong,glibc*

Build strong hash algorithms recommended for security use cases, and the hash algorithms provided by traditional Glibc `libcrypt` for compatibility.

*--enable-obsolete-api=no*

Disable obsolete API functions. They are not needed for a modern Linux system built from source.

*--disable-failure-tokens*

Disable failure token feature. It's needed for compatibility with the traditional hash libraries of some platforms, but a Linux system based on Glibc does not need it.

Compile the package:

```
make
```

To test the results, issue:

```
make check
```

Install the package:

```
make install
```



#### Note

The instructions above disabled obsolete API functions since no package installed by compiling from sources would link against them at runtime. However, the only known binary-only applications that link against these functions require ABI version 1. If you must have such functions because of some binary-only application or to be compliant with LSB, build the package again with the following commands:

```
make distclean
./configure --prefix=/usr \
            --enable-hashes=strong,glibc \
            --enable-obsolete-api=glibc \
            --disable-static \
            --disable-failure-tokens
make
cp -av --remove-destination .libs/libcrypt.so.1* /usr/lib
```

## 8.27.2. Contents of Libxcrypt

**Installed libraries:**       libcrypt.so

### Short Descriptions

`libcrypt`     Contains functions to hash passwords

## 8.28. Shadow-4.16.0

The Shadow package contains programs for handling passwords in a secure way.

**Approximate build time:** 0.1 SBU

**Required disk space:** 112 MB

### 8.28.1. Installation of Shadow



#### Important

If you've installed Linux-PAM, you should follow *the BLFS shadow page* instead of this page to build (or, rebuild or upgrade) shadow.



#### Note

If you would like to enforce the use of strong passwords, refer to <https://www.linuxfromscratch.org/blfs/view/stable-systemd/postlfs/cracklib.html> for installing CrackLib prior to building Shadow. Then add `--with-libcrack` to the **configure** command below.

Disable the installation of the **groups** program and its man pages, as Coreutils provides a better version. Also, prevent the installation of manual pages that were already installed in Section 8.3, “Man-pages-6.9.1”:

```
sed -i 's/groups$(EXEEXT) //' src/Makefile.in
find man -name Makefile.in -exec sed -i 's/groups\.1 / /' {} \;
find man -name Makefile.in -exec sed -i 's/getspnam\.3 / /' {} \;
find man -name Makefile.in -exec sed -i 's/passwd\.5 / /' {} \;
```

Instead of using the default *crypt* method, use the much more secure *YESCRYPT* method of password encryption, which also allows passwords longer than 8 characters. It is also necessary to change the obsolete `/var/spool/mail` location for user mailboxes that Shadow uses by default to the `/var/mail` location used currently. And, remove `/bin` and `/sbin` from the `PATH`, since they are simply symlinks to their counterparts in `/usr`.



#### Note

If you wish to include `/bin` and/or `/sbin` in the `PATH` for some reason, modify the `PATH` in `.bashrc` after LFS has been built.

```
sed -e 's:#ENCRYPT_METHOD DES:ENCRYPT_METHOD YESCRYPT:' \
-e 's:/var/spool/mail:/var/mail:' \
-e '/PATH={s@/sbin:@;s@/bin:@}' \
-i etc/login.defs
```



#### Note

If you chose to build Shadow with Cracklib support, issue this command:

```
sed -i 's:DICTPATH.*:DICTPATH\t/lib/cracklib/pw_dict:' etc/login.defs
```

Prepare Shadow for compilation:

```
touch /usr/bin/passwd
./configure --sysconfdir=/etc \
            --disable-static \
            --with-{b,yes}crypt \
            --without-libbsd \
            --with-group-name-max-length=32
```

**The meaning of the new configuration options:**

#### **touch /usr/bin/passwd**

The file `/usr/bin/passwd` needs to exist because its location is hardcoded in some programs; if it does not already exist, the installation script will create it in the wrong place.

`--with-{b,yes}crypt`

The shell expands this to two switches, `--with-bcrypt` and `--with-yescrypt`. They allow shadow to use the Bcrypt and Yescrypt algorithms implemented by Libxcrypt for hashing passwords. These algorithms are more secure (in particular, much more resistant to GPU-based attacks) than the traditional SHA algorithms.

`--with-group-name-max-length=32`

The longest permissible user name is 32 characters. Make the maximum length of a group name the same.

`--without-libbsd`

Do not use the `readpassphrase` function from `libbsd` which is not in LFS. Use the internal copy instead.

Compile the package:

```
make
```

This package does not come with a test suite.

Install the package:

```
make exec_prefix=/usr install
make -C man install-man
```

## 8.28.2. Configuring Shadow

This package contains utilities to add, modify, and delete users and groups; set and change their passwords; and perform other administrative tasks. For a full explanation of what *password shadowing* means, see the `doc/HOWTO` file within the unpacked source tree. If you use Shadow support, keep in mind that programs which need to verify passwords (display managers, FTP programs, `pop3` daemons, etc.) must be Shadow-compliant. That is, they must be able to work with shadowed passwords.

To enable shadowed passwords, run the following command:

```
pwconv
```

To enable shadowed group passwords, run:

```
grpconv
```

Shadow's default configuration for the **useradd** utility needs some explanation. First, the default action for the **useradd** utility is to create the user and a group with the same name as the user. By default the user ID (UID) and group ID (GID) numbers will begin at 1000. This means if you don't pass extra parameters to **useradd**, each user will be a member of a unique group on the system. If this behavior is undesirable, you'll need to pass either the `-g` or `-N` parameter to **useradd**, or else change the setting of `USERGROUPS_ENAB` in `/etc/login.defs`. See *useradd(8)* for more information.

Second, to change the default parameters, the file `/etc/default/useradd` must be created and tailored to suit your particular needs. Create it with:

```
mkdir -p /etc/default
useradd -D --gid 999
```

#### `/etc/default/useradd` parameter explanations

`GROUP=999`

This parameter sets the beginning of the group numbers used in the `/etc/group` file. The particular value 999 comes from the `--gid` parameter above. You may set it to any desired value. Note that **useradd** will never reuse a UID or GID. If the number identified in this parameter is used, it will use the next available number. Note also that if you don't have a group with an ID equal to this number on your system, then the first time you use **useradd** without the `-g` parameter, an error message will be generated—`useradd: unknown GID 999`, even though the account has been created correctly. That is why we created the group `users` with this group ID in Section 7.6, “Creating Essential Files and Symlinks.”

`CREATE_MAIL_SPOOL=yes`

This parameter causes **useradd** to create a mailbox file for each new user. **useradd** will assign the group ownership of this file to the `mail` group with 0660 permissions. If you would rather not create these files, issue the following command:

```
sed -i '/MAIL/s/yes/no/' /etc/default/useradd
```

### 8.28.3. Setting the Root Password

Choose a password for user `root` and set it by running:

```
passwd root
```

### 8.28.4. Contents of Shadow

<b>Installed programs:</b>	<code>chage</code> , <code>chfn</code> , <code>chgpaswd</code> , <code>chpaswd</code> , <code>chsh</code> , <code>expiry</code> , <code>faillog</code> , <code>getsubids</code> , <code>gpaswd</code> , <code>groupadd</code> , <code>groupdel</code> , <code>groupmems</code> , <code>groupmod</code> , <code>grpck</code> , <code>grpconv</code> , <code>grpunconv</code> , <code>login</code> , <code>logoutd</code> , <code>newgidmap</code> , <code>newgrp</code> , <code>newuidmap</code> , <code>newusers</code> , <code>nologin</code> , <code>passwd</code> , <code>pwck</code> , <code>pwconv</code> , <code>pwunconv</code> , <code>sg</code> (link to <code>newgrp</code> ), <code>su</code> , <code>useradd</code> , <code>userdel</code> , <code>usermod</code> , <code>vigr</code> (link to <code>vipw</code> ), and <code>vipw</code>
<b>Installed directories:</b>	<code>/etc/default</code> and <code>/usr/include/shadow</code>
<b>Installed libraries:</b>	<code>libsubid.so</code>

### Short Descriptions

<b>chage</b>	Used to change the maximum number of days between obligatory password changes
<b>chfn</b>	Used to change a user's full name and other information
<b>chgpaswd</b>	Used to update group passwords in batch mode
<b>chpaswd</b>	Used to update user passwords in batch mode
<b>chsh</b>	Used to change a user's default login shell
<b>expiry</b>	Checks and enforces the current password expiration policy
<b>faillog</b>	Is used to examine the log of login failures, to set a maximum number of failures before an account is blocked, and to reset the failure count
<b>getsubids</b>	Is used to list the subordinate id ranges for a user



<b>gpasswd</b>	Is used to add and delete members and administrators to groups
<b>groupadd</b>	Creates a group with the given name
<b>groupdel</b>	Deletes the group with the given name
<b>groupmems</b>	Allows a user to administer his/her own group membership list without the requirement of super user privileges.
<b>groupmod</b>	Is used to modify the given group's name or GID
<b>grpck</b>	Verifies the integrity of the group files <code>/etc/group</code> and <code>/etc/gshadow</code>
<b>grpconv</b>	Creates or updates the shadow group file from the normal group file
<b>grpunconv</b>	Updates <code>/etc/group</code> from <code>/etc/gshadow</code> and then deletes the latter
<b>login</b>	Is used by the system to let users sign on
<b>logoutd</b>	Is a daemon used to enforce restrictions on log-on time and ports
<b>newgidmap</b>	Is used to set the gid mapping of a user namespace
<b>newgrp</b>	Is used to change the current GID during a login session
<b>newuidmap</b>	Is used to set the uid mapping of a user namespace
<b>newusers</b>	Is used to create or update an entire series of user accounts
<b>nologin</b>	Displays a message saying an account is not available; it is designed to be used as the default shell for disabled accounts
<b>passwd</b>	Is used to change the password for a user or group account
<b>pwck</b>	Verifies the integrity of the password files <code>/etc/passwd</code> and <code>/etc/shadow</code>
<b>pwconv</b>	Creates or updates the shadow password file from the normal password file
<b>pwunconv</b>	Updates <code>/etc/passwd</code> from <code>/etc/shadow</code> and then deletes the latter
<b>sg</b>	Executes a given command while the user's GID is set to that of the given group
<b>su</b>	Runs a shell with substitute user and group IDs
<b>useradd</b>	Creates a new user with the given name, or updates the default new-user information
<b>userdel</b>	Deletes the specified user account
<b>usermod</b>	Is used to modify the given user's login name, user identification (UID), shell, initial group, home directory, etc.
<b>vigr</b>	Edits the <code>/etc/group</code> or <code>/etc/gshadow</code> files
<b>vipw</b>	Edits the <code>/etc/passwd</code> or <code>/etc/shadow</code> files
<code>libsubid</code>	library to handle subordinate id ranges for users and groups

## 8.29. GCC-14.2.0

The GCC package contains the GNU compiler collection, which includes the C and C++ compilers.

**Approximate build time:** 46 SBU (with tests)

**Required disk space:** 6.3 GB

### 8.29.1. Installation of GCC

If building on `x86_64`, change the default directory name for 64-bit libraries to “lib”:

```
case $(uname -m) in
  x86_64)
    sed -e '/m64=/s/lib64/lib/' \
        -i.orig gcc/config/i386/t-linux64
    ;;
esac
```

The GCC documentation recommends building GCC in a dedicated build directory:

```
mkdir -v build
cd      build
```

Prepare GCC for compilation:

```
../configure --prefix=/usr          \
             LD=ld                  \
             --enable-languages=c,c++ \
             --enable-default-pie    \
             --enable-default-ssp    \
             --enable-host-pie       \
             --disable-multilib      \
             --disable-bootstrap     \
             --disable-fixincludes   \
             --with-system-zlib
```

GCC supports seven different computer languages, but the prerequisites for most of them have not yet been installed. See the *BLFS Book GCC page* for instructions on how to build all of GCC's supported languages.

#### The meaning of the new configure parameters:

*LD=ld*

This parameter makes the configure script use the `ld` program installed by the `Binutils` package built earlier in this chapter, rather than the cross-built version which would otherwise be used.

*--disable-fixincludes*

By default, during the installation of GCC some system headers would be “fixed” to be used with GCC. This is not necessary for a modern Linux system, and potentially harmful if a package is reinstalled after installing GCC. This switch prevents GCC from “fixing” the headers.

*--with-system-zlib*

This switch tells GCC to link to the system installed copy of the Zlib library, rather than its own internal copy.



## Note

PIE (position-independent executables) are binary programs that can be loaded anywhere in memory. Without PIE, the security feature named ASLR (Address Space Layout Randomization) can be applied for the shared libraries, but not for the executables themselves. Enabling PIE allows ASLR for the executables in addition to the shared libraries, and mitigates some attacks based on fixed addresses of sensitive code or data in the executables.

SSP (Stack Smashing Protection) is a technique to ensure that the parameter stack is not corrupted. Stack corruption can, for example, alter the return address of a subroutine, thus transferring control to some dangerous code (existing in the program or shared libraries, or injected by the attacker somehow).

Compile the package:

```
make
```



## Important

In this section, the test suite for GCC is considered important, but it takes a long time. First-time builders are encouraged to run the test suite. The time to run the tests can be reduced significantly by adding `-jx` to the **make -k check** command below, where `x` is the number of CPU cores on your system.

GCC may need more stack space compiling some extremely complex code patterns. As a precaution for the host distros with a tight stack limit, explicitly set the stack size hard limit to infinite. On most host distros (and the final LFS system) the hard limit is infinite by default, but there is no harm done by setting it explicitly. It's not necessary to change the stack size soft limit because GCC will automatically set it to an appropriate value, as long as the value does not exceed the hard limit:

```
ulimit -s -H unlimited
```

Now remove/fix several known test failures:

```
sed -e '/cpython/d' -i ../gcc/testsuite/gcc.dg/plugin/plugin.exp
sed -e 's/no-pic /&-no-pie /' -i ../gcc/testsuite/gcc.target/i386/pr113689-1.c
sed -e 's/300000/(1|300000)/' -i ../libgomp/testsuite/libgomp.c-c++-common/pr109062.c
sed -e 's/{ target nonpic } //' \
-e '/GOTPCREL/d' -i ../gcc/testsuite/gcc.target/i386/fentryname3.c
```

Test the results as a non-privileged user, but do not stop at errors:

```
chown -R tester .
su tester -c "PATH=$PATH make -k check"
```

To extract a summary of the test suite results, run:

```
../contrib/test_summary
```

To filter out only the summaries, pipe the output through `grep -A7 Summ.`

Results can be compared with those located at <https://www.linuxfromscratch.org/lfs/build-logs/12.2/> and <https://gcc.gnu.org/ml/gcc-testresults/>.

A few unexpected failures cannot always be avoided. In some cases test failures depend on the specific hardware of the system. Unless the test results are vastly different from those at the above URL, it is safe to continue.

Install the package:

```
make install
```

The GCC build directory is owned by `tester` now, and the ownership of the installed header directory (and its content) is incorrect. Change the ownership to the `root` user and group:

```
chown -v -R root:root \
  /usr/lib/gcc/$(gcc -dumpmachine)/14.2.0/include{,-fixed}
```

Create a symlink required by the *FHS* for "historical" reasons.

```
ln -svr /usr/bin/cpp /usr/lib
```

Many packages use the name `cc` to call the C compiler. We've already created `cc` as a symlink in `gcc-pass2`, create its man page as a symlink as well:

```
ln -sv gcc.1 /usr/share/man/man1/cc.1
```

Add a compatibility symlink to enable building programs with Link Time Optimization (LTO):

```
ln -sfv ../../libexec/gcc/$(gcc -dumpmachine)/14.2.0/liblto_plugin.so \
  /usr/lib/bfd-plugins/
```

Now that our final toolchain is in place, it is important to again ensure that compiling and linking will work as expected. We do this by performing some sanity checks:

```
echo 'int main(){}' > dummy.c
cc dummy.c -v -Wl,--verbose &> dummy.log
readelf -l a.out | grep ': /lib'
```

There should be no errors, and the output of the last command will be (allowing for platform-specific differences in the dynamic linker name):

```
[Requesting program interpreter: /lib64/ld-linux-x86-64.so.2]
```

Now make sure that we're set up to use the correct start files:

```
grep -E -o '/usr/lib.*S?crt[lin].*succeeded' dummy.log
```

The output of the last command should be:

```
/usr/lib/gcc/x86_64-pc-linux-gnu/14.2.0/../../../../lib/Scrt1.o succeeded
/usr/lib/gcc/x86_64-pc-linux-gnu/14.2.0/../../../../lib/crti.o succeeded
/usr/lib/gcc/x86_64-pc-linux-gnu/14.2.0/../../../../lib/crtn.o succeeded
```

Depending on your machine architecture, the above may differ slightly. The difference will be the name of the directory after `/usr/lib/gcc`. The important thing to look for here is that `gcc` has found all three `crt*.o` files under the `/usr/lib` directory.

Verify that the compiler is searching for the correct header files:

```
grep -B4 '^ /usr/include' dummy.log
```

This command should return the following output:

```
#include <...> search starts here:
 /usr/lib/gcc/x86_64-pc-linux-gnu/14.2.0/include
 /usr/local/include
 /usr/lib/gcc/x86_64-pc-linux-gnu/14.2.0/include-fixed
 /usr/include
```

Again, the directory named after your target triplet may be different than the above, depending on your system architecture.

Next, verify that the new linker is being used with the correct search paths:

```
grep 'SEARCH.*usr/lib' dummy.log | sed 's|;| |\n|g'
```

References to paths that have components with '-linux-gnu' should be ignored, but otherwise the output of the last command should be:

```
SEARCH_DIR( "/usr/x86_64-pc-linux-gnu/lib64" )
SEARCH_DIR( "/usr/local/lib64" )
SEARCH_DIR( "/lib64" )
SEARCH_DIR( "/usr/lib64" )
SEARCH_DIR( "/usr/x86_64-pc-linux-gnu/lib" )
SEARCH_DIR( "/usr/local/lib" )
SEARCH_DIR( "/lib" )
SEARCH_DIR( "/usr/lib" );
```

A 32-bit system may use a few other directories. For example, here is the output from an i686 machine:

```
SEARCH_DIR( "/usr/i686-pc-linux-gnu/lib32" )
SEARCH_DIR( "/usr/local/lib32" )
SEARCH_DIR( "/lib32" )
SEARCH_DIR( "/usr/lib32" )
SEARCH_DIR( "/usr/i686-pc-linux-gnu/lib" )
SEARCH_DIR( "/usr/local/lib" )
SEARCH_DIR( "/lib" )
SEARCH_DIR( "/usr/lib" );
```

Next make sure that we're using the correct libc:

```
grep "/lib.*/libc.so.6 " dummy.log
```

The output of the last command should be:

```
attempt to open /usr/lib/libc.so.6 succeeded
```

Make sure GCC is using the correct dynamic linker:

```
grep found dummy.log
```

The output of the last command should be (allowing for platform-specific differences in dynamic linker name):

```
found ld-linux-x86-64.so.2 at /usr/lib/ld-linux-x86-64.so.2
```

If the output does not appear as shown above or is not received at all, then something is seriously wrong. Investigate and retrace the steps to find out where the problem is and correct it. Any issues should be resolved before continuing with the process.

Once everything is working correctly, clean up the test files:

```
rm -v dummy.c a.out dummy.log
```

Finally, move a misplaced file:

```
mkdir -pv /usr/share/gdb/auto-load/usr/lib
mv -v /usr/lib/*gdb.py /usr/share/gdb/auto-load/usr/lib
```

## 8.29.2. Contents of GCC

<b>Installed programs:</b>	c++, cc (link to gcc), cpp, g++, gcc, gcc-ar, gcc-nm, gcc-ranlib, gcov, gcov-dump, gcov-tool, and lto-dump
<b>Installed libraries:</b>	libasan.{a,so}, libatomic.{a,so}, libcc1.so, libgcc.a, libgcc_eh.a, libgcc_s.so, libgcov.a, libgomp.{a,so}, libhwasan.{a,so}, libitm.{a,so}, liblsan.{a,so}, liblto_plugin.so, libquadmath.{a,so}, libssp.{a,so}, libssp_nonshared.a, libstdc++.a, libstdc++exp.a, libstdc++fs.a, libsupc++.a, libtsan.{a,so}, and libubsan.{a,so}
<b>Installed directories:</b>	/usr/include/c++, /usr/lib/gcc, /usr/libexec/gcc, and /usr/share/gcc-14.2.0

## Short Descriptions

<b>c++</b>	The C++ compiler
<b>cc</b>	The C compiler
<b>cpp</b>	The C preprocessor; it is used by the compiler to expand the <code>#include</code> , <code>#define</code> , and similar directives in the source files
<b>g++</b>	The C++ compiler
<b>gcc</b>	The C compiler
<b>gcc-ar</b>	A wrapper around <b>ar</b> that adds a plugin to the command line. This program is only used to add "link time optimization" and is not useful with the default build options.
<b>gcc-nm</b>	A wrapper around <b>nm</b> that adds a plugin to the command line. This program is only used to add "link time optimization" and is not useful with the default build options.
<b>gcc-ranlib</b>	A wrapper around <b>ranlib</b> that adds a plugin to the command line. This program is only used to add "link time optimization" and is not useful with the default build options.
<b>gcov</b>	A coverage testing tool; it is used to analyze programs to determine where optimizations will have the greatest effect
<b>gcov-dump</b>	Offline gcda and gcno profile dump tool
<b>gcov-tool</b>	Offline gcda profile processing tool
<b>lto-dump</b>	Tool for dumping object files produced by GCC with LTO enabled
<b>libasan</b>	The Address Sanitizer runtime library
<b>libatomic</b>	GCC atomic built-in runtime library
<b>libgcc1</b>	A library that allows GDB to make use of GCC
<b>libgcc</b>	Contains run-time support for <b>gcc</b>
<b>libgcov</b>	This library is linked into a program when GCC is instructed to enable profiling
<b>libgomp</b>	GNU implementation of the OpenMP API for multi-platform shared-memory parallel programming in C/C++ and Fortran
<b>libhwasan</b>	The Hardware-assisted Address Sanitizer runtime library
<b>libitm</b>	The GNU transactional memory library
<b>liblsan</b>	The Leak Sanitizer runtime library
<b>liblto_plugin</b>	GCC's LTO plugin allows Binutils to process object files produced by GCC with LTO enabled
<b>libquadmath</b>	GCC Quad Precision Math Library API
<b>libssp</b>	Contains routines supporting GCC's stack-smashing protection functionality. Normally it is not used, because Glibc also provides those routines.
<b>libstdc++</b>	The standard C++ library
<b>libstdc++exp</b>	Experimental C++ Contracts library
<b>libstdc++fs</b>	ISO/IEC TS 18822:2015 Filesystem library
<b>libsupc++</b>	Provides supporting routines for the C++ programming language
<b>libtsan</b>	The Thread Sanitizer runtime library
<b>libubsan</b>	The Undefined Behavior Sanitizer runtime library

## 8.30. Ncurses-6.5

The Ncurses package contains libraries for terminal-independent handling of character screens.

**Approximate build time:** 0.2 SBU

**Required disk space:** 46 MB

### 8.30.1. Installation of Ncurses

Prepare Ncurses for compilation:

```
./configure --prefix=/usr \
            --mandir=/usr/share/man \
            --with-shared \
            --without-debug \
            --without-normal \
            --with-cxx-shared \
            --enable-pc-files \
            --with-pkg-config-libdir=/usr/lib/pkgconfig
```

**The meaning of the new configure options:**

*--with-shared*

This makes Ncurses build and install shared C libraries.

*--without-normal*

This prevents Ncurses building and installing static C libraries.

*--without-debug*

This prevents Ncurses building and installing debug libraries.

*--with-cxx-shared*

This makes Ncurses build and install shared C++ bindings. It also prevents it building and installing static C++ bindings.

*--enable-pc-files*

This switch generates and installs .pc files for pkg-config.

Compile the package:

```
make
```

This package has a test suite, but it can only be run after the package has been installed. The tests reside in the `test/` directory. See the `README` file in that directory for further details.

The installation of this package will overwrite `libncursesw.so.6.5` in-place. It may crash the shell process which is using code and data from the library file. Install the package with `DESTDIR`, and replace the library file correctly using `install` command (the header `curses.h` is also edited to ensure the wide-character ABI to be used as what we've done in Section 6.3, “Ncurses-6.5”):

```
make DESTDIR=$PWD/dest install
install -vm755 dest/usr/lib/libncursesw.so.6.5 /usr/lib
rm -v dest/usr/lib/libncursesw.so.6.5
sed -e 's/^#if.*XOPEN.*$/#if 1/' \
     -i dest/usr/include/curses.h
cp -av dest/* /
```

Many applications still expect the linker to be able to find non-wide-character Ncurses libraries. Trick such applications into linking with wide-character libraries by means of symlinks (note that the `.so` links are only safe with `courses.h` edited to always use the wide-character ABI):

```
for lib in ncurses form panel menu ; do
    ln -sfv lib${lib}w.so /usr/lib/lib${lib}.so
    ln -sfv ${lib}w.pc    /usr/lib/pkgconfig/${lib}.pc
done
```

Finally, make sure that old applications that look for `-lcurses` at build time are still buildable:

```
ln -sfv libncursesw.so /usr/lib/libcurses.so
```

If desired, install the Ncurses documentation:

```
cp -v -R doc -T /usr/share/doc/ncurses-6.5
```



## Note

The instructions above don't create non-wide-character Ncurses libraries since no package installed by compiling from sources would link against them at runtime. However, the only known binary-only applications that link against non-wide-character Ncurses libraries require version 5. If you must have such libraries because of some binary-only application or to be compliant with LSB, build the package again with the following commands:

```
make distclean
./configure --prefix=/usr \
            --with-shared \
            --without-normal \
            --without-debug \
            --without-cxx-binding \
            --with-abi-version=5
make sources libs
cp -av lib/lib*.so.5* /usr/lib
```

## 8.30.2. Contents of Ncurses

<b>Installed programs:</b>	captinfo (link to tic), clear, infocmp, infotocap (link to tic), ncursesw6-config, reset (link to tset), tabs, tic, toe, tput, and tset
<b>Installed libraries:</b>	libcurses.so (symlink), libform.so (symlink), libformw.so, libmenu.so (symlink), libmenuw.so, libncurses.so (symlink), libncursesw.so, libncurses++w.so, libpanel.so (symlink), and libpanelw.so,
<b>Installed directories:</b>	/usr/share/tabset, /usr/share/terminfo, and /usr/share/doc/ncurses-6.5

## Short Descriptions

<b>captinfo</b>	Converts a termcap description into a terminfo description
<b>clear</b>	Clears the screen, if possible
<b>infocmp</b>	Compares or prints out terminfo descriptions
<b>infotocap</b>	Converts a terminfo description into a termcap description
<b>ncursesw6-config</b>	Provides configuration information for ncurses
<b>reset</b>	Reinitializes a terminal to its default values
<b>tabs</b>	Clears and sets tab stops on a terminal



<b>tic</b>	The terminfo entry-description compiler that translates a terminfo file from source format into the binary format needed for the ncurses library routines [A terminfo file contains information on the capabilities of a certain terminal.]
<b>toe</b>	Lists all available terminal types, giving the primary name and description for each
<b>tput</b>	Makes the values of terminal-dependent capabilities available to the shell; it can also be used to reset or initialize a terminal or report its long name
<b>tset</b>	Can be used to initialize terminals
<code>libncursesw</code>	Contains functions to display text in many complex ways on a terminal screen; a good example of the use of these functions is the menu displayed during the kernel's <b>make menuconfig</b>
<code>libncurses++w</code>	Contains C++ binding for other libraries in this package
<code>libformw</code>	Contains functions to implement forms
<code>libmenuw</code>	Contains functions to implement menus
<code>libpanelw</code>	Contains functions to implement panels

## 8.31. Sed-4.9

The Sed package contains a stream editor.

**Approximate build time:** 0.3 SBU

**Required disk space:** 30 MB

### 8.31.1. Installation of Sed

Prepare Sed for compilation:

```
./configure --prefix=/usr
```

Compile the package and generate the HTML documentation:

```
make
make html
```

To test the results, issue:

```
chown -R tester .
su tester -c "PATH=$PATH make check"
```

Install the package and its documentation:

```
make install
install -d -m755 /usr/share/doc/sed-4.9
install -m644 doc/sed.html /usr/share/doc/sed-4.9
```

### 8.31.2. Contents of Sed

**Installed program:** sed

**Installed directory:** /usr/share/doc/sed-4.9

#### Short Descriptions

**sed** Filters and transforms text files in a single pass

## 8.32. Psmisc-23.7

The Psmisc package contains programs for displaying information about running processes.

**Approximate build time:** less than 0.1 SBU

**Required disk space:** 6.7 MB

### 8.32.1. Installation of Psmisc

Prepare Psmisc for compilation:

```
./configure --prefix=/usr
```

Compile the package:

```
make
```

To run the test suite, run:

```
make check
```

Install the package:

```
make install
```

### 8.32.2. Contents of Psmisc

**Installed programs:** fuser, killall, peekfd, prtstat, pslog, pstree, and pstree.x11 (link to pstree)

#### Short Descriptions

<b>fuser</b>	Reports the Process IDs (PIDs) of processes that use the given files or file systems
<b>killall</b>	Kills processes by name; it sends a signal to all processes running any of the given commands
<b>peekfd</b>	Peek at file descriptors of a running process, given its PID
<b>prtstat</b>	Prints information about a process
<b>pslog</b>	Reports current logs path of a process
<b>pstree</b>	Displays running processes as a tree
<b>pstree.x11</b>	Same as <b>pstree</b> , except that it waits for confirmation before exiting

## 8.33. Gettext-0.22.5

The Gettext package contains utilities for internationalization and localization. These allow programs to be compiled with NLS (Native Language Support), enabling them to output messages in the user's native language.

**Approximate build time:** 1.6 SBU  
**Required disk space:** 260 MB

### 8.33.1. Installation of Gettext

Prepare Gettext for compilation:

```
./configure --prefix=/usr \
            --disable-static \
            --docdir=/usr/share/doc/gettext-0.22.5
```

Compile the package:

```
make
```

To test the results (this takes a long time, around 3 SBUs), issue:

```
make check
```

Install the package:

```
make install
chmod -v 0755 /usr/lib/preloadable_libintl.so
```

### 8.33.2. Contents of Gettext

**Installed programs:** autopoint, envsubst, gettext, gettext.sh, gettextize, msgattrib, msgcat, msgcmp, msgcomm, msgconv, msgen, msgexec, msgfilter, msgfmt, msggrep, msginit, msgmerge, msgunfmt, msguniq, ngettext, recode-sr-latin, and xgettext

**Installed libraries:** libasprintf.so, libgettextlib.so, libgettextpo.so, libgettextsrc.so, libtextstyle.so, and preloadable\_libintl.so

**Installed directories:** /usr/lib/gettext, /usr/share/doc/gettext-0.22.5, /usr/share/gettext, and /usr/share/gettext-0.22.5

### Short Descriptions

<b>autopoint</b>	Copies standard Gettext infrastructure files into a source package
<b>envsubst</b>	Substitutes environment variables in shell format strings
<b>gettext</b>	Translates a natural language message into the user's language by looking up the translation in a message catalog
<b>gettext.sh</b>	Primarily serves as a shell function library for gettext
<b>gettextize</b>	Copies all standard Gettext files into the given top-level directory of a package to begin internationalizing it
<b>msgattrib</b>	Filters the messages of a translation catalog according to their attributes and manipulates the attributes
<b>msgcat</b>	Concatenates and merges the given .po files
<b>msgcmp</b>	Compares two .po files to check that both contain the same set of msgid strings

<b>msgcomm</b>	Finds the messages that are common to the given <code>.po</code> files
<b>msgconv</b>	Converts a translation catalog to a different character encoding
<b>msgen</b>	Creates an English translation catalog
<b>msgexec</b>	Applies a command to all translations of a translation catalog
<b>msgfilter</b>	Applies a filter to all translations of a translation catalog
<b>msgfmt</b>	Generates a binary message catalog from a translation catalog
<b>msggrep</b>	Extracts all messages of a translation catalog that match a given pattern or belong to some given source files
<b>msginit</b>	Creates a new <code>.po</code> file, initializing the meta information with values from the user's environment
<b>msgmerge</b>	Combines two raw translations into a single file
<b>msgunfmt</b>	Decompiles a binary message catalog into raw translation text
<b>msguniq</b>	Unifies duplicate translations in a translation catalog
<b>ngettext</b>	Displays native language translations of a textual message whose grammatical form depends on a number
<b>recode-sr-latin</b>	Recodes Serbian text from Cyrillic to Latin script
<b>xgettext</b>	Extracts the translatable message lines from the given source files to make the first translation template
<code>libasprintf</code>	Defines the <i>autosprintf</i> class, which makes C formatted output routines usable in C++ programs, for use with the <code>&lt;string&gt;</code> strings and the <code>&lt;iostream&gt;</code> streams
<code>libgettextlib</code>	Contains common routines used by the various Gettext programs; these are not intended for general use
<code>libgettextpo</code>	Used to write specialized programs that process <code>.po</code> files; this library is used when the standard applications shipped with Gettext (such as <b>msgcomm</b> , <b>msgcmp</b> , <b>msgattrib</b> , and <b>msgen</b> ) will not suffice
<code>libgettextsrc</code>	Provides common routines used by the various Gettext programs; these are not intended for general use
<code>libtextstyle</code>	Text styling library
<code>preloadable_libintl</code>	A library, intended to be used by <code>LD_PRELOAD</code> , that helps <code>libintl</code> log untranslated messages

## 8.34. Bison-3.8.2

The Bison package contains a parser generator.

**Approximate build time:** 2.2 SBU

**Required disk space:** 62 MB

### 8.34.1. Installation of Bison

Prepare Bison for compilation:

```
./configure --prefix=/usr --docdir=/usr/share/doc/bison-3.8.2
```

Compile the package:

```
make
```

To test the results (about 5.5 SBU), issue:

```
make check
```

Install the package:

```
make install
```

### 8.34.2. Contents of Bison

**Installed programs:** bison and yacc

**Installed library:** liby.a

**Installed directory:** /usr/share/bison

### Short Descriptions

- bison** Generates, from a series of rules, a program for analyzing the structure of text files; Bison is a replacement for Yacc (Yet Another Compiler Compiler)
- yacc** A wrapper for **bison**, meant for programs that still call **yacc** instead of **bison**; it calls **bison** with the `-y` option
- liby** The Yacc library containing implementations of Yacc-compatible `yyerror` and `main` functions; this library is normally not very useful, but POSIX requires it

## 8.35. Grep-3.11

The Grep package contains programs for searching through the contents of files.

**Approximate build time:** 0.4 SBU

**Required disk space:** 39 MB

### 8.35.1. Installation of Grep

First, remove a warning about using `egrep` and `fgrep` that makes tests on some packages fail:

```
sed -i "s/echo/#echo/" src/egrep.sh
```

Prepare Grep for compilation:

```
./configure --prefix=/usr
```

Compile the package:

```
make
```

To test the results, issue:

```
make check
```

Install the package:

```
make install
```

### 8.35.2. Contents of Grep

**Installed programs:** `egrep`, `fgrep`, and `grep`

#### Short Descriptions

**egrep** Prints lines matching an extended regular expression. It is obsolete, use **grep -E** instead

**fgrep** Prints lines matching a list of fixed strings. It is obsolete, use **grep -F** instead

**grep** Prints lines matching a basic regular expression

## 8.36. Bash-5.2.32

The Bash package contains the Bourne-Again Shell.

**Approximate build time:** 1.4 SBU

**Required disk space:** 52 MB

### 8.36.1. Installation of Bash

Prepare Bash for compilation:

```
./configure --prefix=/usr \
            --without-bash-malloc \
            --with-installed-readline \
            bash_cv_strtold_broken=no \
            --docdir=/usr/share/doc/bash-5.2.32
```

**The meaning of the new configure option:**

*--with-installed-readline*

This option tells Bash to use the `readline` library that is already installed on the system rather than using its own `readline` version.

Compile the package:

```
make
```

Skip down to “Install the package” if not running the test suite.

To prepare the tests, ensure that the `tester` user can write to the sources tree:

```
chown -R tester .
```

The test suite of this package is designed to be run as a non-`root` user who owns the terminal connected to standard input. To satisfy the requirement, spawn a new pseudo terminal using Expect and run the tests as the `tester` user:

```
su -s /usr/bin/expect tester << "EOF"
set timeout -1
spawn make tests
expect eof
lassign [wait] _ _ _ value
exit $value
EOF
```

The test suite uses **diff** to detect the difference between test script output and the expected output. Any output from **diff** (prefixed with `<` and `>`) indicates a test failure, unless there is a message saying the difference can be ignored. One test named `run-builtins` is known to fail on some host distros with a difference on the first line of the output.

Install the package:

```
make install
```

Run the newly compiled **bash** program (replacing the one that is currently being executed):

```
exec /usr/bin/bash --login
```

### 8.36.2. Contents of Bash

**Installed programs:** bash, bashbug, and sh (link to bash)

**Installed directory:** /usr/include/bash, /usr/lib/bash, and /usr/share/doc/bash-5.2.32



## Short Descriptions

- bash** A widely-used command interpreter; it performs many types of expansions and substitutions on a given command line before executing it, thus making this interpreter a powerful tool
- bashbug** A shell script to help the user compose and mail standard formatted bug reports concerning **bash**
- sh** A symlink to the **bash** program; when invoked as **sh**, **bash** tries to mimic the startup behavior of historical versions of **sh** as closely as possible, while conforming to the POSIX standard as well

## 8.37. Libtool-2.4.7

The Libtool package contains the GNU generic library support script. It makes the use of shared libraries simpler with a consistent, portable interface.

**Approximate build time:** 0.8 SBU

**Required disk space:** 45 MB

### 8.37.1. Installation of Libtool

Prepare Libtool for compilation:

```
./configure --prefix=/usr
```

Compile the package:

```
make
```

To test the results, issue:

```
make -k check
```

Five tests are known to fail in the LFS build environment due to a circular dependency, but these tests pass if rechecked after automake has been installed. Additionally, with grep-3.8 or newer, two tests will trigger a warning for non-POSIX regular expressions and fail.

Install the package:

```
make install
```

Remove a useless static library:

```
rm -fv /usr/lib/libltdl.a
```

### 8.37.2. Contents of Libtool

**Installed programs:** libtool and libtoolize

**Installed libraries:** libltdl.so

**Installed directories:** /usr/include/libltdl and /usr/share/libtool

#### Short Descriptions

<b>libtool</b>	Provides generalized library-building support services
<b>libtoolize</b>	Provides a standard way to add <b>libtool</b> support to a package
libltdl	Hides the various difficulties of opening dynamically loaded libraries

## 8.38. GDBM-1.24

The GDBM package contains the GNU Database Manager. It is a library of database functions that uses extensible hashing and works like the standard UNIX dbm. The library provides primitives for storing key/data pairs, searching and retrieving the data by its key and deleting a key along with its data.

**Approximate build time:** less than 0.1 SBU

**Required disk space:** 13 MB

### 8.38.1. Installation of GDBM

Prepare GDBM for compilation:

```
./configure --prefix=/usr \
            --disable-static \
            --enable-libgdbm-compat
```

**The meaning of the configure option:**

`--enable-libgdbm-compat`

This switch enables building the libgdbm compatibility library. Some packages outside of LFS may require the older DBM routines it provides.

Compile the package:

```
make
```

To test the results, issue:

```
make check
```

Install the package:

```
make install
```

### 8.38.2. Contents of GDBM

**Installed programs:** gdbm\_dump, gdbm\_load, and gdbmtool

**Installed libraries:** libgdbm.so and libgdbm\_compat.so

#### Short Descriptions

<b><code>gdbm_dump</code></b>	Dumps a GDBM database to a file
<b><code>gdbm_load</code></b>	Recreates a GDBM database from a dump file
<b><code>gdbmtool</code></b>	Tests and modifies a GDBM database
<code>libgdbm</code>	Contains functions to manipulate a hashed database
<code>libgdbm_compat</code>	Compatibility library containing older DBM functions

## 8.39. Gperf-3.1

Gperf generates a perfect hash function from a key set.

**Approximate build time:** less than 0.1 SBU

**Required disk space:** 6.1 MB

### 8.39.1. Installation of Gperf

Prepare Gperf for compilation:

```
./configure --prefix=/usr --docdir=/usr/share/doc/gperf-3.1
```

Compile the package:

```
make
```

The tests are known to fail if running multiple simultaneous tests (-j option greater than 1). To test the results, issue:

```
make -j1 check
```

Install the package:

```
make install
```

### 8.39.2. Contents of Gperf

**Installed program:** gperf

**Installed directory:** /usr/share/doc/gperf-3.1

### Short Descriptions

**gperf** Generates a perfect hash from a key set

## 8.40. Expat-2.6.2

The Expat package contains a stream oriented C library for parsing XML.

**Approximate build time:** 0.1 SBU

**Required disk space:** 13 MB

### 8.40.1. Installation of Expat

Prepare Expat for compilation:

```
./configure --prefix=/usr \
            --disable-static \
            --docdir=/usr/share/doc/expat-2.6.2
```

Compile the package:

```
make
```

To test the results, issue:

```
make check
```

Install the package:

```
make install
```

If desired, install the documentation:

```
install -v -m644 doc/*.{html,css} /usr/share/doc/expat-2.6.2
```

### 8.40.2. Contents of Expat

<b>Installed program:</b>	xmlwf
<b>Installed libraries:</b>	libexpat.so
<b>Installed directory:</b>	/usr/share/doc/expat-2.6.2

### Short Descriptions

<b>xmlwf</b>	Is a non-validating utility to check whether or not XML documents are well formed
<b>libexpat</b>	Contains API functions for parsing XML

## 8.41. Inetutils-2.5

The Inetutils package contains programs for basic networking.

**Approximate build time:** 0.2 SBU

**Required disk space:** 35 MB

### 8.41.1. Installation of Inetutils

First, make the package build with gcc-14.1 or later::

```
sed -i 's/def HAVE_TERMCAP_TGETENT/ 1/' telnet/telnet.c
```

Prepare Inetutils for compilation:

```
./configure --prefix=/usr      \
            --bindir=/usr/bin  \
            --localstatedir=/var \
            --disable-logger   \
            --disable-whois    \
            --disable-rcp      \
            --disable-rexec    \
            --disable-rlogin   \
            --disable-rsh      \
            --disable-servers
```

**The meaning of the configure options:**

*--disable-logger*

This option prevents Inetutils from installing the **logger** program, which is used by scripts to pass messages to the System Log Daemon. Do not install it because Util-linux installs a more recent version.

*--disable-whois*

This option disables the building of the Inetutils **whois** client, which is out of date. Instructions for a better **whois** client are in the BLFS book.

*--disable-r\**

These parameters disable building obsolete programs that should not be used due to security issues. The functions provided by these programs can be provided by the openssh package in the BLFS book.

*--disable-servers*

This disables the installation of the various network servers included as part of the Inetutils package. These servers are deemed not appropriate in a basic LFS system. Some are insecure by nature and are only considered safe on trusted networks. Note that better replacements are available for many of these servers.

Compile the package:

```
make
```

To test the results, issue:

```
make check
```

Install the package:

```
make install
```

Move a program to the proper location:

```
mv -v /usr/{,s}bin/ifconfig
```

## 8.41.2. Contents of Inetutils

**Installed programs:** dnsdomainname, ftp, ifconfig, hostname, ping, ping6, talk, telnet, tftp, and traceroute

### Short Descriptions

<b>dnsdomainname</b>	Show the system's DNS domain name
<b>ftp</b>	Is the file transfer protocol program
<b>hostname</b>	Reports or sets the name of the host
<b>ifconfig</b>	Manages network interfaces
<b>ping</b>	Sends echo-request packets and reports how long the replies take
<b>ping6</b>	A version of <b>ping</b> for IPv6 networks
<b>talk</b>	Is used to chat with another user
<b>telnet</b>	An interface to the TELNET protocol
<b>tftp</b>	A trivial file transfer program
<b>traceroute</b>	Traces the route your packets take from the host you are working on to another host on a network, showing all the intermediate hops (gateways) along the way

## 8.42. Less-661

The Less package contains a text file viewer.

**Approximate build time:** less than 0.1 SBU

**Required disk space:** 14 MB

### 8.42.1. Installation of Less

Prepare Less for compilation:

```
./configure --prefix=/usr --sysconfdir=/etc
```

**The meaning of the configure options:**

```
--sysconfdir=/etc
```

This option tells the programs created by the package to look in `/etc` for the configuration files.

Compile the package:

```
make
```

To test the results, issue:

```
make check
```

Install the package:

```
make install
```

### 8.42.2. Contents of Less

**Installed programs:** less, lessecho, and lesskey

#### Short Descriptions

- less**            A file viewer or pager; it displays the contents of the given file, letting the user scroll, find strings, and jump to marks
- lessecho**       Needed to expand meta-characters, such as `*` and `?`, in filenames on Unix systems
- lesskey**        Used to specify the key bindings for **less**



## 8.43. Perl-5.40.0

The Perl package contains the Practical Extraction and Report Language.

**Approximate build time:** 1.4 SBU

**Required disk space:** 245 MB

### 8.43.1. Installation of Perl

This version of Perl builds the Compress::Raw::Zlib and Compress::Raw::BZip2 modules. By default Perl will use an internal copy of the sources for the build. Issue the following command so that Perl will use the libraries installed on the system:

```
export BUILD_ZLIB=False
export BUILD_BZIP2=0
```

To have full control over the way Perl is set up, you can remove the “-des” options from the following command and hand-pick the way this package is built. Alternatively, use the command exactly as shown below to use the defaults that Perl auto-detects:

```
sh Configure -des \
-D prefix=/usr \
-D vendorprefix=/usr \
-D privlib=/usr/lib/perl5/5.40/core_perl \
-D archlib=/usr/lib/perl5/5.40/core_perl \
-D sitelib=/usr/lib/perl5/5.40/site_perl \
-D sitearch=/usr/lib/perl5/5.40/site_perl \
-D vendorlib=/usr/lib/perl5/5.40/vendor_perl \
-D vendorarch=/usr/lib/perl5/5.40/vendor_perl \
-D man1dir=/usr/share/man/man1 \
-D man3dir=/usr/share/man/man3 \
-D pager="/usr/bin/less -isR" \
-D useshrplib \
-D usethreads
```

**The meaning of the new Configure options:**

```
-D pager="/usr/bin/less -isR"
```

This ensures that `less` is used instead of `more`.

```
-D man1dir=/usr/share/man/man1 -D man3dir=/usr/share/man/man3
```

Since Groff is not installed yet, **Configure** will not create man pages for Perl. These parameters override this behavior.

```
-D usethreads
```

Build Perl with support for threads.

Compile the package:

```
make
```

To test the results (approximately 11 SBU), issue:

```
TEST_JOBS=$(nproc) make test_harness
```

Install the package and clean up:

```
make install
unset BUILD_ZLIB BUILD_BZIP2
```

## 8.43.2. Contents of Perl

<b>Installed programs:</b>	corelist, cpan, enc2xs, encguess, h2ph, h2xs, instmodsh, json_pp, libnetcfg, perl, perl5.40.0 (hard link to perl), perlbug, perldoc, perlivp, perlthanks (hard link to perlbug), piconv, pl2pm, pod2html, pod2man, pod2text, pod2usage, podchecker, podselect, prove, ptar, ptardiff, ptargrep, shasum, splain, xsubpp, and zipdetails
<b>Installed libraries:</b>	Many which cannot all be listed here
<b>Installed directory:</b>	/usr/lib/perl5

### Short Descriptions

<b>corelist</b>	A command line front end to Module::CoreList
<b>cpan</b>	Interact with the Comprehensive Perl Archive Network (CPAN) from the command line
<b>enc2xs</b>	Builds a Perl extension for the Encode module from either Unicode Character Mappings or Tcl Encoding Files
<b>encguess</b>	Guess the encoding type of one or several files
<b>h2ph</b>	Converts .h C header files to .ph Perl header files
<b>h2xs</b>	Converts .h C header files to Perl extensions
<b>instmodsh</b>	Shell script for examining installed Perl modules; it can create a tarball from an installed module
<b>json_pp</b>	Converts data between certain input and output formats
<b>libnetcfg</b>	Can be used to configure the libnet Perl module
<b>perl</b>	Combines some of the best features of C, <b>sed</b> , <b>awk</b> and <b>sh</b> into a single Swiss Army language
<b>perl5.40.0</b>	A hard link to <b>perl</b>
<b>perlbug</b>	Used to generate bug reports about Perl, or the modules that come with it, and mail them
<b>perldoc</b>	Displays a piece of documentation in pod format that is embedded in the Perl installation tree or in a Perl script
<b>perlivp</b>	The Perl Installation Verification Procedure; it can be used to verify that Perl and its libraries have been installed correctly
<b>perlthanks</b>	Used to generate thank you messages to mail to the Perl developers
<b>piconv</b>	A Perl version of the character encoding converter <b>iconv</b>
<b>pl2pm</b>	A rough tool for converting Perl4 .pl files to Perl5 .pm modules
<b>pod2html</b>	Converts files from pod format to HTML format
<b>pod2man</b>	Converts pod data to formatted *roff input
<b>pod2text</b>	Converts pod data to formatted ASCII text
<b>pod2usage</b>	Prints usage messages from embedded pod docs in files
<b>podchecker</b>	Checks the syntax of pod format documentation files
<b>podselect</b>	Displays selected sections of pod documentation
<b>prove</b>	Command line tool for running tests against the Test::Harness module
<b>ptar</b>	A <b>tar</b> -like program written in Perl
<b>ptardiff</b>	A Perl program that compares an extracted archive with an unextracted one

<b>ptargrep</b>	A Perl program that applies pattern matching to the contents of files in a tar archive
<b>shasum</b>	Prints or checks SHA checksums
<b>splain</b>	Is used to force verbose warning diagnostics in Perl
<b>xsubpp</b>	Converts Perl XS code into C code
<b>zipdetails</b>	Displays details about the internal structure of a Zip file

## 8.44. XML::Parser-2.47

The XML::Parser module is a Perl interface to James Clark's XML parser, Expat.

**Approximate build time:** less than 0.1 SBU

**Required disk space:** 2.4 MB

### 8.44.1. Installation of XML::Parser

Prepare XML::Parser for compilation:

```
perl Makefile.PL
```

Compile the package:

```
make
```

To test the results, issue:

```
make test
```

Install the package:

```
make install
```

### 8.44.2. Contents of XML::Parser

**Installed module:** Expat.so

#### Short Descriptions

`Expat` provides the Perl Expat interface

## 8.45. Intltool-0.51.0

The Intltool is an internationalization tool used for extracting translatable strings from source files.

**Approximate build time:** less than 0.1 SBU

**Required disk space:** 1.5 MB

### 8.45.1. Installation of Intltool

First fix a warning that is caused by perl-5.22 and later:

```
sed -i 's:\\\\${:\\\\$\\{: intltool-update.in
```



#### Note

The above regular expression looks unusual because of all the backslashes. What it does is add a backslash before the right brace character in the sequence '\${' resulting in '\$\{'.

Prepare Intltool for compilation:

```
./configure --prefix=/usr
```

Compile the package:

```
make
```

To test the results, issue:

```
make check
```

Install the package:

```
make install
install -v -Dm644 doc/I18N-HOWTO /usr/share/doc/intltool-0.51.0/I18N-HOWTO
```

### 8.45.2. Contents of Intltool

**Installed programs:** intltool-extract, intltool-merge, intltool-prepare, intltool-update, and intltoolize

**Installed directories:** /usr/share/doc/intltool-0.51.0 and /usr/share/intltool

#### Short Descriptions

<b>intltoolize</b>	Prepares a package to use intltool
<b>intltool-extract</b>	Generates header files that can be read by <b>gettext</b>
<b>intltool-merge</b>	Merges translated strings into various file types
<b>intltool-prepare</b>	Updates pot files and merges them with translation files
<b>intltool-update</b>	Updates the po template files and merges them with the translations

## 8.46. Autoconf-2.72

The Autoconf package contains programs for producing shell scripts that can automatically configure source code.

**Approximate build time:** less than 0.1 SBU (about 1.8 SBU with tests)

**Required disk space:** 25 MB

### 8.46.1. Installation of Autoconf

Prepare Autoconf for compilation:

```
./configure --prefix=/usr
```

Compile the package:

```
make
```

To test the results, issue:

```
make check
```

Install the package:

```
make install
```

### 8.46.2. Contents of Autoconf

**Installed programs:** autoconf, autoheader, autom4te, autoreconf, autoscan, autoupdate, and ifnames

**Installed directory:** /usr/share/autoconf

#### Short Descriptions

<b>autoconf</b>	Produces shell scripts that automatically configure software source code packages to adapt to many kinds of Unix-like systems; the configuration scripts it produces are independent—running them does not require the <b>autoconf</b> program
<b>autoheader</b>	A tool for creating template files of <i>C #define</i> statements for configure to use
<b>autom4te</b>	A wrapper for the M4 macro processor
<b>autoreconf</b>	Automatically runs <b>autoconf</b> , <b>autoheader</b> , <b>aclocal</b> , <b>automake</b> , <b>gettextize</b> , and <b>libtoolize</b> in the correct order to save time when changes are made to <b>autoconf</b> and <b>automake</b> template files
<b>autoscan</b>	Helps to create a <code>configure.in</code> file for a software package; it examines the source files in a directory tree, searching them for common portability issues, and creates a <code>configure.scan</code> file that serves as a preliminary <code>configure.in</code> file for the package
<b>autoupdate</b>	Modifies a <code>configure.in</code> file that still calls <b>autoconf</b> macros by their old names to use the current macro names
<b>ifnames</b>	Helps when writing <code>configure.in</code> files for a software package; it prints the identifiers that the package uses in C preprocessor conditionals [If a package has already been set up to have some portability, this program can help determine what <b>configure</b> needs to check for. It can also fill in gaps in a <code>configure.in</code> file generated by <b>autoscan</b> .]

## 8.47. Automake-1.17

The Automake package contains programs for generating Makefiles for use with Autoconf.

**Approximate build time:** less than 0.1 SBU (about 1.1 SBU with tests)

**Required disk space:** 121 MB

### 8.47.1. Installation of Automake

Prepare Automake for compilation:

```
./configure --prefix=/usr --docdir=/usr/share/doc/automake-1.17
```

Compile the package:

```
make
```

Using four parallel jobs speeds up the tests, even on systems with less logical cores, due to internal delays in individual tests. To test the results, issue:

```
make -j$( ($(nproc)>4?$(nproc):4) ) check
```

Replace  $\$( (\dots) )$  with the number of logical cores you want to use if you don't want to use all.

Install the package:

```
make install
```

### 8.47.2. Contents of Automake

**Installed programs:** `aclocal`, `aclocal-1.17` (hard linked with `aclocal`), `automake`, and `automake-1.17` (hard linked with `automake`)

**Installed directories:** `/usr/share/aclocal-1.17`, `/usr/share/automake-1.17`, and `/usr/share/doc/automake-1.17`

### Short Descriptions

<b>aclocal</b>	Generates <code>aclocal.m4</code> files based on the contents of <code>configure.in</code> files
<b>aclocal-1.17</b>	A hard link to <b>aclocal</b>
<b>automake</b>	A tool for automatically generating <code>Makefile.in</code> files from <code>Makefile.am</code> files [To create all the <code>Makefile.in</code> files for a package, run this program in the top-level directory. By scanning the <code>configure.in</code> file, it automatically finds each appropriate <code>Makefile.am</code> file and generates the corresponding <code>Makefile.in</code> file.]
<b>automake-1.17</b>	A hard link to <b>automake</b>

## 8.48. OpenSSL-3.3.1

The OpenSSL package contains management tools and libraries relating to cryptography. These are useful for providing cryptographic functions to other packages, such as OpenSSH, email applications, and web browsers (for accessing HTTPS sites).

**Approximate build time:** 1.7 SBU

**Required disk space:** 883 MB

### 8.48.1. Installation of OpenSSL

Prepare OpenSSL for compilation:

```
./config --prefix=/usr      \  
        --openssldir=/etc/ssl \  
        --libdir=lib        \  
        shared              \  
        zlib-dynamic
```

Compile the package:

```
make
```

To test the results, issue:

```
HARNESSE_JOBS=$(nproc) make test
```

One test, 30-test\_afalg.t, is known to fail if the host kernel does not have `CONFIG_CRYPT_USER_API_SKCIPHER` enabled, or does not have any options providing an AES with CBC implementation (for example, the combination of `CONFIG_CRYPT_AES` and `CONFIG_CRYPT_CBC`, or `CONFIG_CRYPT_AES_NI_INTEL` if the CPU supports AES-NI) enabled. If it fails, it can safely be ignored.

Install the package:

```
sed -i '/INSTALL_LIBS/s/libcrypto.a libssl.a/' Makefile  
make MANSUFFIX=ssl install
```

Add the version to the documentation directory name, to be consistent with other packages:

```
mv -v /usr/share/doc/openssl /usr/share/doc/openssl-3.3.1
```

If desired, install some additional documentation:

```
cp -vfr doc/* /usr/share/doc/openssl-3.3.1
```



#### Note

You should update OpenSSL when a new version which fixes vulnerabilities is announced. Since OpenSSL 3.0.0, the OpenSSL versioning scheme follows the MAJOR.MINOR.PATCH format. API/ABI compatibility is guaranteed for the same MAJOR version number. Because LFS installs only the shared libraries, there is no need to recompile packages which link to `libcrypto.so` or `libssl.so` *when upgrading to a version with the same MAJOR version number*.

However, any running programs linked to those libraries need to be stopped and restarted. Read the related entries in Section 8.2.1, “Upgrade Issues” for details.



## 8.48.2. Contents of OpenSSL

**Installed programs:** c\_rehash and openssl  
**Installed libraries:** libcrypto.so and libssl.so  
**Installed directories:** /etc/ssl, /usr/include/openssl, /usr/lib/engines and /usr/share/doc/openssl-3.3.1

### Short Descriptions

**c\_rehash** is a Perl script that scans all files in a directory and adds symbolic links to their hash values. Use of **c\_rehash** is considered obsolete and should be replaced by **openssl rehash** command

**openssl** is a command-line tool for using the various cryptography functions of OpenSSL's crypto library from the shell. It can be used for various functions which are documented in *openssl(1)*

**libcrypto.so** implements a wide range of cryptographic algorithms used in various Internet standards. The services provided by this library are used by the OpenSSL implementations of SSL, TLS and S/MIME, and they have also been used to implement OpenSSH, OpenPGP, and other cryptographic standards

**libssl.so** implements the Transport Layer Security (TLS v1) protocol. It provides a rich API, documentation on which can be found in *ssl(7)*

## 8.49. Kmod-33

The Kmod package contains libraries and utilities for loading kernel modules

**Approximate build time:** less than 0.1 SBU

**Required disk space:** 11 MB

### 8.49.1. Installation of Kmod

Prepare Kmod for compilation:

```
./configure --prefix=/usr \
            --sysconfdir=/etc \
            --with-openssl \
            --with-xz \
            --with-zstd \
            --with-zlib \
            --disable-manpages
```

**The meaning of the configure options:**

*--with-openssl*

This option enables Kmod to handle PKCS7 signatures for kernel modules.

*--with-xz*, *--with-zlib*, and *--with-zstd*

These options enable Kmod to handle compressed kernel modules.

*--disable-manpages*

This option disables generating the man pages which requires an external program.

Compile the package:

```
make
```

The test suite of this package requires raw kernel headers (not the “sanitized” kernel headers installed earlier), which are beyond the scope of LFS.

Install the package and recreate some symlinks for compatibility with Module-Init-Tools (the package that previously handled Linux kernel modules). The building system will create all these symlinks in `/usr/bin`, but we only want **lsmod** there and all other symlinks in `/usr/sbin` instead:

```
make install

for target in depmod insmod modinfo modprobe rmmmod; do
  ln -sfv ../bin/kmod /usr/sbin/$target
  rm -fv /usr/bin/$target
done
```

### 8.49.2. Contents of Kmod

**Installed programs:** depmod (link to kmod), insmod (link to kmod), kmod, lsmod (link to kmod), modinfo (link to kmod), modprobe (link to kmod), and rmmmod (link to kmod)

**Installed library:** libkmod.so

### Short Descriptions

**depmod** Creates a dependency file based on the symbols it finds in the existing set of modules; this dependency file is used by **modprobe** to automatically load the required modules

<b>insmod</b>	Installs a loadable module in the running kernel
<b>kmod</b>	Loads and unloads kernel modules
<b>lsmod</b>	Lists currently loaded modules
<b>modinfo</b>	Examines an object file associated with a kernel module and displays any information that it can glean
<b>modprobe</b>	Uses a dependency file, created by <b>depmod</b> , to automatically load relevant modules
<b>rmmod</b>	Unloads modules from the running kernel
<code>libkmod</code>	This library is used by other programs to load and unload kernel modules

## 8.50. Libelf from Elfutils-0.191

Libelf is a library for handling ELF (Executable and Linkable Format) files.

**Approximate build time:** 0.3 SBU

**Required disk space:** 127 MB

### 8.50.1. Installation of Libelf

Libelf is part of the elfutils-0.191 package. Use the elfutils-0.191.tar.bz2 file as the source tarball.

Prepare Libelf for compilation:

```
./configure --prefix=/usr          \
            --disable-debuginfod   \
            --enable-libdebuginfod=dummy
```

Compile the package:

```
make
```

To test the results, issue:

```
make check
```

Install only Libelf:

```
make -C libelf install
install -vm644 config/libelf.pc /usr/lib/pkgconfig
rm /usr/lib/libelf.a
```

### 8.50.2. Contents of Libelf

**Installed library:** libelf.so

**Installed directory:** /usr/include/elfutils

### Short Descriptions

libelf.so      Contains API functions to handle ELF object files

## 8.51. Libffi-3.4.6

The Libffi library provides a portable, high level programming interface to various calling conventions. This allows a programmer to call any function specified by a call interface description at run time.

FFI stands for Foreign Function Interface. An FFI allows a program written in one language to call a program written in another language. Specifically, Libffi can provide a bridge between an interpreter like Perl, or Python, and shared library subroutines written in C, or C++.

**Approximate build time:** 1.7 SBU

**Required disk space:** 11 MB

### 8.51.1. Installation of Libffi



#### Note

Like GMP, Libffi builds with optimizations specific to the processor in use. If building for another system, change the value of the `--with-gcc-arch=` parameter in the following command to an architecture name fully implemented by the CPU on that system. If this is not done, all applications that link to `libffi` will trigger Illegal Operation Errors.

Prepare Libffi for compilation:

```
./configure --prefix=/usr \
            --disable-static \
            --with-gcc-arch=native
```

The meaning of the configure option:

`--with-gcc-arch=native`

Ensure GCC optimizes for the current system. If this is not specified, the system is guessed and the code generated may not be correct. If the generated code will be copied from the native system to a less capable system, use the less capable system as a parameter. For details about alternative system types, see *the x86 options in the GCC manual*.

Compile the package:

```
make
```

To test the results, issue:

```
make check
```

Install the package:

```
make install
```

### 8.51.2. Contents of Libffi

**Installed library:** libffi.so

#### Short Descriptions

`libffi` Contains the foreign function interface API functions

## 8.52. Python-3.12.5

The Python 3 package contains the Python development environment. It is useful for object-oriented programming, writing scripts, prototyping large programs, and developing entire applications. Python is an interpreted computer language.

**Approximate build time:** 2.2 SBU

**Required disk space:** 530 MB

### 8.52.1. Installation of Python 3

Prepare Python for compilation:

```
./configure --prefix=/usr      \
            --enable-shared    \
            --with-system-expat \
            --enable-optimizations
```

**The meaning of the configure options:**

*--with-system-expat*

This switch enables linking against the system version of Expat.

*--enable-optimizations*

This switch enables extensive, but time-consuming, optimization steps. The interpreter is built twice; tests performed on the first build are used to improve the optimized final version.

Compile the package:

```
make
```

Some tests are known to occasionally hang indefinitely. So to test the results, run the test suite but set a 2-minute time limit for each test case:

```
make test TESTOPTS="--timeout 120"
```

For a relatively slow system you may need to increase the time limit and 1 SBU (measured when building Binutils pass 1 with one CPU core) should be enough. Some tests are flaky, so the test suite will automatically re-run failed tests. If a test failed but then passed when re-run, it should be considered as passed.

Install the package:

```
make install
```

We use the **pip3** command to install Python 3 programs and modules for all users as `root` in several places in this book. This conflicts with the Python developers' recommendation: to install packages into a virtual environment, or into the home directory of a regular user (by running **pip3** as this user). A multi-line warning is triggered whenever **pip3** is issued by the `root` user.

The main reason for the recommendation is to avoid conflicts with the system's package manager (**dpkg**, for example). LFS does not have a system-wide package manager, so this is not a problem. Also, **pip3** will check for a new version of itself whenever it's run. Since domain name resolution is not yet configured in the LFS chroot environment, **pip3** cannot check for a new version of itself, and will produce a warning.

After we boot the LFS system and set up a network connection, a different warning will be issued, telling the user to update **pip3** from a pre-built wheel on PyPI (whenever a new version is available). But LFS considers **pip3** to be a part of Python 3, so it should not be updated separately. Also, an update from a pre-built wheel would deviate

from our objective: to build a Linux system from source code. So the warning about a new version of **pip3** should be ignored as well. If you wish, you can suppress all these warnings by running the following command, which creates a configuration file:

```
cat > /etc/pip.conf << EOF
[global]
root-user-action = ignore
disable-pip-version-check = true
EOF
```



### Important

In LFS and BLFS we normally build and install Python modules with the **pip3** command. Please be sure that the **pip3 install** commands in both books are run as the `root` user (unless it's for a Python virtual environment). Running **pip3 install** as a non-`root` user may seem to work, but it will cause the installed module to be inaccessible by other users.

**pip3 install** will not reinstall an already installed module automatically. When using the **pip3 install** command to upgrade a module (for example, from `meson-0.61.3` to `meson-0.62.0`), insert the option `--upgrade` into the command line. If it's really necessary to downgrade a module, or reinstall the same version for some reason, insert `--force-reinstall --no-deps` into the command line.

If desired, install the preformatted documentation:

```
install -v -dm755 /usr/share/doc/python-3.12.5/html

tar --no-same-owner \
-xvf ../python-3.12.5-docs-html.tar.bz2
cp -R --no-preserve=mode python-3.12.5-docs-html/* \
/usr/share/doc/python-3.12.5/html
```

#### The meaning of the documentation install commands:

`--no-same-owner` (tar) and `--no-preserve=mode` (cp)

Ensure the installed files have the correct ownership and permissions. Without these options, tar will install the package files with the upstream creator's values and files would have restrictive permissions.

## 8.52.2. Contents of Python 3

**Installed programs:** 2to3, idle3, pip3, pydoc3, python3, and python3-config  
**Installed library:** libpython3.12.so and libpython3.so  
**Installed directories:** /usr/include/python3.12, /usr/lib/python3, and /usr/share/doc/python-3.12.5

### Short Descriptions

**2to3** is a Python program that reads Python 2.x source code and applies a series of fixes to transform it into valid Python 3.x code

**idle3** is a wrapper script that opens a Python aware GUI editor. For this script to run, you must have installed Tk before Python, so that the Tkinter Python module is built.

**pip3** The package installer for Python. You can use pip to install packages from Python Package Index and other indexes.

**pydoc3** is the Python documentation tool

**python3** is the interpreter for Python, an interpreted, interactive, object-oriented programming language

## 8.53. Flit-Core-3.9.0

Flit-core is the distribution-building parts of Flit (a packaging tool for simple Python modules).

**Approximate build time:** less than 0.1 SBU

**Required disk space:** 1.6 MB

### 8.53.1. Installation of Flit-Core

Build the package:

```
pip3 wheel -w dist --no-cache-dir --no-build-isolation --no-deps $PWD
```

Install the package:

```
pip3 install --no-index --no-user --find-links dist flit_core
```

**The meaning of the pip3 configuration options and commands:**

#### **wheel**

This command builds the wheel archive for this package.

*-w dist*

Instructs pip to put the created wheel into the `dist` directory.

*--no-cache-dir*

Prevents pip from copying the created wheel into the `/root/.cache/pip` directory.

#### **install**

This command installs the package.

*--no-build-isolation*, *--no-deps*, and *--no-index*

These options prevent fetching files from the online package repository (PyPI). If packages are installed in the correct order, pip won't need to fetch any files in the first place; these options add some safety in case of user error.

*--find-links dist*

Instructs pip to search for wheel archives in the `dist` directory.

### 8.53.2. Contents of Flit-Core

**Installed directory:** `/usr/lib/python3.12/site-packages/flit_core` and `/usr/lib/python3.12/site-packages/flit_core-3.9.0.dist-info`



## 8.54. Wheel-0.44.0

Wheel is a Python library that is the reference implementation of the Python wheel packaging standard.

**Approximate build time:** less than 0.1 SBU

**Required disk space:** 1.5 MB

### 8.54.1. Installation of Wheel

Compile Wheel with the following command:

```
pip3 wheel -w dist --no-cache-dir --no-build-isolation --no-deps $PWD
```

Install Wheel with the following command:

```
pip3 install --no-index --find-links=dist wheel
```

### 8.54.2. Contents of Wheel

**Installed program:** wheel

**Installed directories:** /usr/lib/python3.12/site-packages/wheel and /usr/lib/python3.12/site-packages/wheel-0.44.0.dist-info

### Short Descriptions

**wheel** is a utility to unpack, pack, or convert wheel archives

## 8.55. Setuptools-72.2.0

Setuptools is a tool used to download, build, install, upgrade, and uninstall Python packages.

**Approximate build time:** less than 0.1 SBU

**Required disk space:** 35 MB

### 8.55.1. Installation of Setuptools

Build the package:

```
pip3 wheel -w dist --no-cache-dir --no-build-isolation --no-deps $PWD
```

Install the package:

```
pip3 install --no-index --find-links dist setuptools
```

### 8.55.2. Contents of Setuptools

**Installed directory:** /usr/lib/python3.12/site-packages/\_distutils\_hack, /usr/lib/python3.12/site-packages/pkg\_resources, /usr/lib/python3.12/site-packages/setuptools, and /usr/lib/python3.12/site-packages/setuptools-72.2.0.dist-info

## 8.56. Ninja-1.12.1

Ninja is a small build system with a focus on speed.

**Approximate build time:** 0.2 SBU

**Required disk space:** 37 MB

### 8.56.1. Installation of Ninja

When run, **ninja** normally utilizes the greatest possible number of processes in parallel. By default this is the number of cores on the system, plus two. This may overheat the CPU, or make the system run out of memory. When **ninja** is invoked from the command line, passing the `-jN` parameter will limit the number of parallel processes. Some packages embed the execution of **ninja**, and do not pass the `-j` parameter on to it.

Using the *optional* procedure below allows a user to limit the number of parallel processes via an environment variable, `NINJAJOBS`. **For example**, setting:

```
export NINJAJOBS=4
```

will limit **ninja** to four parallel processes.

If desired, make **ninja** recognize the environment variable `NINJAJOBS` by running the stream editor:

```
sed -i '/int Guess/a \
int j = 0;\
char* jobs = getenv( "NINJAJOBS" );\
if ( jobs != NULL ) j = atoi( jobs );\
if ( j > 0 ) return j;\
' src/ninja.cc
```

Build Ninja with:

```
python3 configure.py --bootstrap
```

**The meaning of the build option:**

`--bootstrap`

This parameter forces Ninja to rebuild itself for the current system.

The package tests cannot run in the chroot environment. They require *cmake*.

Install the package:

```
install -vm755 ninja /usr/bin/
install -vDm644 misc/bash-completion /usr/share/bash-completion/completions/ninja
install -vDm644 misc/zsh-completion /usr/share/zsh/site-functions/_ninja
```

### 8.56.2. Contents of Ninja

**Installed programs:** ninja

#### Short Descriptions

**ninja** is the Ninja build system

## 8.57. Meson-1.5.1

Meson is an open source build system designed to be both extremely fast and as user friendly as possible.

**Approximate build time:** less than 0.1 SBU

**Required disk space:** 43 MB

### 8.57.1. Installation of Meson

Compile Meson with the following command:

```
pip3 wheel -w dist --no-cache-dir --no-build-isolation --no-deps $PWD
```

The test suite requires some packages outside the scope of LFS.

Install the package:

```
pip3 install --no-index --find-links dist meson
install -vDm644 data/shell-completions/bash/meson /usr/share/bash-completion/completions/meson
install -vDm644 data/shell-completions/zsh/_meson /usr/share/zsh/site-functions/_meson
```

**The meaning of the install parameters:**

*-w dist*

Puts the created wheels into the `dist` directory.

*--find-links dist*

Installs wheels from the `dist` directory.

### 8.57.2. Contents of Meson

**Installed programs:** meson

**Installed directory:** /usr/lib/python3.12/site-packages/meson-1.5.1.dist-info and /usr/lib/python3.12/site-packages/mesonbuild

### Short Descriptions

**meson** A high productivity build system

## 8.58. Coreutils-9.5

The Coreutils package contains the basic utility programs needed by every operating system.

**Approximate build time:** 1.1 SBU

**Required disk space:** 173 MB

### 8.58.1. Installation of Coreutils

POSIX requires that programs from Coreutils recognize character boundaries correctly even in multibyte locales. The following patch fixes this non-compliance and other internationalization-related bugs.

```
patch -Np1 -i ../coreutils-9.5-i18n-2.patch
```



#### Note

Many bugs have been found in this patch. When reporting new bugs to the Coreutils maintainers, please check first to see if those bugs are reproducible without this patch.

Now prepare Coreutils for compilation:

```
autoreconf -fiv
FORCE_UNSAFE_CONFIGURE=1 ./configure \
    --prefix=/usr \
    --enable-no-install-program=kill,uptime
```

**The meaning of the configure options:**

#### autoreconf

The patch for internationalization has modified the build system, so the configuration files must be regenerated.

```
FORCE_UNSAFE_CONFIGURE=1
```

This environment variable allows the package to be built by the `root` user.

```
--enable-no-install-program=kill,uptime
```

The purpose of this switch is to prevent Coreutils from installing programs that will be installed by other packages.

Compile the package:

```
make
```

Skip down to “Install the package” if not running the test suite.

Now the test suite is ready to be run. First, run the tests that are meant to be run as user `root`:

```
make NON_ROOT_USERNAME=tester check-root
```

We're going to run the remainder of the tests as the `tester` user. Certain tests require that the user be a member of more than one group. So that these tests are not skipped, add a temporary group and make the user `tester` a part of it:

```
groupadd -g 102 dummy -U tester
```

Fix some of the permissions so that the non-`root` user can compile and run the tests:

```
chown -R tester .
```

Now run the tests (using `/dev/null` for the standard input, or two tests may be broken if building LFS in a graphical terminal or a session in SSH or GNU Screen because the standard input is connected to a PTY from host distro, and the device node for such a PTY cannot be accessed from the LFS chroot environment):

```
su tester -c "PATH=$PATH make -k RUN_EXPENSIVE_TESTS=yes check" \  
< /dev/null
```

Remove the temporary group:

```
groupdel dummy
```

Two tests, `tests/cp/preserve-mode.sh` and `tests/mv/acl.sh`, are known to fail in the chroot environment, but pass in a complete system.

Install the package:

```
make install
```

Move programs to the locations specified by the FHS:

```
mv -v /usr/bin/chroot /usr/sbin \  
mv -v /usr/share/man/man1/chroot.1 /usr/share/man/man8/chroot.8 \  
sed -i 's/"1"/"8"/' /usr/share/man/man8/chroot.8
```

## 8.58.2. Contents of Coreutils

**Installed programs:** `[], b2sum, base32, base64, basename, basenc, cat, chcon, chgrp, chmod, chown, chroot, cksum, comm, cp, csplit, cut, date, dd, df, dir, dircolors, dirname, du, echo, env, expand, expr, factor, false, fmt, fold, groups, head, hostid, id, install, join, link, ln, logname, ls, md5sum, mkdir, mkfifo, mknod, mktemp, mv, nice, nl, nohup, nproc, numfmt, od, paste, pathchk, pinky, pr, printenv, printf, ptx, pwd, readlink, realpath, rm, rmdir, runcon, seq, sha1sum, sha224sum, sha256sum, sha384sum, sha512sum, shred, shuf, sleep, sort, split, stat, stdbuf, stty, sum, sync, tac, tail, tee, test, timeout, touch, tr, true, truncate, tsort, tty, uname, unexpand, uniq, unlink, users, vdir, wc, who, whoami, and yes`

**Installed library:** `libstdbuf.so` (in `/usr/libexec/coreutils`)

**Installed directory:** `/usr/libexec/coreutils`

## Short Descriptions

<code>[]</code>	Is an actual command, <code>/usr/bin/[]</code> ; it is a synonym for the <b>test</b> command
<b>base32</b>	Encodes and decodes data according to the base32 specification (RFC 4648)
<b>base64</b>	Encodes and decodes data according to the base64 specification (RFC 4648)
<b>b2sum</b>	Prints or checks BLAKE2 (512-bit) checksums
<b>basename</b>	Strips any path and a given suffix from a file name
<b>basenc</b>	Encodes or decodes data using various algorithms
<b>cat</b>	Concatenates files to standard output
<b>chcon</b>	Changes security context for files and directories
<b>chgrp</b>	Changes the group ownership of files and directories
<b>chmod</b>	Changes the permissions of each file to the given mode; the mode can be either a symbolic representation of the changes to be made, or an octal number representing the new permissions

<b>chown</b>	Changes the user and/or group ownership of files and directories
<b>chroot</b>	Runs a command with the specified directory as the / directory
<b>cksum</b>	Prints the Cyclic Redundancy Check (CRC) checksum and the byte counts of each specified file
<b>comm</b>	Compares two sorted files, outputting in three columns the lines that are unique and the lines that are common
<b>cp</b>	Copies files
<b>csplit</b>	Splits a given file into several new files, separating them according to given patterns or line numbers, and outputting the byte count of each new file
<b>cut</b>	Prints sections of lines, selecting the parts according to given fields or positions
<b>date</b>	Displays the current date and time in the given format, or sets the system date and time
<b>dd</b>	Copies a file using the given block size and count, while optionally performing conversions on it
<b>df</b>	Reports the amount of disk space available (and used) on all mounted file systems, or only on the file systems holding the selected files
<b>dir</b>	Lists the contents of each given directory (the same as the <b>ls</b> command)
<b>dircolors</b>	Outputs commands to set the <code>LS_COLOR</code> environment variable to change the color scheme used by <b>ls</b>
<b>dirname</b>	Extracts the directory portion(s) of the given name(s)
<b>du</b>	Reports the amount of disk space used by the current directory, by each of the given directories (including all subdirectories) or by each of the given files
<b>echo</b>	Displays the given strings
<b>env</b>	Runs a command in a modified environment
<b>expand</b>	Converts tabs to spaces
<b>expr</b>	Evaluates expressions
<b>factor</b>	Prints the prime factors of the specified integers
<b>false</b>	Does nothing, unsuccessfully; it always exits with a status code indicating failure
<b>fmt</b>	Reformats the paragraphs in the given files
<b>fold</b>	Wraps the lines in the given files
<b>groups</b>	Reports a user's group memberships
<b>head</b>	Prints the first ten lines (or the given number of lines) of each given file
<b>hostid</b>	Reports the numeric identifier (in hexadecimal) of the host
<b>id</b>	Reports the effective user ID, group ID, and group memberships of the current user or specified user
<b>install</b>	Copies files while setting their permission modes and, if possible, their owner and group
<b>join</b>	Joins the lines that have identical join fields from two separate files
<b>link</b>	Creates a hard link (with the given name) to a file
<b>ln</b>	Makes hard links or soft (symbolic) links between files
<b>logname</b>	Reports the current user's login name
<b>ls</b>	Lists the contents of each given directory
<b>md5sum</b>	Reports or checks Message Digest 5 (MD5) checksums

<b>mkdir</b>	Creates directories with the given names
<b>mkfifo</b>	Creates First-In, First-Outs (FIFOs), "named pipes" in UNIX parlance, with the given names
<b>mknod</b>	Creates device nodes with the given names; a device node is a character special file, a block special file, or a FIFO
<b>mktemp</b>	Creates temporary files in a secure manner; it is used in scripts
<b>mv</b>	Moves or renames files or directories
<b>nice</b>	Runs a program with modified scheduling priority
<b>nl</b>	Numbers the lines from the given files
<b>nohup</b>	Runs a command immune to hangups, with its output redirected to a log file
<b>nproc</b>	Prints the number of processing units available to a process
<b>numfmt</b>	Converts numbers to or from human-readable strings
<b>od</b>	Dumps files in octal and other formats
<b>paste</b>	Merges the given files, joining sequentially corresponding lines side by side, separated by tab characters
<b>pathchk</b>	Checks if file names are valid or portable
<b>pinky</b>	Is a lightweight finger client; it reports some information about the given users
<b>pr</b>	Paginates and columnates files for printing
<b>printenv</b>	Prints the environment
<b>printf</b>	Prints the given arguments according to the given format, much like the C printf function
<b>ptx</b>	Produces a permuted index from the contents of the given files, with each keyword in its context
<b>pwd</b>	Reports the name of the current working directory
<b>readlink</b>	Reports the value of the given symbolic link
<b>realpath</b>	Prints the resolved path
<b>rm</b>	Removes files or directories
<b>rmdir</b>	Removes directories if they are empty
<b>runcon</b>	Runs a command with specified security context
<b>seq</b>	Prints a sequence of numbers within a given range and with a given increment
<b>sha1sum</b>	Prints or checks 160-bit Secure Hash Algorithm 1 (SHA1) checksums
<b>sha224sum</b>	Prints or checks 224-bit Secure Hash Algorithm checksums
<b>sha256sum</b>	Prints or checks 256-bit Secure Hash Algorithm checksums
<b>sha384sum</b>	Prints or checks 384-bit Secure Hash Algorithm checksums
<b>sha512sum</b>	Prints or checks 512-bit Secure Hash Algorithm checksums
<b>shred</b>	Overwrites the given files repeatedly with complex patterns, making it difficult to recover the data
<b>shuf</b>	Shuffles lines of text
<b>sleep</b>	Pauses for the given amount of time
<b>sort</b>	Sorts the lines from the given files
<b>split</b>	Splits the given file into pieces, by size or by number of lines



<b>stat</b>	Displays file or filesystem status
<b>stdbuf</b>	Runs commands with altered buffering operations for its standard streams
<b>stty</b>	Sets or reports terminal line settings
<b>sum</b>	Prints checksum and block counts for each given file
<b>sync</b>	Flushes file system buffers; it forces changed blocks to disk and updates the super block
<b>tac</b>	Concatenates the given files in reverse
<b>tail</b>	Prints the last ten lines (or the given number of lines) of each given file
<b>tee</b>	Reads from standard input while writing both to standard output and to the given files
<b>test</b>	Compares values and checks file types
<b>timeout</b>	Runs a command with a time limit
<b>touch</b>	Changes file timestamps, setting the access and modification times of the given files to the current time; files that do not exist are created with zero length
<b>tr</b>	Translates, squeezes, and deletes the given characters from standard input
<b>true</b>	Does nothing, successfully; it always exits with a status code indicating success
<b>truncate</b>	Shrinks or expands a file to the specified size
<b>tsort</b>	Performs a topological sort; it writes a completely ordered list according to the partial ordering in a given file
<b>tty</b>	Reports the file name of the terminal connected to standard input
<b>uname</b>	Reports system information
<b>unexpand</b>	Converts spaces to tabs
<b>uniq</b>	Discards all but one of successive identical lines
<b>unlink</b>	Removes the given file
<b>users</b>	Reports the names of the users currently logged on
<b>vdir</b>	Is the same as <b>ls -l</b>
<b>wc</b>	Reports the number of lines, words, and bytes for each given file, as well as grand totals when more than one file is given
<b>who</b>	Reports who is logged on
<b>whoami</b>	Reports the user name associated with the current effective user ID
<b>yes</b>	Repeatedly outputs <i>y</i> or a given string, until killed
<code>libstdbuf</code>	Library used by <b>stdbuf</b>

## 8.59. Check-0.15.2

Check is a unit testing framework for C.

**Approximate build time:** 0.1 SBU (about 2.1 SBU with tests)

**Required disk space:** 11 MB

### 8.59.1. Installation of Check

Prepare Check for compilation:

```
./configure --prefix=/usr --disable-static
```

Build the package:

```
make
```

Compilation is now complete. To run the Check test suite, issue the following command:

```
make check
```

Install the package:

```
make docdir=/usr/share/doc/check-0.15.2 install
```

### 8.59.2. Contents of Check

**Installed program:** checkmk

**Installed library:** libcheck.so

#### Short Descriptions

**checkmk** Awk script for generating C unit tests for use with the Check unit testing framework

libcheck.so Contains functions that allow Check to be called from a test program

## 8.60. Diffutils-3.10

The Diffutils package contains programs that show the differences between files or directories.

**Approximate build time:** 0.3 SBU

**Required disk space:** 42 MB

### 8.60.1. Installation of Diffutils

Prepare Diffutils for compilation:

```
./configure --prefix=/usr
```

Compile the package:

```
make
```

To test the results, issue:

```
make check
```

Install the package:

```
make install
```

### 8.60.2. Contents of Diffutils

**Installed programs:** cmp, diff, diff3, and sdiff

#### Short Descriptions

- cmp** Compares two files and reports any differences byte by byte
- diff** Compares two files or directories and reports which lines in the files differ
- diff3** Compares three files line by line
- sdiff** Merges two files and interactively outputs the results

## 8.61. Gawk-5.3.0

The Gawk package contains programs for manipulating text files.

**Approximate build time:** 0.2 SBU

**Required disk space:** 42 MB

### 8.61.1. Installation of Gawk

First, ensure some unneeded files are not installed:

```
sed -i 's/extras//' Makefile.in
```

Prepare Gawk for compilation:

```
./configure --prefix=/usr
```

Compile the package:

```
make
```

To test the results, issue:

```
chown -R tester .
su tester -c "PATH=$PATH make check"
```

Install the package:

```
rm -f /usr/bin/gawk-5.3.0
make install
```

**The meaning of the command:**

**rm -f /usr/bin/gawk-5.3.0**

The building system will not recreate the hard link `gawk-5.3.0` if it already exists. Remove it to ensure that the previous hard link installed in Section 6.9, “Gawk-5.3.0” is updated here.

The installation process already created **awk** as a symlink to **gawk**, create its man page as a symlink as well:

```
ln -sv gawk.1 /usr/share/man/man1/awk.1
```

If desired, install the documentation:

```
mkdir -pv /usr/share/doc/gawk-5.3.0
cp -v doc/{awkforai.txt,*.eps,pdf,jpg} /usr/share/doc/gawk-5.3.0
```

### 8.61.2. Contents of Gawk

<b>Installed programs:</b>	awk (link to gawk), gawk, and gawk-5.3.0
<b>Installed libraries:</b>	filefuncs.so, fnmatch.so, fork.so, inplace.so, intdiv.so, ordchr.so, readdir.so, readfile.so, revoutput.so, revtwoway.so, rwwarray.so, and time.so (all in /usr/lib/gawk)
<b>Installed directories:</b>	/usr/lib/gawk, /usr/libexec/awk, /usr/share/awk, and /usr/share/doc/gawk-5.3.0

### Short Descriptions

<b>awk</b>	A link to <b>gawk</b>
<b>gawk</b>	A program for manipulating text files; it is the GNU implementation of <b>awk</b>
<b>gawk-5.3.0</b>	A hard link to <b>gawk</b>

## 8.62. Findutils-4.10.0

The Findutils package contains programs to find files. Programs are provided to search through all the files in a directory tree and to create, maintain, and search a database (often faster than the recursive find, but unreliable unless the database has been updated recently). Findutils also supplies the **xargs** program, which can be used to run a specified command on each file selected by a search.

**Approximate build time:** 0.7 SBU

**Required disk space:** 62 MB

### 8.62.1. Installation of Findutils

Prepare Findutils for compilation:

```
./configure --prefix=/usr --localstatedir=/var/lib/locate
```

**The meaning of the configure options:**

*--localstatedir*

This option moves the **locate** database to `/var/lib/locate`, which is the FHS-compliant location.

Compile the package:

```
make
```

To test the results, issue:

```
chown -R tester .
su tester -c "PATH=$PATH make check"
```

Install the package:

```
make install
```

### 8.62.2. Contents of Findutils

**Installed programs:** find, locate, updatedb, and xargs

**Installed directory:** /var/lib/locate

#### Short Descriptions

<b>find</b>	Searches given directory trees for files matching the specified criteria
<b>locate</b>	Searches through a database of file names and reports the names that contain a given string or match a given pattern
<b>updatedb</b>	Updates the <b>locate</b> database; it scans the entire file system (including other file systems that are currently mounted, unless told not to) and puts every file name it finds into the database
<b>xargs</b>	Can be used to apply a given command to a list of files

## 8.63. Groff-1.23.0

The Groff package contains programs for processing and formatting text and images.

**Approximate build time:** 0.2 SBU

**Required disk space:** 107 MB

### 8.63.1. Installation of Groff

Groff expects the environment variable `PAGE` to contain the default paper size. For users in the United States, `PAGE=letter` is appropriate. Elsewhere, `PAGE=A4` may be more suitable. While the default paper size is configured during compilation, it can be overridden later by echoing either “A4” or “letter” to the `/etc/papersize` file.

Prepare Groff for compilation:

```
PAGE=<paper_size> ./configure --prefix=/usr
```

Build the package:

```
make
```

To test the results, issue:

```
make check
```

Install the package:

```
make install
```

### 8.63.2. Contents of Groff

**Installed programs:** addftinfo, afmtodit, chem, eqn, eqn2graph, gdiffmk, glilypond, gperl, gpinyin, grap2graph, grn, grodvi, groff, groffer, grog, grolbp, grolj4, gropdf, grops, grotty, hpftodit, indxbib, lkbib, lookbib, mmroff, neqn, nroff, pdfmom, pdfroff, pfbtops, pic, pic2graph, post-grohtml, preconv, pre-grohtml, refer, roff2dvi, roff2html, roff2pdf, roff2ps, roff2text, roff2x, soelim, tbl, tfmtodit, and troff

**Installed directories:** /usr/lib/groff and /usr/share/doc/groff-1.23.0, /usr/share/groff

### Short Descriptions

<b>addftinfo</b>	Reads a troff font file and adds some additional font-metric information that is used by the <b>groff</b> system
<b>afmtodit</b>	Creates a font file for use with <b>groff</b> and <b>grops</b>
<b>chem</b>	Groff preprocessor for producing chemical structure diagrams
<b>eqn</b>	Compiles descriptions of equations embedded within troff input files into commands that are understood by <b>troff</b>
<b>eqn2graph</b>	Converts a troff EQN (equation) into a cropped image
<b>gdiffmk</b>	Marks differences between groff/nroff/troff files
<b>glilypond</b>	Transforms sheet music written in the lilypond language into the groff language
<b>gperl</b>	Preprocessor for groff, allowing the insertion of perl code into groff files
<b>gpinyin</b>	Preprocessor for groff, allowing the insertion of Pinyin (Mandarin Chinese spelled with the Roman alphabet) into groff files.

<b>grap2graph</b>	Converts a grap program file into a cropped bitmap image (grap is an old Unix programming language for creating diagrams)
<b>grn</b>	A <b>groff</b> preprocessor for gremlin files
<b>grodvi</b>	A driver for <b>groff</b> that produces TeX dvi format output files
<b>groff</b>	A front end to the groff document formatting system; normally, it runs the <b>troff</b> program and a post-processor appropriate for the selected device
<b>groffer</b>	Displays groff files and man pages on X and tty terminals
<b>grog</b>	Reads files and guesses which of the <b>groff</b> options <code>-e</code> , <code>-man</code> , <code>-me</code> , <code>-mm</code> , <code>-ms</code> , <code>-p</code> , <code>-s</code> , and <code>-t</code> are required for printing files, and reports the <b>groff</b> command including those options
<b>grolbp</b>	Is a <b>groff</b> driver for Canon CAPSL printers (LBP-4 and LBP-8 series laser printers)
<b>grolj4</b>	Is a driver for <b>groff</b> that produces output in PCL5 format suitable for an HP LaserJet 4 printer
<b>gropdf</b>	Translates the output of GNU <b>troff</b> to PDF
<b>grops</b>	Translates the output of GNU <b>troff</b> to PostScript
<b>grotty</b>	Translates the output of GNU <b>troff</b> into a form suitable for typewriter-like devices
<b>hpftodit</b>	Creates a font file for use with <b>groff -Tlj4</b> from an HP-tagged font metric file
<b>indxbib</b>	Creates an inverted index for the bibliographic databases with a specified file for use with <b>refer</b> , <b>lookbib</b> , and <b>lkbib</b>
<b>lkbib</b>	Searches bibliographic databases for references that contain specified keys and reports any references found
<b>lookbib</b>	Prints a prompt on the standard error (unless the standard input is not a terminal), reads a line containing a set of keywords from the standard input, searches the bibliographic databases in a specified file for references containing those keywords, prints any references found on the standard output, and repeats this process until the end of input
<b>mmroff</b>	A simple preprocessor for <b>groff</b>
<b>neqn</b>	Formats equations for American Standard Code for Information Interchange (ASCII) output
<b>nroff</b>	A script that emulates the <b>nroff</b> command using <b>groff</b>
<b>pdfmom</b>	Is a wrapper around groff that facilitates the production of PDF documents from files formatted with the mom macros.
<b>pdfroff</b>	Creates pdf documents using groff
<b>pfbtops</b>	Translates a PostScript font in <code>.pfb</code> format to ASCII
<b>pic</b>	Compiles descriptions of pictures embedded within troff or TeX input files into commands understood by TeX or <b>troff</b>
<b>pic2graph</b>	Converts a PIC diagram into a cropped image
<b>post-grohtml</b>	Translates the output of GNU <b>troff</b> to HTML
<b>preconv</b>	Converts encoding of input files to something GNU <b>troff</b> understands
<b>pre-grohtml</b>	Translates the output of GNU <b>troff</b> to HTML
<b>refer</b>	Copies the contents of a file to the standard output, except that lines between <code>./</code> and <code>./</code> are interpreted as citations, and lines between <code>.R1</code> and <code>.R2</code> are interpreted as commands for how citations are to be processed

<b>roff2dvi</b>	Transforms roff files into DVI format
<b>roff2html</b>	Transforms roff files into HTML format
<b>roff2pdf</b>	Transforms roff files into PDFs
<b>roff2ps</b>	Transforms roff files into ps files
<b>roff2text</b>	Transforms roff files into text files
<b>roff2x</b>	Transforms roff files into other formats
<b>soelim</b>	Reads files and replaces lines of the form <i>.so file</i> by the contents of the mentioned <i>file</i>
<b>tbl</b>	Compiles descriptions of tables embedded within troff input files into commands that are understood by <b>troff</b>
<b>tfmtofit</b>	Creates a font file for use with <b>groff -Tdvi</b>
<b>troff</b>	Is highly compatible with Unix <b>troff</b> ; it should usually be invoked using the <b>groff</b> command, which will also run preprocessors and post-processors in the appropriate order and with the appropriate options



## 8.64. GRUB-2.12

The GRUB package contains the GRand Unified Bootloader.

**Approximate build time:** 0.3 SBU

**Required disk space:** 166 MB

### 8.64.1. Installation of GRUB



#### Note

If your system has UEFI support and you wish to boot LFS with UEFI, you need to install GRUB with UEFI support (and its dependencies) by following the instructions on *the BLFS page*. You may skip this package, or install this package and the BLFS GRUB for UEFI package without conflict (the BLFS page provides instructions for both cases).



#### Warning

Unset any environment variables which may affect the build:

```
unset {C,CPP,CXX,LD}FLAGS
```

Don't try “tuning” this package with custom compilation flags. This package is a bootloader. The low-level operations in the source code may be broken by aggressive optimization.

Add a file missing from the release tarball:

```
echo depends bli part_gpt > grub-core/extra_deps.lst
```

Prepare GRUB for compilation:

```
./configure --prefix=/usr          \
            --sysconfdir=/etc      \
            --disable-efiemu      \
            --disable-werror
```

**The meaning of the new configure options:**

`--disable-werror`

This allows the build to complete with warnings introduced by more recent versions of Flex.

`--disable-efiemu`

This option minimizes what is built by disabling a feature and eliminating some test programs not needed for LFS.

Compile the package:

```
make
```

The test suite for this packages is not recommended. Most of the tests depend on packages that are not available in the limited LFS environment. To run the tests anyway, run **make check**.

Install the package:

```
make install
mv -v /etc/bash_completion.d/grub /usr/share/bash-completion/completions
```

Making your LFS system bootable with GRUB will be discussed in Section 10.4, “Using GRUB to Set Up the Boot Process.”

## 8.64.2. Contents of GRUB

**Installed programs:** grub-bios-setup, grub-editenv, grub-file, grub-fstest, grub-glue-efi, grub-install, grub-kbdcomp, grub-macbless, grub-menulst2cfg, grub-mkconfig, grub-mkimage, grub-mklayout, grub-mknetdir, grub-mkpasswd-pbkdf2, grub-mkrelpath, grub-mkrescue, grub-mkstandalone, grub-ofpathname, grub-probe, grub-reboot, grub-render-label, grub-script-check, grub-set-default, grub-sparc64-setup, and grub-syslinux2cfg

**Installed directories:** /usr/lib/grub, /etc/grub.d, /usr/share/grub, and /boot/grub (when grub-install is first run)

### Short Descriptions

<b>grub-bios-setup</b>	Is a helper program for <b>grub-install</b>
<b>grub-editenv</b>	Is a tool to edit the environment block
<b>grub-file</b>	Checks to see if the given file is of the specified type
<b>grub-fstest</b>	Is a tool to debug the filesystem driver
<b>grub-glue-efi</b>	Glues 32-bit and 64-bit binaries into a single file (for Apple machines)
<b>grub-install</b>	Installs GRUB on your drive
<b>grub-kbdcomp</b>	Is a script that converts an xkb layout into one recognized by GRUB
<b>grub-macbless</b>	Is the Mac-style bless for HFS or HFS+ file systems ( <b>bless</b> is peculiar to Apple machines; it makes a device bootable)
<b>grub-menulst2cfg</b>	Converts a GRUB Legacy <code>menu.lst</code> into a <code>grub.cfg</code> for use with GRUB 2
<b>grub-mkconfig</b>	Generates a <code>grub.cfg</code> file
<b>grub-mkimage</b>	Makes a bootable image of GRUB
<b>grub-mklayout</b>	Generates a GRUB keyboard layout file
<b>grub-mknetdir</b>	Prepares a GRUB netboot directory
<b>grub-mkpasswd-pbkdf2</b>	Generates an encrypted PBKDF2 password for use in the boot menu
<b>grub-mkrelpath</b>	Makes a system pathname relative to its root
<b>grub-mkrescue</b>	Makes a bootable image of GRUB suitable for a floppy disk, CDROM/DVD, or a USB drive
<b>grub-mkstandalone</b>	Generates a standalone image
<b>grub-ofpathname</b>	Is a helper program that prints the path to a GRUB device
<b>grub-probe</b>	Probes device information for a given path or device
<b>grub-reboot</b>	Sets the default boot entry for GRUB for the next boot only
<b>grub-render-label</b>	Renders Apple <code>.disk_label</code> for Apple Macs
<b>grub-script-check</b>	Checks the GRUB configuration script for syntax errors
<b>grub-set-default</b>	Sets the default boot entry for GRUB
<b>grub-sparc64-setup</b>	Is a helper program for grub-setup
<b>grub-syslinux2cfg</b>	Transforms a syslinux config file into <code>grub.cfg</code> format

## 8.65. Gzip-1.13

The Gzip package contains programs for compressing and decompressing files.

**Approximate build time:** 0.3 SBU

**Required disk space:** 21 MB

### 8.65.1. Installation of Gzip

Prepare Gzip for compilation:

```
./configure --prefix=/usr
```

Compile the package:

```
make
```

To test the results, issue:

```
make check
```

Install the package:

```
make install
```

### 8.65.2. Contents of Gzip

**Installed programs:** gunzip, gzexe, gzip, uncompress (hard link with gunzip), zcat, zcmp, zdiff, zegrep, zfgrep, zforce, zgrep, zless, zmore, and znew

#### Short Descriptions

<b>gunzip</b>	Decompresses gzipped files
<b>gzexe</b>	Creates self-decompressing executable files
<b>gzip</b>	Compresses the given files using Lempel-Ziv (LZ77) coding
<b>uncompress</b>	Decompresses compressed files
<b>zcat</b>	Decompresses the given gzipped files to standard output
<b>zcmp</b>	Runs <b>cmp</b> on gzipped files
<b>zdiff</b>	Runs <b>diff</b> on gzipped files
<b>zegrep</b>	Runs <b>egrep</b> on gzipped files
<b>zfgrep</b>	Runs <b>fgrep</b> on gzipped files
<b>zforce</b>	Forces a <b>.gz</b> extension on all given files that are gzipped files, so that <b>gzip</b> will not compress them again; this can be useful when file names were truncated during a file transfer
<b>zgrep</b>	Runs <b>grep</b> on gzipped files
<b>zless</b>	Runs <b>less</b> on gzipped files
<b>zmore</b>	Runs <b>more</b> on gzipped files
<b>znew</b>	Re-compresses files from <b>compress</b> format to <b>gzip</b> format— <b>.z</b> to <b>.gz</b>

## 8.66. IPRoute2-6.10.0

The IPRoute2 package contains programs for basic and advanced IPV4-based networking.

**Approximate build time:** 0.1 SBU

**Required disk space:** 17 MB

### 8.66.1. Installation of IPRoute2

The **arpd** program included in this package will not be built since it depends on Berkeley DB, which is not installed in LFS. However, a directory and a man page for **arpd** will still be installed. Prevent this by running the commands shown below.

```
sed -i /ARPD/d Makefile
rm -fv man/man8/arpd.8
```

Compile the package:

```
make NETNS_RUN_DIR=/run/netns
```

This package does not have a working test suite.

Install the package:

```
make SBINDIR=/usr/sbin install
```

If desired, install the documentation:

```
mkdir -pv /usr/share/doc/iproute2-6.10.0
cp -v COPYING README* /usr/share/doc/iproute2-6.10.0
```

### 8.66.2. Contents of IPRoute2

**Installed programs:** bridge, ctstat (link to lstat), genl, ifstat, ip, lstat, nstat, routil, rtacct, rtmon, rtpr, rtstat (link to lstat), ss, and tc

**Installed directories:** /etc/iproute2, /usr/lib/tc, and /usr/share/doc/iproute2-6.10.0

### Short Descriptions

**bridge** Configures network bridges

**ctstat** Connection status utility

**genl** Generic netlink utility front end

**ifstat** Shows interface statistics, including the number of packets transmitted and received, by interface

**ip** The main executable. It has several different functions, including these:

**ip link** <device> allows users to look at the state of devices and to make changes

**ip addr** allows users to look at addresses and their properties, add new addresses, and delete old ones

**ip neighbor** allows users to look at neighbor bindings and their properties, add new neighbor entries, and delete old ones

**ip rule** allows users to look at the routing policies and change them

**ip route** allows users to look at the routing table and change routing table rules

**ip tunnel** allows users to look at the IP tunnels and their properties, and change them

**ip maddr** allows users to look at the multicast addresses and their properties, and change them

**ip mroute** allows users to set, change, or delete the multicast routing

**ip monitor** allows users to continuously monitor the state of devices, addresses and routes

- lnstat** Provides Linux network statistics; it is a generalized and more feature-complete replacement for the old **rtstat** program
- nstat** Displays network statistics
- routel** A component of **ip route**, for listing the routing tables
- rtacct** Displays the contents of `/proc/net/rt_acct`
- rtmon** Route monitoring utility
- rtpr** Converts the output of **ip -o** into a readable form
- rtstat** Route status utility
- ss** Similar to the **netstat** command; shows active connections
- tc** Traffic control for Quality of Service (QoS) and Class of Service (CoS) implementations
- tc qdisc** allows users to set up the queuing discipline
- tc class** allows users to set up classes based on the queuing discipline scheduling
- tc filter** allows users to set up the QoS/CoS packet filtering
- tc monitor** can be used to view changes made to Traffic Control in the kernel.

## 8.67. Kbd-2.6.4

The Kbd package contains key-table files, console fonts, and keyboard utilities.

**Approximate build time:** 0.1 SBU

**Required disk space:** 34 MB

### 8.67.1. Installation of Kbd

The behavior of the backspace and delete keys is not consistent across the keymaps in the Kbd package. The following patch fixes this issue for i386 keymaps:

```
patch -Np1 -i ../kbd-2.6.4-backspace-1.patch
```

After patching, the backspace key generates the character with code 127, and the delete key generates a well-known escape sequence.

Remove the redundant **resizecons** program (it requires the defunct **svgalib** to provide the video mode files - for normal use **setfont** sizes the console appropriately) together with its manpage.

```
sed -i '/RESIZECONS_PROGS=/s/yes/no/' configure
sed -i 's/resizecons.8 //' docs/man/man8/Makefile.in
```

Prepare Kbd for compilation:

```
./configure --prefix=/usr --disable-vlock
```

**The meaning of the configure option:**

*--disable-vlock*

This option prevents the vlock utility from being built because it requires the PAM library, which isn't available in the chroot environment.

Compile the package:

```
make
```

To test the results, issue:

```
make check
```

Install the package:

```
make install
```



#### Note

For some languages (e.g., Belarusian) the Kbd package doesn't provide a useful keymap where the stock “by” keymap assumes the ISO-8859-5 encoding, and the CP1251 keymap is normally used. Users of such languages have to download working keymaps separately.

If desired, install the documentation:

```
cp -R -v docs/doc -T /usr/share/doc/kbd-2.6.4
```

## 8.67.2. Contents of Kbd

<b>Installed programs:</b>	chvt, deallocvt, dumpkeys, fgconsole, getkeycodes, kbinfo, kbd_mode, kbdrate, loadkeys, loadunimap, mapscrn, openvt, psfaddtable (link to psfxtable), psfgettable (link to psfxtable), psfstrietable (link to psfxtable), psfxtable, setfont, setkeycodes, settled, setmetamode, setvtrgb, showconsolefont, showkey, unicode_start, and unicode_stop
<b>Installed directories:</b>	/usr/share/consolefonts, /usr/share/consoletrans, /usr/share/keymaps, /usr/share/doc/kbd-2.6.4, and /usr/share/unimaps

### Short Descriptions

<b>chvt</b>	Changes the foreground virtual terminal
<b>deallocvt</b>	Deallocates unused virtual terminals
<b>dumpkeys</b>	Dumps the keyboard translation tables
<b>fgconsole</b>	Prints the number of the active virtual terminal
<b>getkeycodes</b>	Prints the kernel scancode-to-keycode mapping table
<b>kbinfo</b>	Obtains information about the status of a console
<b>kbd_mode</b>	Reports or sets the keyboard mode
<b>kbdrate</b>	Sets the keyboard repeat and delay rates
<b>loadkeys</b>	Loads the keyboard translation tables
<b>loadunimap</b>	Loads the kernel unicode-to-font mapping table
<b>mapscrn</b>	An obsolete program that used to load a user-defined output character mapping table into the console driver; this is now done by <b>setfont</b>
<b>openvt</b>	Starts a program on a new virtual terminal (VT)
<b>psfaddtable</b>	Adds a Unicode character table to a console font
<b>psfgettable</b>	Extracts the embedded Unicode character table from a console font
<b>psfstrietable</b>	Removes the embedded Unicode character table from a console font
<b>psfxtable</b>	Handles Unicode character tables for console fonts
<b>setfont</b>	Changes the Enhanced Graphic Adapter (EGA) and Video Graphics Array (VGA) fonts on the console
<b>setkeycodes</b>	Loads kernel scancode-to-keycode mapping table entries; this is useful if there are unusual keys on the keyboard
<b>settleds</b>	Sets the keyboard flags and Light Emitting Diodes (LEDs)
<b>setmetamode</b>	Defines the keyboard meta-key handling
<b>setvtrgb</b>	Sets the console color map in all virtual terminals
<b>showconsolefont</b>	Shows the current EGA/VGA console screen font
<b>showkey</b>	Reports the scancodes, keycodes, and ASCII codes of the keys pressed on the keyboard
<b>unicode_start</b>	Puts the keyboard and console in UNICODE mode [Don't use this program unless your keymap file is in the ISO-8859-1 encoding. For other encodings, this utility produces incorrect results.]
<b>unicode_stop</b>	Reverts keyboard and console from UNICODE mode

## 8.68. Libpipeline-1.5.7

The Libpipeline package contains a library for manipulating pipelines of subprocesses in a flexible and convenient way.

**Approximate build time:** 0.1 SBU

**Required disk space:** 9.7 MB

### 8.68.1. Installation of Libpipeline

Prepare Libpipeline for compilation:

```
./configure --prefix=/usr
```

Compile the package:

```
make
```

To test the results, issue:

```
make check
```

Install the package:

```
make install
```

### 8.68.2. Contents of Libpipeline

**Installed library:** libpipeline.so

#### Short Descriptions

`libpipeline` This library is used to safely construct pipelines between subprocesses



## 8.69. Make-4.4.1

The Make package contains a program for controlling the generation of executables and other non-source files of a package from source files.

**Approximate build time:** 0.7 SBU

**Required disk space:** 13 MB

### 8.69.1. Installation of Make

Prepare Make for compilation:

```
./configure --prefix=/usr
```

Compile the package:

```
make
```

To test the results, issue:

```
chown -R tester .  
su tester -c "PATH=$PATH make check"
```

Install the package:

```
make install
```

### 8.69.2. Contents of Make

**Installed program:** make

#### Short Descriptions

**make** Automatically determines which pieces of a package need to be (re)compiled and then issues the relevant commands

## 8.70. Patch-2.7.6

The Patch package contains a program for modifying or creating files by applying a “patch” file typically created by the **diff** program.

**Approximate build time:** 0.2 SBU

**Required disk space:** 12 MB

### 8.70.1. Installation of Patch

Prepare Patch for compilation:

```
./configure --prefix=/usr
```

Compile the package:

```
make
```

To test the results, issue:

```
make check
```

Install the package:

```
make install
```

### 8.70.2. Contents of Patch

**Installed program:** patch

#### Short Descriptions

**patch** Modifies files according to a patch file (A patch file is normally a difference listing created with the **diff** program. By applying these differences to the original files, **patch** creates the patched versions.)

## 8.71. Tar-1.35

The Tar package provides the ability to create tar archives as well as perform various other kinds of archive manipulation. Tar can be used on previously created archives to extract files, to store additional files, or to update or list files which were already stored.

**Approximate build time:** 0.7 SBU

**Required disk space:** 43 MB

### 8.71.1. Installation of Tar

Prepare Tar for compilation:

```
FORCE_UNSAFE_CONFIGURE=1 \
./configure --prefix=/usr
```

**The meaning of the configure option:**

```
FORCE_UNSAFE_CONFIGURE=1
```

This forces the test for `mknod` to be run as `root`. It is generally considered dangerous to run this test as the `root` user, but as it is being run on a system that has only been partially built, overriding it is OK.

Compile the package:

```
make
```

To test the results, issue:

```
make check
```

One test, capabilities: binary store/restore, is known to fail if it is run because LFS lacks selinux, but will be skipped if the host kernel does not support extended attributes or security labels on the filesystem used for building LFS.

Install the package:

```
make install
make -C doc install-html docdir=/usr/share/doc/tar-1.35
```

### 8.71.2. Contents of Tar

**Installed programs:** tar

**Installed directory:** /usr/share/doc/tar-1.35

### Short Descriptions

**tar** Creates, extracts files from, and lists the contents of archives, also known as tarballs

## 8.72. Texinfo-7.1

The Texinfo package contains programs for reading, writing, and converting info pages.

**Approximate build time:** 0.3 SBU

**Required disk space:** 139 MB

### 8.72.1. Installation of Texinfo

Prepare Texinfo for compilation:

```
./configure --prefix=/usr
```

Compile the package:

```
make
```

To test the results, issue:

```
make check
```

Install the package:

```
make install
```

Optionally, install the components belonging in a TeX installation:

```
make TEXMF=/usr/share/texmf install-tex
```

**The meaning of the make parameter:**

```
TEXMF=/usr/share/texmf
```

The `TEXMF` makefile variable holds the location of the root of the TeX tree if, for example, a TeX package will be installed later.

The Info documentation system uses a plain text file to hold its list of menu entries. The file is located at `/usr/share/info/dir`. Unfortunately, due to occasional problems in the Makefiles of various packages, it can sometimes get out of sync with the info pages installed on the system. If the `/usr/share/info/dir` file ever needs to be recreated, the following optional commands will accomplish the task:

```
pushd /usr/share/info
  rm -v dir
  for f in *
  do install-info $f dir 2>/dev/null
  done
popd
```

### 8.72.2. Contents of Texinfo

**Installed programs:** info, install-info, makeinfo (link to texi2any), pdftexi2dvi, pod2texi, texi2any, texi2dvi, texi2pdf, and texindex

**Installed library:** MiscXS.so, Parsetexi.so, and XSParagraph.so (all in `/usr/lib/texinfo`)

**Installed directories:** `/usr/share/texinfo` and `/usr/lib/texinfo`

### Short Descriptions

**info** Used to read info pages which are similar to man pages, but often go much deeper than just explaining all the available command line options [For example, compare **man bison** and **info bison**.]

<b>install-info</b>	Used to install info pages; it updates entries in the <b>info</b> index file
<b>makeinfo</b>	Translates the given Texinfo source documents into info pages, plain text, or HTML
<b>pdfTEXi2dvi</b>	Used to format the given Texinfo document into a Portable Document Format (PDF) file
<b>pod2texi</b>	Converts Pod to Texinfo format
<b>texi2any</b>	Translate Texinfo source documentation to various other formats
<b>texi2dvi</b>	Used to format the given Texinfo document into a device-independent file that can be printed
<b>texi2pdf</b>	Used to format the given Texinfo document into a Portable Document Format (PDF) file
<b>texindex</b>	Used to sort Texinfo index files

## 8.73. Vim-9.1.0660

The Vim package contains a powerful text editor.

**Approximate build time:** 2.9 SBU

**Required disk space:** 245 MB



### Alternatives to Vim

If you prefer another editor—such as Emacs, Joe, or Nano—please refer to <https://www.linuxfromscratch.org/blfs/view/stable-systemd/postlfs/editors.html> for suggested installation instructions.

### 8.73.1. Installation of Vim

First, change the default location of the `vimrc` configuration file to `/etc`:

```
echo '#define SYS_VIMRC_FILE "/etc/vimrc"' >> src/feature.h
```

Prepare Vim for compilation:

```
./configure --prefix=/usr
```

Compile the package:

```
make
```

To prepare the tests, ensure that user `tester` can write to the source tree:

```
chown -R tester .
```

Now run the tests as user `tester`:

```
su tester -c "TERM=xterm-256color LANG=en_US.UTF-8 make -j1 test" \
&&> vim-test.log
```

The test suite outputs a lot of binary data to the screen. This can cause issues with the settings of the current terminal (especially while we are overriding the `TERM` variable to satisfy some assumptions of the test suite). The problem can be avoided by redirecting the output to a log file as shown above. A successful test will result in the words `ALL DONE` in the log file at completion.

Install the package:

```
make install
```

Many users reflexively type `vi` instead of `vim`. To allow execution of `vim` when users habitually enter `vi`, create a symlink for both the binary and the man page in the provided languages:

```
ln -sv vim /usr/bin/vi
for L in /usr/share/man/{,*/}man1/vim.1; do
  ln -sv vim.1 $(dirname $L)/vi.1
done
```

By default, Vim's documentation is installed in `/usr/share/vim`. The following symlink allows the documentation to be accessed via `/usr/share/doc/vim-9.1.0660`, making it consistent with the location of documentation for other packages:

```
ln -sv ../vim/vim91/doc /usr/share/doc/vim-9.1.0660
```

If an X Window System is going to be installed on the LFS system, it may be necessary to recompile Vim after installing X. Vim comes with a GUI version of the editor that requires X and some additional libraries to be installed. For more information on this process, refer to the Vim documentation and the Vim installation page in the BLFS book at <https://www.linuxfromscratch.org/blfs/view/stable-systemd/postlfs/vim.html>.

## 8.73.2. Configuring Vim

By default, **vim** runs in vi-incompatible mode. This may be new to users who have used other editors in the past. The “*nocompatible*” setting is included below to highlight the fact that a new behavior is being used. It also reminds those who would change to “*compatible*” mode that it should be the first setting in the configuration file. This is necessary because it changes other settings, and overrides must come after this setting. Create a default **vim** configuration file by running the following:

```
cat > /etc/vimrc << "EOF"
" Begin /etc/vimrc

" Ensure defaults are set before customizing settings, not after
source $VIMRUNTIME/defaults.vim
let skip_defaults_vim=1

set nocompatible
set backspace=2
set mouse=
syntax on
if (&term == "xterm") || (&term == "putty")
    set background=dark
endif

" End /etc/vimrc
EOF
```

The *set nocompatible* setting makes **vim** behave in a more useful way (the default) than the vi-compatible manner. Remove the “no” to keep the old **vi** behavior. The *set backspace=2* setting allows backspacing over line breaks, autoindents, and the start of an insert. The *syntax on* parameter enables vim's syntax highlighting. The *set mouse=* setting enables proper pasting of text with the mouse when working in chroot or over a remote connection. Finally, the *if* statement with the *set background=dark* setting corrects **vim**'s guess about the background color of some terminal emulators. This gives the highlighting a better color scheme for use on the black background of these programs.

Documentation for other available options can be obtained by running the following command:

```
vim -c ':options'
```



### Note

By default, vim only installs spell-checking files for the English language. To install spell-checking files for your preferred language, copy the `.spl` and optionally, the `.sug` files for your language and character encoding from `runtime/spell` into `/usr/share/vim/vim91/spell/`.

To use these spell-checking files, some configuration in `/etc/vimrc` is needed, e.g.:

```
set spelllang=en,ru
set spell
```

For more information, see `runtime/spell/README.txt`.

## 8.73.3. Contents of Vim

**Installed programs:** `ex` ([link to vim](#)), `rview` ([link to vim](#)), `rvim` ([link to vim](#)), `vi` ([link to vim](#)), `view` ([link to vim](#)), `vim`, `vimdiff` ([link to vim](#)), `vimtutor`, and `xxd`

**Installed directory:** `/usr/share/vim`

## Short Descriptions

<b>ex</b>	Starts <b>vim</b> in ex mode
<b>rview</b>	Is a restricted version of <b>view</b> ; no shell commands can be started and <b>view</b> cannot be suspended
<b>rvim</b>	Is a restricted version of <b>vim</b> ; no shell commands can be started and <b>vim</b> cannot be suspended
<b>vi</b>	Link to <b>vim</b>
<b>view</b>	Starts <b>vim</b> in read-only mode
<b>vim</b>	Is the editor
<b>vimdiff</b>	Edits two or three versions of a file with <b>vim</b> and shows differences
<b>vimtutor</b>	Teaches the basic keys and commands of <b>vim</b>
<b>xxd</b>	Creates a hex dump of the given file; it can also perform the inverse operation, so it can be used for binary patching



## 8.74. MarkupSafe-2.1.5

MarkupSafe is a Python module that implements an XML/HTML/XHTML Markup safe string.

**Approximate build time:** less than 0.1 SBU

**Required disk space:** 508 KB

### 8.74.1. Installation of MarkupSafe

Compile MarkupSafe with the following command:

```
pip3 wheel -w dist --no-cache-dir --no-build-isolation --no-deps $PWD
```

This package does not come with a test suite.

Install the package:

```
pip3 install --no-index --no-user --find-links dist MarkupSafe
```

### 8.74.2. Contents of MarkupSafe

**Installed directory:** /usr/lib/python3.12/site-packages/MarkupSafe-2.1.5.dist-info

## 8.75. Jinja2-3.1.4

Jinja2 is a Python module that implements a simple pythonic template language.

**Approximate build time:** less than 0.1 SBU

**Required disk space:** 2.5 MB

### 8.75.1. Installation of Jinja2

Build the package:

```
pip3 wheel -w dist --no-cache-dir --no-build-isolation --no-deps $PWD
```

Install the package:

```
pip3 install --no-index --no-user --find-links dist Jinja2
```

### 8.75.2. Contents of Jinja2

**Installed directory:** /usr/lib/python3.12/site-packages/Jinja2-3.1.4.dist-info

## 8.76. Systemd-256.4

The systemd package contains programs for controlling the startup, running, and shutdown of the system.

**Approximate build time:** 0.8 SBU

**Required disk space:** 267 MB

### 8.76.1. Installation of systemd

Remove two unneeded groups, `render` and `sgx`, from the default udev rules:

```
sed -i -e 's/GROUP="render"/GROUP="video"/' \
      -e 's/GROUP="sgx", //' rules.d/50-udev-default.rules.in
```

Prepare systemd for compilation:

```
mkdir -p build
cd      build

meson setup .. \
  --prefix=/usr \
  --buildtype=release \
  -D default-dnssec=no \
  -D firstboot=false \
  -D install-tests=false \
  -D ldconfig=false \
  -D sysusers=false \
  -D rpmmacrosdir=no \
  -D homed=disabled \
  -D userdb=false \
  -D man=disabled \
  -D mode=release \
  -D pamconffdir=no \
  -D dev-kvm-mode=0660 \
  -D nobody-group=nogroup \
  -D sysupdate=disabled \
  -D ukify=disabled \
  -D docdir=/usr/share/doc/systemd-256.4
```

**The meaning of the meson options:**

`--buildtype=release`

This switch overrides the default buildtype (“debug”), which produces unoptimized binaries.

`-D default-dnssec=no`

This switch turns off the experimental DNSSEC support.

`-D firstboot=false`

This switch prevents installation of systemd services responsible for setting up the system for the first time. These are not useful in LFS, because everything is done manually.

`-D install-tests=false`

This switch prevents installation of the compiled tests.

`-D ldconfig=false`

This switch prevents installation of a systemd unit that runs **ldconfig** at boot; this is not useful for source distributions such as LFS, and makes the boot time longer. Remove this option to enable running **ldconfig** at boot.

`-D sysusers=false`

This switch prevents installation of systemd services responsible for setting up the `/etc/group` and `/etc/passwd` files. Both files were created in the previous chapter. This daemon is not useful on an LFS system since user accounts are manually created.

`-D rpmmacrosdir=no`

This switch disables installation of RPM Macros for use with systemd, because LFS does not support RPM.

`-D homed=disabled` and `-D userdb=false`

Remove two daemons with dependencies that do not fit within the scope of LFS.

`-D man=disabled`

Prevent the generation of man pages to avoid extra dependencies. We will install pre-generated man pages for systemd from a tarball.

`-D mode=release`

Disable some features considered experimental by upstream.

`-D pamconfdir=no`

Prevent the installation of a PAM configuration file not functional on LFS.

`-D dev-kvm-mode=0660`

The default udev rule would allow all users to access `/dev/kvm`. The editors consider it dangerous. This option overrides it.

`-D nobody-group=nogroup`

Tell the package the group name with GID 65534 is `nogroup`.

`-D sysupdate=disabled`

Do not install the **systemd-sysupdate** tool. It's designed for automatically upgrading binary distros, so it's useless for a basic Linux system built from source. And it will report errors on boot if it's enabled but not properly configured.

`-D ukify=disabled`

Do not install the **systemd-ukify** script. At runtime this script requires the `pefile` Python module that neither LFS nor BLFS provides.

Compile the package:

```
ninja
```

Some tests need a basic `/etc/os-release` file. To test the results, issue:

```
echo 'NAME="Linux From Scratch"' > /etc/os-release
ninja test
```

One test named `systemd:core / test-namespace` is known to fail in the LFS chroot environment. Some other tests may fail because they depend on various kernel configuration options.

Install the package:

```
ninja install
```

Install the man pages:

```
tar -xf ../../systemd-man-pages-256.4.tar.xz \
--no-same-owner --strip-components=1 \
-C /usr/share/man
```

Create the `/etc/machine-id` file needed by **systemd-journald**:

```
systemd-machine-id-setup
```

Set up the basic target structure:

```
systemctl preset-all
```

## 8.76.2. Contents of systemd

<b>Installed programs:</b>	busctl, coredumpctl, halt (symlink to systemctl), hostnamectl, init, journalctl, kernel-install, localectl, loginctl, machinectl, mount.ddi (symlink to systemd-dissect), networkctl, oomctl, portablectl, poweroff (symlink to systemctl), reboot (symlink to systemctl), resolvconf (symlink to resolvectl), resolvectl, runlevel (symlink to systemctl), shutdown (symlink to systemctl), systemctl, systemd-ac-power, systemd-analyze, systemd-ask-password, systemd-cat, systemd-cgls, systemd-cgtop, systemd-confext (symlink to systemd-sysex), systemd-creds, systemd-delta, systemd-detect-virt, systemd-dissect, systemd-escape, systemd-hwdb, systemd-id128, systemd-inhibit, systemd-machine-id-setup, systemd-mount, systemd-notify, systemd-nspawn, systemd-path, systemd-repart, systemd-resolve (symlink to resolvectl), systemd-run, systemd-socket-activate, systemd-stdio-bridge, systemd-sysex, systemd-tmpfiles, systemd-tty-ask-password-agent, systemd-umount (symlink to systemd-mount), telinit (symlink to systemctl), timedatectl, and udevadm
<b>Installed libraries:</b>	libnss_myhostname.so.2, libnss_mymachines.so.2, libnss_resolve.so.2, libnss_systemd.so.2, libsystemd.so, libsystemd-shared-256.4.so (in <code>/usr/lib/systemd</code> ), and libudev.so
<b>Installed directories:</b>	<code>/etc/binfmt.d</code> , <code>/etc/init.d</code> , <code>/etc/kernel</code> , <code>/etc/modules-load.d</code> , <code>/etc/sysctl.d</code> , <code>/etc/systemd</code> , <code>/etc/tmpfiles.d</code> , <code>/etc/udev</code> , <code>/etc/xdg/systemd</code> , <code>/usr/lib/systemd</code> , <code>/usr/lib/udev</code> , <code>/usr/include/systemd</code> , <code>/usr/lib/binfmt.d</code> , <code>/usr/lib/environment.d</code> , <code>/usr/lib/kernel</code> , <code>/usr/lib/modules-load.d</code> , <code>/usr/lib/sysctl.d</code> , <code>/usr/lib/systemd</code> , <code>/usr/lib/tmpfiles.d</code> , <code>/usr/share/doc/systemd-256.4</code> , <code>/usr/share/factory</code> , <code>/usr/share/systemd</code> , <code>/var/lib/systemd</code> , and <code>/var/log/journal</code>

## Short Descriptions

<b>busctl</b>	Is used to introspect and monitor the D-Bus bus
<b>coredumpctl</b>	Is used to retrieve coredumps from the systemd journal
<b>halt</b>	Normally invokes <b>shutdown</b> with the <code>-h</code> option, except when already in run-level 0, when it tells the kernel to halt the system; it notes in the file <code>/var/log/wtmp</code> that the system is being brought down
<b>hostnamectl</b>	Is used to query and change the system hostname and related settings
<b>init</b>	Is the first process to be started after the kernel has initialized the hardware; <b>init</b> takes over the boot process and starts the processes specified by its configuration files; in this case, it starts systemd
<b>journalctl</b>	Is used to query the contents of the systemd journal
<b>kernel-install</b>	Is used to add and remove kernel and initramfs images to and from <code>/boot</code> ; in LFS, this is done manually

<b>localectl</b>	Is used to query and change the system locale and keyboard layout settings
<b>loginctl</b>	Is used to introspect and control the state of the systemd Login Manager
<b>machinectl</b>	Is used to introspect and control the state of the systemd Virtual Machine and Container Registration Manager
<b>networkctl</b>	Is used to introspect and configure the state of the network links configured by systemd-networkd
<b>oomctl</b>	Controls the systemd Out Of Memory daemon
<b>portablectl</b>	Is used to attach or detach portable services from the local system
<b>poweroff</b>	Instructs the kernel to halt the system and switch off the computer (see <b>halt</b> )
<b>reboot</b>	Instructs the kernel to reboot the system (see <b>halt</b> )
<b>resolvconf</b>	Registers DNS server and domain configuration with <b>systemd-resolved</b>
<b>resolvectl</b>	Sends control commands to the network name resolution manager, or resolves domain names, IPv4 and IPv6 addresses, DNS records, and services
<b>runlevel</b>	Outputs the previous and the current run-level, as noted in the last run-level record in <code>/run/utmp</code>
<b>shutdown</b>	Brings the system down in a safe and secure manner, signaling all processes and notifying all logged-in users
<b>systemctl</b>	Is used to introspect and control the state of the systemd system and service manager
<b>systemd-ac-power</b>	Reports whether the system is connected to an external power source.
<b>systemd-analyze</b>	Is used to analyze system startup performance, as well as identify troublesome systemd units
<b>systemd-ask-password</b>	Is used to query a system password or passphrase from the user, using a message specified on the Linux command line
<b>systemd-cat</b>	Is used to connect the STDOUT and STDERR outputs of a process with the systemd journal
<b>systemd-cgls</b>	Recursively shows the contents of the selected Linux control group hierarchy in a tree
<b>systemd-cgtop</b>	Shows the top control groups of the local Linux control group hierarchy, ordered by their CPU, memory and disk I/O loads
<b>systemd-creds</b>	Displays and processes credentials
<b>systemd-delta</b>	Is used to identify and compare configuration files in <code>/etc</code> that override the defaults in <code>/usr</code>
<b>systemd-detect-virt</b>	Detects whether the system is being run in a virtual environment, and adjusts udev accordingly
<b>systemd-dissect</b>	Is used to inspect OS disk images

<b>systemd-escape</b>	Is used to escape strings for inclusion in systemd unit names
<b>systemd-hwdb</b>	Is used to manage the hardware database (hwdb)
<b>systemd-id128</b>	Generates and prints id128 (UUID) strings
<b>systemd-inhibit</b>	Is used to execute a program with a shutdown, sleep or idle inhibitor lock taken, preventing an action such as a system shutdown until the process is completed
<b>systemd-machine-id-setup</b>	Is used by system installer tools to initialize the machine ID stored in <code>/etc/machine-id</code> at install time with a randomly generated ID
<b>systemd-mount</b>	Is used to temporarily mount or automount disks
<b>systemd-notify</b>	Is used by daemon scripts to notify the init system of status changes
<b>systemd-nspawn</b>	Is used to run a command, or an entire OS, in a light-weight namespace container
<b>systemd-path</b>	Is used to query system and user paths
<b>systemd-repart</b>	Is used to grow and add partitions to a partition table when systemd is used with an OS image (e.g. a container)
<b>systemd-resolve</b>	Is used to resolve domain names, IPV4 and IPV6 addresses, DNS resource records, and services
<b>systemd-run</b>	Is used to create and start a transient <code>.service</code> or a <code>.scope</code> unit and run the specified command in it; this is useful for validating systemd units
<b>systemd-socket-activate</b>	Is used to listen on socket devices and launch a process upon a successful connection to the socket
<b>systemd-sysext</b>	Activates system extension images
<b>systemd-tmpfiles</b>	Creates, deletes, and cleans up volatile and temporary files and directories, based on the configuration file format and location specified in <code>tmpfiles.d</code> directories
<b>systemd-umount</b>	Unmounts mount points
<b>systemd-tty-ask-password-agent</b>	Is used to list and/or process pending systemd password requests
<b>telinit</b>	Tells <b>init</b> which run-level to change to
<b>timedatectl</b>	Is used to query and change the system clock and its settings
<b>udevadm</b>	Is a generic udev administration tool which controls the udevd daemon, provides info from the udev hardware database, monitors uevents, waits for uevents to finish, tests udev configuration, and triggers uevents for a given device
<code>libsystemd</code>	Is the main systemd utility library
<code>libudev</code>	Is a library to access Udev device information

## 8.77. D-Bus-1.14.10

D-Bus is a message bus system, a simple way for applications to talk to one another. D-Bus supplies both a system daemon (for events such as "new hardware device added" or "printer queue changed") and a per-user-login-session daemon (for general IPC needs among user applications). Also, the message bus is built on top of a general one-to-one message passing framework, which can be used by any two applications to communicate directly (without going through the message bus daemon).

**Approximate build time:** 0.1 SBU

**Required disk space:** 19 MB

### 8.77.1. Installation of D-Bus

Prepare D-Bus for compilation:

```
./configure --prefix=/usr \
            --sysconfdir=/etc \
            --localstatedir=/var \
            --runstatedir=/run \
            --enable-user-session \
            --disable-static \
            --disable-doxygen-docs \
            --disable-xml-docs \
            --docdir=/usr/share/doc/dbus-1.14.10 \
            --with-system-socket=/run/dbus/system_bus_socket
```

**The meaning of the configure options:**

`--runstatedir=/run` and `--with-system-socket=/run/dbus/system_bus_socket`

These cause the PID file and the system bus socket to be in `/run`, instead of the deprecated `/var/run`.

`--enable-user-session`

This ensures the D-Bus per-user service and socket unit files are installed for Systemd. They are not useful (but harmless) in a base LFS installation, however they can be used once systemd is rebuilt with PAM support in BLFS.

Compile the package:

```
make
```

To test the results, issue:

```
make check
```

Many tests are disabled because they require additional packages that are not included in LFS. Instructions for running the comprehensive test suite can be found in *the BLFS book*.

Install the package:

```
make install
```

Create a symlink so that D-Bus and systemd can use the same `machine-id` file:

```
ln -sfv /etc/machine-id /var/lib/dbus
```

### 8.77.2. Contents of D-Bus

**Installed programs:** dbus-cleanup-sockets, dbus-daemon, dbus-launch, dbus-monitor, dbus-run-session, dbus-send, dbus-test-tool, dbus-update-activation-environment, and dbus-uuidgen

**Installed libraries:** libdbus-1.so

**Installed directories:** /etc/dbus-1, /usr/include/dbus-1.0, /usr/lib/dbus-1.0, /usr/share/dbus-1, /usr/share/doc/dbus-1.14.10, and /var/lib/dbus



## Short Descriptions

**dbus-cleanup-sockets**

is used to remove leftover sockets in a directory

**dbus-daemon**

Is the D-Bus message bus daemon

**dbus-launch**

Starts **dbus-daemon** from a shell script

**dbus-monitor**

Monitors messages passing through a D-Bus message bus

**dbus-run-session**

Starts a session bus instance of **dbus-daemon** from a shell script and starts a specified program in that session

**dbus-send**

Sends a message to a D-Bus message bus

**dbus-test-tool**

Is a tool to help packages test D-Bus

**dbus-update-activation-environment**

Updates environment variables that will be set for D-Bus session services

**dbus-uuidgen**

Generates a universally unique ID

libdbus-1

Contains API functions used to communicate with the D-Bus message bus

## 8.78. Man-DB-2.12.1

The Man-DB package contains programs for finding and viewing man pages.

**Approximate build time:** 0.3 SBU

**Required disk space:** 43 MB

### 8.78.1. Installation of Man-DB

Prepare Man-DB for compilation:

```
./configure --prefix=/usr \
            --docdir=/usr/share/doc/man-db-2.12.1 \
            --sysconfdir=/etc \
            --disable-setuid \
            --enable-cache-owner=bin \
            --with-browser=/usr/bin/lynx \
            --with-vgrind=/usr/bin/vgrind \
            --with-grap=/usr/bin/grap
```

**The meaning of the configure options:**

`--disable-setuid`

This disables making the **man** program setuid to user `man`.

`--enable-cache-owner=bin`

This changes ownership of the system-wide cache files to user `bin`.

`--with-...`

These three parameters are used to set some default programs. **lynx** is a text-based web browser (see BLFS for installation instructions), **vgrind** converts program sources to Groff input, and **grap** is useful for typesetting graphs in Groff documents. The **vgrind** and **grap** programs are not normally needed for viewing manual pages. They are not part of LFS or BLFS, but you should be able to install them yourself after finishing LFS if you wish to do so.

Compile the package:

```
make
```

To test the results, issue:

```
make check
```

Install the package:

```
make install
```

### 8.78.2. Non-English Manual Pages in LFS

The following table shows the character set that Man-DB assumes manual pages installed under `/usr/share/man/<ll>` will be encoded with. In addition to this, Man-DB correctly determines if manual pages installed in that directory are UTF-8 encoded.

**Table 8.1. Expected character encoding of legacy 8-bit manual pages**

Language (code)	Encoding	Language (code)	Encoding
Danish (da)	ISO-8859-1	Croatian (hr)	ISO-8859-2
German (de)	ISO-8859-1	Hungarian (hu)	ISO-8859-2

Language (code)	Encoding	Language (code)	Encoding
English (en)	ISO-8859-1	Japanese (ja)	EUC-JP
Spanish (es)	ISO-8859-1	Korean (ko)	EUC-KR
Estonian (et)	ISO-8859-1	Lithuanian (lt)	ISO-8859-13
Finnish (fi)	ISO-8859-1	Latvian (lv)	ISO-8859-13
French (fr)	ISO-8859-1	Macedonian (mk)	ISO-8859-5
Irish (ga)	ISO-8859-1	Polish (pl)	ISO-8859-2
Galician (gl)	ISO-8859-1	Romanian (ro)	ISO-8859-2
Indonesian (id)	ISO-8859-1	Greek (el)	ISO-8859-7
Icelandic (is)	ISO-8859-1	Slovak (sk)	ISO-8859-2
Italian (it)	ISO-8859-1	Slovenian (sl)	ISO-8859-2
Norwegian Bokmal (nb)	ISO-8859-1	Serbian Latin (sr@latin)	ISO-8859-2
Dutch (nl)	ISO-8859-1	Serbian (sr)	ISO-8859-5
Norwegian Nynorsk (nn)	ISO-8859-1	Turkish (tr)	ISO-8859-9
Norwegian (no)	ISO-8859-1	Ukrainian (uk)	KOI8-U
Portuguese (pt)	ISO-8859-1	Vietnamese (vi)	TCVN5712-1
Swedish (sv)	ISO-8859-1	Simplified Chinese (zh_CN)	GBK
Belarusian (be)	CP1251	Simplified Chinese, Singapore (zh_SG)	GBK
Bulgarian (bg)	CP1251	Traditional Chinese, Hong Kong (zh_HK)	BIG5HKSCS
Czech (cs)	ISO-8859-2	Traditional Chinese (zh_TW)	BIG5



### Note

Manual pages in languages not in the list are not supported.

## 8.78.3. Contents of Man-DB

- Installed programs:** accessdb, apropos (link to whatis), catman, lexgrog, man, man-recode, mandb, manpath, and whatis
- Installed libraries:** libman.so and libmandb.so (both in /usr/lib/man-db)
- Installed directories:** /usr/lib/man-db, /usr/libexec/man-db, and /usr/share/doc/man-db-2.12.1

### Short Descriptions

- accessdb** Dumps the **whatis** database contents in human-readable form
- apropos** Searches the **whatis** database and displays the short descriptions of system commands that contain a given string

<b>catman</b>	Creates or updates the pre-formatted manual pages
<b>lexgrog</b>	Displays one-line summary information about a given manual page
<b>man</b>	Formats and displays the requested manual page
<b>man-recode</b>	Converts manual pages to another encoding
<b>mandb</b>	Creates or updates the <b>whatis</b> database
<b>manpath</b>	Displays the contents of \$MANPATH or (if \$MANPATH is not set) a suitable search path based on the settings in man.conf and the user's environment
<b>whatis</b>	Searches the <b>whatis</b> database and displays the short descriptions of system commands that contain the given keyword as a separate word
libman	Contains run-time support for <b>man</b>
libmandb	Contains run-time support for <b>man</b>

## 8.79. Procps-ng-4.0.4

The Procps-ng package contains programs for monitoring processes.

**Approximate build time:** 0.1 SBU

**Required disk space:** 26 MB

### 8.79.1. Installation of Procps-ng

Prepare Procps-ng for compilation:

```
./configure --prefix=/usr \
            --docdir=/usr/share/doc/procps-ng-4.0.4 \
            --disable-static \
            --disable-kill \
            --with-systemd
```

The meaning of the configure option:

*--disable-kill*

This switch disables building the **kill** command; it will be installed from the Util-linux package.

Compile the package:

```
make src_w_LDADD='${LDADD} -lsystemd'
```

To run the test suite, run:

```
chown -R tester .
su tester -c "PATH=$PATH make check"
```

One test named `ps` with output flag `bsdtime,cputime,etime,etimes` is known to fail if the host kernel is not built with `CONFIG_BSD_PROCESS_ACCT` enabled.

Install the package:

```
make install
```

### 8.79.2. Contents of Procps-ng

**Installed programs:** free, pgrep, pidof, pkill, pmap, ps, pwdx, slabtop, sysctl, tload, top, uptime, vmstat, w, and watch

**Installed library:** libproc-2.so

**Installed directories:** /usr/include/procps and /usr/share/doc/procps-ng-4.0.4

#### Short Descriptions

<b>free</b>	Reports the amount of free and used memory (both physical and swap memory) in the system
<b>pgrep</b>	Looks up processes based on their name and other attributes
<b>pidof</b>	Reports the PIDs of the given programs
<b>pkill</b>	Signals processes based on their name and other attributes
<b>pmap</b>	Reports the memory map of the given process
<b>ps</b>	Lists the current running processes
<b>pwdx</b>	Reports the current working directory of a process

<b>slabtop</b>	Displays detailed kernel slab cache information in real time
<b>sysctl</b>	Modifies kernel parameters at run time
<b>tload</b>	Prints a graph of the current system load average
<b>top</b>	Displays a list of the most CPU intensive processes; it provides an ongoing look at processor activity in real time
<b>uptime</b>	Reports how long the system has been running, how many users are logged on, and the system load averages
<b>vmstat</b>	Reports virtual memory statistics, giving information about processes, memory, paging, block Input/Output (IO), traps, and CPU activity
<b>w</b>	Shows which users are currently logged on, where, and since when
<b>watch</b>	Runs a given command repeatedly, displaying the first screen-full of its output; this allows a user to watch the output change over time
<code>libproc-2</code>	Contains the functions used by most programs in this package

## 8.80. Util-linux-2.40.2

The Util-linux package contains miscellaneous utility programs. Among them are utilities for handling file systems, consoles, partitions, and messages.

**Approximate build time:** 0.5 SBU

**Required disk space:** 315 MB

### 8.80.1. Installation of Util-linux

Prepare Util-linux for compilation:

```
./configure --bindir=/usr/bin \
            --libdir=/usr/lib \
            --runstatedir=/run \
            --sbindir=/usr/sbin \
            --disable-chfn-chsh \
            --disable-login \
            --disable-nologin \
            --disable-su \
            --disable-setpriv \
            --disable-runuser \
            --disable-pylibmount \
            --disable-liblastlog2 \
            --disable-static \
            --without-python \
            ADJTIME_PATH=/var/lib/hwclock/adjtime \
            --docdir=/usr/share/doc/util-linux-2.40.2
```

The `--disable` and `--without` options prevent warnings about building components that either require packages not in LFS, or are inconsistent with programs installed by other packages.

Compile the package:

```
make
```

If desired, create a dummy `/etc/fstab` file to satisfy two tests and run the test suite as a non-root user:



#### Warning

Running the test suite as the `root` user can be harmful to your system. To run it, the `CONFIG_SCSI_DEBUG` option for the kernel must be available in the currently running system and must be built as a module. Building it into the kernel will prevent booting. For complete coverage, other BLFS packages must be installed. If desired, this test can be run by booting into the completed LFS system and running:

```
bash tests/run.sh --srcdir=$PWD --builddir=$PWD
```

```
touch /etc/fstab
chown -R tester .
su tester -c "make -k check"
```

The *hardlink* tests will fail if the host's kernel does not have the option `CONFIG_CRYPTO_USER_API_HASH` enabled or does not have any options providing a SHA256 implementation (for example, `CONFIG_CRYPTO_SHA256`, or `CONFIG_CRYPTO_SHA256_SSSE3` if the CPU supports Supplemental SSE3) enabled. In addition, the `lsfd: inotify` test will fail if the kernel option `CONFIG_NETLINK_DIAG` is not enabled.

Install the package:

```
make install
```

## 8.80.2. Contents of Util-linux

<b>Installed programs:</b>	addpart, agetty, blkdiscard, blkid, blkzone, blockdev, cal, cfdisk, chcpu, chmem, choom, chrt, col, colcrt, colrm, column, ctrlaltdel, delpart, dmesg, eject, fallocate, fdisk, findcore, findfs, findmnt, flock, fsck, fsck.cramfs, fsck.minix, fsfreeze, fstrim, getopt, hardlink, hexdump, hwclock, i386 (link to setarch), ionice, ipcmk, ipcrm, ipcs, irqtop, isosize, kill, last, lastb (link to last), ldattach, linux32 (link to setarch), linux64 (link to setarch), logger, look, losetup, lsblk, lscpu, lsipc, lsirq, lsfd, lslocks, lslogins, lsmem, lsns, mcookie, mesg, mkfs, mkfs.bfs, mkfs.cramfs, mkfs.minix, mkswap, more, mount, mountpoint, namei, nsenter, partx, pivot_root, prlimit, readprofile, rename, renice, resizepart, rev, rfcill, rtcwake, script, scriptlive, scriptreplay, setarch, setsid, setterm, sfdisk, sulogin, swaplabel, swapoff, swapon, switch_root, taskset, uclampset, ul, umount, uname26 (link to setarch), unshare, utmpdump, uuid, uuidgen, uuidparse, wall, wdctl, whereis, wpefs, x86_64 (link to setarch), and zramctl
<b>Installed libraries:</b>	libblkid.so, libfdisk.so, libmount.so, libsmartcols.so, and libuuid.so
<b>Installed directories:</b>	/usr/include/blkid, /usr/include/libfdisk, /usr/include/libmount, /usr/include/libsmartcols, /usr/include/uuid, /usr/share/doc/util-linux-2.40.2, and /var/lib/hwclock

### Short Descriptions

<b>addpart</b>	Informs the Linux kernel of new partitions
<b>agetty</b>	Opens a tty port, prompts for a login name, and then invokes the <b>login</b> program
<b>blkdiscard</b>	Discards sectors on a device
<b>blkid</b>	A command line utility to locate and print block device attributes
<b>blkzone</b>	Is used to manage zoned storage block devices
<b>blockdev</b>	Allows users to call block device ioctls from the command line
<b>cal</b>	Displays a simple calendar
<b>cfdisk</b>	Manipulates the partition table of the given device
<b>chcpu</b>	Modifies the state of CPUs
<b>chmem</b>	Configures memory
<b>choom</b>	Displays and adjusts OOM-killer scores, used to determine which process to kill first when Linux is Out Of Memory
<b>chrt</b>	Manipulates real-time attributes of a process
<b>col</b>	Filters out reverse line feeds
<b>colcrt</b>	Filters <b>nroff</b> output for terminals that lack some capabilities, such as overstriking and half-lines
<b>colrm</b>	Filters out the given columns
<b>column</b>	Formats a given file into multiple columns
<b>ctrlaltdel</b>	Sets the function of the Ctrl+Alt+Del key combination to a hard or a soft reset
<b>delpart</b>	Asks the Linux kernel to remove a partition
<b>dmesg</b>	Dumps the kernel boot messages
<b>eject</b>	Ejects removable media
<b>fallocate</b>	Preallocates space to a file



<b>fdisk</b>	Manipulates the partition table of the given device
<b>findcore</b>	Counts pages of file contents in core
<b>findfs</b>	Finds a file system, either by label or Universally Unique Identifier (UUID)
<b>findmnt</b>	Is a command line interface to the libmount library for working with mountinfo, fstab and mtab files
<b>flock</b>	Acquires a file lock and then executes a command with the lock held
<b>fsck</b>	Is used to check, and optionally repair, file systems
<b>fsck.cramfs</b>	Performs a consistency check on the Cramfs file system on the given device
<b>fsck.minix</b>	Performs a consistency check on the Minix file system on the given device
<b>fsfreeze</b>	Is a very simple wrapper around FIFREEZE/FITHAW ioctl kernel driver operations
<b>fstrim</b>	Discards unused blocks on a mounted filesystem
<b>getopt</b>	Parses options in the given command line
<b>hardlink</b>	Consolidates duplicate files by creating hard links
<b>hexdump</b>	Dumps the given file in hexadecimal, decimal, octal, or ascii
<b>hwclock</b>	Reads or sets the system's hardware clock, also called the Real-Time Clock (RTC) or Basic Input-Output System (BIOS) clock
<b>i386</b>	A symbolic link to setarch
<b>ionice</b>	Gets or sets the io scheduling class and priority for a program
<b>ipcmk</b>	Creates various IPC resources
<b>ipcrm</b>	Removes the given Inter-Process Communication (IPC) resource
<b>ipcs</b>	Provides IPC status information
<b>irqtop</b>	Displays kernel interrupt counter information in <i>top(1)</i> style view
<b>isozsize</b>	Reports the size of an iso9660 file system
<b>kill</b>	Sends signals to processes
<b>last</b>	Shows which users last logged in (and out), searching back through the <code>/var/log/wtmp</code> file; it also shows system boots, shutdowns, and run-level changes
<b>lastb</b>	Shows the failed login attempts, as logged in <code>/var/log/btmp</code>
<b>ldattach</b>	Attaches a line discipline to a serial line
<b>linux32</b>	A symbolic link to setarch
<b>linux64</b>	A symbolic link to setarch
<b>logger</b>	Enters the given message into the system log
<b>look</b>	Displays lines that begin with the given string
<b>losetup</b>	Sets up and controls loop devices
<b>lsblk</b>	Lists information about all or selected block devices in a tree-like format
<b>lscpu</b>	Prints CPU architecture information
<b>lsfd</b>	Displays information about open files; replaces <b>lsdf</b>
<b>lsipc</b>	Prints information on IPC facilities currently employed in the system

<b>lsirq</b>	Displays kernel interrupt counter information
<b>lslocks</b>	Lists local system locks
<b>lslogins</b>	Lists information about users, groups and system accounts
<b>lsmem</b>	Lists the ranges of available memory with their online status
<b>lsns</b>	Lists namespaces
<b>mcookie</b>	Generates magic cookies (128-bit random hexadecimal numbers) for <b>xauth</b>
<b>mesg</b>	Controls whether other users can send messages to the current user's terminal
<b>mkfs</b>	Builds a file system on a device (usually a hard disk partition)
<b>mkfs.bfs</b>	Creates a Santa Cruz Operations (SCO) bfs file system
<b>mkfs.cramfs</b>	Creates a cramfs file system
<b>mkfs.minix</b>	Creates a Minix file system
<b>mkswap</b>	Initializes the given device or file to be used as a swap area
<b>more</b>	A filter for paging through text one screen at a time
<b>mount</b>	Attaches the file system on the given device to a specified directory in the file-system tree
<b>mountpoint</b>	Checks if the directory is a mountpoint
<b>namei</b>	Shows the symbolic links in the given paths
<b>nsenter</b>	Runs a program with namespaces of other processes
<b>partx</b>	Tells the kernel about the presence and numbering of on-disk partitions
<b>pivot_root</b>	Makes the given file system the new root file system of the current process
<b>prlimit</b>	Gets and sets a process's resource limits
<b>readprofile</b>	Reads kernel profiling information
<b>rename</b>	Renames the given files, replacing a given string with another
<b>renice</b>	Alters the priority of running processes
<b>resizepart</b>	Asks the Linux kernel to resize a partition
<b>rev</b>	Reverses the lines of a given file
<b>rftkill</b>	Tool for enabling and disabling wireless devices
<b>rtcwake</b>	Used to enter a system sleep state until the specified wakeup time
<b>script</b>	Makes a typescript of a terminal session
<b>scriptlive</b>	Re-runs session typescripts using timing information
<b>scriptreplay</b>	Plays back typescripts using timing information
<b>setarch</b>	Changes reported architecture in a new program environment, and sets personality flags
<b>setsid</b>	Runs the given program in a new session
<b>setterm</b>	Sets terminal attributes
<b>sfdisk</b>	A disk partition table manipulator
<b>sulogin</b>	Allows <code>root</code> to log in; it is normally invoked by <b>init</b> when the system goes into single user mode
<b>swaponlabel</b>	Makes changes to the swap area's UUID and label

<b>swapoff</b>	Disables devices and files for paging and swapping
<b>swapon</b>	Enables devices and files for paging and swapping, and lists the devices and files currently in use
<b>switch_root</b>	Switches to another filesystem as the root of the mount tree
<b>taskset</b>	Retrieves or sets a process's CPU affinity
<b>uclampset</b>	Manipulates the utilization clamping attributes of the system or a process
<b>ul</b>	A filter for translating underscores into escape sequences indicating underlining for the terminal in use
<b>umount</b>	Disconnects a file system from the system's file tree
<b>uname26</b>	A symbolic link to setarch
<b>unshare</b>	Runs a program with some namespaces unshared from parent
<b>utmpdump</b>	Displays the content of the given login file in a user-friendly format
<b>uidd</b>	A daemon used by the UUID library to generate time-based UUIDs in a secure and guaranteed-unique fashion
<b>uuidgen</b>	Creates new UUIDs. Each new UUID is a random number likely to be unique among all UUIDs created, on the local system and on other systems, in the past and in the future, with extremely high probability ( $2^{128}$ UUIDs are possible)
<b>uuidparse</b>	A utility to parse unique identifiers
<b>wall</b>	Displays the contents of a file or, by default, its standard input, on the terminals of all currently logged in users
<b>wdctl</b>	Shows hardware watchdog status
<b>whereis</b>	Reports the location of the binary, source, and man page files for the given command
<b>wipefs</b>	Wipes a filesystem signature from a device
<b>x86_64</b>	A symbolic link to setarch
<b>zramctl</b>	A program to set up and control zram (compressed ram disk) devices
<code>libblkid</code>	Contains routines for device identification and token extraction
<code>libfdisk</code>	Contains routines for manipulating partition tables
<code>libmount</code>	Contains routines for block device mounting and unmounting
<code>libsmartcols</code>	Contains routines for aiding screen output in tabular form
<code>libuuid</code>	Contains routines for generating unique identifiers for objects that may be accessible beyond the local system

## 8.81. E2fsprogs-1.47.1

The E2fsprogs package contains the utilities for handling the `ext2` file system. It also supports the `ext3` and `ext4` journaling file systems.

**Approximate build time:** 2.4 SBU on a spinning disk, 0.5 SBU on an SSD

**Required disk space:** 98 MB

### 8.81.1. Installation of E2fsprogs

The E2fsprogs documentation recommends that the package be built in a subdirectory of the source tree:

```
mkdir -v build
cd      build
```

Prepare E2fsprogs for compilation:

```
../configure --prefix=/usr      \
             --sysconfdir=/etc  \
             --enable-elf-shlibs \
             --disable-libblkid \
             --disable-libuuid  \
             --disable-uuidd    \
             --disable-fsck
```

**The meaning of the configure options:**

`--enable-elf-shlibs`

This creates the shared libraries which some programs in this package use.

`--disable-*`

These prevent building and installing the `libuuid` and `libblkid` libraries, the `uuid` daemon, and the `fsck` wrapper; `util-linux` installs more recent versions.

Compile the package:

```
make
```

To run the tests, issue:

```
make check
```

One test named `m_assume_storage_prezeroed` is known to fail.

Install the package:

```
make install
```

Remove useless static libraries:

```
rm -fv /usr/lib/{libcom_err,libe2p,libext2fs,libss}.a
```

This package installs a gzipped `.info` file but doesn't update the system-wide `dir` file. Unzip this file and then update the system `dir` file using the following commands:

```
gunzip -v /usr/share/info/libext2fs.info.gz
install-info --dir-file=/usr/share/info/dir /usr/share/info/libext2fs.info
```

If desired, create and install some additional documentation by issuing the following commands:

```
makeinfo -o      doc/com_err.info ../lib/et/com_err.texinfo
install -v -m644 doc/com_err.info /usr/share/info
install-info --dir-file=/usr/share/info/dir /usr/share/info/com_err.info
```

## 8.81.2. Configuring E2fsprogs

`/etc/mke2fs.conf` contains the default value of various command line options of **mke2fs**. You may edit the file to make the default values suitable for your need. For example, some utilities (not in LFS or BLFS) cannot recognize a `ext4` file system with `metadata_csum_seed` feature enabled. **If** you need such an utility, you may remove the feature from the default `ext4` feature list with the command:

```
sed 's/metadata_csum_seed,/' -i /etc/mke2fs.conf
```

Read the man page `mke2fs.conf(5)` for details.

## 8.81.3. Contents of E2fsprogs

**Installed programs:** badblocks, chatter, compile\_et, debugfs, dumpe2fs, e2freefrag, e2fsck, e2image, e2label, e2mmpstatus, e2scrub, e2scrub\_all, e2undo, e4crypt, e4defrag, filefrag, fsck.ext2, fsck.ext3, fsck.ext4, logsave, lsattr, mk\_cmds, mke2fs, mkfs.ext2, mkfs.ext3, mkfs.ext4, mklost+found, resize2fs, and tune2fs

**Installed libraries:** libcom\_err.so, libe2p.so, libext2fs.so, and libss.so

**Installed directories:** `/usr/include/e2p`, `/usr/include/et`, `/usr/include/ext2fs`, `/usr/include/ss`, `/usr/lib/e2fsprogs`, `/usr/share/et`, and `/usr/share/ss`

## Short Descriptions

<b>badblocks</b>	Searches a device (usually a disk partition) for bad blocks
<b>chattr</b>	Changes the attributes of files on <code>ext{234}</code> file systems
<b>compile_et</b>	An error table compiler; it converts a table of error-code names and messages into a C source file suitable for use with the <code>com_err</code> library
<b>debugfs</b>	A file system debugger; it can be used to examine and change the state of <code>ext{234}</code> file systems
<b>dumpe2fs</b>	Prints the super block and blocks group information for the file system present on a given device
<b>e2freefrag</b>	Reports free space fragmentation information
<b>e2fsck</b>	Is used to check and optionally repair <code>ext{234}</code> file systems
<b>e2image</b>	Is used to save critical <code>ext{234}</code> file system data to a file
<b>e2label</b>	Displays or changes the file system label on the <code>ext{234}</code> file system on a given device
<b>e2mmpstatus</b>	Checks MMP (Multiple Mount Protection) status of an <code>ext4</code> file system
<b>e2scrub</b>	Checks the contents of a mounted <code>ext{234}</code> file system
<b>e2scrub_all</b>	Checks all mounted <code>ext{234}</code> file systems for errors
<b>e2undo</b>	Replays the undo log for an <code>ext{234}</code> file system found on a device. [This can be used to undo a failed operation by an E2fsprogs program.]
<b>e4crypt</b>	<code>Ext4</code> file system encryption utility
<b>e4defrag</b>	Online defragmenter for <code>ext4</code> file systems
<b>filefrag</b>	Reports on how badly fragmented a particular file might be
<b>fsck.ext2</b>	By default checks <code>ext2</code> file systems and is a hard link to <b>e2fsck</b>
<b>fsck.ext3</b>	By default checks <code>ext3</code> file systems and is a hard link to <b>e2fsck</b>
<b>fsck.ext4</b>	By default checks <code>ext4</code> file systems and is a hard link to <b>e2fsck</b>

<b>logsave</b>	Saves the output of a command in a log file
<b>lsattr</b>	Lists the attributes of files on a second extended file system
<b>mk_cmds</b>	Converts a table of command names and help messages into a C source file suitable for use with the <code>libss</code> subsystem library
<b>mke2fs</b>	Creates an <code>ext{234}</code> file system on the given device
<b>mkfs.ext2</b>	By default creates <code>ext2</code> file systems and is a hard link to <b>mke2fs</b>
<b>mkfs.ext3</b>	By default creates <code>ext3</code> file systems and is a hard link to <b>mke2fs</b>
<b>mkfs.ext4</b>	By default creates <code>ext4</code> file systems and is a hard link to <b>mke2fs</b>
<b>mklost+found</b>	Creates a <code>lost+found</code> directory on an <code>ext{234}</code> file system; it pre-allocates disk blocks to this directory to lighten the task of <b>e2fsck</b>
<b>resize2fs</b>	Can be used to enlarge or shrink <code>ext{234}</code> file systems
<b>tune2fs</b>	Adjusts tunable file system parameters on <code>ext{234}</code> file systems
<code>libcom_err</code>	The common error display routine
<code>libe2p</code>	Used by <b>dumpe2fs</b> , <b>chattr</b> , and <b>lsattr</b>
<code>libext2fs</code>	Contains routines to enable user-level programs to manipulate <code>ext{234}</code> file systems
<code>libss</code>	Used by <b>debugfs</b>

## 8.82. About Debugging Symbols

Most programs and libraries are, by default, compiled with debugging symbols included (with `gcc`'s `-g` option). This means that when debugging a program or library that was compiled with debugging information, the debugger can provide not only memory addresses, but also the names of the routines and variables.

The inclusion of these debugging symbols enlarges a program or library significantly. Here are two examples of the amount of space these symbols occupy:

- A **bash** binary with debugging symbols: 1200 KB
- A **bash** binary without debugging symbols: 480 KB (60% smaller)
- Glibc and GCC files (`/lib` and `/usr/lib`) with debugging symbols: 87 MB
- Glibc and GCC files without debugging symbols: 16 MB (82% smaller)

Sizes will vary depending on which compiler and C library were used, but a program that has been stripped of debugging symbols is usually some 50% to 80% smaller than its unstripped counterpart. Because most users will never use a debugger on their system software, a lot of disk space can be regained by removing these symbols. The next section shows how to strip all debugging symbols from the programs and libraries.

## 8.83. Stripping

This section is optional. If the intended user is not a programmer and does not plan to do any debugging of the system software, the system's size can be decreased by some 2 GB by removing the debugging symbols, and some unnecessary symbol table entries, from binaries and libraries. This causes no real inconvenience for a typical Linux user.

Most people who use the commands mentioned below do not experience any difficulties. However, it is easy to make a mistake and render the new system unusable. So before running the **strip** commands, it is a good idea to make a backup of the LFS system in its current state.

A **strip** command with the `--strip-unneeded` option removes all debug symbols from a binary or library. It also removes all symbol table entries not needed by the linker (for static libraries) or dynamic linker (for dynamically linked binaries and shared libraries).

The debugging symbols from selected libraries are compressed with Zlib and preserved in separate files. That debugging information is needed to run regression tests with *valgrind* or *gdb* later, in BLFS.

Note that **strip** will overwrite the binary or library file it is processing. This can crash the processes using code or data from the file. If the process running **strip** is affected, the binary or library being stripped can be destroyed; this can make the system completely unusable. To avoid this problem we copy some libraries and binaries into `/tmp`, strip them there, then reinstall them with the **install** command. (The related entry in Section 8.2.1, “Upgrade Issues” gives the rationale for using the **install** command here.)



### Note

The ELF loader's name is `ld-linux-x86-64.so.2` on 64-bit systems and `ld-linux.so.2` on 32-bit systems. The construct below selects the correct name for the current architecture, excluding anything ending with `_g`, in case the commands below have already been run.

**Important**

If there is any package whose version is different from the version specified by the book (either following a security advisory or satisfying personal preference), it may be necessary to update the library file name in `save_usrlib` or `online_usrlib`. **Failing to do so may render the system completely unusable.**

```
save_usrlib="$(cd /usr/lib; ls ld-linux*[^g])
    libc.so.6
    libthread_db.so.1
    libquadmath.so.0.0.0
    libstdc++.so.6.0.33
    libitm.so.1.0.0
    libatomic.so.1.2.0"

cd /usr/lib

for LIB in $save_usrlib; do
    objcopy --only-keep-debug --compress-debug-sections=zlib $LIB $LIB.dbg
    cp $LIB /tmp/$LIB
    strip --strip-unnneeded /tmp/$LIB
    objcopy --add-gnu-debuglink=$LIB.dbg /tmp/$LIB
    install -vm755 /tmp/$LIB /usr/lib
    rm /tmp/$LIB
done

online_usrbin="bash find strip"
online_usrlib="libbfd-2.43.1.so
    libframe.so.1.0.0
    libhistory.so.8.2
    libncursesw.so.6.5
    libm.so.6
    libreadline.so.8.2
    libz.so.1.3.1
    libzstd.so.1.5.6
    $(cd /usr/lib; find libnss*.so* -type f)"

for BIN in $online_usrbin; do
    cp /usr/bin/$BIN /tmp/$BIN
    strip --strip-unnneeded /tmp/$BIN
    install -vm755 /tmp/$BIN /usr/bin
    rm /tmp/$BIN
done

for LIB in $online_usrlib; do
    cp /usr/lib/$LIB /tmp/$LIB
    strip --strip-unnneeded /tmp/$LIB
    install -vm755 /tmp/$LIB /usr/lib
    rm /tmp/$LIB
done

for i in $(find /usr/lib -type f -name \*.so* ! -name \*dbg) \
    $(find /usr/lib -type f -name \*.a) \
    $(find /usr/{bin,sbin,libexec} -type f); do
    case "$online_usrbin $online_usrlib $save_usrlib" in
        *$(basename $i)* )
            ;;
        * ) strip --strip-unnneeded $i
            ;;
    esac
done

unset BIN LIB save_usrlib online_usrbin online_usrlib
```



A large number of files will be flagged as errors because their file format is not recognized. These warnings can be safely ignored. They indicate that those files are scripts, not binaries.

## 8.84. Cleaning Up

Finally, clean up some extra files left over from running tests:

```
rm -rf /tmp/{*,.*}
```

There are also several files in the `/usr/lib` and `/usr/libexec` directories with a file name extension of `.la`. These are "libtool archive" files. On a modern Linux system the libtool `.la` files are only useful for `libltdl`. No libraries in LFS are expected to be loaded by `libltdl`, and it's known that some `.la` files can break BLFS package builds. Remove those files now:

```
find /usr/lib /usr/libexec -name \*.la -delete
```

For more information about libtool archive files, see the *BLFS section "About Libtool Archive (.la) files"*.

The compiler built in Chapter 6 and Chapter 7 is still partially installed and not needed anymore. Remove it with:

```
find /usr -depth -name $(uname -m)-lfs-linux-gnu\* | xargs rm -rf
```

Finally, remove the temporary 'tester' user account created at the beginning of the previous chapter.

```
userdel -r tester
```

# Chapter 9. System Configuration

## 9.1. Introduction

This chapter discusses configuration files and systemd services. First, the general configuration files needed to set up networking are presented.

- Section 9.2, “General Network Configuration.”
- Section 9.2.3, “Configuring the system hostname.”
- Section 9.2.4, “Customizing the `/etc/hosts` File.”

Second, issues that affect the proper setup of devices are discussed.

- Section 9.3, “Overview of Device and Module Handling.”
- Section 9.4, “Managing Devices.”

Third, configuring the system clock and keyboard layout is shown.

- Section 9.5, “Configuring the System Clock.”
- Section 9.6, “Configuring the Linux Console.”

Fourth, a brief introduction to the scripts and configuration files used when the user logs into the system is presented.

- Section 9.7, “Configuring the System Locale.”
- Section 9.8, “Creating the `/etc/inputrc` File.”

And finally, configuring the behavior of systemd is discussed.

- Section 9.10, “Systemd Usage and Configuration.”

## 9.2. General Network Configuration

This section only applies if a network card is to be configured.

### 9.2.1. Network Interface Configuration Files

Starting with version 209, systemd ships a network configuration daemon called **systemd-networkd** which can be used for basic network configuration. Additionally, since version 213, DNS name resolution can be handled by **systemd-resolved** in place of a static `/etc/resolv.conf` file. Both services are enabled by default.



#### Note

If you will not use **systemd-networkd** for network configuration (for example, when the system is not connected to network, or you want to use another utility like NetworkManager for network configuration), disable a service to prevent an error message during boot:

```
systemctl disable systemd-networkd-wait-online
```

Configuration files for **systemd-networkd** (and **systemd-resolved**) can be placed in `/usr/lib/systemd/network` or `/etc/systemd/network`. Files in `/etc/systemd/network` have a higher priority than the ones in `/usr/lib/systemd/network`. There are three types of configuration files: `.link`, `.netdev` and `.network` files. For detailed descriptions and example contents of these configuration files, consult the `systemd.link(5)`, `systemd.netdev(5)`, and `systemd.network(5)` manual pages.

### 9.2.1.1. Network Device Naming

Udev normally assigns network card interface names based on physical system characteristics such as `enp2s1`. If you are not sure what your interface name is, you can always run **ip link** after you have booted your system.



#### Note

The interface names depend on the implementation and configuration of the udev daemon running on the system. The udev daemon for LFS (**systemd-udev**, installed in Section 8.76, “Systemd-256.4”) will not run unless the LFS system is booted. So it's unreliable to determine the interface names being used in LFS system by running those commands on the host distro, *even though you are in the chroot environment*.

For most systems, there is only one network interface for each type of connection. For example, the classic interface name for a wired connection is `eth0`. A wireless connection will usually have the name `wifi0` or `wlan0`.

If you prefer to use the classic or customized network interface names, there are three alternative ways to do that:

- Mask udev's `.link` file for the default policy:

```
ln -s /dev/null /etc/systemd/network/99-default.link
```

- Create a manual naming scheme, for example by naming the interfaces something like `internet0`, `dmz0`, or `lan0`. To do that, create `.link` files in `/etc/systemd/network/` that select an explicit name or a better naming scheme for your network interfaces. For example:

```
cat > /etc/systemd/network/10-ether0.link << "EOF"
[Match]
# Change the MAC address as appropriate for your network device
MACAddress=12:34:45:78:90:AB

[Link]
Name=ether0
EOF
```

See `systemd.link(5)` for more information.

- In `/boot/grub/grub.cfg`, pass the option `net.ifnames=0` on the kernel command line.

### 9.2.1.2. Static IP Configuration

The command below creates a basic configuration file for a Static IP setup (using both `systemd-networkd` and `systemd-resolved`):

```
cat > /etc/systemd/network/10-eth-static.network << "EOF"
[Match]
Name=<network-device-name>

[Network]
Address=192.168.0.2/24
Gateway=192.168.0.1
DNS=192.168.0.1
Domains=<Your Domain Name>
EOF
```

Multiple DNS entries can be added if you have more than one DNS server. Do not include DNS or Domains entries if you intend to use a static `/etc/resolv.conf` file.

### 9.2.1.3. DHCP Configuration

The command below creates a basic configuration file for an IPv4 DHCP setup:

```
cat > /etc/systemd/network/10-eth-dhcp.network << "EOF"
[Match]
Name=<network-device-name>

[Network]
DHCP=ipv4

[DHCPv4]
UseDomains=true
EOF
```

## 9.2.2. Creating the /etc/resolv.conf File

If the system is going to be connected to the Internet, it will need some means of Domain Name Service (DNS) name resolution to resolve Internet domain names to IP addresses, and vice versa. This is best achieved by placing the IP address of the DNS server, available from the ISP or network administrator, into `/etc/resolv.conf`.

### 9.2.2.1. systemd-resolved Configuration



#### Note

If using methods incompatible with `systemd-resolved` to configure your network interfaces (ex: `ppp`, etc.), or if using any type of local resolver (ex: `bind`, `dnsmasq`, `unbound`, etc.), or any other software that generates an `/etc/resolv.conf` (ex: a **resolvconf** program other than the one provided by `systemd`), the **systemd-resolved** service should not be used.

To disable `systemd-resolved`, issue the following command:

```
systemctl disable systemd-resolved
```

When using **systemd-resolved** for DNS configuration, it creates the file `/run/systemd/resolve/stub-resolv.conf`. And, if `/etc/resolv.conf` does not exist, it will be created by **systemd-resolved** as a symlink to `/run/systemd/resolve/stub-resolv.conf`. So it's unnecessary to create a `/etc/resolv.conf` manually.

### 9.2.2.2. Static resolv.conf Configuration

If a static `/etc/resolv.conf` is desired, create it by running the following command:

```
cat > /etc/resolv.conf << "EOF"
# Begin /etc/resolv.conf

domain <Your Domain Name>
nameserver <IP address of your primary nameserver>
nameserver <IP address of your secondary nameserver>

# End /etc/resolv.conf
EOF
```

The `domain` statement can be omitted or replaced with a `search` statement. See the man page for `resolv.conf` for more details.

Replace *<IP address of the nameserver>* with the IP address of the DNS server most appropriate for your setup. There will often be more than one entry (requirements demand secondary servers for fallback capability). If you only need or want one DNS server, remove the second *nameserver* line from the file. The IP address may also be a router on the local network. Another option is to use the Google Public DNS service using the IP addresses below as nameservers.



### Note

The Google Public IPv4 DNS addresses are *8.8.8.8* and *8.8.4.4* for IPv4, and *2001:4860:4860::8888* and *2001:4860:4860::8844* for IPv6.

## 9.2.3. Configuring the system hostname

During the boot process, the file `/etc/hostname` is used for establishing the system's hostname.

Create the `/etc/hostname` file and enter a hostname by running:

```
echo "<lfs>" > /etc/hostname
```

*<lfs>* needs to be replaced with the name given to the computer. Do not enter the Fully Qualified Domain Name (FQDN) here. That information is put in the `/etc/hosts` file.

## 9.2.4. Customizing the `/etc/hosts` File

Decide on a fully-qualified domain name (FQDN), and possible aliases for use in the `/etc/hosts` file. If using static IP addresses, you'll also need to decide on an IP address. The syntax for a hosts file entry is:

```
IP_address myhost.example.org aliases
```

Unless the computer is to be visible to the Internet (i.e., there is a registered domain and a valid block of assigned IP addresses—most users do not have this), make sure that the IP address is in the private network IP address range. Valid ranges are:

Private Network Address Range	Normal Prefix
10.0.0.1 - 10.255.255.254	8
172.x.0.1 - 172.x.255.254	16
192.168.y.1 - 192.168.y.254	24

x can be any number in the range 16-31. y can be any number in the range 0-255.

A valid private IP address could be 192.168.1.1.

If the computer is to be visible to the Internet, a valid FQDN can be the domain name itself, or a string resulted by concatenating a prefix (often the hostname) and the domain name with a “.” character. And, you need to contact the domain provider to resolve the FQDN to your public IP address.

Even if the computer is not visible to the Internet, a FQDN is still needed for certain programs, such as MTAs, to operate properly. A special FQDN, `localhost.localdomain`, can be used for this purpose.

Create the `/etc/hosts` file using the following command:

```
cat > /etc/hosts << "EOF"
# Begin /etc/hosts

<192.168.0.2> <FQDN> [alias1] [alias2] ...
::1          ip6-localhost ip6-loopback
ff02::1     ip6-allnodes
ff02::2     ip6-allrouters

# End /etc/hosts
EOF
```

The `<192.168.0.2>` and `<FQDN>` values need to be changed for specific uses or requirements (if assigned an IP address by a network/system administrator and the machine will be connected to an existing network). The optional alias name(s) can be omitted, and the `<192.168.0.2>` line can be omitted if you are using a connection configured with DHCP or IPv6 Autoconfiguration, or using `localhost.localdomain` as the FQDN.

The `/etc/hostname` does not contain entries for `localhost`, `localhost.localdomain`, or the `hostname` (without a domain) because they are handled by the `myhostname` NSS module, read the man page `nss-myhostname(8)` for details.

The `::1` entry is the IPv6 counterpart of 127.0.0.1 and represents the IPv6 loopback interface.

## 9.3. Overview of Device and Module Handling

In Chapter 8, we installed the `udev` daemon when `systemd` was built. Before we go into the details regarding how `udev` works, a brief history of previous methods of handling devices is in order.

Linux systems in general traditionally used a static device creation method, whereby a great many device nodes were created under `/dev` (sometimes literally thousands of nodes), regardless of whether the corresponding hardware devices actually existed. This was typically done via a **MAKEDEV** script, which contained a number of calls to the **mknod** program with the relevant major and minor device numbers for every possible device that might exist in the world.

Using the `udev` method, device nodes are only created for those devices which are detected by the kernel. These device nodes are created each time the system boots; they are stored in a `devtmpfs` file system (a virtual file system that resides entirely in system memory). Device nodes do not require much space, so the memory that is used is negligible.

### 9.3.1. History

In February 2000, a new filesystem called `devfs` was merged into the 2.3.46 kernel and was made available during the 2.4 series of stable kernels. Although it was present in the kernel source itself, this method of creating devices dynamically never received overwhelming support from the core kernel developers.

The main problem with the approach adopted by `devfs` was the way it handled device detection, creation, and naming. The latter issue, that of device node naming, was perhaps the most critical. It is generally accepted that if device names are configurable, the device naming policy should be chosen by system administrators, and not imposed on them by the developer(s). The `devfs` file system also suffered from race conditions that were inherent in its design; these could not be fixed without a substantial revision of the kernel. `devfs` was marked as deprecated for a long time, and was finally removed from the kernel in June, 2006.

With the development of the unstable 2.5 kernel tree, later released as the 2.6 series of stable kernels, a new virtual filesystem called `sysfs` came to be. The job of `sysfs` is to provide information about the system's hardware configuration to userspace processes. With this userspace-visible representation, it became possible to develop a userspace replacement for `devfs`.

### 9.3.2. Udev Implementation

#### 9.3.2.1. Sysfs

The `sysfs` filesystem was mentioned briefly above. One may wonder how `sysfs` knows about the devices present on a system and what device numbers should be used for them. Drivers that have been compiled into the kernel register their objects in `sysfs` (`devtmpfs` internally) as they are detected by the kernel. For drivers compiled as modules, registration happens when the module is loaded. Once the `sysfs` filesystem is mounted (on `/sys`), data which the drivers have registered with `sysfs` are available to userspace processes and to `udev`d for processing (including modifications to device nodes).

### 9.3.2.2. Device Node Creation

Device files are created by the kernel in the `devtmpfs` file system. Any driver that wishes to register a device node will use the `devtmpfs` (via the driver core) to do it. When a `devtmpfs` instance is mounted on `/dev`, the device node will initially be exposed to userspace with a fixed name, permissions, and owner.

A short time later, the kernel will send a uevent to **udev**. Based on the rules specified in the files within the `/etc/udev/rules.d`, `/usr/lib/udev/rules.d`, and `/run/udev/rules.d` directories, **udev** will create additional symlinks to the device node, or change its permissions, owner, or group, or modify the internal **udev** database entry (name) for that object.

The rules in these three directories are numbered and all three directories are merged together. If **udev** can't find a rule for the device it is creating, it will leave the permissions and ownership at whatever `devtmpfs` used initially.

### 9.3.2.3. Module Loading

Device drivers compiled as modules may have aliases built into them. Aliases are visible in the output of the **modinfo** program and are usually related to the bus-specific identifiers of devices supported by a module. For example, the `snd-fm801` driver supports PCI devices with vendor ID `0x1319` and device ID `0x0801`, and has an alias of `pci:v00001319d00000801sv*sd*bc04sc01i*`. For most devices, the bus driver exports the alias of the driver that would handle the device via `sysfs`. E.g., the `/sys/bus/pci/devices/0000:00:0d.0/modalias` file might contain the string `pci:v00001319d00000801sv00001319sd00001319bc04sc01i00`. The default rules provided with `udev` will cause **udev** to call out to `/sbin/modprobe` with the contents of the `MODALIAS` uevent environment variable (which should be the same as the contents of the `modalias` file in `sysfs`), thus loading all modules whose aliases match this string after wildcard expansion.

In this example, this means that, in addition to `snd-fm801`, the obsolete (and unwanted) `forte` driver will be loaded if it is available. See below for ways in which the loading of unwanted drivers can be prevented.

The kernel itself is also able to load modules for network protocols, filesystems, and NLS support on demand.

### 9.3.2.4. Handling Hotpluggable/Dynamic Devices

When you plug in a device, such as a Universal Serial Bus (USB) MP3 player, the kernel recognizes that the device is now connected and generates a uevent. This uevent is then handled by **udev** as described above.

## 9.3.3. Problems with Loading Modules and Creating Devices

There are a few possible problems when it comes to automatically creating device nodes.

### 9.3.3.1. A Kernel Module Is Not Loaded Automatically

`Udev` will only load a module if it has a bus-specific alias and the bus driver properly exports the necessary aliases to `sysfs`. In other cases, one should arrange module loading by other means. With Linux-6.10.5, `udev` is known to load properly-written drivers for `INPUT`, `IDE`, `PCI`, `USB`, `SCSI`, `SERIO`, and `FireWire` devices.

To determine if the device driver you require has the necessary support for `udev`, run **modinfo** with the module name as the argument. Now try locating the device directory under `/sys/bus` and check whether there is a `modalias` file there.

If the `modalias` file exists in `sysfs`, the driver supports the device and can talk to it directly, but doesn't have the alias, it is a bug in the driver. Load the driver without the help from `udev` and expect the issue to be fixed later.

If there is no `modalias` file in the relevant directory under `/sys/bus`, this means that the kernel developers have not yet added `modalias` support to this bus type. With Linux-6.10.5, this is the case with ISA busses. Expect this issue to be fixed in later kernel versions.

Udev is not intended to load “wrapper” drivers such as *snd-pcm-oss* and non-hardware drivers such as *loop* at all.

### 9.3.3.2. A Kernel Module Is Not Loaded Automatically, and Udev Is Not Intended to Load It

If the “wrapper” module only enhances the functionality provided by some other module (e.g., *snd-pcm-oss* enhances the functionality of *snd-pcm* by making the sound cards available to OSS applications), configure **modprobe** to load the wrapper after udev loads the wrapped module. To do this, add a “softdep” line to the corresponding `/etc/modprobe.d/<filename>.conf` file. For example:

```
softdep snd-pcm post: snd-pcm-oss
```

Note that the “softdep” command also allows `pre:` dependencies, or a mixture of both `pre:` and `post:` dependencies. See the *modprobe.d(5)* manual page for more information on “softdep” syntax and capabilities.

### 9.3.3.3. Udev Loads Some Unwanted Module

Either don't build the module, or blacklist it in a `/etc/modprobe.d/blacklist.conf` file as done with the *forte* module in the example below:

```
blacklist forte
```

Blacklisted modules can still be loaded manually with the explicit **modprobe** command.

### 9.3.3.4. Udev Creates a Device Incorrectly, or Makes the Wrong Symlink

This usually happens if a rule unexpectedly matches a device. For example, a poorly-written rule can match both a SCSI disk (as desired) and the corresponding SCSI generic device (incorrectly) by vendor. Find the offending rule and make it more specific, with the help of the **udevadm info** command.

### 9.3.3.5. Udev Rule Works Unreliably

This may be another manifestation of the previous problem. If not, and your rule uses `sysfs` attributes, it may be a kernel timing issue, to be fixed in later kernels. For now, you can work around it by creating a rule that waits for the used `sysfs` attribute and appending it to the `/etc/udev/rules.d/10-wait_for_sysfs.rules` file (create this file if it does not exist). Please notify the LFS Development list if you do so and it helps.

### 9.3.3.6. Udev Does Not Create a Device

First, be certain that the driver is built into the kernel or already loaded as a module, and that udev isn't creating a misnamed device.

If a kernel driver does not export its data to `sysfs`, udev lacks the information needed to create a device node. This is most likely to happen with third party drivers from outside the kernel tree. Create a static device node in `/usr/lib/udev/devices` with the appropriate major/minor numbers (see the file `devices.txt` inside the kernel documentation or the documentation provided by the third party driver vendor). The static device node will be copied to `/dev` by **udev**.

### 9.3.3.7. Device Naming Order Changes Randomly After Rebooting

This is due to the fact that udev, by design, handles uevents and loads modules in parallel, and thus in an unpredictable order. This will never be “fixed.” You should not rely upon the kernel device names being stable. Instead, create your own rules that make symlinks with stable names based on some stable attributes of the device, such as a serial number or the output of various `*_id` utilities installed by udev. See Section 9.4, “Managing Devices” and Section 9.2, “General Network Configuration” for examples.



### 9.3.4. Useful Reading

Additional helpful documentation is available at the following sites:

- A Userspace Implementation of `devfs` [http://www.kroah.com/linux/talks/ols\\_2003\\_udev\\_paper/Reprint-Kroah-Hartman-OLS2003.pdf](http://www.kroah.com/linux/talks/ols_2003_udev_paper/Reprint-Kroah-Hartman-OLS2003.pdf)
- The `sysfs` Filesystem <https://www.kernel.org/pub/linux/kernel/people/mochel/doc/papers/ols-2005/mochel.pdf>

## 9.4. Managing Devices

### 9.4.1. Dealing with Duplicate Devices

As explained in Section 9.3, “Overview of Device and Module Handling,” the order in which devices with the same function appear in `/dev` is essentially random. E.g., if you have a USB web camera and a TV tuner, sometimes `/dev/video0` refers to the camera and `/dev/video1` refers to the tuner, and sometimes after a reboot the order changes. For all classes of hardware except sound cards and network cards, this is fixable by creating udev rules to create persistent symlinks. The case of network cards is covered separately in Section 9.2, “General Network Configuration,” and sound card configuration can be found in *BLFS*.

For each of your devices that is likely to have this problem (even if the problem doesn't exist in your current Linux distribution), find the corresponding directory under `/sys/class` or `/sys/block`. For video devices, this may be `/sys/class/video4linux/videoX`. Figure out the attributes that identify the device uniquely (usually, vendor and product IDs and/or serial numbers work):

```
udevadm info -a -p /sys/class/video4linux/video0
```

Then write rules that create the symlinks, e.g.:

```
cat > /etc/udev/rules.d/83-duplicate_devs.rules << "EOF"

# Persistent symlinks for webcam and tuner
KERNEL=="video*", ATTRS{idProduct}=="1910", ATTRS{idVendor}=="0d81", SYMLINK+="webcam"
KERNEL=="video*", ATTRS{device}=="0x036f", ATTRS{vendor}=="0x109e", SYMLINK+="tvtuner"

EOF
```

The result is that `/dev/video0` and `/dev/video1` devices still refer randomly to the tuner and the web camera (and thus should never be used directly), but there are symlinks `/dev/tvtuner` and `/dev/webcam` that always point to the correct device.

## 9.5. Configuring the System Clock

This section discusses how to configure the **systemd-timedated** system service, which configures the system clock and timezone.

If you cannot remember whether or not the hardware clock is set to UTC, find out by running the `hwclock --localtime --show` command. This will display what the current time is according to the hardware clock. If this time matches whatever your watch says, then the hardware clock is set to local time. If the output from **hwclock** is not local time, chances are it is set to UTC time. Verify this by adding or subtracting the proper amount of hours for the timezone to the time shown by **hwclock**. For example, if you are currently in the MST timezone, which is also known as GMT -0700, add seven hours to the local time.

**systemd-timedated** reads `/etc/adjtime`, and depending on the contents of the file, sets the clock to either UTC or local time.

Create the `/etc/adjtime` file with the following contents if your hardware clock is set to local time:

```
cat > /etc/adjtime << "EOF"
0.0 0 0.0
0
LOCAL
EOF
```

If `/etc/adjtime` isn't present at first boot, **systemd-timedated** will assume that hardware clock is set to UTC and adjust the file according to that.

You can also use the **timedatectl** utility to tell **systemd-timedated** if your hardware clock is set to UTC or local time:

```
timedatectl set-local-rtc 1
```

**timedatectl** can also be used to change system time and time zone.

To change your current system time, issue:

```
timedatectl set-time YYYY-MM-DD HH:MM:SS
```

The hardware clock will also be updated accordingly.

To change your current time zone, issue:

```
timedatectl set-timezone TIMEZONE
```

You can get a list of available time zones by running:

```
timedatectl list-timezones
```



### Note

Please note that the **timedatectl** command doesn't work in the chroot environment. It can only be used after the LFS system is booted with systemd.

## 9.5.1. Network Time Synchronization

Starting with version 213, systemd ships a daemon called **systemd-timesyncd** which can be used to synchronize the system time with remote NTP servers.

The daemon is not intended as a replacement for the well established NTP daemon, but as a client only implementation of the SNTP protocol which can be used for less advanced tasks and on resource limited systems.

Starting with systemd version 216, the **systemd-timesyncd** daemon is enabled by default. If you want to disable it, issue the following command:

```
systemctl disable systemd-timesyncd
```

The `/etc/systemd/timesyncd.conf` file can be used to change the NTP servers that **systemd-timesyncd** synchronizes with.

Please note that when system clock is set to Local Time, **systemd-timesyncd** won't update hardware clock.

## 9.6. Configuring the Linux Console

This section discusses how to configure the **systemd-vconsole-setup** system service, which configures the virtual console font and console keymap.

The **systemd-vconsole-setup** service reads the `/etc/vconsole.conf` file for configuration information. Decide which keymap and screen font will be used. Various language-specific HOWTOs can also help with this, see <https://tldp.org/HOWTO/HOWTO-INDEX/other-lang.html>. Examine the output of **localectl list-keymaps** for a list of valid console keymaps. Look in the `/usr/share/consolefonts` directory for valid screen fonts.

The `/etc/vconsole.conf` file should contain lines of the form: `VARIABLE=value`. The following variables are recognized:

#### KEYMAP

This variable specifies the key mapping table for the keyboard. If unset, it defaults to `us`.

#### KEYMAP\_TOGGLE

This variable can be used to configure a second toggle keymap and is unset by default.

#### FONT

This variable specifies the font used by the virtual console.

#### FONT\_MAP

This variable specifies the console map to be used.

#### FONT\_UNIMAP

This variable specifies the Unicode font map.

We'll use `C.UTF-8` as the locale for interactive sessions in the Linux console in Section 9.7, “Configuring the System Locale.” The console fonts shipped by the `Kbd` package containing the glyphs for all characters from the program messages in the `C.UTF-8` locale are `LatArCyrHeb*.psfu.gz`, `LatGrkCyr*.psfu.gz`, `Lat2-Terminus16.psfu.gz`, and `pancyrillic.f16.psfu.gz` in `/usr/share/consolefonts` (the other shipped console fonts lack glyphs of some characters like the Unicode left/right quotation marks and the Unicode English dash). So set one of them, for example `Lat2-Terminus16.psfu.gz` as the default console font:

```
echo FONT=Lat2-Terminus16 > /etc/vconsole.conf
```

An example for a German keyboard and console is given below:

```
cat > /etc/vconsole.conf << "EOF"
KEYMAP=de-latin1
FONT=Lat2-Terminus16
EOF
```

You can change `KEYMAP` value at runtime by using the **localectl** utility:

```
localectl set-keymap MAP
```



#### Note

Please note that the **localectl** command doesn't work in the `chroot` environment. It can only be used after the `LFS` system is booted with `systemd`.

You can also use **localectl** utility with the corresponding parameters to change X11 keyboard layout, model, variant and options:

```
localectl set-x11-keymap LAYOUT [MODEL] [VARIANT] [OPTIONS]
```

To list possible values for **localectl set-x11-keymap** parameters, run **localectl** with parameters listed below:

`list-x11-keymap-models`

Shows known X11 keyboard mapping models.

`list-x11-keymap-layouts`

Shows known X11 keyboard mapping layouts.

`list-x11-keymap-variants`

Shows known X11 keyboard mapping variants.

`list-x11-keymap-options`

Shows known X11 keyboard mapping options.



### Note

Using any of the parameters listed above requires the XKeyboard-Config package from BLFS.

## 9.7. Configuring the System Locale

Some environment variables are necessary for native language support. Setting them properly results in:

- The output of programs being translated into your native language
- The correct classification of characters into letters, digits and other classes. This is necessary for **bash** to properly accept non-ASCII characters in command lines in non-English locales
- The correct alphabetical sorting order for the country
- The appropriate default paper size
- The correct formatting of monetary, time, and date values

Replace `<ll>` below with the two-letter code for your desired language (e.g., `en`) and `<cc>` with the two-letter code for the appropriate country (e.g., `GB`). `<charmap>` should be replaced with the canonical charmap for your chosen locale. Optional modifiers such as `@euro` may also be present.

The list of all locales supported by Glibc can be obtained by running the following command:

```
locale -a
```

Charmaps can have a number of aliases, e.g., `ISO-8859-1` is also referred to as `iso8859-1` and `iso88591`. Some applications cannot handle the various synonyms correctly (e.g., require that `UTF-8` is written as `UTF-8`, not `utf8`), so it is the safest in most cases to choose the canonical name for a particular locale. To determine the canonical name, run the following command, where `<locale name>` is the output given by **locale -a** for your preferred locale (`en_GB.iso88591` in our example).

```
LC_ALL=<locale name> locale charmap
```

For the `en_GB.iso88591` locale, the above command will print:

```
ISO-8859-1
```

This results in a final locale setting of `en_GB.ISO-8859-1`. It is important that the locale found using the heuristic above is tested prior to it being added to the Bash startup files:

```
LC_ALL=<locale name> locale language
LC_ALL=<locale name> locale charmap
LC_ALL=<locale name> locale int_curr_symbol
LC_ALL=<locale name> locale int_prefix
```

The above commands should print the language name, the character encoding used by the locale, the local currency, and the prefix to dial before the telephone number in order to get into the country. If any of the commands above fail with a message similar to the one shown below, this means that your locale was either not installed in Chapter 8 or is not supported by the default installation of Glibc.

```
locale: Cannot set LC_* to default locale: No such file or directory
```

If this happens, you should either install the desired locale using the **localedef** command, or consider choosing a different locale. Further instructions assume that there are no such error messages from Glibc.

Other packages can also function incorrectly (but may not necessarily display any error messages) if the locale name does not meet their expectations. In those cases, investigating how other Linux distributions support your locale might provide some useful information.

Once the proper locale settings have been determined, create the `/etc/locale.conf` file:

```
cat > /etc/locale.conf << "EOF"
LANG=<ll>_<CC>.<charmap><@modifiers>
EOF
```

The shell program **/bin/bash** (here after referred as “the shell”) uses a collection of startup files to help create the environment to run in. Each file has a specific use and may affect login and interactive environments differently. The files in the `/etc` directory provide global settings. If equivalent files exist in the home directory, they may override the global settings.

An interactive login shell is started after a successful login, using **/bin/login**, by reading the `/etc/passwd` file. An interactive non-login shell is started at the command-line (e.g. `[prompt]$/bin/bash`). A non-interactive shell is usually present when a shell script is running. It is non-interactive because it is processing a script and not waiting for user input between commands.

The login shells are often unaffected by the settings in `/etc/locale.conf`. Create the `/etc/profile` to read the locale settings from `/etc/locale.conf` and export them, but set the `C.UTF-8` locale instead if running in the Linux console (to prevent programs from outputting characters that the Linux console is unable to render):

```
cat > /etc/profile << "EOF"
# Begin /etc/profile

for i in $(locale); do
    unset ${i%=*}
done

if [[ "$TERM" = linux ]]; then
    export LANG=C.UTF-8
else
    source /etc/locale.conf

    for i in $(locale); do
        key=${i%=*}
        if [[ -v $key ]]; then
            export $key
        fi
    done
fi

# End /etc/profile
EOF
```

Note that you can modify `/etc/locale.conf` with the systemd **localectl** utility. To use **localectl** for the example above, run:

```
localectl set-locale LANG="<ll>_<CC>.<charmap><@modifiers>"
```

You can also specify other language specific environment variables such as `LANG`, `LC_CTYPE`, `LC_NUMERIC` or any other environment variable from **locale** output. Just separate them with a space. An example where `LANG` is set as `en_US.UTF-8` but `LC_CTYPE` is set as just `en_US` is:

```
localectl set-locale LANG="en_US.UTF-8" LC_CTYPE="en_US"
```

**Note**

Please note that the **localectl** command doesn't work in the chroot environment. It can only be used after the LFS system is booted with systemd.

The `c` (default) and `en_US` (the recommended one for United States English users) locales are different. `c` uses the US-ASCII 7-bit character set, and treats bytes with the high bit set as invalid characters. That's why, e.g., the `ls` command substitutes them with question marks in that locale. Also, an attempt to send mail with such characters from Mutt or Pine results in non-RFC-conforming messages being sent (the charset in the outgoing mail is indicated as `unknown 8-bit`). It's suggested that you use the `c` locale only if you are certain that you will never need 8-bit characters.

## 9.8. Creating the `/etc/inputrc` File

The `inputrc` file is the configuration file for the readline library, which provides editing capabilities while the user is entering a line from the terminal. It works by translating keyboard inputs into specific actions. Readline is used by bash and most other shells as well as many other applications.

Most people do not need user-specific functionality so the command below creates a global `/etc/inputrc` used by everyone who logs in. If you later decide you need to override the defaults on a per user basis, you can create a `.inputrc` file in the user's home directory with the modified mappings.

For more information on how to edit the `inputrc` file, see **info bash** under the *Readline Init File* section. **info readline** is also a good source of information.

Below is a generic global `inputrc` along with comments to explain what the various options do. Note that comments cannot be on the same line as commands. Create the file using the following command:

```
cat > /etc/inputrc << "EOF"
# Begin /etc/inputrc
# Modified by Chris Lynn <roryo@roryo.dynup.net>

# Allow the command prompt to wrap to the next line
set horizontal-scroll-mode Off

# Enable 8-bit input
set meta-flag On
set input-meta On

# Turns off 8th bit stripping
set convert-meta Off

# Keep the 8th bit for display
set output-meta On

# none, visible or audible
set bell-style none

# All of the following map the escape sequence of the value
# contained in the 1st argument to the readline specific functions
"\eOd": backward-word
"\eOc": forward-word

# for linux console
"\e[1~": beginning-of-line
"\e[4~": end-of-line
"\e[5~": beginning-of-history
"\e[6~": end-of-history
"\e[3~": delete-char
"\e[2~": quoted-insert

# for xterm
"\eOH": beginning-of-line
"\eOF": end-of-line

# for Konsole
"\e[H": beginning-of-line
"\e[F": end-of-line

# End /etc/inputrc
EOF
```

## 9.9. Creating the `/etc/shells` File

The `shells` file contains a list of login shells on the system. Applications use this file to determine whether a shell is valid. For each shell a single line should be present, consisting of the shell's path relative to the root of the directory structure (`/`).

For example, this file is consulted by `chsh` to determine whether an unprivileged user may change the login shell for her own account. If the command name is not listed, the user will be denied the ability to change shells.

It is a requirement for applications such as GDM which does not populate the face browser if it can't find `/etc/shells`, or FTP daemons which traditionally disallow access to users with shells not included in this file.

```
cat > /etc/shells << "EOF"
# Begin /etc/shells

/bin/sh
/bin/bash

# End /etc/shells
EOF
```

## 9.10. Systemd Usage and Configuration

### 9.10.1. Basic Configuration

The `/etc/systemd/system.conf` file contains a set of options to control basic systemd operations. The default file has all entries commented out with the default settings indicated. This file is where the log level may be changed as well as some basic logging settings. See the `systemd-system.conf(5)` manual page for details on each configuration option.

### 9.10.2. Disabling Screen Clearing at Boot Time

The normal behavior for systemd is to clear the screen at the end of the boot sequence. If desired, this behavior may be changed by running the following command:

```
mkdir -pv /etc/systemd/system/getty@tty1.service.d

cat > /etc/systemd/system/getty@tty1.service.d/noclear.conf << EOF
[Service]
TTYVTDisallocate=no
EOF
```

The boot messages can always be reviewed by using the `journalctl -b` command as the `root` user.

### 9.10.3. Disabling tmpfs for /tmp

By default, `/tmp` is created as a tmpfs. If this is not desired, it can be overridden by executing the following command:

```
ln -sfv /dev/null /etc/systemd/system/tmp.mount
```

Alternatively, if a separate partition for `/tmp` is desired, specify that partition in a `/etc/fstab` entry.



#### Warning

Do not create the symbolic link above if a separate partition is used for `/tmp`. This will prevent the root file system (`/`) from being remounted `r/w` and make the system unusable when booted.

### 9.10.4. Configuring Automatic File Creation and Deletion

There are several services that create or delete files or directories:

- `systemd-tmpfiles-clean.service`
- `systemd-tmpfiles-setup-dev.service`
- `systemd-tmpfiles-setup.service`



The system location for the configuration files is `/usr/lib/tmpfiles.d/*.conf`. The local configuration files are in `/etc/tmpfiles.d`. Files in `/etc/tmpfiles.d` override files with the same name in `/usr/lib/tmpfiles.d`. See *tmpfiles.d(5)* manual page for file format details.

Note that the syntax for the `/usr/lib/tmpfiles.d/*.conf` files can be confusing. For example, the default deletion of files in the `/tmp` directory is located in `/usr/lib/tmpfiles.d/tmp.conf` with the line:

```
q /tmp 1777 root root 10d
```

The type field, `q`, indicates the creation of a subvolume with quotas which is really only applicable to btrfs filesystems. It references type `v` which in turn references type `d` (directory). This then creates the specified directory if it is not present and adjusts the permissions and ownership as specified. Contents of the directory will be subject to time based cleanup if the age argument is specified.

If the default parameters are not desired, then the file should be copied to `/etc/tmpfiles.d` and edited as desired. For example:

```
mkdir -p /etc/tmpfiles.d
cp /usr/lib/tmpfiles.d/tmp.conf /etc/tmpfiles.d
```

### 9.10.5. Overriding Default Services Behavior

The parameters of a unit can be overridden by creating a directory and a configuration file in `/etc/systemd/system`. For example:

```
mkdir -pv /etc/systemd/system/foobar.service.d

cat > /etc/systemd/system/foobar.service.d/foobar.conf << EOF
[Service]
Restart=always
RestartSec=30
EOF
```

See *systemd.unit(5)* manual page for more information. After creating the configuration file, run `systemctl daemon-reload` and `systemctl restart foobar` to activate the changes to a service.

### 9.10.6. Debugging the Boot Sequence

Rather than plain shell scripts used in SysVinit or BSD style init systems, systemd uses a unified format for different types of startup files (or units). The command `systemctl` is used to enable, disable, control state, and obtain status of unit files. Here are some examples of frequently used commands:

- `systemctl list-units -t <service> [--all]`: lists loaded unit files of type service.
- `systemctl list-units -t <target> [--all]`: lists loaded unit files of type target.
- `systemctl show -p Wants <multi-user.target>`: shows all units that depend on the multi-user target. Targets are special unit files that are analogous to runlevels under SysVinit.
- `systemctl status <servicename.service>`: shows the status of the servicename service. The `.service` extension can be omitted if there are no other unit files with the same name, such as `.socket` files (which create a listening socket that provides similar functionality to `inetd/xinetd`).

### 9.10.7. Working with the Systemd Journal

Logging on a system booted with systemd is handled with `systemd-journald` (by default), rather than a typical unix `syslog` daemon. You can also add a normal `syslog` daemon and have both operate side by side if desired. The `systemd-journald` program stores journal entries in a binary format rather than a plain text log file. To assist with parsing the file, the command `journalctl` is provided. Here are some examples of frequently used commands:

- **journalctl -r**: shows all contents of the journal in reverse chronological order.
- **journalctl -u UNIT**: shows the journal entries associated with the specified UNIT file.
- **journalctl -b[=ID] -r**: shows the journal entries since last successful boot (or for boot ID) in reverse chronological order.
- **journalctl -f**: provides functionality similar to tail -f (follow).

## 9.10.8. Working with Core Dumps

Core dumps are useful to debug crashed programs, especially when a daemon process crashes. On systemd booted systems the core dumping is handled by **systemd-coredump**. It will log the core dump in the journal and store the core dump itself in `/var/lib/systemd/coredump`. To retrieve and process core dumps, the **coredumpctl** tool is provided. Here are some examples of frequently used commands:

- **coredumpctl -r**: lists all core dumps in reverse chronological order.
- **coredumpctl -1 info**: shows the information from the last core dump.
- **coredumpctl -1 debug**: loads the last core dump into *GDB*.

Core dumps may use a lot of disk space. The maximum disk space used by core dumps can be limited by creating a configuration file in `/etc/systemd/coredump.conf.d`. For example:

```
mkdir -pv /etc/systemd/coredump.conf.d

cat > /etc/systemd/coredump.conf.d/maxuse.conf << EOF
[CoreDump]
MaxUse=5G
EOF
```

See the *systemd-coredump(8)*, *coredumpctl(1)*, and *coredump.conf.d(5)* manual pages for more information.

## 9.10.9. Long Running Processes

Beginning with systemd-230, all user processes are killed when a user session is ended, even if `nohup` is used, or the process uses the `daemon()` or `setsid()` functions. This is a deliberate change from a historically permissive environment to a more restrictive one. The new behavior may cause issues if you depend on long running programs (e.g., **screen** or **tmux**) to remain active after ending your user session. There are three ways to enable lingering processes to remain after a user session is ended.

- *Enable process lingering for only selected users*: Normal users have permission to enable process lingering with the command **loginctl enable-linger** for their own user. System administrators can use the same command with a *user* argument to enable for a user. That user can then use the **systemd-run** command to start long running processes. For example: **systemd-run --scope --user /usr/bin/screen**. If you enable lingering for your user, the `user@.service` will remain even after all login sessions are closed, and will automatically start at system boot. This has the advantage of explicitly allowing and disallowing processes to run after the user session has ended, but breaks backwards compatibility with tools like **nohup** and utilities that use `daemon()`.
- *Enable system-wide process lingering*: You can set `KillUserProcesses=no` in `/etc/systemd/logind.conf` to enable process lingering globally for all users. This has the benefit of leaving the old method available to all users at the expense of explicit control.
- *Disable at build-time*: You can disable lingering by default while building systemd by adding the switch `-D default-kill-user-processes=false` to the **meson** command for systemd. This completely disables the ability of systemd to kill user processes at session end.

# Chapter 10. Making the LFS System Bootable

## 10.1. Introduction

It is time to make the LFS system bootable. This chapter discusses creating the `/etc/fstab` file, building a kernel for the new LFS system, and installing the GRUB boot loader so that the LFS system can be selected for booting at startup.

## 10.2. Creating the `/etc/fstab` File

The `/etc/fstab` file is used by some programs to determine where file systems are to be mounted by default, in which order, and which must be checked (for integrity errors) prior to mounting. Create a new file systems table like this:

```
cat > /etc/fstab << "EOF"
# Begin /etc/fstab

# file system  mount-point  type      options          dump  fsck
#                                     order

/dev/<xxx>     /             <fff>     defaults         1     1
/dev/<yyy>     swap          swap      pri=1             0     0

# End /etc/fstab
EOF
```

Replace `<xxx>`, `<yyy>`, and `<fff>` with the values appropriate for the system, for example, `sda2`, `sda5`, and `ext4`. For details on the six fields in this file, see *fstab(5)*.

Filesystems with MS-DOS or Windows origin (i.e. `vfat`, `ntfs`, `smbfs`, `cifs`, `iso9660`, `udf`) need a special option, `utf8`, in order for non-ASCII characters in file names to be interpreted properly. For non-UTF-8 locales, the value of `iocharset` should be set to be the same as the character set of the locale, adjusted in such a way that the kernel understands it. This works if the relevant character set definition (found under File systems -> Native Language Support when configuring the kernel) has been compiled into the kernel or built as a module. However, if the character set of the locale is UTF-8, the corresponding option `iocharset=utf8` would make the file system case sensitive. To fix this, use the special option `utf8` instead of `iocharset=utf8`, for UTF-8 locales. The “codepage” option is also needed for `vfat` and `smbfs` filesystems. It should be set to the codepage number used under MS-DOS in your country. For example, in order to mount USB flash drives, a `ru_RU.KOI8-R` user would need the following in the options portion of its mount line in `/etc/fstab`:

```
noauto,user,quiet,showexec,codepage=866,iocharset=koi8r
```

The corresponding options fragment for `ru_RU.UTF-8` users is:

```
noauto,user,quiet,showexec,codepage=866,utf8
```

Note that using `iocharset` is the default for `iso8859-1` (which keeps the file system case insensitive), and the `utf8` option tells the kernel to convert the file names using UTF-8 so they can be interpreted in the UTF-8 locale.

It is also possible to specify default `codepage` and `iocharset` values for some filesystems during kernel configuration. The relevant parameters are named “Default NLS Option” (`CONFIG_NLS_DEFAULT`), “Default Remote NLS Option” (`CONFIG_SMB_NLS_DEFAULT`), “Default codepage for FAT” (`CONFIG_FAT_DEFAULT_CODEPAGE`), and “Default `iocharset` for FAT” (`CONFIG_FAT_DEFAULT_IOCHARSET`). There is no way to specify these settings for the `ntfs` filesystem at kernel compilation time.

It is possible to make the ext3 filesystem reliable across power failures for some hard disk types. To do this, add the `barrier=1` mount option to the appropriate entry in `/etc/fstab`. To check if the disk drive supports this option, run `hdparm` on the applicable disk drive. For example, if:

```
hdparm -I /dev/sda | grep NCQ
```

returns non-empty output, the option is supported.

Note: Logical Volume Management (LVM) based partitions cannot use the `barrier` option.

## 10.3. Linux-6.10.5

The Linux package contains the Linux kernel.

**Approximate build time:** 0.4 - 32 SBU (typically about 2.5 SBU)

**Required disk space:** 1.7 - 14 GB (typically about 2.3 GB)

### 10.3.1. Installation of the kernel

Building the kernel involves a few steps—configuration, compilation, and installation. Read the `README` file in the kernel source tree for alternative methods to the way this book configures the kernel.



#### Important

Building the linux kernel for the first time is one of the most challenging tasks in LFS. Getting it right depends on the specific hardware for the target system and your specific needs. There are almost 12,000 configuration items that are available for the kernel although only about a third of them are needed for most computers. The LFS editors recommend that users not familiar with this process follow the procedures below fairly closely. The objective is to get an initial system to a point where you can log in at the command line when you reboot later in Section 11.3, “Rebooting the System.” At this point optimization and customization is not a goal.

For general information on kernel configuration see <https://www.linuxfromscratch.org/hints/downloads/files/kernel-configuration.txt>. Additional information about configuring and building the kernel can be found at <https://andu.in.linuxfromscratch.org/LFS/kernel-nutshell/>. These references are a bit dated, but still give a reasonable overview of the process.

If all else fails, you can ask for help on the *lfs-support* mailing list. Note that subscribing is required in order for the list to avoid spam.

Prepare for compilation by running the following command:

```
make mrproper
```

This ensures that the kernel tree is absolutely clean. The kernel team recommends that this command be issued prior to each kernel compilation. Do not rely on the source tree being clean after un-tarring.

There are several ways to configure the kernel options. Usually, this is done through a menu-driven interface, for example:

```
make menuconfig
```

#### The meaning of optional make environment variables:

```
LANG=<host_LANG_value> LC_ALL=
```

This establishes the locale setting to the one used on the host. This may be needed for a proper menuconfig ncurses interface line drawing on a UTF-8 linux text console.

If used, be sure to replace `<host_LANG_value>` by the value of the `$LANG` variable from your host. You can alternatively use instead the host's value of `$LC_ALL` or `$LC_CTYPE`.

#### make menuconfig

This launches an ncurses menu-driven interface. For other (graphical) interfaces, type **make help**.



#### Note

A good starting place for setting up the kernel configuration is to run **make defconfig**. This will set the base configuration to a good state that takes your current system architecture into account.

Be sure to enable/disable/set the following features or the system might not work correctly or boot at all:

```

General setup --->
[ ] Compile the kernel with warnings as errors                [WERROR]
CPU/Task time and stats accounting --->
[*] Pressure stall information tracking                        [PSI]
[ ]   Require boot parameter to enable pressure stall information tracking
      ... [PSI_DEFAULT_DISABLED]
< > Enable kernel headers through /sys/kernel/kheaders.tar.xz [IKHEADERS]
[*] Control Group support --->                               [CGROUPS]
[*]   Memory controller                                     [MEMCG]
[ /*] CPU controller --->                                   [CGROUP_SCHED]
# This may cause some systemd features malfunction:
[ ]   Group scheduling for SCHED_RR/FIFO                     [RT_GROUP_SCHED]
[ ] Configure standard kernel features (expert users) ---> [EXPERT]

Processor type and features --->
[*] Build a relocatable kernel                               [RELOCATABLE]
[*]   Randomize the address of the kernel image (KASLR)      [RANDOMIZE_BASE]

General architecture-dependent options --->
[*] Stack Protector buffer overflow detection                [STACKPROTECTOR]
[*]   Strong Stack Protector                                [STACKPROTECTOR_STRONG]

[*] Networking support --->                                  [NET]
Networking options --->
[*] TCP/IP networking                                       [INET]
< * >   The IPv6 protocol --->                               [IPv6]

Device Drivers --->
Generic Driver Options --->
[ ] Support for uevent helper                                [UEVENT_HELPER]
[*] Maintain a devtmpfs filesystem to mount at /dev          [DEVTMPFS]
[*]   Automount devtmpfs at /dev, after the kernel mounted the rootfs
      ... [DEVTMPFS_MOUNT]

Firmware loader --->
< /* > Firmware loading facility                             [FW_LOADER]
[ ]   Enable the firmware sysfs fallback mechanism
      ... [FW_LOADER_USER_HELPER]

Firmware Drivers --->
[*] Export DMI identification via sysfs to userspace         [DMIID]

Graphics support --->
< /*/M > Direct Rendering Manager (XFree86 4.1.0 and higher DRI support) --->
      ... [DRM]

# If [DRM] is selected as * or M, this must be selected:
[ /*] Enable legacy fbdev support for your modesetting driver
      ... [DRM_FBDEV_EMULATION]

Console display driver support --->
# If [DRM] is selected as * or M, this must be selected:
[ /*] Framebuffer Console support                            [FRAMEBUFFER_CONSOLE]

File systems --->
[*] Inotify support for userspace                            [INOTIFY_USER]
Pseudo filesystems --->
[*] Tmpfs virtual memory file system support (former shm fs) [TMPFS]
[*]   Tmpfs POSIX Access Control Lists                       [TMPFS_POSIX_ACL]

```

Enable some additional features if you are building a 64-bit system. If you are using menuconfig, enable them in the order of `CONFIG_PCI_MSI` first, then `CONFIG_IRQ_REMAP`, at last `CONFIG_X86_X2APIC` because an option only shows up after its dependencies are selected.

```
Processor type and features --->
  [*] Support x2apic                                     [X86_X2APIC]

Device Drivers --->
  [*] PCI support --->                                  [PCI]
  [*] Message Signaled Interrupts (MSI and MSI-X)       [PCI_MSI]
  [*] IOMMU Hardware Support --->                       [IOMMU_SUPPORT]
  [*] Support for Interrupt Remapping                   [IRQ_REMAP]
```

If you are building a 32-bit system running on a hardware with RAM more than 4GB, adjust the configuration so the kernel will be able to use up to 64GB physical RAM:

```
Processor type and features --->
  High Memory Support --->
    (X) 64GB                                             [HIGHMEM64G]
```

If the partition for the LFS system is in a NVME SSD (i. e. the device node for the partition is `/dev/nvme*` instead of `/dev/sd*`), enable NVME support or the LFS system won't boot:

```
Device Drivers --->
  NVME Support --->
    <*> NVM Express block device                         [BLK_DEV_NVME]
```



## Note

While "The IPv6 Protocol" is not strictly required, it is highly recommended by the systemd developers.

There are several other options that may be desired depending on the requirements for the system. For a list of options needed for BLFS packages, see the *BLFS Index of Kernel Settings*.



## Note

If your host hardware is using UEFI and you wish to boot the LFS system with it, you should adjust some kernel configuration following *the BLFS page even if you'll use the UEFI bootloader from the host distro*.

### The rationale for the above configuration items:

*Randomize the address of the kernel image (KASLR)*

Enable ASLR for kernel image, to mitigate some attacks based on fixed addresses of sensitive data or code in the kernel.

*Compile the kernel with warnings as errors*

This may cause building failure if the compiler and/or configuration are different from those of the kernel developers.

*Enable kernel headers through /sys/kernel/kheaders.tar.xz*

This will require **cpio** building the kernel. **cpio** is not installed by LFS.

*Configure standard kernel features (expert users)*

This will make some options show up in the configuration interface but changing those options may be dangerous. Do not use this unless you know what you are doing.

*Strong Stack Protector*

Enable SSP for the kernel. We've enabled it for the entire userspace with `--enable-default-ssp` configuring GCC, but the kernel does not use GCC default setting for SSP. We enable it explicitly here.

*Support for uevent helper*

Having this option set may interfere with device management when using Udev.

*Maintain a devtmpfs*

This will create automated device nodes which are populated by the kernel, even without Udev running. Udev then runs on top of this, managing permissions and adding symlinks. This configuration item is required for all users of Udev.

*Automount devtmpfs at /dev*

This will mount the kernel view of the devices on /dev upon switching to root filesystem just before starting init.

*Enable legacy fbdev support for your modesetting driver and Framebuffer Console support*

These are needed to display the Linux console on a GPU driven by a DRI (Direct Rendering Infrastructure) driver. If `CONFIG_DRM` (Direct Rendering Manager) is enabled, you should enable these two options as well or you'll see a blank screen once the DRI driver is loaded.

*Support x2apic*

Support running the interrupt controller of 64-bit x86 processors in x2APIC mode. x2APIC may be enabled by firmware on 64-bit x86 systems, and a kernel without this option enabled will panic on boot if x2APIC is enabled by firmware. This option has no effect, but also does no harm if x2APIC is disabled by the firmware.

Alternatively, **make oldconfig** may be more appropriate in some situations. See the `README` file for more information.

If desired, skip kernel configuration by copying the kernel config file, `.config`, from the host system (assuming it is available) to the unpacked `linux-6.10.5` directory. However, we do not recommend this option. It is often better to explore all the configuration menus and create the kernel configuration from scratch.

Compile the kernel image and modules:

```
make
```

If using kernel modules, module configuration in `/etc/modprobe.d` may be required. Information pertaining to modules and kernel configuration is located in Section 9.3, “Overview of Device and Module Handling” and in the kernel documentation in the `linux-6.10.5/Documentation` directory. Also, `modprobe.d(5)` may be of interest.

Unless module support has been disabled in the kernel configuration, install the modules with:

```
make modules_install
```

After kernel compilation is complete, additional steps are required to complete the installation. Some files need to be copied to the `/boot` directory.



### Caution

If you've decided to use a separate `/boot` partition for the LFS system (maybe sharing a `/boot` partition with the host distro), the files copied below should go there. The easiest way to do that is to create the entry for `/boot` in `/etc/fstab` first (read the previous section for details), then issue the following command as the `root` user in the *chroot environment*:

```
mount /boot
```

The path to the device node is omitted in the command because **mount** can read it from `/etc/fstab`.



The path to the kernel image may vary depending on the platform being used. The filename below can be changed to suit your taste, but the stem of the filename should be *vmlinuz* to be compatible with the automatic setup of the boot process described in the next section. The following command assumes an x86 architecture:

```
cp -iv arch/x86/boot/bzImage /boot/vmlinuz-6.10.5-lfs-12.2-systemd
```

`System.map` is a symbol file for the kernel. It maps the function entry points of every function in the kernel API, as well as the addresses of the kernel data structures for the running kernel. It is used as a resource when investigating kernel problems. Issue the following command to install the map file:

```
cp -iv System.map /boot/System.map-6.10.5
```

The kernel configuration file `.config` produced by the **make menuconfig** step above contains all the configuration selections for the kernel that was just compiled. It is a good idea to keep this file for future reference:

```
cp -iv .config /boot/config-6.10.5
```

Install the documentation for the Linux kernel:

```
cp -r Documentation -T /usr/share/doc/linux-6.10.5
```

It is important to note that the files in the kernel source directory are not owned by *root*. Whenever a package is unpacked as user *root* (like we did inside `chroot`), the files have the user and group IDs of whatever they were on the packager's computer. This is usually not a problem for any other package to be installed because the source tree is removed after the installation. However, the Linux source tree is often retained for a long time. Because of this, there is a chance that whatever user ID the packager used will be assigned to somebody on the machine. That person would then have write access to the kernel source.



## Note

In many cases, the configuration of the kernel will need to be updated for packages that will be installed later in BLFS. Unlike other packages, it is not necessary to remove the kernel source tree after the newly built kernel is installed.

If the kernel source tree is going to be retained, run **chown -R 0:0** on the `linux-6.10.5` directory to ensure all files are owned by user *root*.



## Warning

Some kernel documentation recommends creating a symlink from `/usr/src/linux` pointing to the kernel source directory. This is specific to kernels prior to the 2.6 series and *must not* be created on an LFS system as it can cause problems for packages you may wish to build once your base LFS system is complete.



## Warning

The headers in the system's `include` directory (`/usr/include`) should *always* be the ones against which Glibc was compiled, that is, the sanitised headers installed in Section 5.4, “Linux-6.10.5 API Headers”. Therefore, they should *never* be replaced by either the raw kernel headers or any other kernel sanitized headers.

## 10.3.2. Configuring Linux Module Load Order

Most of the time Linux modules are loaded automatically, but sometimes it needs some specific direction. The program that loads modules, **modprobe** or **insmod**, uses `/etc/modprobe.d/usb.conf` for this purpose. This file needs to be created so that if the USB drivers (`ehci_hcd`, `ohci_hcd` and `uhci_hcd`) have been built as modules, they will be loaded in the correct order; `ehci_hcd` needs to be loaded prior to `ohci_hcd` and `uhci_hcd` in order to avoid a warning being output at boot time.

Create a new file `/etc/modprobe.d/usb.conf` by running the following:

```
install -v -m755 -d /etc/modprobe.d
cat > /etc/modprobe.d/usb.conf << "EOF"
# Begin /etc/modprobe.d/usb.conf

install ohci_hcd /sbin/modprobe ehci_hcd ; /sbin/modprobe -i ohci_hcd ; true
install uhci_hcd /sbin/modprobe ehci_hcd ; /sbin/modprobe -i uhci_hcd ; true

# End /etc/modprobe.d/usb.conf
EOF
```

## 10.3.3. Contents of Linux

**Installed files:** `config-6.10.5`, `vmlinuz-6.10.5-lfs-12.2-systemd`, and `System.map-6.10.5`  
**Installed directories:** `/lib/modules`, `/usr/share/doc/linux-6.10.5`

### Short Descriptions

<code>config-6.10.5</code>	Contains all the configuration selections for the kernel
<code>vmlinuz-6.10.5-lfs-12.2-systemd</code>	The engine of the Linux system. When turning on the computer, the kernel is the first part of the operating system that gets loaded. It detects and initializes all components of the computer's hardware, then makes these components available as a tree of files to the software and turns a single CPU into a multitasking machine capable of running scores of programs seemingly at the same time
<code>System.map-6.10.5</code>	A list of addresses and symbols; it maps the entry points and addresses of all the functions and data structures in the kernel

## 10.4. Using GRUB to Set Up the Boot Process



### Note

If your system has UEFI support and you wish to boot LFS with UEFI, you should skip the instructions in this page but still learn the syntax of `grub.cfg` and the method to specify a partition in the file from this page, and configure GRUB with UEFI support using the instructions provided in *the BLFS page*.

### 10.4.1. Introduction



### Warning

Configuring GRUB incorrectly can render your system inoperable without an alternate boot device such as a CD-ROM or bootable USB drive. This section is not required to boot your LFS system. You may just want to modify your current boot loader, e.g. Grub-Legacy, GRUB2, or LILO.

Ensure that an emergency boot disk is ready to “rescue” the computer if the computer becomes unusable (un-bootable). If you do not already have a boot device, you can create one. In order for the procedure below to work, you need to jump ahead to BLFS and install `xorriso` from the *libisoburn* package.

```
cd /tmp
grub-mkrescue --output=grub-img.iso
xorriso -as cdrecord -v dev=/dev/cdrw blank=as_needed grub-img.iso
```

### 10.4.2. GRUB Naming Conventions

GRUB uses its own naming structure for drives and partitions in the form of  $(hdn,m)$ , where  $n$  is the hard drive number and  $m$  is the partition number. The hard drive numbers start from zero, but the partition numbers start from one for normal partitions (from five for extended partitions). Note that this is different from earlier versions where both numbers started from zero. For example, partition `sda1` is  $(hd0,1)$  to GRUB and `sdb3` is  $(hd1,3)$ . In contrast to Linux, GRUB does not consider CD-ROM drives to be hard drives. For example, if using a CD on `hdb` and a second hard drive on `hdc`, that second hard drive would still be  $(hd1)$ .

### 10.4.3. Setting Up the Configuration

GRUB works by writing data to the first physical track of the hard disk. This area is not part of any file system. The programs there access GRUB modules in the boot partition. The default location is `/boot/grub/`.

The location of the boot partition is a choice of the user that affects the configuration. One recommendation is to have a separate small (suggested size is 200 MB) partition just for boot information. That way each build, whether LFS or some commercial distro, can access the same boot files and access can be made from any booted system. If you choose to do this, you will need to mount the separate partition, move all files in the current `/boot` directory (e.g. the Linux kernel you just built in the previous section) to the new partition. You will then need to unmount the partition and remount it as `/boot`. If you do this, be sure to update `/etc/fstab`.

Leaving `/boot` on the current LFS partition will also work, but configuration for multiple systems is more difficult.

Using the above information, determine the appropriate designator for the root partition (or boot partition, if a separate one is used). For the following example, it is assumed that the root (or separate boot) partition is `sda2`.

Install the GRUB files into `/boot/grub` and set up the boot track:



## Warning

The following command will overwrite the current boot loader. Do not run the command if this is not desired, for example, if using a third party boot manager to manage the Master Boot Record (MBR).

```
grub-install /dev/sda
```



## Note

If the system has been booted using UEFI, **grub-install** will try to install files for the *x86\_64-efi* target, but those files have not been installed in Chapter 8. If this is the case, add `--target i386-pc` to the command above.

## 10.4.4. Creating the GRUB Configuration File

Generate `/boot/grub/grub.cfg`:

```
cat > /boot/grub/grub.cfg << "EOF"
# Begin /boot/grub/grub.cfg
set default=0
set timeout=5

insmod part_gpt
insmod ext2
set root=(hd0,2)

menuentry "GNU/Linux, Linux 6.10.5-lfs-12.2-systemd" {
    linux /boot/vmlinuz-6.10.5-lfs-12.2-systemd root=/dev/sda2 ro
}
EOF
```

The **insmod** commands load the GRUB modules named `part_gpt` and `ext2`. Despite the naming, `ext2` actually supports `ext2`, `ext3`, and `ext4` filesystems. The **grub-install** command has embedded some modules into the main GRUB image (installed into the MBR or the GRUB BIOS partition) to access the other modules (in `/boot/grub/i386-pc`) without a chicken-or-egg issue, so with a typical configuration these two modules are already embedded and those two **insmod** commands will do nothing. But they do no harm anyway, and they may be needed with some rare configurations.



## Note

From GRUB's perspective, the kernel files are relative to the partition used. If you used a separate `/boot` partition, remove `/boot` from the above `linux` line. You will also need to change the `set root` line to point to the boot partition.



## Note

The GRUB designator for a partition may change if you added or removed some disks (including removable disks like USB thumb devices). The change may cause boot failure because `grub.cfg` refers to some “old” designators. If you wish to avoid such a problem, you may use the UUID of a partition and the UUID of a filesystem instead of a GRUB designator to specify a device. Run **`lsblk -o UUID,PARTUUID,PATH,MOUNTPOINT`** to show the UUIDs of your filesystems (in the `UUID` column) and partitions (in the `PARTUUID` column). Then replace `set root=(hdx,y)` with `search --set=root --fs-uuid <UUID of the filesystem where the kernel is installed>`, and replace `root=/dev/sda2` with `root=PARTUUID=<UUID of the partition where LFS is built>`.

Note that the UUID of a partition is completely different from the UUID of the filesystem in this partition. Some online resources may instruct you to use `root=UUID=<filesystem UUID>` instead of `root=PARTUUID=<partition UUID>`, but doing so will require an `initramfs`, which is beyond the scope of LFS.

The name of the device node for a partition in `/dev` may also change (this is less likely than a GRUB designator change). You can also replace paths to device nodes like `/dev/sda1` with `PARTUUID=<partition UUID>`, in `/etc/fstab`, to avoid a potential boot failure in case the device node name has changed.

GRUB is an extremely powerful program and it provides a tremendous number of options for booting from a wide variety of devices, operating systems, and partition types. There are also many options for customization such as graphical splash screens, playing sounds, mouse input, etc. The details of these options are beyond the scope of this introduction.



## Caution

There is a command, `grub-mkconfig`, that can write a configuration file automatically. It uses a set of scripts in `/etc/grub.d/` and will destroy any customizations that you make. These scripts are designed primarily for non-source distributions and are not recommended for LFS. If you install a commercial Linux distribution, there is a good chance that this program will be run. Be sure to back up your `grub.cfg` file.

# Chapter 11. The End

## 11.1. The End

Well done! The new LFS system is installed! We wish you much success with your shiny new custom-built Linux system.

It may be a good idea to create an `/etc/lfs-release` file. By having this file, it is very easy for you (and for us if you need to ask for help at some point) to find out which LFS version is installed on the system. Create this file by running:

```
echo 12.2-systemd > /etc/lfs-release
```

Two files describing the installed system may be used by packages that can be installed on the system later, either in binary form or by building them.

The first one shows the status of your new system with respect to the Linux Standards Base (LSB). To create this file, run:

```
cat > /etc/lsb-release << "EOF"
DISTRIB_ID="Linux From Scratch"
DISTRIB_RELEASE="12.2-systemd"
DISTRIB_CODENAME="<your name here>"
DISTRIB_DESCRIPTION="Linux From Scratch"
EOF
```

The second one contains roughly the same information, and is used by `systemd` and some graphical desktop environments. To create this file, run:

```
cat > /etc/os-release << "EOF"
NAME="Linux From Scratch"
VERSION="12.2-systemd"
ID=lfs
PRETTY_NAME="Linux From Scratch 12.2-systemd"
VERSION_CODENAME="<your name here>"
HOME_URL="https://www.linuxfromscratch.org/lfs/"
EOF
```

Be sure to customize the fields 'DISTRIB\_CODENAME' and 'VERSION\_CODENAME' to make the system uniquely yours.

## 11.2. Get Counted

Now that you have finished the book, do you want to be counted as an LFS user? Head over to <https://www.linuxfromscratch.org/cgi-bin/lfscounter.php> and register as an LFS user by entering your name and the first LFS version you have used.

Let's reboot into LFS now.

## 11.3. Rebooting the System

Now that all of the software has been installed, it is time to reboot your computer. However, there are still a few things to check. Here are some suggestions:

- Install any *firmware* needed if the kernel driver for your hardware requires some firmware files to function properly.
- Ensure a password is set for the `root` user.

- A review of the following configuration files is also appropriate at this point.
  - /etc/bashrc
  - /etc/dircolors
  - /etc/fstab
  - /etc/hosts
  - /etc/inputrc
  - /etc/profile
  - /etc/resolv.conf
  - /etc/vimrc
  - /root/.bash\_profile
  - /root/.bashrc

Now that we have said that, let's move on to booting our shiny new LFS installation for the first time! *First exit from the chroot environment:*

```
logout
```

Then unmount the virtual file systems:

```
umount -v $LFS/dev/pts
mountpoint -q $LFS/dev/shm && umount -v $LFS/dev/shm
umount -v $LFS/dev
umount -v $LFS/run
umount -v $LFS/proc
umount -v $LFS/sys
```

If multiple partitions were created, unmount the other partitions before unmounting the main one, like this:

```
umount -v $LFS/home
umount -v $LFS
```

Unmount the LFS file system itself:

```
umount -v $LFS
```

Now, reboot the system.

Assuming the GRUB boot loader was set up as outlined earlier, the menu is set to boot *LFS 12.2-systemd* automatically.

When the reboot is complete, the LFS system is ready for use. What you will see is a simple “login: ” prompt. At this point, you can proceed to *the BLFS Book* where you can add more software to suit your needs.

If your reboot is **not** successful, it is time to troubleshoot. For hints on solving initial booting problems, see <https://www.linuxfromscratch.org/lfs/troubleshooting.html>.

## 11.4. Additional Resources

Thank you for reading this LFS book. We hope that you have found this book helpful and have learned more about the system creation process.

Now that the LFS system is installed, you may be wondering “What next?” To answer that question, we have compiled a list of resources for you.

- Maintenance

Bugs and security notices are reported regularly for all software. Since an LFS system is compiled from source, it is up to you to keep abreast of such reports. There are several online resources that track such reports, some of which are shown below:

- *LFS Security Advisories*

This is a list of security vulnerabilities discovered in the LFS book after it's published.

- *Open Source Security Mailing List*

This is a mailing list for discussion of security flaws, concepts, and practices in the Open Source community.

- LFS Hints

The LFS Hints are a collection of educational documents submitted by volunteers in the LFS community. The hints are available at <https://www.linuxfromscratch.org/hints/downloads/files/>.

- Mailing lists

There are several LFS mailing lists you may subscribe to if you are in need of help, want to stay current with the latest developments, want to contribute to the project, and more. See Chapter 1 - Mailing Lists for more information.

- The Linux Documentation Project

The goal of The Linux Documentation Project (TLDP) is to collaborate on all of the issues of Linux documentation. The TLDP features a large collection of HOWTOs, guides, and man pages. It is located at <https://tldp.org/>.

## 11.5. Getting Started After LFS

### 11.5.1. Deciding what to do next

Now that LFS is complete and you have a bootable system, what do you do? The next step is to decide how to use it. Generally, there are two broad categories to consider: workstation or server. Indeed, these categories are not mutually exclusive. The applications needed for each category can be combined onto a single system, but let's look at them separately for now.

A server is the simpler category. Generally this consists of a web server such as the *Apache HTTP Server* and a database server such as *MariaDB*. However other services are possible. The operating system embedded in a single use device falls into this category.

On the other hand, a workstation is much more complex. It generally requires a graphical user environment such as *LXDE*, *XFCE*, *KDE*, or *Gnome* based on a basic *graphical environment* and several graphical based applications such as the *Firefox web browser*, *Thunderbird email client*, or *LibreOffice office suite*. These applications require many (several hundred depending on desired capabilities) more packages of support applications and libraries.

In addition to the above, there is a set of applications for system management for all kinds of systems. These applications are all in the BLFS book. Not all packages are needed in every environments. For example *dhcpcd*, is not normally appropriate for a server and *wireless\_tools*, are normally only useful for a laptop system.

### 11.5.2. Working in a basic LFS environment

When you initially boot into LFS, you have all the internal tools to build additional packages. Unfortunately, the user environment is quite sparse. There are a couple of ways to improve this:



### 11.5.2.1. Work from the LFS host in chroot

This method provides a complete graphical environment where a full featured browser and copy/paste capabilities are available. This method allows using applications like the host's version of `wget` to download package sources to a location available when working in the chroot environment.

In order to properly build packages in chroot, you will also need to remember to mount the virtual file systems if they are not already mounted. One way to do this is to create a script on the **HOST** system:

```
cat > ~/mount-virt.sh << "EOF"
#!/bin/bash

function mountbind
{
    if ! mountpoint $LFS/$1 >/dev/null; then
        $SUDO mount --bind /$1 $LFS/$1
        echo $LFS/$1 mounted
    else
        echo $LFS/$1 already mounted
    fi
}

function mounttype
{
    if ! mountpoint $LFS/$1 >/dev/null; then
        $SUDO mount -t $2 $3 $4 $5 $LFS/$1
        echo $LFS/$1 mounted
    else
        echo $LFS/$1 already mounted
    fi
}

if [ $EUID -ne 0 ]; then
    SUDO=sudo
else
    SUDO=""
fi

if [ x$LFS == x ]; then
    echo "LFS not set"
    exit 1
fi

mountbind dev
mounttype dev/pts devpts devpts -o gid=5,mode=620
mounttype proc proc proc
mounttype sys sysfs sysfs
mounttype run tmpfs run
if [ -h $LFS/dev/shm ]; then
    install -v -d -m 1777 $LFS$(realpath /dev/shm)
else
    mounttype dev/shm tmpfs tmpfs -o nosuid,nodev
fi

#mountbind usr/src
#mountbind boot
#mountbind home
EOF
```

Note that the last three commands in the script are commented out. These are useful if those directories are mounted as separate partitions on the host system and will be mounted when booting the completed LFS/BLFS system.

The script can be run with **bash ~/mount-virt.sh** as either a regular user (recommended) or as `root`. If run as a regular user, `sudo` is required on the host system.

Another issue pointed out by the script is where to store downloaded package files. This location is arbitrary. It can be in a regular user's home directory such as `~/sources` or in a global location like `/usr/src`. Our recommendation is not to mix BLFS sources and LFS sources in (from the chroot environment) `/sources`. In any case, the packages must be accessible inside the chroot environment.

A last convenience feature presented here is to streamline the process of entering the chroot environment. This can be done with an alias placed in a user's `~/.bashrc` file on the host system:

```
alias lfs='sudo /usr/sbin/chroot /mnt/lfs /usr/bin/env -i HOME=/root TERM="$TERM" PS1="\u:\w\\\$ "
PATH=/bin:/usr/bin:/sbin:/usr/sbin /bin/bash --login'
```

This alias is a little tricky because of the quoting and levels of backslash characters. It must be all on a single line. The above command has been split in two for presentation purposes.

### 11.5.2.2. Work remotely via ssh

This method also provides a full graphical environment, but first requires installing `sshd` on the LFS system, usually in chroot. It also requires a second computer. This method has the advantage of being simple by not requiring the complexity of the chroot environment. It also uses your LFS built kernel for all additional packages and still provides a complete system for installing packages.

You may use the `scp` command to upload the package sources to be built onto the LFS system. If you want to download the sources onto the LFS system directly instead, install `libtasn1`, `p11-kit`, `make-ca`, and `wget` in chroot (or upload their sources using `scp` after booting the LFS system).

### 11.5.2.3. Work from the LFS command line

This method requires installing `libtasn1`, `p11-kit`, `make-ca`, `wget`, `gpm`, and `links` (or `lynx`) in chroot and then rebooting into the new LFS system. At this point the default system has six virtual consoles. Switching consoles is as easy as using the **Alt+Fx** key combinations where **Fx** is between **F1** and **F6**. The **Alt+←** and **Alt+→** combinations also will change the console.

At this point you can log into two different virtual consoles and run the `links` or `lynx` browser in one console and `bash` in the other. `GPM` then allows copying commands from the browser with the left mouse button, switching consoles, and pasting into the other console.



#### Note

As a side note, switching of virtual consoles can also be done from an X Window instance with the **Ctrl+Alt+Fx** key combination, but the mouse copy operation does not work between the graphical interface and a virtual console. You can return to the X Window display with the **Ctrl+Alt+Fx** combination, where **Fx** is usually **F1** but may be **F7**.

## **Part V. Appendices**

# Appendix A. Acronyms and Terms

<b>ABI</b>	Application Binary Interface
<b>ALFS</b>	Automated Linux From Scratch
<b>API</b>	Application Programming Interface
<b>ASCII</b>	American Standard Code for Information Interchange
<b>BIOS</b>	Basic Input/Output System
<b>BLFS</b>	Beyond Linux From Scratch
<b>BSD</b>	Berkeley Software Distribution
<b>chroot</b>	change root
<b>CMOS</b>	Complementary Metal Oxide Semiconductor
<b>COS</b>	Class Of Service
<b>CPU</b>	Central Processing Unit
<b>CRC</b>	Cyclic Redundancy Check
<b>CVS</b>	Concurrent Versions System
<b>DHCP</b>	Dynamic Host Configuration Protocol
<b>DNS</b>	Domain Name Service
<b>EGA</b>	Enhanced Graphics Adapter
<b>ELF</b>	Executable and Linkable Format
<b>EOF</b>	End of File
<b>EQN</b>	equation
<b>ext2</b>	second extended file system
<b>ext3</b>	third extended file system
<b>ext4</b>	fourth extended file system
<b>FAQ</b>	Frequently Asked Questions
<b>FHS</b>	Filesystem Hierarchy Standard
<b>FIFO</b>	First-In, First Out
<b>FQDN</b>	Fully Qualified Domain Name
<b>FTP</b>	File Transfer Protocol
<b>GB</b>	Gigabytes
<b>GCC</b>	GNU Compiler Collection
<b>GID</b>	Group Identifier
<b>GMT</b>	Greenwich Mean Time
<b>HTML</b>	Hypertext Markup Language
<b>IDE</b>	Integrated Drive Electronics
<b>IEEE</b>	Institute of Electrical and Electronic Engineers

<b>IO</b>	Input/Output
<b>IP</b>	Internet Protocol
<b>IPC</b>	Inter-Process Communication
<b>IRC</b>	Internet Relay Chat
<b>ISO</b>	International Organization for Standardization
<b>ISP</b>	Internet Service Provider
<b>KB</b>	Kilobytes
<b>LED</b>	Light Emitting Diode
<b>LFS</b>	Linux From Scratch
<b>LSB</b>	Linux Standard Base
<b>MB</b>	Megabytes
<b>MBR</b>	Master Boot Record
<b>MD5</b>	Message Digest 5
<b>NIC</b>	Network Interface Card
<b>NLS</b>	Native Language Support
<b>NNTP</b>	Network News Transport Protocol
<b>NPTL</b>	Native POSIX Threading Library
<b>OSS</b>	Open Sound System
<b>PCH</b>	Pre-Compiled Headers
<b>PCRE</b>	Perl Compatible Regular Expression
<b>PID</b>	Process Identifier
<b>PTY</b>	pseudo terminal
<b>QOS</b>	Quality Of Service
<b>RAM</b>	Random Access Memory
<b>RPC</b>	Remote Procedure Call
<b>RTC</b>	Real Time Clock
<b>SBU</b>	Standard Build Unit
<b>SCO</b>	The Santa Cruz Operation
<b>SHA1</b>	Secure-Hash Algorithm 1
<b>TLDP</b>	The Linux Documentation Project
<b>TFTP</b>	Trivial File Transfer Protocol
<b>TLS</b>	Thread-Local Storage
<b>UID</b>	User Identifier
<b>umask</b>	user file-creation mask
<b>USB</b>	Universal Serial Bus
<b>UTC</b>	Coordinated Universal Time

<b>UUID</b>	Universally Unique Identifier
<b>VC</b>	Virtual Console
<b>VGA</b>	Video Graphics Array
<b>VT</b>	Virtual Terminal

# Appendix B. Acknowledgments

We would like to thank the following people and organizations for their contributions to the Linux From Scratch Project.

- *Gerard Beekmans* <gerard@linuxfromscratch.org> – LFS Creator
- *Bruce Dubbs* <bdubbs@linuxfromscratch.org> – LFS Managing Editor
- *Jim Gifford* <jim@linuxfromscratch.org> – CLFS Project Co-Leader
- *Pierre Labastie* <pierre@linuxfromscratch.org> – BLFS Editor and ALFS Lead
- *DJ Lucas* <dj@linuxfromscratch.org> – LFS and BLFS Editor
- *Ken Moffat* <ken@linuxfromscratch.org> – BLFS Editor
- Countless other people on the various LFS and BLFS mailing lists who helped make this book possible by giving their suggestions, testing the book, and submitting bug reports, instructions, and their experiences with installing various packages.

## Translators

- *Manuel Canales Esparcia* <macana@macana-es.com> – Spanish LFS translation project
- *Johan Lenglet* <johan@linuxfromscratch.org> – French LFS translation project until 2008
- *Jean-Philippe Mengual* <jmengual@linuxfromscratch.org> – French LFS translation project 2008-2016
- *Julien Lepiller* <jlepiller@linuxfromscratch.org> – French LFS translation project 2017-present
- *Anderson Lizardo* <lizardo@linuxfromscratch.org> – Portuguese LFS translation project historical
- *Jamenson Espindula* <jafesp@gmail.com> – Portuguese LFS translation project 2022-present
- *Thomas Reitelbach* <tr@erdfunkstelle.de> – German LFS translation project

## Mirror Maintainers

### North American Mirrors

- *Scott Kveton* <scott@osuosl.org> – lfs.oregonstate.edu mirror
- *William Astle* <lost@l-w.net> – ca.linuxfromscratch.org mirror
- *Eujon Sellers* <jpolen@rackspace.com> – lfs.introspeed.com mirror
- *Justin Knierim* <tim@idge.net> – lfs-matrix.net mirror

### South American Mirrors

- *Manuel Canales Esparcia* <manuel@linuxfromscratch.org> – lfsmirror.lfs-es.info mirror
- *Luis Falcon* <Luis Falcon> – torredehanoi.org mirror

### European Mirrors

- *Guido Passet* <guido@primerelay.net> – nl.linuxfromscratch.org mirror
- *Bastiaan Jacques* <baafie@planet.nl> – lfs.pagefault.net mirror
- *Sven Cranshoff* <sven.cranshoff@lineo.be> – lfs.lineo.be mirror

- Scarlet Belgium – lfs.scarlet.be mirror
- *Sebastian Faulborn* <info@aliensoft.org> – lfs.aliensoft.org mirror
- *Stuart Fox* <stuart@dontuse.ms> – lfs.dontuse.ms mirror
- *Ralf Uhlemann* <admin@realhost.de> – lfs.oss-mirror.org mirror
- *Antonin Sprinzl* <Antonin.Sprinzl@tuwien.ac.at> – at.linuxfromscratch.org mirror
- *Fredrik Danerklint* <fredan-lfs@fredan.org> – se.linuxfromscratch.org mirror
- *Franck* <franck@linuxpourtous.com> – lfs.linuxpourtous.com mirror
- *Philippe Baque* <baque@cict.fr> – lfs.cict.fr mirror
- *Vitaly Chekasin* <gyouja@pilgrims.ru> – lfs.pilgrims.ru mirror
- *Benjamin Heil* <kontakt@wankoo.org> – lfs.wankoo.org mirror
- *Anton Maisak* <info@linuxfromscratch.org.ru> – linuxfromscratch.org.ru mirror

## Asian Mirrors

- *Satit Phermsawang* <satit@wbac.ac.th> – lfs.phayoune.org mirror
- *Shizunet Co.,Ltd.* <info@shizu-net.jp> – lfs.mirror.shizu-net.jp mirror

## Australian Mirrors

- *Jason Andrade* <jason@dstc.edu.au> – au.linuxfromscratch.org mirror

## Former Project Team Members

- *Christine Barczak* <theladyskye@linuxfromscratch.org> – LFS Book Editor
- *Archaic* <archaic@linuxfromscratch.org> – LFS Technical Writer/Editor, HLFS Project Leader, BLFS Editor, Hints and Patches Project Maintainer
- *Matthew Burgess* <matthew@linuxfromscratch.org> – LFS Project Leader, LFS Technical Writer/Editor
- *Nathan Coulson* <nathan@linuxfromscratch.org> – LFS-Bootscripts Maintainer
- Timothy Bauscher
- Robert Briggs
- Ian Chilton
- *Jeroen Coumans* <jeroen@linuxfromscratch.org> – Website Developer, FAQ Maintainer
- *Manuel Canales Esparcia* <manuel@linuxfromscratch.org> – LFS/BLFS/HLFS XML and XSL Maintainer
- Alex Groenewoud – LFS Technical Writer
- Marc Heerdink
- *Jeremy Huntwork* <jhuntwork@linuxfromscratch.org> – LFS Technical Writer, LFS LiveCD Maintainer
- *Bryan Kadzban* <bryan@linuxfromscratch.org> – LFS Technical Writer
- Mark Hymers
- Seth W. Klein – FAQ maintainer
- *Nicholas Leippe* <nicholas@linuxfromscratch.org> – Wiki Maintainer



- *Anderson Lizardo* <lizardo@linuxfromscratch.org> – Website Backend-Scripts Maintainer
- *Randy McMurchy* <randy@linuxfromscratch.org> – BLFS Project Leader, LFS Editor
- *Dan Nicholson* <dnicholson@linuxfromscratch.org> – LFS and BLFS Editor
- *Alexander E. Patrakov* <alexander@linuxfromscratch.org> – LFS Technical Writer, LFS Internationalization Editor, LFS Live CD Maintainer
- *Simon Perreault*
- *Scot Mc Pherson* <scot@linuxfromscratch.org> – LFS NNTP Gateway Maintainer
- *Douglas R. Reno* <renodr@linuxfromscratch.org> – Systemd Editor
- *Ryan Oliver* <ryan@linuxfromscratch.org> – CLFS Project Co-Leader
- *Greg Schafer* <gschafer@zip.com.au> – LFS Technical Writer and Architect of the Next Generation 64-bit-enabling Build Method
- *Jesse Tie-Ten-Quee* – LFS Technical Writer
- *James Robertson* <jwrober@linuxfromscratch.org> – Bugzilla Maintainer
- *Tushar Teredesai* <tushar@linuxfromscratch.org> – BLFS Book Editor, Hints and Patches Project Leader
- *Jeremy Utey* <jeremy@linuxfromscratch.org> – LFS Technical Writer, Bugzilla Maintainer, LFS-Bootscripts Maintainer
- *Zack Winkles* <zwinkles@gmail.com> – LFS Technical Writer

# Appendix C. Dependencies

Every package built in LFS relies on one or more other packages in order to build and install properly. Some packages even participate in circular dependencies, that is, the first package depends on the second which in turn depends on the first. Because of these dependencies, the order in which packages are built in LFS is very important. The purpose of this page is to document the dependencies of each package built in LFS.

For each package that is built, there are three, and sometimes up to five types of dependencies listed below. The first lists what other packages need to be available in order to compile and install the package in question. The second lists the packages that must be available when any programs or libraries from the package are used at runtime. The third lists what packages, in addition to those on the first list, need to be available in order to run the test suites. The fourth list of dependencies are packages that require this package to be built and installed in its final location before they are built and installed.

The last list of dependencies are optional packages that are not addressed in LFS, but could be useful to the user. These packages may have additional mandatory or optional dependencies of their own. For these dependencies, the recommended practice is to install them after completion of the LFS book and then go back and rebuild the LFS package. In several cases, re-installation is addressed in BLFS.

## Acl

**Installation depends on:** Attr, Bash, Binutils, Coreutils, GCC, Gettext, Grep, M4, Make, Perl, Sed, and Texinfo  
**Required at runtime:** Attr and Glibc  
**Test suite depends on:** Automake, Diffutils, Findutils, and Libtool  
**Must be installed before:** Coreutils, Sed, Tar, and Vim  
**Optional dependencies:** None

## Attr

**Installation depends on:** Bash, Binutils, Coreutils, GCC, Gettext, Glibc, Grep, M4, Make, Perl, Sed, and Texinfo  
**Required at runtime:** Glibc  
**Test suite depends on:** Automake, Diffutils, Findutils, and Libtool  
**Must be installed before:** Acl, Libcap, and Patch  
**Optional dependencies:** None

## Autoconf

**Installation depends on:** Bash, Coreutils, Grep, M4, Make, Perl, Sed, and Texinfo  
**Required at runtime:** Bash, Coreutils, Grep, M4, Make, Sed, and Texinfo  
**Test suite depends on:** Automake, Diffutils, Findutils, GCC, and Libtool  
**Must be installed before:** Automake and Coreutils  
**Optional dependencies:** *Emacs*

## Automake

**Installation depends on:** Autoconf, Bash, Coreutils, Gettext, Grep, M4, Make, Perl, Sed, and Texinfo  
**Required at runtime:** Bash, Coreutils, Grep, M4, Sed, and Texinfo  
**Test suite depends on:** Binutils, Bison, Bzip2, DejaGNU, Diffutils, Expect, Findutils, Flex, GCC, Gettext, Gzip, Libtool, and Tar  
**Must be installed before:** Coreutils  
**Optional dependencies:** None

## Bash

<b>Installation depends on:</b>	Bash, Binutils, Bison, Coreutils, Diffutils, Gawk, GCC, Glibc, Grep, Make, Ncurses, Patch, Readline, Sed, and Texinfo
<b>Required at runtime:</b>	Glibc, Ncurses, and Readline
<b>Test suite depends on:</b>	Expect and Shadow
<b>Must be installed before:</b>	None
<b>Optional dependencies:</b>	<i>Xorg</i>

## Bc

<b>Installation depends on:</b>	Bash, Binutils, Coreutils, GCC, Glibc, Grep, Make, and Readline
<b>Required at runtime:</b>	Glibc, Ncurses, and Readline
<b>Test suite depends on:</b>	Gawk
<b>Must be installed before:</b>	Linux
<b>Optional dependencies:</b>	None

## Binutils

<b>Installation depends on:</b>	Bash, Binutils, Coreutils, Diffutils, File, Flex, Gawk, GCC, Glibc, Grep, Make, Perl, Pkgconf, Sed, Texinfo, Zlib, and Zstd
<b>Required at runtime:</b>	Glibc, Zlib, and Zstd
<b>Test suite depends on:</b>	DejaGNU and Expect
<b>Must be installed before:</b>	None
<b>Optional dependencies:</b>	<i>Elfutils</i> and <i>Jansson</i>

## Bison

<b>Installation depends on:</b>	Bash, Binutils, Coreutils, Diffutils, GCC, Gettext, Glibc, Grep, M4, Make, Perl, and Sed
<b>Required at runtime:</b>	Glibc
<b>Test suite depends on:</b>	Diffutils, Findutils, and Flex
<b>Must be installed before:</b>	Kbd and Tar
<b>Optional dependencies:</b>	<i>Doxygen</i>

## Bzip2

<b>Installation depends on:</b>	Bash, Binutils, Coreutils, Diffutils, GCC, Glibc, Make, and Patch
<b>Required at runtime:</b>	Glibc
<b>Test suite depends on:</b>	None
<b>Must be installed before:</b>	File and Libelf
<b>Optional dependencies:</b>	None

## Check

<b>Installation depends on:</b>	Gawk, GCC, Grep, Make, Sed, and Texinfo
<b>Required at runtime:</b>	Bash and Gawk
<b>Test suite depends on:</b>	None
<b>Must be installed before:</b>	None
<b>Optional dependencies:</b>	<i>libsubunit</i> and <i>patchutils</i>

## Coreutils

- Installation depends on:** Autoconf, Automake, Bash, Binutils, Coreutils, GCC, Gettext, Glibc, GMP, Grep, Libcap, Make, OpenSSL, Patch, Perl, Sed, and Texinfo
- Required at runtime:** Glibc
- Test suite depends on:** Diffutils, E2fsprogs, Findutils, Shadow, and Util-linux
- Must be installed before:** Bash, Diffutils, Findutils, Man-DB, and Systemd
- Optional dependencies:** *Expect.pm* and *IO::Tty*

## D-Bus

- Installation depends on:** Bash, Binutils, Coreutils, Diffutils, Gawk, GCC, Glibc, Grep, Make, Pkgconf, Sed, Systemd, and Util-linux
- Required at runtime:** Glibc and Systemd
- Test suite depends on:** Several packages in BLFS
- Must be installed before:** None
- Optional dependencies:** *Xorg Libraries*

## DejaGNU

- Installation depends on:** Bash, Coreutils, Diffutils, Expect, GCC, Grep, Make, Sed, and Texinfo
- Required at runtime:** Expect and Bash
- Test suite depends on:** None
- Must be installed before:** None
- Optional dependencies:** None

## Diffutils

- Installation depends on:** Bash, Binutils, Coreutils, Gawk, GCC, Gettext, Glibc, Grep, Make, Sed, and Texinfo
- Required at runtime:** Glibc
- Test suite depends on:** Perl
- Must be installed before:** None
- Optional dependencies:** None

## E2fsprogs

- Installation depends on:** Bash, Binutils, Coreutils, Diffutils, Gawk, GCC, Glibc, Grep, Gzip, Make, Pkgconf, Sed, Systemd, Texinfo, and Util-linux
- Required at runtime:** Glibc and Util-linux
- Test suite depends on:** Procps-ng and Psmisc
- Must be installed before:** None
- Optional dependencies:** None

## Expat

- Installation depends on:** Bash, Binutils, Coreutils, Gawk, GCC, Glibc, Grep, Make, and Sed
- Required at runtime:** Glibc
- Test suite depends on:** None
- Must be installed before:** Python and XML::Parser
- Optional dependencies:** None

## Expect

<b>Installation depends on:</b>	Bash, Binutils, Coreutils, Diffutils, GCC, Glibc, Grep, Make, Patch, Sed, and Tcl
<b>Required at runtime:</b>	Glibc and Tcl
<b>Test suite depends on:</b>	None
<b>Must be installed before:</b>	None
<b>Optional dependencies:</b>	<i>Tk</i>

## File

<b>Installation depends on:</b>	Bash, Binutils, Bzip2, Coreutils, Diffutils, Gawk, GCC, Glibc, Grep, Make, Sed, Xz, and Zlib
<b>Required at runtime:</b>	Glibc, Bzip2, Xz, and Zlib
<b>Test suite depends on:</b>	None
<b>Must be installed before:</b>	None
<b>Optional dependencies:</b>	<i>libseccomp</i>

## Findutils

<b>Installation depends on:</b>	Bash, Binutils, Coreutils, GCC, Gettext, Glibc, Grep, Make, Sed, and Texinfo
<b>Required at runtime:</b>	Bash and Glibc
<b>Test suite depends on:</b>	DejaGNU, Diffutils, and Expect
<b>Must be installed before:</b>	None
<b>Optional dependencies:</b>	None

## Flex

<b>Installation depends on:</b>	Bash, Binutils, Coreutils, GCC, Gettext, Glibc, Grep, M4, Make, Patch, Sed, and Texinfo
<b>Required at runtime:</b>	Bash, Glibc, and M4
<b>Test suite depends on:</b>	Bison and Gawk
<b>Must be installed before:</b>	Binutils, IProute2, Kbd, Kmod, and Man-DB
<b>Optional dependencies:</b>	None

## Flit-Core

<b>Installation depends on:</b>	Python
<b>Required at runtime:</b>	Python
<b>Test suite depends on:</b>	No test suite available
<b>Must be installed before:</b>	Wheel
<b>Optional dependencies:</b>	<i>pytest</i> and <i>testpath</i>

## Gawk

<b>Installation depends on:</b>	Bash, Binutils, Coreutils, GCC, Gettext, Glibc, GMP, Grep, Make, MPFR, Patch, Readline, Sed, and Texinfo
<b>Required at runtime:</b>	Bash, Glibc, and Mpfr
<b>Test suite depends on:</b>	Diffutils
<b>Must be installed before:</b>	None
<b>Optional dependencies:</b>	<i>libsigsegv</i>

## GCC

<b>Installation depends on:</b>	Bash, Binutils, Coreutils, Diffutils, Findutils, Gawk, GCC, Gettext, Glibc, GMP, Grep, M4, Make, MPC, MPFR, Patch, Perl, Sed, Tar, Texinfo, and Zstd
<b>Required at runtime:</b>	Bash, Binutils, Glibc, Mpc, and Python
<b>Test suite depends on:</b>	DejaGNU, Expect, and Shadow
<b>Must be installed before:</b>	None
<b>Optional dependencies:</b>	<i>GDC</i> , <i>GNAT</i> , and <i>ISL</i>

## GDBM

<b>Installation depends on:</b>	Bash, Binutils, Coreutils, Diffutils, GCC, Grep, Make, and Sed
<b>Required at runtime:</b>	Bash, Glibc, and Readline
<b>Test suite depends on:</b>	None
<b>Must be installed before:</b>	None
<b>Optional dependencies:</b>	None

## Gettext

<b>Installation depends on:</b>	Bash, Binutils, Coreutils, Gawk, GCC, Glibc, Grep, Make, Ncurses, Sed, and Texinfo
<b>Required at runtime:</b>	Acl, Bash, Gcc, and Glibc
<b>Test suite depends on:</b>	Diffutils, Perl, and Tcl
<b>Must be installed before:</b>	Automake and Bison
<b>Optional dependencies:</b>	<i>libunistring</i> and <i>libxml2</i>

## Glibc

<b>Installation depends on:</b>	Bash, Binutils, Bison, Coreutils, Diffutils, Gawk, GCC, Gettext, Grep, Gzip, Linux API Headers, Make, Perl, Python, Sed, and Texinfo
<b>Required at runtime:</b>	None
<b>Test suite depends on:</b>	File
<b>Must be installed before:</b>	None
<b>Optional dependencies:</b>	None

## GMP

<b>Installation depends on:</b>	Bash, Binutils, Coreutils, Diffutils, Gawk, GCC, Glibc, Grep, M4, Make, Sed, and Texinfo
<b>Required at runtime:</b>	GCC and Glibc
<b>Test suite depends on:</b>	None
<b>Must be installed before:</b>	MPFR and GCC
<b>Optional dependencies:</b>	None

## Gperf

<b>Installation depends on:</b>	Bash, Binutils, Coreutils, GCC, Glibc, and Make
<b>Required at runtime:</b>	GCC and Glibc
<b>Test suite depends on:</b>	Diffutils and Expect
<b>Must be installed before:</b>	None
<b>Optional dependencies:</b>	None

## Grep

<b>Installation depends on:</b>	Bash, Binutils, Coreutils, Diffutils, GCC, Gettext, Glibc, Grep, Make, Patch, Sed, and Texinfo
<b>Required at runtime:</b>	Glibc
<b>Test suite depends on:</b>	Gawk
<b>Must be installed before:</b>	Man-DB
<b>Optional dependencies:</b>	<i>PCRE2</i> and <i>libsigsigv</i>

## Groff

<b>Installation depends on:</b>	Bash, Binutils, Bison, Coreutils, Gawk, GCC, Glibc, Grep, Make, Patch, Sed, and Texinfo
<b>Required at runtime:</b>	GCC, Glibc, and Perl
<b>Test suite depends on:</b>	No test suite available
<b>Must be installed before:</b>	Man-DB
<b>Optional dependencies:</b>	<i>ghostscript</i> and <i>Uchardet</i>

## GRUB

<b>Installation depends on:</b>	Bash, Binutils, Bison, Coreutils, Diffutils, GCC, Gettext, Glibc, Grep, Make, Ncurses, Sed, Texinfo, and Xz
<b>Required at runtime:</b>	Bash, GCC, Gettext, Glibc, Xz, and Sed.
<b>Test suite depends on:</b>	None
<b>Must be installed before:</b>	None
<b>Optional dependencies:</b>	None

## Gzip

<b>Installation depends on:</b>	Bash, Binutils, Coreutils, GCC, Glibc, Grep, Make, Sed, and Texinfo
<b>Required at runtime:</b>	Bash and Glibc
<b>Test suite depends on:</b>	Diffutils and Less
<b>Must be installed before:</b>	Man-DB
<b>Optional dependencies:</b>	None

## lana-Etc

<b>Installation depends on:</b>	Coreutils
<b>Required at runtime:</b>	None
<b>Test suite depends on:</b>	No test suite available
<b>Must be installed before:</b>	Perl
<b>Optional dependencies:</b>	None

## Inetutils

<b>Installation depends on:</b>	Bash, Binutils, Coreutils, GCC, Glibc, Grep, Make, Ncurses, Patch, Sed, Texinfo, and Zlib
<b>Required at runtime:</b>	GCC, Glibc, Ncurses, and Readline
<b>Test suite depends on:</b>	None
<b>Must be installed before:</b>	Tar
<b>Optional dependencies:</b>	None

## Intltool

**Installation depends on:** Bash, Gawk, Glibc, Make, Perl, Sed, and XML::Parser  
**Required at runtime:** Autoconf, Automake, Bash, Glibc, Grep, Perl, and Sed  
**Test suite depends on:** Perl  
**Must be installed before:** None  
**Optional dependencies:** None

## IProute2

**Installation depends on:** Bash, Bison, Coreutils, Flex, GCC, Glibc, Make, Libcap, Libelf, Linux API Headers, Pkgconf, and Zlib  
**Required at runtime:** Bash, Coreutils, Glibc, Libcap, Libelf, and Zlib  
**Test suite depends on:** No test suite available  
**Must be installed before:** None  
**Optional dependencies:** *Berkeley DB, iptables, libbpf, libmnl, and libtirpc*

## Jinja2

**Installation depends on:** MarkupSafe, Python, Setuptools, and Wheel  
**Required at runtime:** MarkupSafe and Python  
**Test suite depends on:** No test suite available  
**Must be installed before:** Systemd  
**Optional dependencies:** None

## Kbd

**Installation depends on:** Bash, Binutils, Bison, Check, Coreutils, Flex, GCC, Gettext, Glibc, Gzip, Make, Patch, and Sed  
**Required at runtime:** Bash, Coreutils, and Glibc  
**Test suite depends on:** None  
**Must be installed before:** None  
**Optional dependencies:** *Linux-PAM*

## Kmod

**Installation depends on:** Bash, Binutils, Bison, Coreutils, Flex, GCC, Gettext, Glibc, Gzip, Make, OpenSSL, Pkgconf, Sed, Xz, and Zlib  
**Required at runtime:** Glibc, Xz, and Zlib  
**Test suite depends on:** No test suite available  
**Must be installed before:** Systemd  
**Optional dependencies:** *scdoc* (for man pages)

## Less

**Installation depends on:** Bash, Binutils, Coreutils, Diffutils, GCC, Glibc, Grep, Make, Ncurses, and Sed  
**Required at runtime:** Glibc and Ncurses  
**Test suite depends on:** No test suite available  
**Must be installed before:** Gzip  
**Optional dependencies:** *PCRE2* or *PCRE*



## Libcap

**Installation depends on:** Attr, Bash, Binutils, Coreutils, GCC, Glibc, Perl, Make, and Sed  
**Required at runtime:** Glibc  
**Test suite depends on:** None  
**Must be installed before:** IProute2 and Shadow  
**Optional dependencies:** *Linux-PAM*

## Libelf

**Installation depends on:** Bash, Binutils, Bzip2, Coreutils, GCC, Glibc, Make, Xz, Zlib, and Zstd  
**Required at runtime:** Bzip2, Glibc, Xz, Zlib, and Zstd  
**Test suite depends on:** None  
**Must be installed before:** IProute2 and Linux  
**Optional dependencies:** None

## Libffi

**Installation depends on:** Bash, Binutils, Coreutils, GCC, Glibc, Make, and Sed  
**Required at runtime:** Glibc  
**Test suite depends on:** DejaGnu  
**Must be installed before:** Python  
**Optional dependencies:** None

## Libpipeline

**Installation depends on:** Bash, Binutils, Coreutils, Diffutils, Gawk, GCC, Glibc, Grep, Make, Sed, and Texinfo  
**Required at runtime:** Glibc  
**Test suite depends on:** Check and Pkgconf  
**Must be installed before:** Man-DB  
**Optional dependencies:** None

## Libtool

**Installation depends on:** Bash, Binutils, Coreutils, Diffutils, Gawk, GCC, Glibc, Grep, Make, Sed, and Texinfo  
**Required at runtime:** Autoconf, Automake, Bash, Binutils, Coreutils, File, GCC, Glibc, Grep, Make, and Sed  
**Test suite depends on:** Autoconf, Automake, and Findutils  
**Must be installed before:** None  
**Optional dependencies:** None

## Libxcrypt

**Installation depends on:** Bash, Binutils, Coreutils, Diffutils, Gawk, GCC, Glibc, Grep, Make, Perl, and Sed  
**Required at runtime:** Glibc  
**Test suite depends on:** None  
**Must be installed before:** Perl, Python, Shadow, and Systemd  
**Optional dependencies:** None

## Linux

<b>Installation depends on:</b>	Bash, Bc, Binutils, Coreutils, Diffutils, Findutils, GCC, Glibc, Grep, Gzip, Kmod, Libelf, Make, Ncurses, OpenSSL, Perl, and Sed
<b>Required at runtime:</b>	None
<b>Test suite depends on:</b>	No test suite available
<b>Must be installed before:</b>	None
<b>Optional dependencies:</b>	<i>cpio</i> , <i>LLVM</i> (with Clang), and <i>Rust-bindgen</i>

## Linux API Headers

<b>Installation depends on:</b>	Bash, Binutils, Coreutils, Findutils, GCC, Glibc, Grep, Gzip, Make, Perl, and Sed
<b>Required at runtime:</b>	None
<b>Test suite depends on:</b>	No test suite available
<b>Must be installed before:</b>	None
<b>Optional dependencies:</b>	None

## Lz4

<b>Installation depends on:</b>	Bash, Binutils, Coreutils, GCC, Glibc, and Make
<b>Required at runtime:</b>	Glibc
<b>Test suite depends on:</b>	Python
<b>Must be installed before:</b>	Zstd and Systemd
<b>Optional dependencies:</b>	None

## M4

<b>Installation depends on:</b>	Bash, Binutils, Coreutils, GCC, Glibc, Grep, Make, Sed, and Texinfo
<b>Required at runtime:</b>	Bash and Glibc
<b>Test suite depends on:</b>	Diffutils
<b>Must be installed before:</b>	Autoconf and Bison
<b>Optional dependencies:</b>	<i>libsigsegv</i>

## Make

<b>Installation depends on:</b>	Bash, Binutils, Coreutils, GCC, Gettext, Glibc, Grep, Make, Sed, and Texinfo
<b>Required at runtime:</b>	Glibc
<b>Test suite depends on:</b>	Perl and Procps-ng
<b>Must be installed before:</b>	None
<b>Optional dependencies:</b>	<i>Guile</i>

## Man-DB

<b>Installation depends on:</b>	Bash, Binutils, Bzip2, Coreutils, Flex, GCC, GDBM, Gettext, Glibc, Grep, Groff, Gzip, Less, Libpipeline, Make, Pkgconf, Sed, Systemd, and Xz
<b>Required at runtime:</b>	Bash, GDBM, Groff, Glibc, Gzip, Less, Libpipeline, and Zlib
<b>Test suite depends on:</b>	Util-linux
<b>Must be installed before:</b>	None
<b>Optional dependencies:</b>	<i>libseccomp</i> and <i>po4a</i>

## Man-Pages

<b>Installation depends on:</b>	Bash, Coreutils, Make, and Sed
<b>Required at runtime:</b>	None
<b>Test suite depends on:</b>	No test suite available
<b>Must be installed before:</b>	None
<b>Optional dependencies:</b>	None

## MarkupSafe

<b>Installation depends on:</b>	Python, Setuptools, and Wheel
<b>Required at runtime:</b>	Python
<b>Test suite depends on:</b>	No test suite available
<b>Must be installed before:</b>	Jinja2
<b>Optional dependencies:</b>	None

## Meson

<b>Installation depends on:</b>	Ninja, Python, Setuptools, and Wheel
<b>Required at runtime:</b>	Python
<b>Test suite depends on:</b>	No test suite available
<b>Must be installed before:</b>	Systemd
<b>Optional dependencies:</b>	None

## MPC

<b>Installation depends on:</b>	Bash, Binutils, Coreutils, Diffutils, Gawk, GCC, Glibc, Grep, GMP, Make, MPFR, Sed, and Texinfo
<b>Required at runtime:</b>	Glibc, GMP, and MPFR
<b>Test suite depends on:</b>	None
<b>Must be installed before:</b>	GCC
<b>Optional dependencies:</b>	None

## MPFR

<b>Installation depends on:</b>	Bash, Binutils, Coreutils, Diffutils, Gawk, GCC, Glibc, Grep, GMP, Make, Sed, and Texinfo
<b>Required at runtime:</b>	Glibc and GMP
<b>Test suite depends on:</b>	None
<b>Must be installed before:</b>	Gawk and GCC
<b>Optional dependencies:</b>	None

## Ncurses

<b>Installation depends on:</b>	Bash, Binutils, Coreutils, Diffutils, Gawk, GCC, Glibc, Grep, Make, Patch, and Sed
<b>Required at runtime:</b>	Glibc
<b>Test suite depends on:</b>	No test suite available
<b>Must be installed before:</b>	Bash, GRUB, Inetutils, Less, Procps-ng, Psmisc, Readline, Texinfo, Util-linux, and Vim
<b>Optional dependencies:</b>	None

## Ninja

**Installation depends on:** Binutils, Coreutils, GCC, and Python  
**Required at runtime:** GCC and Glibc  
**Test suite depends on:** *cmake*  
**Must be installed before:** Meson  
**Optional dependencies:** *Asciidoc, Doxygen, Emacs, and re2c*

## OpenSSL

**Installation depends on:** Binutils, Coreutils, GCC, Make, and Perl  
**Required at runtime:** Glibc and Perl  
**Test suite depends on:** None  
**Must be installed before:** Coreutils, Kmod, Linux, and Systemd  
**Optional dependencies:** None

## Patch

**Installation depends on:** Attr, Bash, Binutils, Coreutils, GCC, Glibc, Grep, Make, and Sed  
**Required at runtime:** Attr and Glibc  
**Test suite depends on:** Diffutils  
**Must be installed before:** None  
**Optional dependencies:** *Ed*

## Perl

**Installation depends on:** Bash, Binutils, Coreutils, Gawk, GCC, GDBM, Glibc, Grep, Libxcrypt, Make, Sed, and Zlib  
**Required at runtime:** GDBM, Glibc, and Libxcrypt  
**Test suite depends on:** Iana-Etc, Less, and Procps-ng  
**Must be installed before:** Autoconf  
**Optional dependencies:** *Berkeley DB*

## Pkgconf

**Installation depends on:** Bash, Binutils, Coreutils, Gawk, GCC, Glibc, Grep, Make, and Sed  
**Required at runtime:** Glibc  
**Test suite depends on:** None  
**Must be installed before:** Binutils, D-Bus, E2fsprogs, IProute2, Kmod, Man-DB, Procps-ng, Python, Systemd , and Util-linux  
**Optional dependencies:** None

## Procps-ng

**Installation depends on:** Bash, Binutils, Coreutils, GCC, Glibc, Make, Ncurses, Pkgconf, and Systemd  
**Required at runtime:** Glibc  
**Test suite depends on:** DejaGNU  
**Must be installed before:** None  
**Optional dependencies:** None

## Psmisc

<b>Installation depends on:</b>	Bash, Binutils, Coreutils, GCC, Gettext, Glibc, Grep, Make, Ncurses, and Sed
<b>Required at runtime:</b>	Glibc and Ncurses
<b>Test suite depends on:</b>	No test suite available
<b>Must be installed before:</b>	None
<b>Optional dependencies:</b>	None

## Python

<b>Installation depends on:</b>	Bash, Binutils, Coreutils, Expat, GCC, Gdbm, Gettext, Glibc, Grep, Libffi, Libxcrypt, Make, Ncurses, OpenSSL, Pkgconf, Sed, and Util-linux
<b>Required at runtime:</b>	Bzip2, Expat, Gdbm, Glibc, Libffi, Libxcrypt, Ncurses, OpenSSL, and Zlib
<b>Test suite depends on:</b>	GDB and Valgrind
<b>Must be installed before:</b>	Ninja
<b>Optional dependencies:</b>	<i>Berkeley DB, libnsl, SQLite, and Tk</i>

## Readline

<b>Installation depends on:</b>	Bash, Binutils, Coreutils, Gawk, GCC, Glibc, Grep, Make, Ncurses, Patch, Sed, and Texinfo
<b>Required at runtime:</b>	Glibc and Ncurses
<b>Test suite depends on:</b>	No test suite available
<b>Must be installed before:</b>	Bash, Bc, and Gawk
<b>Optional dependencies:</b>	None

## Sed

<b>Installation depends on:</b>	Bash, Binutils, Coreutils, GCC, Gettext, Glibc, Grep, Make, Sed, and Texinfo
<b>Required at runtime:</b>	Acl, Attr, and Glibc
<b>Test suite depends on:</b>	Diffutils and Gawk
<b>Must be installed before:</b>	E2fsprogs, File, Libtool, and Shadow
<b>Optional dependencies:</b>	None

## Setuptools

<b>Installation depends on:</b>	Python and Wheel
<b>Required at runtime:</b>	Python
<b>Test suite depends on:</b>	No test suite available
<b>Must be installed before:</b>	Jinja2, MarkupSafe, and Meson
<b>Optional dependencies:</b>	None

## Shadow

<b>Installation depends on:</b>	Acl, Attr, Bash, Binutils, Coreutils, Diffutils, Findutils, Gawk, GCC, Gettext, Glibc, Grep, Libcap, Libxcrypt, Make, and Sed
<b>Required at runtime:</b>	Glibc and Libxcrypt
<b>Test suite depends on:</b>	No test suite available
<b>Must be installed before:</b>	Coreutils
<b>Optional dependencies:</b>	<i>CrackLib and Linux-PAM</i>

## Systemd

<b>Installation depends on:</b>	Acl, Bash, Binutils, Coreutils, Diffutils, Gawk, GCC, Glibc, Gperf, Grep, Jinja2, Libcap, Libxcrypt, Lz4, Meson, OpenSSL, Pkgconf, Sed, Util-linux, and Zstd
<b>Required at runtime:</b>	Acl, Glibc, Libcap, Libxcrypt, OpenSSL, Util-linux, Xz, Zlib, and Zstd
<b>Test suite depends on:</b>	None
<b>Must be installed before:</b>	D-Bus, E2fsprogs, Man-DB, Procps-ng, and Util-linux
<b>Optional dependencies:</b>	<i>AppArmor, audit-userspace, bash-completion, btrfs-progs, cURL, cryptsetup, docbook-xml, docbook-xsl-nons, Git, GnuTLS, iptables, jekyll, kexec-tools, libbpf, libdw, libfido2, libgcrypt, libidn2, libmicrohttpd, libpwquality, libseccomp, libxkbcommon, libxslt, Linux-PAM, lxml, make-ca, p11-kit, PCRE2, pefile, Polkit, pyelftools, qemu, qrencode, quota-tools, rpm, rsync, SELinux, Sphinx, systemtap, tpm2-tss, Valgrind, Xen, and zsh</i>

## Tar

<b>Installation depends on:</b>	Acl, Attr, Bash, Binutils, Bison, Coreutils, GCC, Gettext, Glibc, Grep, Inetutils, Make, Sed, and Texinfo
<b>Required at runtime:</b>	Acl, Attr, Bzip2, Glibc, Gzip, and Xz
<b>Test suite depends on:</b>	Autoconf, Diffutils, Findutils, Gawk, and Gzip
<b>Must be installed before:</b>	None
<b>Optional dependencies:</b>	None

## Tcl

<b>Installation depends on:</b>	Bash, Binutils, Coreutils, Diffutils, GCC, Glibc, Grep, Make, and Sed
<b>Required at runtime:</b>	Glibc and Zlib
<b>Test suite depends on:</b>	None
<b>Must be installed before:</b>	None
<b>Optional dependencies:</b>	None

## Texinfo

<b>Installation depends on:</b>	Bash, Binutils, Coreutils, GCC, Gettext, Glibc, Grep, Make, Ncurses, Patch, and Sed
<b>Required at runtime:</b>	Glibc and Ncurses
<b>Test suite depends on:</b>	None
<b>Must be installed before:</b>	None
<b>Optional dependencies:</b>	None

## Util-linux

<b>Installation depends on:</b>	Bash, Binutils, Coreutils, Diffutils, File, Findutils, Gawk, GCC, Gettext, Glibc, Grep, Make, Ncurses, Pkgconf, Sed, Systemd , and Zlib
<b>Required at runtime:</b>	Glibc, Ncurses, Readline, Systemd , and Zlib
<b>Test suite depends on:</b>	None
<b>Must be installed before:</b>	None
<b>Optional dependencies:</b>	<i>Asciidoctor, Libcap-NG, libeconf, libuser, libutempter, Linux-PAM, smartmontools, po4a, and slang</i>

## Vim

<b>Installation depends on:</b>	Acl, Attr, Bash, Binutils, Coreutils, Diffutils, GCC, Glibc, Grep, Make, Ncurses, and Sed
<b>Required at runtime:</b>	Acl, Attr, Glibc, Python, Ncurses, and Tcl
<b>Test suite depends on:</b>	None
<b>Must be installed before:</b>	None
<b>Optional dependencies:</b>	<i>Xorg, GTK+2, LessTif, Ruby, and GPM</i>

## Wheel

<b>Installation depends on:</b>	Python and Flit-core
<b>Required at runtime:</b>	Python
<b>Test suite depends on:</b>	No test suite available
<b>Must be installed before:</b>	Jinja2, MarkupSafe, Meson, and Setuptools
<b>Optional dependencies:</b>	None

## XML::Parser

<b>Installation depends on:</b>	Bash, Binutils, Coreutils, Expat, GCC, Glibc, Make, and Perl
<b>Required at runtime:</b>	Expat, Glibc, and Perl
<b>Test suite depends on:</b>	Perl
<b>Must be installed before:</b>	Intltool
<b>Optional dependencies:</b>	None

## Xz

<b>Installation depends on:</b>	Bash, Binutils, Coreutils, Diffutils, GCC, Glibc, and Make
<b>Required at runtime:</b>	Glibc
<b>Test suite depends on:</b>	None
<b>Must be installed before:</b>	File, GRUB, Kmod, Libelf, Man-DB, and Systemd
<b>Optional dependencies:</b>	None

## Zlib

<b>Installation depends on:</b>	Bash, Binutils, Coreutils, GCC, Glibc, Make, and Sed
<b>Required at runtime:</b>	Glibc
<b>Test suite depends on:</b>	None
<b>Must be installed before:</b>	File, Kmod, Libelf, Perl, and Util-linux
<b>Optional dependencies:</b>	None

## Zstd

<b>Installation depends on:</b>	Binutils, Coreutils, GCC, Glibc, Gzip, Lz4, Make, Xz, and Zlib
<b>Required at runtime:</b>	Glibc
<b>Test suite depends on:</b>	None
<b>Must be installed before:</b>	Binutils, GCC, Libelf, and Systemd
<b>Optional dependencies:</b>	None

# Appendix D. LFS Licenses

This book is licensed under the Creative Commons Attribution-NonCommercial-ShareAlike 2.0 License.

Computer instructions may be extracted from the book under the MIT License.

## D.1. Creative Commons License

Creative Commons Legal Code

Attribution-NonCommercial-ShareAlike 2.0



### Important

CREATIVE COMMONS CORPORATION IS NOT A LAW FIRM AND DOES NOT PROVIDE LEGAL SERVICES. DISTRIBUTION OF THIS LICENSE DOES NOT CREATE AN ATTORNEY-CLIENT RELATIONSHIP. CREATIVE COMMONS PROVIDES THIS INFORMATION ON AN "AS-IS" BASIS. CREATIVE COMMONS MAKES NO WARRANTIES REGARDING THE INFORMATION PROVIDED, AND DISCLAIMS LIABILITY FOR DAMAGES RESULTING FROM ITS USE.

License

THE WORK (AS DEFINED BELOW) IS PROVIDED UNDER THE TERMS OF THIS CREATIVE COMMONS PUBLIC LICENSE ("CCPL" OR "LICENSE"). THE WORK IS PROTECTED BY COPYRIGHT AND/OR OTHER APPLICABLE LAW. ANY USE OF THE WORK OTHER THAN AS AUTHORIZED UNDER THIS LICENSE OR COPYRIGHT LAW IS PROHIBITED.

BY EXERCISING ANY RIGHTS TO THE WORK PROVIDED HERE, YOU ACCEPT AND AGREE TO BE BOUND BY THE TERMS OF THIS LICENSE. THE LICENSOR GRANTS YOU THE RIGHTS CONTAINED HERE IN CONSIDERATION OF YOUR ACCEPTANCE OF SUCH TERMS AND CONDITIONS.

### 1. Definitions

- a. "Collective Work" means a work, such as a periodical issue, anthology or encyclopedia, in which the Work in its entirety in unmodified form, along with a number of other contributions, constituting separate and independent works in themselves, are assembled into a collective whole. A work that constitutes a Collective Work will not be considered a Derivative Work (as defined below) for the purposes of this License.
- b. "Derivative Work" means a work based upon the Work or upon the Work and other pre-existing works, such as a translation, musical arrangement, dramatization, fictionalization, motion picture version, sound recording, art reproduction, abridgment, condensation, or any other form in which the Work may be recast, transformed, or adapted, except that a work that constitutes a Collective Work will not be considered a Derivative Work for the purpose of this License. For the avoidance of doubt, where the Work is a musical composition or sound recording, the synchronization of the Work in timed-relation with a moving image ("synching") will be considered a Derivative Work for the purpose of this License.
- c. "Licensor" means the individual or entity that offers the Work under the terms of this License.
- d. "Original Author" means the individual or entity who created the Work.
- e. "Work" means the copyrightable work of authorship offered under the terms of this License.
- f. "You" means an individual or entity exercising rights under this License who has not previously violated the terms of this License with respect to the Work, or who has received express permission from the Licensor to exercise rights under this License despite a previous violation.



- g. "License Elements" means the following high-level license attributes as selected by Licensor and indicated in the title of this License: Attribution, Noncommercial, ShareAlike.
2. Fair Use Rights. Nothing in this license is intended to reduce, limit, or restrict any rights arising from fair use, first sale or other limitations on the exclusive rights of the copyright owner under copyright law or other applicable laws.
  3. License Grant. Subject to the terms and conditions of this License, Licensor hereby grants You a worldwide, royalty-free, non-exclusive, perpetual (for the duration of the applicable copyright) license to exercise the rights in the Work as stated below:
    - a. to reproduce the Work, to incorporate the Work into one or more Collective Works, and to reproduce the Work as incorporated in the Collective Works;
    - b. to create and reproduce Derivative Works;
    - c. to distribute copies or phonorecords of, display publicly, perform publicly, and perform publicly by means of a digital audio transmission the Work including as incorporated in Collective Works;
    - d. to distribute copies or phonorecords of, display publicly, perform publicly, and perform publicly by means of a digital audio transmission Derivative Works;

The above rights may be exercised in all media and formats whether now known or hereafter devised. The above rights include the right to make such modifications as are technically necessary to exercise the rights in other media and formats. All rights not expressly granted by Licensor are hereby reserved, including but not limited to the rights set forth in Sections 4(e) and 4(f).

4. Restrictions. The license granted in Section 3 above is expressly made subject to and limited by the following restrictions:
  - a. You may distribute, publicly display, publicly perform, or publicly digitally perform the Work only under the terms of this License, and You must include a copy of, or the Uniform Resource Identifier for, this License with every copy or phonorecord of the Work You distribute, publicly display, publicly perform, or publicly digitally perform. You may not offer or impose any terms on the Work that alter or restrict the terms of this License or the recipients' exercise of the rights granted hereunder. You may not sublicense the Work. You must keep intact all notices that refer to this License and to the disclaimer of warranties. You may not distribute, publicly display, publicly perform, or publicly digitally perform the Work with any technological measures that control access or use of the Work in a manner inconsistent with the terms of this License Agreement. The above applies to the Work as incorporated in a Collective Work, but this does not require the Collective Work apart from the Work itself to be made subject to the terms of this License. If You create a Collective Work, upon notice from any Licensor You must, to the extent practicable, remove from the Collective Work any reference to such Licensor or the Original Author, as requested. If You create a Derivative Work, upon notice from any Licensor You must, to the extent practicable, remove from the Derivative Work any reference to such Licensor or the Original Author, as requested.
  - b. You may distribute, publicly display, publicly perform, or publicly digitally perform a Derivative Work only under the terms of this License, a later version of this License with the same License Elements as this License, or a Creative Commons iCommons license that contains the same License Elements as this License (e.g. Attribution-NonCommercial-ShareAlike 2.0 Japan). You must include a copy of, or the Uniform Resource Identifier for, this License or other license specified in the previous sentence with every copy or phonorecord of each Derivative Work You distribute, publicly display, publicly perform, or publicly digitally perform. You may not offer or impose any terms on the Derivative Works that alter or restrict the terms of this License or the recipients' exercise of the rights granted hereunder, and You must keep intact all notices that refer to this License and to the disclaimer of warranties. You may not distribute, publicly display, publicly perform, or publicly digitally perform the Derivative Work with any technological measures that control access or use of the Work in a manner

inconsistent with the terms of this License Agreement. The above applies to the Derivative Work as incorporated in a Collective Work, but this does not require the Collective Work apart from the Derivative Work itself to be made subject to the terms of this License.

- c. You may not exercise any of the rights granted to You in Section 3 above in any manner that is primarily intended for or directed toward commercial advantage or private monetary compensation. The exchange of the Work for other copyrighted works by means of digital file-sharing or otherwise shall not be considered to be intended for or directed toward commercial advantage or private monetary compensation, provided there is no payment of any monetary compensation in connection with the exchange of copyrighted works.
- d. If you distribute, publicly display, publicly perform, or publicly digitally perform the Work or any Derivative Works or Collective Works, You must keep intact all copyright notices for the Work and give the Original Author credit reasonable to the medium or means You are utilizing by conveying the name (or pseudonym if applicable) of the Original Author if supplied; the title of the Work if supplied; to the extent reasonably practicable, the Uniform Resource Identifier, if any, that Licensor specifies to be associated with the Work, unless such URI does not refer to the copyright notice or licensing information for the Work; and in the case of a Derivative Work, a credit identifying the use of the Work in the Derivative Work (e.g., "French translation of the Work by Original Author," or "Screenplay based on original Work by Original Author"). Such credit may be implemented in any reasonable manner; provided, however, that in the case of a Derivative Work or Collective Work, at a minimum such credit will appear where any other comparable authorship credit appears and in a manner at least as prominent as such other comparable authorship credit.
- e. For the avoidance of doubt, where the Work is a musical composition:
  - i. Performance Royalties Under Blanket Licenses. Licensor reserves the exclusive right to collect, whether individually or via a performance rights society (e.g. ASCAP, BMI, SESAC), royalties for the public performance or public digital performance (e.g. webcast) of the Work if that performance is primarily intended for or directed toward commercial advantage or private monetary compensation.
  - ii. Mechanical Rights and Statutory Royalties. Licensor reserves the exclusive right to collect, whether individually or via a music rights agency or designated agent (e.g. Harry Fox Agency), royalties for any phonorecord You create from the Work ("cover version") and distribute, subject to the compulsory license created by 17 USC Section 115 of the US Copyright Act (or the equivalent in other jurisdictions), if Your distribution of such cover version is primarily intended for or directed toward commercial advantage or private monetary compensation.
- f. Webcasting Rights and Statutory Royalties. For the avoidance of doubt, where the Work is a sound recording, Licensor reserves the exclusive right to collect, whether individually or via a performance-rights society (e.g. SoundExchange), royalties for the public digital performance (e.g. webcast) of the Work, subject to the compulsory license created by 17 USC Section 114 of the US Copyright Act (or the equivalent in other jurisdictions), if Your public digital performance is primarily intended for or directed toward commercial advantage or private monetary compensation.

## 5. Representations, Warranties and Disclaimer

UNLESS OTHERWISE MUTUALLY AGREED TO BY THE PARTIES IN WRITING, LICENSOR OFFERS THE WORK AS-IS AND MAKES NO REPRESENTATIONS OR WARRANTIES OF ANY KIND CONCERNING THE WORK, EXPRESS, IMPLIED, STATUTORY OR OTHERWISE, INCLUDING, WITHOUT LIMITATION, WARRANTIES OF TITLE, MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE, NON-INFRINGEMENT, OR THE ABSENCE OF LATENT OR OTHER DEFECTS, ACCURACY, OR THE PRESENCE OF ABSENCE OF ERRORS, WHETHER OR NOT DISCOVERABLE. SOME JURISDICTIONS DO NOT ALLOW THE EXCLUSION OF IMPLIED WARRANTIES, SO SUCH EXCLUSION MAY NOT APPLY TO YOU.

6. **Limitation on Liability.** EXCEPT TO THE EXTENT REQUIRED BY APPLICABLE LAW, IN NO EVENT WILL LICENSOR BE LIABLE TO YOU ON ANY LEGAL THEORY FOR ANY SPECIAL, INCIDENTAL, CONSEQUENTIAL, PUNITIVE OR EXEMPLARY DAMAGES ARISING OUT OF THIS LICENSE OR THE USE OF THE WORK, EVEN IF LICENSOR HAS BEEN ADVISED OF THE POSSIBILITY OF SUCH DAMAGES.
7. **Termination**
  - a. This License and the rights granted hereunder will terminate automatically upon any breach by You of the terms of this License. Individuals or entities who have received Derivative Works or Collective Works from You under this License, however, will not have their licenses terminated provided such individuals or entities remain in full compliance with those licenses. Sections 1, 2, 5, 6, 7, and 8 will survive any termination of this License.
  - b. Subject to the above terms and conditions, the license granted here is perpetual (for the duration of the applicable copyright in the Work). Notwithstanding the above, Licensor reserves the right to release the Work under different license terms or to stop distributing the Work at any time; provided, however that any such election will not serve to withdraw this License (or any other license that has been, or is required to be, granted under the terms of this License), and this License will continue in full force and effect unless terminated as stated above.
8. **Miscellaneous**
  - a. Each time You distribute or publicly digitally perform the Work or a Collective Work, the Licensor offers to the recipient a license to the Work on the same terms and conditions as the license granted to You under this License.
  - b. Each time You distribute or publicly digitally perform a Derivative Work, Licensor offers to the recipient a license to the original Work on the same terms and conditions as the license granted to You under this License.
  - c. If any provision of this License is invalid or unenforceable under applicable law, it shall not affect the validity or enforceability of the remainder of the terms of this License, and without further action by the parties to this agreement, such provision shall be reformed to the minimum extent necessary to make such provision valid and enforceable.
  - d. No term or provision of this License shall be deemed waived and no breach consented to unless such waiver or consent shall be in writing and signed by the party to be charged with such waiver or consent.
  - e. This License constitutes the entire agreement between the parties with respect to the Work licensed here. There are no understandings, agreements or representations with respect to the Work not specified here. Licensor shall not be bound by any additional provisions that may appear in any communication from You. This License may not be modified without the mutual written agreement of the Licensor and You.



### Important

Creative Commons is not a party to this License, and makes no warranty whatsoever in connection with the Work. Creative Commons will not be liable to You or any party on any legal theory for any damages whatsoever, including without limitation any general, special, incidental or consequential damages arising in connection to this license. Notwithstanding the foregoing two (2) sentences, if Creative Commons has expressly identified itself as the Licensor hereunder, it shall have all rights and obligations of Licensor.

Except for the limited purpose of indicating to the public that the Work is licensed under the CCPL, neither party will use the trademark "Creative Commons" or any related trademark or logo of Creative Commons without the prior written consent of Creative Commons. Any permitted use will be in compliance with Creative Commons' then-current trademark usage guidelines, as may be published on its website or otherwise made available upon request from time to time.

Creative Commons may be contacted at <http://creativecommons.org/>.

## D.2. The MIT License

Copyright © 1999-2024 Gerard Beekmans

Permission is hereby granted, free of charge, to any person obtaining a copy of this software and associated documentation files (the "Software"), to deal in the Software without restriction, including without limitation the rights to use, copy, modify, merge, publish, distribute, sublicense, and/or sell copies of the Software, and to permit persons to whom the Software is furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING FROM, OUT OF OR IN CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.

# Index

## Packages

- Acl: 135
- Attr: 134
- Autoconf: 171
- Automake: 172
- Bash: 157
  - tools: 62
- Bash: 157
  - tools: 62
- Bc: 119
- Binutils: 127
  - tools, pass 1: 47
  - tools, pass 2: 75
- Binutils: 127
  - tools, pass 1: 47
  - tools, pass 2: 75
- Binutils: 127
  - tools, pass 1: 47
  - tools, pass 2: 75
- Bison: 155
  - tools: 85
- Bison: 155
  - tools: 85
- Bzip2: 109
- Check: 191
- Coreutils: 186
  - tools: 63
- Coreutils: 186
  - tools: 63
- D-Bus: 221
- DejaGNU: 125
- Diffutils: 192
  - tools: 64
- Diffutils: 192
  - tools: 64
- E2fsprogs: 233
- Expat: 162
- Expect: 123
- File: 115
  - tools: 65
- File: 115
  - tools: 65
- Findutils: 194
  - tools: 66
- Findutils: 194
  - tools: 66
- Flex: 120
- Flit-core: 181
- Gawk: 193
  - tools: 67
- Gawk: 193
  - tools: 67
- GCC: 143
  - tools, libstdc++ pass 1: 56
  - tools, pass 1: 49
  - tools, pass 2: 76
- GCC: 143
  - tools, libstdc++ pass 1: 56
  - tools, pass 1: 49
  - tools, pass 2: 76
- GCC: 143
  - tools, libstdc++ pass 1: 56
  - tools, pass 1: 49
  - tools, pass 2: 76
- GCC: 143
  - tools, libstdc++ pass 1: 56
  - tools, pass 1: 49
  - tools, pass 2: 76
- GCC: 143
  - tools, libstdc++ pass 1: 56
  - tools, pass 1: 49
  - tools, pass 2: 76
- GDBM: 160
- Gettext: 153
  - tools: 84
- Gettext: 153
  - tools: 84
- Glibc: 100
  - tools: 53
- Glibc: 100
  - tools: 53
- GMP: 130
- Gperf: 161
- Grep: 156
  - tools: 68
- Grep: 156
  - tools: 68
- Grep: 156
  - tools: 68
- Groff: 195
- GRUB: 198
- Gzip: 200
  - tools: 69
- Gzip: 200
  - tools: 69
- Iana-Etc: 99
- Inetutils: 163

Intltool: 170  
 IPRoute2: 201  
 Jinja2: 215  
 Kbd: 203  
 Kmod: 175  
 Less: 165  
 Libcap: 136  
 Libelf: 177  
 libffi: 178  
 Libpipeline: 205  
 Libtool: 159  
 Libxcrypt: 137  
 Linux: 258  
   tools, API headers: 52  
 Linux: 258  
   tools, API headers: 52  
 Lz4: 113  
 M4: 118  
   tools: 59  
 M4: 118  
   tools: 59  
 Make: 206  
   tools: 70  
 Make: 206  
   tools: 70  
 Man-DB: 223  
 Man-pages: 98  
 MarkupSafe: 214  
 Meson: 185  
 MPC: 133  
 MPFR: 132  
 Ncurses: 148  
   tools: 60  
 Ncurses: 148  
   tools: 60  
 Ninja: 184  
 OpenSSL: 173  
 Patch: 207  
   tools: 71  
 Patch: 207  
   tools: 71  
 Perl: 166  
   tools: 86  
 Perl: 166  
   tools: 86  
 Pkgconf: 126  
 Procps-ng: 226

Psmisc: 152  
 Python: 179  
   temporary: 87  
 Python: 179  
   temporary: 87  
 Readline: 116  
 Sed: 151  
   tools: 72  
 Sed: 151  
   tools: 72  
 Setuptools: 183  
 Shadow: 139  
   configuring: 140  
 Shadow: 139  
   configuring: 140  
 systemd: 216  
 Tar: 208  
   tools: 73  
 Tar: 208  
   tools: 73  
 Tcl: 121  
 Texinfo: 209  
   temporary: 88  
 Texinfo: 209  
   temporary: 88  
 Udev  
   usage: 243  
 Util-linux: 228  
   tools: 89  
 Util-linux: 228  
   tools: 89  
 Vim: 211  
 wheel: 182  
 XML::Parser: 169  
 Xz: 111  
   tools: 74  
 Xz: 111  
   tools: 74  
 Zlib: 108  
 zstd: 114

## Programs

[: 186, 187  
 2to3: 179  
 accessdb: 223, 224  
 aclocal: 172, 172  
 aclocal-1.17: 172, 172

addftinfo: 195, 195  
 addpart: 228, 229  
 addr2line: 127, 128  
 afmtodit: 195, 195  
 agetty: 228, 229  
 apropos: 223, 224  
 ar: 127, 128  
 as: 127, 128  
 attr: 134, 134  
 autoconf: 171, 171  
 autoheader: 171, 171  
 autom4te: 171, 171  
 automake: 172, 172  
 automake-1.17: 172, 172  
 autopoint: 153, 153  
 autoreconf: 171, 171  
 autoscan: 171, 171  
 autoupdate: 171, 171  
 awk: 193, 193  
 b2sum: 186, 187  
 badblocks: 233, 234  
 base64: 186, 187, 186, 187  
 base64: 186, 187, 186, 187  
 basename: 186, 187  
 basenc: 186, 187  
 bash: 157, 158  
 bashbug: 157, 158  
 bc: 119, 119  
 bison: 155, 155  
 blkdiscard: 228, 229  
 blkid: 228, 229  
 blkzone: 228, 229  
 blockdev: 228, 229  
 bomtool: 126, 126  
 bridge: 201, 201  
 bunzip2: 109, 110  
 busctl: 216, 218  
 bzcat: 109, 110  
 bzcmp: 109, 110  
 bzdiff: 109, 110  
 bzegrep: 109, 110  
 bzfgrep: 109, 110  
 bzgrep: 109, 110  
 bzip2: 109, 110  
 bzip2recover: 109, 110  
 bzless: 109, 110  
 bzmored: 109, 110

c++: 143, 147  
 c++filt: 127, 128  
 cal: 228, 229  
 capsh: 136, 136  
 captinfo: 148, 149  
 cat: 186, 187  
 catman: 223, 225  
 cc: 143, 147  
 cfdisk: 228, 229  
 chacl: 135, 135  
 chage: 139, 141  
 chattr: 233, 234  
 chcon: 186, 187  
 chcpu: 228, 229  
 checkmk: 191, 191  
 chem: 195, 195  
 chfn: 139, 141  
 chgpasswd: 139, 141  
 chgrp: 186, 187  
 chmem: 228, 229  
 chmod: 186, 187  
 choom: 228, 229  
 chown: 186, 188  
 chpasswd: 139, 141  
 chroot: 186, 188  
 chrt: 228, 229  
 chsh: 139, 141  
 chvt: 203, 204  
 cksum: 186, 188  
 clear: 148, 149  
 cmp: 192, 192  
 col: 228, 229  
 colcrt: 228, 229  
 colrm: 228, 229  
 column: 228, 229  
 comm: 186, 188  
 compile\_et: 233, 234  
 coredumpctl: 216, 218  
 corelist: 166, 167  
 cp: 186, 188  
 cpan: 166, 167  
 cpp: 143, 147  
 csplit: 186, 188  
 ctrlaltdel: 228, 229  
 ctstat: 201, 201  
 cut: 186, 188  
 c\_rehash: 173, 174

date: 186, 188  
 dbus-cleanup-sockets: 221, 222  
 dbus-daemon: 221, 222  
 dbus-launch: 221, 222  
 dbus-monitor: 221, 222  
 dbus-run-session: 221, 222  
 dbus-send: 221, 222  
 dbus-test-tool: 221, 222  
 dbus-update-activation-environment: 221, 222  
 dbus-uuidgen: 221, 222  
 dc: 119, 119  
 dd: 186, 188  
 deallocvt: 203, 204  
 debugfs: 233, 234  
 dejagnu: 125, 125  
 delpart: 228, 229  
 depmod: 175, 175  
 df: 186, 188  
 diff: 192, 192  
 diff3: 192, 192  
 dir: 186, 188  
 dircolors: 186, 188  
 dirname: 186, 188  
 dmesg: 228, 229  
 dnsdomainname: 163, 164  
 du: 186, 188  
 dumpe2fs: 233, 234  
 dumpkeys: 203, 204  
 e2freefrag: 233, 234  
 e2fsck: 233, 234  
 e2image: 233, 234  
 e2label: 233, 234  
 e2mmpstatus: 233, 234  
 e2scrub: 233, 234  
 e2scrub\_all: 233, 234  
 e2undo: 233, 234  
 e4crypt: 233, 234  
 e4defrag: 233, 234  
 echo: 186, 188  
 egrep: 156, 156  
 eject: 228, 229  
 elfedit: 127, 128  
 enc2xs: 166, 167  
 encguess: 166, 167  
 env: 186, 188  
 envsubst: 153, 153  
 eqn: 195, 195  
 eqn2graph: 195, 195  
 ex: 211, 213  
 expand: 186, 188  
 expect: 123, 124  
 expiry: 139, 141  
 expr: 186, 188  
 factor: 186, 188  
 faillog: 139, 141  
 fallocate: 228, 229  
 false: 186, 188  
 fdisk: 228, 230  
 fgconsole: 203, 204  
 fgrep: 156, 156  
 file: 115, 115  
 filefrag: 233, 234  
 fincore: 228, 230  
 find: 194, 194  
 findfs: 228, 230  
 findmnt: 228, 230  
 flex: 120, 120  
 flex++: 120, 120  
 flock: 228, 230  
 fmt: 186, 188  
 fold: 186, 188  
 free: 226, 226  
 fsck: 228, 230  
 fsck.cramfs: 228, 230  
 fsck.ext2: 233, 234  
 fsck.ext3: 233, 234  
 fsck.ext4: 233, 234  
 fsck.minix: 228, 230  
 fsfreeze: 228, 230  
 fstrim: 228, 230  
 ftp: 163, 164  
 fuser: 152, 152  
 g++: 143, 147  
 gawk: 193, 193  
 gawk-5.3.0: 193, 193  
 gcc: 143, 147  
 gc-ar: 143, 147  
 gc-nm: 143, 147  
 gc-ranlib: 143, 147  
 gcov: 143, 147  
 gcov-dump: 143, 147  
 gcov-tool: 143, 147  
 gdbmtool: 160, 160  
 gdbm\_dump: 160, 160



gdbm\_load: 160, 160  
gdifmk: 195, 195  
gencat: 100, 106  
genl: 201, 201  
getcap: 136, 136  
getconf: 100, 106  
getent: 100, 106  
getfacl: 135, 135  
getfattr: 134, 134  
getkeycodes: 203, 204  
getopt: 228, 230  
getpcaps: 136, 136  
getsubids: 139, 141  
gettext: 153, 153  
gettext.sh: 153, 153  
gettextize: 153, 153  
glilypond: 195, 195  
gpasswd: 139, 142  
gperf: 161, 161  
gperl: 195, 195  
gpinyin: 195, 195  
gprof: 127, 128  
gprofng: 127, 128  
grap2graph: 195, 196  
grep: 156, 156  
grn: 195, 196  
grodvi: 195, 196  
groff: 195, 196  
groffer: 195, 196  
grog: 195, 196  
grolbp: 195, 196  
grolj4: 195, 196  
gropdf: 195, 196  
grops: 195, 196  
grotty: 195, 196  
groupadd: 139, 142  
groupdel: 139, 142  
groupmems: 139, 142  
groupmod: 139, 142  
groups: 186, 188  
grpck: 139, 142  
grpconv: 139, 142  
grpunconv: 139, 142  
grub-bios-setup: 198, 199  
grub-editenv: 198, 199  
grub-file: 198, 199  
grub-fstest: 198, 199  
grub-glue-efi: 198, 199  
grub-install: 198, 199  
grub-kbdcomp: 198, 199  
grub-macbless: 198, 199  
grub-menulst2cfg: 198, 199  
grub-mkconfig: 198, 199  
grub-mkimage: 198, 199  
grub-mklayout: 198, 199  
grub-mknetdir: 198, 199  
grub-mkpasswd-pbkdf2: 198, 199  
grub-mkreldir: 198, 199  
grub-mkrescue: 198, 199  
grub-mkstandalone: 198, 199  
grub-ofpathname: 198, 199  
grub-probe: 198, 199  
grub-reboot: 198, 199  
grub-render-label: 198, 199  
grub-script-check: 198, 199  
grub-set-default: 198, 199  
grub-setup: 198, 199  
grub-syslinux2cfg: 198, 199  
gunzip: 200, 200  
gzexe: 200, 200  
gzip: 200, 200  
h2ph: 166, 167  
h2xs: 166, 167  
halt: 216, 218  
hardlink: 228, 230  
head: 186, 188  
hexdump: 228, 230  
hostid: 186, 188  
hostname: 163, 164  
hostnamectl: 216, 218  
hpftodit: 195, 196  
hwclock: 228, 230  
i386: 228, 230  
iconv: 100, 106  
iconvconfig: 100, 106  
id: 186, 188  
idle3: 179  
ifconfig: 163, 164  
ifnames: 171, 171  
ifstat: 201, 201  
indxbib: 195, 196  
info: 209, 209  
infocmp: 148, 149  
infotocap: 148, 149

init: 216, 218  
 insmod: 175, 176  
 install: 186, 188  
 install-info: 209, 210  
 instmodsh: 166, 167  
 intltool-extract: 170, 170  
 intltool-merge: 170, 170  
 intltool-prepare: 170, 170  
 intltool-update: 170, 170  
 intltoolize: 170, 170  
 ionice: 228, 230  
 ip: 201, 201  
 ipcmk: 228, 230  
 ipcrm: 228, 230  
 ipcs: 228, 230  
 irqtop: 228, 230  
 isosize: 228, 230  
 join: 186, 188  
 journalctl: 216, 218  
 json\_pp: 166, 167  
 kbinfo: 203, 204  
 kbrate: 203, 204  
 kbd\_mode: 203, 204  
 kernel-install: 216, 218  
 kill: 228, 230  
 killall: 152, 152  
 kmod: 175, 176  
 last: 228, 230  
 lastb: 228, 230  
 ld: 127, 128  
 ld.bfd: 127, 128  
 ld.gold: 127, 128  
 ldattach: 228, 230  
 ldconfig: 100, 106  
 ldd: 100, 106  
 lddlibc4: 100, 106  
 less: 165, 165  
 lessecho: 165, 165  
 lesskey: 165, 165  
 lex: 120, 120  
 lexgrog: 223, 225  
 lfskernel-6.10.5: 258, 263  
 libasan: 143, 147  
 libatomic: 143, 147  
 libcc1: 143, 147  
 libnetcfg: 166, 167  
 libtool: 159, 159  
 libtoolize: 159, 159  
 link: 186, 188  
 linux32: 228, 230  
 linux64: 228, 230  
 lkbib: 195, 196  
 ln: 186, 188  
 lnstat: 201, 202  
 loadkeys: 203, 204  
 loadunimap: 203, 204  
 locale: 100, 106  
 localectl: 216, 219  
 localedef: 100, 106  
 locate: 194, 194  
 logger: 228, 230  
 login: 139, 142  
 loginctl: 216, 219  
 logname: 186, 188  
 logoutd: 139, 142  
 logsave: 233, 235  
 look: 228, 230  
 lookbib: 195, 196  
 losetup: 228, 230  
 ls: 186, 188  
 lsattr: 233, 235  
 lsblk: 228, 230  
 lscpu: 228, 230  
 lsfd: 228, 230  
 lspic: 228, 230  
 lsirq: 228, 231  
 lslocks: 228, 231  
 lslogins: 228, 231  
 lsmem: 228, 231  
 lsmod: 175, 176  
 lsns: 228, 231  
 lto-dump: 143, 147  
 lz4: 113, 113  
 lz4c: 113, 113  
 lz4cat: 113, 113  
 lzcat: 111, 111  
 lzcmp: 111, 111  
 lzdiff: 111, 111  
 lzegrep: 111, 111  
 lzfgrep: 111, 111  
 lzgrep: 111, 111  
 lzless: 111, 111  
 lzma: 111, 111  
 lzmadec: 111, 111

lzmainfo: 111, 111  
 lzmore: 111, 112  
 m4: 118, 118  
 machinectl: 216, 219  
 make: 206, 206  
 makedb: 100, 106  
 makeinfo: 209, 210  
 man: 223, 225  
 man-recode: 223, 225  
 mandb: 223, 225  
 manpath: 223, 225  
 mapscrn: 203, 204  
 mcookie: 228, 231  
 md5sum: 186, 188  
 mesg: 228, 231  
 meson: 185, 185  
 mkdir: 186, 189  
 mke2fs: 233, 235  
 mkfifo: 186, 189  
 mkfs: 228, 231  
 mkfs.bfs: 228, 231  
 mkfs.cramfs: 228, 231  
 mkfs.ext2: 233, 235  
 mkfs.ext3: 233, 235  
 mkfs.ext4: 233, 235  
 mkfs.minix: 228, 231  
 mklost+found: 233, 235  
 mknod: 186, 189  
 mkswap: 228, 231  
 mktemp: 186, 189  
 mk\_cmds: 233, 235  
 mmroff: 195, 196  
 modinfo: 175, 176  
 modprobe: 175, 176  
 more: 228, 231  
 mount: 228, 231  
 mountpoint: 228, 231  
 msgattrib: 153, 153  
 msgcat: 153, 153  
 msgcmp: 153, 153  
 msgcomm: 153, 154  
 msgconv: 153, 154  
 msgen: 153, 154  
 msgexec: 153, 154  
 msgfilter: 153, 154  
 msgfmt: 153, 154  
 msggrep: 153, 154  
 msginit: 153, 154  
 msgmerge: 153, 154  
 msgunfmt: 153, 154  
 msguniq: 153, 154  
 mtrace: 100, 106  
 mv: 186, 189  
 namei: 228, 231  
 ncursesw6-config: 148, 149  
 neqn: 195, 196  
 networkctl: 216, 219  
 newgidmap: 139, 142  
 newgrp: 139, 142  
 newuidmap: 139, 142  
 newusers: 139, 142  
 ngettext: 153, 154  
 nice: 186, 189  
 ninja: 184, 184  
 nl: 186, 189  
 nm: 127, 128  
 nohup: 186, 189  
 nologin: 139, 142  
 nproc: 186, 189  
 nroff: 195, 196  
 nsenter: 228, 231  
 nstat: 201, 202  
 numfmt: 186, 189  
 objcopy: 127, 128  
 objdump: 127, 128  
 od: 186, 189  
 oomctl: 216, 219  
 openssl: 173, 174  
 openvt: 203, 204  
 partx: 228, 231  
 passwd: 139, 142  
 paste: 186, 189  
 patch: 207, 207  
 pathchk: 186, 189  
 pcprofiledump: 100, 106  
 pdfmom: 195, 196  
 pdfroff: 195, 196  
 pdftexi2dvi: 209, 210  
 peekfd: 152, 152  
 perl: 166, 167  
 perl5.40.0: 166, 167  
 perlbug: 166, 167  
 perldoc: 166, 167  
 perlvp: 166, 167

perlthanks: 166, 167  
 pfbtops: 195, 196  
 pgrep: 226, 226  
 pic: 195, 196  
 pic2graph: 195, 196  
 piconv: 166, 167  
 pidof: 226, 226  
 ping: 163, 164  
 ping6: 163, 164  
 pinky: 186, 189  
 pip3: 179  
 pivot\_root: 228, 231  
 pkgconf: 126, 126  
 pkill: 226, 226  
 pl2pm: 166, 167  
 pldd: 100, 106  
 pmap: 226, 226  
 pod2html: 166, 167  
 pod2man: 166, 167  
 pod2texi: 209, 210  
 pod2text: 166, 167  
 pod2usage: 166, 167  
 podchecker: 166, 167  
 podselect: 166, 167  
 portablectl: 216, 219  
 post-grohtml: 195, 196  
 poweroff: 216, 219  
 pr: 186, 189  
 pre-grohtml: 195, 196  
 preconv: 195, 196  
 printenv: 186, 189  
 printf: 186, 189  
 prlimit: 228, 231  
 prove: 166, 167  
 prtstat: 152, 152  
 ps: 226, 226  
 psfaddtable: 203, 204  
 psfgettable: 203, 204  
 psfstriptime: 203, 204  
 psfxtable: 203, 204  
 pslog: 152, 152  
 pstree: 152, 152  
 pstree.x11: 152, 152  
 ptar: 166, 167  
 ptardiff: 166, 167  
 ptargrep: 166, 168  
 ptx: 186, 189  
 pwck: 139, 142  
 pwconv: 139, 142  
 pwd: 186, 189  
 pwdx: 226, 226  
 pwunconv: 139, 142  
 pydoc3: 179  
 python3: 179  
 ranlib: 127, 129  
 readelf: 127, 129  
 readlink: 186, 189  
 readprofile: 228, 231  
 realpath: 186, 189  
 reboot: 216, 219  
 recode-sr-latin: 153, 154  
 refer: 195, 196  
 rename: 228, 231  
 renice: 228, 231  
 reset: 148, 149  
 resize2fs: 233, 235  
 resizepart: 228, 231  
 resolvconf: 216, 219  
 resolvectl: 216, 219  
 rev: 228, 231  
 rfcill: 228, 231  
 rm: 186, 189  
 rmdir: 186, 189  
 rmmmod: 175, 176  
 roff2dvi: 195, 197  
 roff2html: 195, 197  
 roff2pdf: 195, 197  
 roff2ps: 195, 197  
 roff2text: 195, 197  
 roff2x: 195, 197  
 routel: 201, 202  
 rtacct: 201, 202  
 rtcwake: 228, 231  
 rtmon: 201, 202  
 rtpr: 201, 202  
 rtstat: 201, 202  
 runcon: 186, 189  
 runlevel: 216, 219  
 runttest: 125, 125  
 rview: 211, 213  
 rvim: 211, 213  
 script: 228, 231  
 scriptlive: 228, 231  
 scriptreplay: 228, 231

sdiff: 192, 192  
sed: 151, 151  
seq: 186, 189  
setarch: 228, 231  
setcap: 136, 136  
setfacl: 135, 135  
setfattr: 134, 134  
setfont: 203, 204  
setkeycodes: 203, 204  
setleds: 203, 204  
setmetamode: 203, 204  
setsid: 228, 231  
setterm: 228, 231  
setvtrgb: 203, 204  
sfdisk: 228, 231  
sg: 139, 142  
sh: 157, 158  
sha1sum: 186, 189  
sha224sum: 186, 189  
sha256sum: 186, 189  
sha384sum: 186, 189  
sha512sum: 186, 189  
shasum: 166, 168  
showconsolefont: 203, 204  
showkey: 203, 204  
shred: 186, 189  
shuf: 186, 189  
shutdown: 216, 219  
size: 127, 129  
slabtop: 226, 227  
sleep: 186, 189  
sln: 100, 106  
soelim: 195, 197  
sort: 186, 189  
sotruss: 100, 106  
splain: 166, 168  
split: 186, 189  
sprof: 100, 106  
ss: 201, 202  
stat: 186, 190  
stdbuf: 186, 190  
strings: 127, 129  
strip: 127, 129  
stty: 186, 190  
su: 139, 142  
sulogin: 228, 231  
sum: 186, 190  
swapon: 228, 232  
swaplabel: 228, 231  
swapoff: 228, 232  
switch\_root: 228, 232  
sync: 186, 190  
sysctl: 226, 227  
systemctl: 216, 219  
systemd-ac-power: 216, 219  
systemd-analyze: 216, 219  
systemd-ask-password: 216, 219  
systemd-cat: 216, 219  
systemd-cgls: 216, 219  
systemd-cgtop: 216, 219  
systemd-creds: 216, 219  
systemd-delta: 216, 219  
systemd-detect-virt: 216, 219  
systemd-dissect: 216, 219  
systemd-escape: 216, 220  
systemd-hwdb: 216, 220  
systemd-id128: 216, 220  
systemd-inhibit: 216, 220  
systemd-machine-id-setup: 216, 220  
systemd-mount: 216, 220  
systemd-notify: 216, 220  
systemd-nspawn: 216, 220  
systemd-path: 216, 220  
systemd-repart: 216, 220  
systemd-resolve: 216, 220  
systemd-run: 216, 220  
systemd-socket-activate: 216, 220  
systemd-sysex: 216, 220  
systemd-tmpfiles: 216, 220  
systemd-tty-ask-password-agent: 216, 220  
systemd-umount: 216, 220  
tabs: 148, 149  
tac: 186, 190  
tail: 186, 190  
talk: 163, 164  
tar: 208, 208  
taskset: 228, 232  
tbl: 195, 197  
tc: 201, 202  
tclsh: 121, 122  
tclsh8.6: 121, 122  
tee: 186, 190  
telinit: 216, 220  
telnet: 163, 164

test: 186, 190  
 texi2dvi: 209, 210  
 texi2pdf: 209, 210  
 texi2any: 209, 210  
 texindex: 209, 210  
 tfmtodit: 195, 197  
 tftp: 163, 164  
 tic: 148, 150  
 timedatectl: 216, 220  
 timeout: 186, 190  
 tload: 226, 227  
 toe: 148, 150  
 top: 226, 227  
 touch: 186, 190  
 tput: 148, 150  
 tr: 186, 190  
 traceroute: 163, 164  
 troff: 195, 197  
 true: 186, 190  
 truncate: 186, 190  
 tset: 148, 150  
 tsort: 186, 190  
 tty: 186, 190  
 tune2fs: 233, 235  
 tzselect: 100, 106  
 uclampset: 228, 232  
 udevadm: 216, 220  
 ul: 228, 232  
 umount: 228, 232  
 uname: 186, 190  
 uname26: 228, 232  
 uncompress: 200, 200  
 unexpand: 186, 190  
 unicode\_start: 203, 204  
 unicode\_stop: 203, 204  
 uniq: 186, 190  
 unlink: 186, 190  
 unlz4: 113, 113  
 unlzma: 111, 112  
 unshare: 228, 232  
 unxz: 111, 112  
 updatedb: 194, 194  
 uptime: 226, 227  
 useradd: 139, 142  
 userdel: 139, 142  
 usermod: 139, 142  
 users: 186, 190  
 utmpdump: 228, 232  
 uuid: 228, 232  
 uuidgen: 228, 232  
 uuidparse: 228, 232  
 vdir: 186, 190  
 vi: 211, 213  
 view: 211, 213  
 vigr: 139, 142  
 vim: 211, 213  
 vimdiff: 211, 213  
 vimtutor: 211, 213  
 vipw: 139, 142  
 vmstat: 226, 227  
 w: 226, 227  
 wall: 228, 232  
 watch: 226, 227  
 wc: 186, 190  
 wdctl: 228, 232  
 whatis: 223, 225  
 wheel: 182  
 whereis: 228, 232  
 who: 186, 190  
 whoami: 186, 190  
 wipefs: 228, 232  
 x86\_64: 228, 232  
 xargs: 194, 194  
 xgettext: 153, 154  
 xmlwf: 162, 162  
 xsubpp: 166, 168  
 xtrace: 100, 106  
 xxd: 211, 213  
 xz: 111, 112  
 xzcat: 111, 112  
 xzcmp: 111, 112  
 xzdec: 111, 112  
 xzdiff: 111, 112  
 xzegrep: 111, 112  
 xzfgrep: 111, 112  
 xzgrep: 111, 112  
 xzless: 111, 112  
 xzmore: 111, 112  
 yacc: 155, 155  
 yes: 186, 190  
 zcat: 200, 200  
 zcmp: 200, 200  
 zdiff: 200, 200  
 zdump: 100, 106

zegrep: 200, 200  
 zfgrep: 200, 200  
 zforce: 200, 200  
 zgrep: 200, 200  
 zic: 100, 106  
 zipdetails: 166, 168  
 zless: 200, 200  
 zmore: 200, 200  
 znew: 200, 200  
 zramctl: 228, 232  
 zstd: 114, 114  
 zstdgrep: 114, 114  
 zstdless: 114, 114

## Libraries

Expat: 169, 169  
 ld-2.40.so: 100, 106  
 libacl: 135, 135  
 libanl: 100, 107  
 libasprintf: 153, 154  
 libattr: 134, 134  
 libbfd: 127, 129  
 libblkid: 228, 232  
 libBrokenLocale: 100, 107  
 libbz2: 109, 110  
 libc: 100, 107  
 libcap: 136, 136  
 libcheck: 191, 191  
 libcom\_err: 233, 235  
 libcrypt: 137, 138  
 libcrypto.so: 173, 174  
 libctf: 127, 129  
 libctf-nobfd: 127, 129  
 libc\_malloc\_debug: 100, 107  
 libdbus-1: 221, 222  
 libdl: 100, 107  
 libe2p: 233, 235  
 libelf: 177, 177  
 libexpat: 162, 162  
 libexpect-5.45.4: 123, 124  
 libext2fs: 233, 235  
 libfdisk: 228, 232  
 libffi: 178  
 libfl: 120, 120  
 libformw: 148, 150  
 libg: 100, 107  
 libgcc: 143, 147  
 libgcov: 143, 147  
 libgdbm: 160, 160  
 libgdbm\_compat: 160, 160  
 libgettextlib: 153, 154  
 libgettextpo: 153, 154  
 libgettextsrc: 153, 154  
 libgmp: 130, 131  
 libgmpxx: 130, 131  
 libgomp: 143, 147  
 libgprofng: 127, 129  
 libhistory: 116, 116  
 libhwasan: 143, 147  
 libitm: 143, 147  
 libkmod: 175  
 liblsan: 143, 147  
 libltdl: 159, 159  
 liblto\_plugin: 143, 147  
 liblz4: 113, 113  
 liblzma: 111, 112  
 libm: 100, 107  
 libmagic: 115, 115  
 libman: 223, 225  
 libmandb: 223, 225  
 libmcheck: 100, 107  
 libmemusage: 100, 107  
 libmenuw: 148, 150  
 libmount: 228, 232  
 libmpc: 133, 133  
 libmpfr: 132, 132  
 libmvec: 100, 107  
 libncurses++w: 148, 150  
 libncursesw: 148, 150  
 libnsl: 100, 107  
 libnss\_\*: 100, 107  
 libopcodes: 127, 129  
 libpanelw: 148, 150  
 libpcprofile: 100, 107  
 libpipeline: 205  
 libpkgconf: 126, 126  
 libproc-2: 226, 227  
 libpsx: 136, 136  
 libpthread: 100, 107  
 libquadmath: 143, 147  
 libreadline: 116, 117  
 libresolv: 100, 107  
 librt: 100, 107  
 libsframe: 127, 129

libsmartcols: 228, 232  
 libss: 233, 235  
 libssl.so: 173, 174  
 libssp: 143, 147  
 libstdbuf: 186, 190  
 libstdc++: 143, 147  
 libstdc++exp: 143, 147  
 libstdc++fs: 143, 147  
 libsubid: 139, 142  
 libsupc++: 143, 147  
 libsystemd: 216, 220  
 libtcl8.6.so: 121, 122  
 libtclstub8.6.a: 121, 122  
 libtextstyle: 153, 154  
 libthread\_db: 100, 107  
 libtsan: 143, 147  
 libubsan: 143, 147  
 libudev: 216, 220  
 libutil: 100, 107  
 libuuid: 228, 232  
 liby: 155, 155  
 libz: 108, 108  
 libzstd: 114, 114  
 preloadable\_libintl: 153, 154

## Scripts

clock  
   configuring: 246  
 console  
   configuring: 247  
 hostname  
   configuring: 242  
 localnet  
   /etc/hosts: 242  
 network  
   /etc/hosts: 242  
   configuring: 239  
 network  
   /etc/hosts: 242  
   configuring: 239  
 dwp: 127, 128

## Others

/boot/config-6.10.5: 258, 263  
 /boot/System.map-6.10.5: 258, 263  
 /dev/\*: 78

/etc/fstab: 256  
 /etc/group: 81  
 /etc/hosts: 242  
 /etc/inputrc: 251  
 /etc/ld.so.conf: 105  
 /etc/lfs-release: 267  
 /etc/localtime: 104  
 /etc/lsb-release: 267  
 /etc/mke2fs.conf: 234  
 /etc/modprobe.d/usb.conf: 263  
 /etc/nsswitch.conf: 104  
 /etc/os-release: 267  
 /etc/passwd: 81  
 /etc/profile: 249  
 /etc/locale.conf: 249  
 /etc/protocols: 99  
 /etc/resolv.conf: 241  
 /etc/services: 99  
 /etc/vimrc: 212  
 /run/utmp: 81  
 /usr/include/asm-generic/\*.h: 52, 52  
 /usr/include/asm/\*.h: 52, 52  
 /usr/include/drm/\*.h: 52, 52  
 /usr/include/linux/\*.h: 52, 52  
 /usr/include/misc/\*.h: 52, 52  
 /usr/include/mtd/\*.h: 52, 52  
 /usr/include/rdma/\*.h: 52, 52  
 /usr/include/scsi/\*.h: 52, 52  
 /usr/include/sound/\*.h: 52, 52  
 /usr/include/video/\*.h: 52, 52  
 /usr/include/xen/\*.h: 52, 52  
 /var/log/btmp: 81  
 /var/log/lastlog: 81  
 /var/log/wtmp: 81  
 /etc/shells: 252  
 man pages: 98, 98  
 Systemd Customization: 253